

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form	: Mixture
Physical state	: Liquid
Product name	: STRONTIUM ZIRCONIUM
Product code	: DSRZR50
Formula	: SrZr(OR) <sub>x</sub>
Synonyms	: DOUBLE METAL ALKOXIDE OF STRONTIUM & ZIRCONIUM
Chemical family	: METAL ALKOXIDE

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Use of the substance/mixture : Chemical intermediate

#### 1.2.2. Uses advised against

No additional information available

### 1.3. Details of the supplier of the safety data sheet

#### GELEST, INC.

11 East Steel Road  
Morrisville, PA 19067

#### USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

[info@gelest.com](mailto:info@gelest.com) - [www.gelest.com](http://www.gelest.com)

#### GELEST INC.

Fritz-Klatte-Strasse 8  
65933 Frankfurt

#### Germany

T +49 (0) 69 3535106-500 - F +49 (0) 69 3535106-501 - (M-F): 8:00 AM - 4:00 PM

[info@gelestde.com](mailto:info@gelestde.com) - [www.gelestde.com](http://www.gelestde.com)

### 1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3	H226
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 1	H318
Specific target organ toxicity — Single exposure, Category 3, Narcosis	H336
Full text of H statements : see section 16	

#### Adverse physicochemical, human health and environmental effects

No additional information available

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) :

Danger

Hazardous ingredients :

Methoxypropanol; n-Butanol

# STRONTIUM ZIRCONIUM

## Safety Data Sheet

Hazard statements (CLP)	: H226 - Flammable liquid and vapour. H315 - Causes skin irritation. H318 - Causes serious eye damage. H336 - May cause drowsiness or dizziness.
Precautionary statements (CLP)	: P280 - Wear protective gloves/protective clothing/eye protection/face protection. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P240 - Ground/bond container and receiving equipment. P261 - Avoid breathing vapours. P264 - Wash hands thoroughly after handling. P310 - Immediately call a POISON CENTER or doctor/physician

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Methoxypropanol	(CAS-No.) 107-98-2 (EC-No.) 203-539-1 (EC Index-No.) 603-064-00-3	> 75	Flam. Liq. 3, H226 STOT SE 3, H336
n-Butanol	(CAS-No.) 71-36-3 (EC-No.) 200-751-6 (EC Index-No.) 603-004-00-6	< 15	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 STOT SE 3, H336
Trade secret		6.2 - 6.4	Not classified
Trade secret		5.9 - 6.1	Not classified

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label. Call a POISON CENTER/doctor.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If you feel unwell, seek medical advice.
First-aid measures after skin contact	: Wash with plenty of water/.... Get medical advice/attention.
First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
First-aid measures after ingestion	: Never give anything by mouth to an unconscious person. Get medical advice/attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: May cause drowsiness or dizziness. May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: May be harmful if swallowed.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Foam. Carbon dioxide. Dry chemical.
Unsuitable extinguishing media	: Do not use straight streams.

# STRONTIUM ZIRCONIUM

## Safety Data Sheet

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapour. Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.

### 5.3. Advice for firefighters

Firefighting instructions : Use water spray to cool exposed surfaces. Exercise caution when fighting any chemical fire.  
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Avoid all eye and skin contact and do not breathe vapour and mist.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges.

#### 6.1.1. For non-emergency personnel

Protective equipment : Wear protective equipment as described in Section 8.  
Emergency procedures : Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

Protective equipment : For further information refer to section 8: "Exposure controls/personal protection". Equip cleanup crew with proper protection. Do not attempt to take action without suitable protective equipment.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.  
Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or shovel spills into appropriate container for disposal. Use only non-sparking tools.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapours are flammable. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapour and mist. Provide good ventilation in process area to prevent formation of vapour. Ground/bond container and receiving equipment. Take precautionary measures against static discharge. Use only outdoors or in a well-ventilated area. Use only non-sparking tools.  
Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof electrical equipment.  
Storage conditions : Keep container tightly closed. Keep in a cool place. Store locked up.  
Incompatible materials : Oxidizing agent. Water.  
Storage area : Store in a well-ventilated place. Store away from heat.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Methoxypropanol (107-98-2)		
EU	IOELV TWA (mg/m <sup>3</sup> )	375 mg/m <sup>3</sup>
EU	IOELV TWA (ppm)	100 ppm
EU	IOELV STEL (mg/m <sup>3</sup> )	568 mg/m <sup>3</sup>
EU	IOELV STEL (ppm)	150 ppm
Austria	MAK (mg/m <sup>3</sup> )	187 mg/m <sup>3</sup>
Austria	MAK (ppm)	50 ppm
Austria	MAK Short time value (mg/m <sup>3</sup> )	187 mg/m <sup>3</sup>
Austria	MAK Short time value (ppm)	50 ppm
Belgium	Limit value (mg/m <sup>3</sup> )	375 mg/m <sup>3</sup>

# STRONTIUM ZIRCONIUM

## Safety Data Sheet

Methoxypropanol (107-98-2)		
Belgium	Limit value (ppm)	100 ppm
Belgium	Short time value (mg/m <sup>3</sup> )	568 mg/m <sup>3</sup>
Belgium	Short time value (ppm)	150 ppm
Bulgaria	OEL TWA (mg/m <sup>3</sup> )	375 mg/m <sup>3</sup>
Bulgaria	OEL TWA (ppm)	100 ppm
Bulgaria	OEL STEL (mg/m <sup>3</sup> )	568 mg/m <sup>3</sup>
Bulgaria	OEL STEL (ppm)	150 ppm
Cyprus	OEL TWA (mg/m <sup>3</sup> )	375 mg/m <sup>3</sup>
Cyprus	OEL TWA (ppm)	100 ppm
Cyprus	OEL STEL (mg/m <sup>3</sup> )	568 mg/m <sup>3</sup>
Cyprus	OEL STEL (ppm)	150 ppm
France	VLE (mg/m <sup>3</sup> )	375 mg/m <sup>3</sup> (restrictive limit)
France	VLE (ppm)	100 ppm (restrictive limit)
France	VME (mg/m <sup>3</sup> )	188 mg/m <sup>3</sup> (restrictive limit)
France	VME (ppm)	50 ppm (restrictive limit)
Germany	TRGS 900 Occupational exposure limit value (mg/m <sup>3</sup> )	370 mg/m <sup>3</sup> (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Germany	TRGS 900 Occupational exposure limit value (ppm)	100 ppm (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Germany	TRGS 903 Biological limit value	15 mg/l (Medium: urine - Time: end of shift - Parameter: 1-Methoxypropan-2-ol)
Gibraltar	Eight hours mg/m <sup>3</sup>	375 mg/m <sup>3</sup>
Gibraltar	Eight hours ppm	100 ppm
Gibraltar	Short-term mg/m <sup>3</sup>	568 mg/m <sup>3</sup>
Gibraltar	Short-term ppm	150 ppm
Greece	OEL TWA (mg/m <sup>3</sup> )	360 mg/m <sup>3</sup>
Greece	OEL TWA (ppm)	100 ppm
Greece	OEL STEL (mg/m <sup>3</sup> )	1080 mg/m <sup>3</sup>
Greece	OEL STEL (ppm)	300 ppm
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	50 ppm
Italy - Portugal - USA ACGIH	ACGIH STEL (ppm)	100 ppm
Italy	OEL TWA (mg/m <sup>3</sup> )	375 mg/m <sup>3</sup>
Italy	OEL TWA (ppm)	100 ppm
Italy	OEL STEL (mg/m <sup>3</sup> )	568 mg/m <sup>3</sup>
Italy	OEL STEL (ppm)	150 ppm
Latvia	OEL TWA (mg/m <sup>3</sup> )	375 mg/m <sup>3</sup>
Latvia	OEL TWA (ppm)	100 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	360 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m <sup>3</sup> )	540 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (STEL) (ppm)	150 ppm
Spain	VLA-ED (mg/m <sup>3</sup> )	375 mg/m <sup>3</sup> (indicative limit value)
Spain	VLA-ED (ppm)	100 ppm (indicative limit value)
Spain	VLA-EC (mg/m <sup>3</sup> )	568 mg/m <sup>3</sup>
Spain	VLA-EC (ppm)	150 ppm
Switzerland	KZGW (mg/m <sup>3</sup> )	720 mg/m <sup>3</sup>
Switzerland	KZGW (ppm)	200 ppm
Switzerland	MAK (mg/m <sup>3</sup> )	360 mg/m <sup>3</sup>
Switzerland	MAK (ppm)	100 ppm
Netherlands	Grenswaarde TGG 8H (mg/m <sup>3</sup> )	375 mg/m <sup>3</sup>
Netherlands	Grenswaarde TGG 15MIN (mg/m <sup>3</sup> )	563 mg/m <sup>3</sup>
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	375 mg/m <sup>3</sup>
United Kingdom	WEL TWA (ppm)	100 ppm
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	560 mg/m <sup>3</sup>
United Kingdom	WEL STEL (ppm)	150 ppm

# STRONTIUM ZIRCONIUM

## Safety Data Sheet

Methoxypropanol (107-98-2)		
Czech Republic	Expoziční limity (PEL) (mg/m <sup>3</sup> )	270 mg/m <sup>3</sup>
Denmark	Grænseværdie (langvarig) (mg/m <sup>3</sup> )	185 mg/m <sup>3</sup>
Denmark	Grænseværdie (langvarig) (ppm)	50 ppm
Finland	HTP-arvo (8h) (mg/m <sup>3</sup> )	370 mg/m <sup>3</sup>
Finland	HTP-arvo (8h) (ppm)	100 ppm
Finland	HTP-arvo (15 min)	560 mg/m <sup>3</sup>
Finland	HTP-arvo (15 min) (ppm)	150 ppm
Hungary	AK-érték	375 mg/m <sup>3</sup>
Hungary	CK-érték	568 mg/m <sup>3</sup>
Ireland	OEL (8 hours ref) (mg/m <sup>3</sup> )	375 mg/m <sup>3</sup>
Ireland	OEL (8 hours ref) (ppm)	100 ppm
Ireland	OEL (15 min ref) (mg/m <sup>3</sup> )	568 mg/m <sup>3</sup>
Ireland	OEL (15 min ref) (ppm)	150 ppm
Lithuania	IPRV (mg/m <sup>3</sup> )	190 mg/m <sup>3</sup>
Lithuania	IPRV (ppm)	50 ppm
Lithuania	TPRV (mg/m <sup>3</sup> )	300 mg/m <sup>3</sup>
Lithuania	TPRV (ppm)	75 ppm
Malta	OEL TWA (mg/m <sup>3</sup> )	375 mg/m <sup>3</sup>
Malta	OEL TWA (ppm)	100 ppm
Malta	OEL STEL (mg/m <sup>3</sup> )	568 mg/m <sup>3</sup>
Malta	OEL STEL (ppm)	150 ppm
Norway	Grænseværdier (AN) (mg/m <sup>3</sup> )	180 mg/m <sup>3</sup>
Norway	Grænseværdier (AN) (ppm)	50 ppm
Norway	Grænseværdier (Korttidsverdi) (mg/m <sup>3</sup> )	180 mg/m <sup>3</sup>
Norway	Grænseværdier (Korttidsverdi) (ppm)	50 ppm
Poland	NDS (mg/m <sup>3</sup> )	180 mg/m <sup>3</sup>
Poland	NDSch (mg/m <sup>3</sup> )	360 mg/m <sup>3</sup>
Romania	OEL TWA (mg/m <sup>3</sup> )	375 mg/m <sup>3</sup>
Romania	OEL TWA (ppm)	100 ppm
Romania	OEL STEL (mg/m <sup>3</sup> )	568 mg/m <sup>3</sup>
Romania	OEL STEL (ppm)	150 ppm
Slovakia	NPHV (priemerná) (mg/m <sup>3</sup> )	375 mg/m <sup>3</sup>
Slovakia	NPHV (priemerná) (ppm)	100 ppm
Slovakia	NPHV (Hraničná) (mg/m <sup>3</sup> )	568 mg/m <sup>3</sup>
Sweden	nivågränsvärde (NVG) (mg/m <sup>3</sup> )	190 mg/m <sup>3</sup>
Sweden	nivågränsvärde (NVG) (ppm)	50 ppm
Sweden	kortidsvärde (KTV) (mg/m <sup>3</sup> )	300 mg/m <sup>3</sup>
Sweden	kortidsvärde (KTV) (ppm)	75 ppm
Canada (Quebec)	VECD (mg/m <sup>3</sup> )	553 mg/m <sup>3</sup>
Canada (Quebec)	VECD (ppm)	150 ppm
Canada (Quebec)	VEMP (mg/m <sup>3</sup> )	369 mg/m <sup>3</sup>
Canada (Quebec)	VEMP (ppm)	100 ppm
Australia	TWA (mg/m <sup>3</sup> )	369 mg/m <sup>3</sup>
Australia	TWA (ppm)	100 ppm
Australia	STEL (mg/m <sup>3</sup> )	553 mg/m <sup>3</sup>
Australia	STEL (ppm)	150 ppm
Portugal	OEL TWA (mg/m <sup>3</sup> )	375 mg/m <sup>3</sup> (indicative limit value)
Portugal	OEL TWA (ppm)	100 ppm (indicative limit value)
Portugal	OEL STEL (mg/m <sup>3</sup> )	568 mg/m <sup>3</sup> (indicative limit value)
Portugal	OEL STEL (ppm)	150 ppm (indicative limit value)

# STRONTIUM ZIRCONIUM

## Safety Data Sheet

n-Butanol (71-36-3)		
Austria	MAK (mg/m <sup>3</sup> )	150 mg/m <sup>3</sup>
Austria	MAK (ppm)	50 ppm
Austria	MAK Short time value (mg/m <sup>3</sup> )	600 mg/m <sup>3</sup>
Austria	MAK Short time value (ppm)	200 ppm
Belgium	Limit value (mg/m <sup>3</sup> )	62 mg/m <sup>3</sup>
Belgium	Limit value (ppm)	20 ppm
Bulgaria	OEL TWA (mg/m <sup>3</sup> )	100 mg/m <sup>3</sup>
Bulgaria	OEL STEL (mg/m <sup>3</sup> )	150 mg/m <sup>3</sup>
France	VLE (mg/m <sup>3</sup> )	150 mg/m <sup>3</sup>
France	VLE (ppm)	50 ppm
Germany	TRGS 900 Occupational exposure limit value (mg/m <sup>3</sup> )	310 mg/m <sup>3</sup> (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Germany	TRGS 900 Occupational exposure limit value (ppm)	100 ppm (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Germany	TRGS 903 Biological limit value	10 mg/g (Medium: urine - Time: end of shift - Parameter: 1-Butanol (after hydrolysis)) 2 mg/g (Medium: urine - Time: before beginning of next shift - Parameter: 1-Butanol (after hydrolysis))
Greece	OEL TWA (mg/m <sup>3</sup> )	300 mg/m <sup>3</sup>
Greece	OEL TWA (ppm)	100 ppm
Greece	OEL STEL (mg/m <sup>3</sup> )	300 mg/m <sup>3</sup>
Greece	OEL STEL (ppm)	100 ppm
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	20 ppm
Latvia	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
USA IDLH	US IDLH (ppm)	1400 ppm (10% LEL)
USA NIOSH	NIOSH REL (ceiling) (mg/m <sup>3</sup> )	150 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (ceiling) (ppm)	50 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	300 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm
Spain	VLA-ED (mg/m <sup>3</sup> )	61 mg/m <sup>3</sup>
Spain	VLA-ED (ppm)	20 ppm
Spain	VLA-EC (mg/m <sup>3</sup> )	154 mg/m <sup>3</sup>
Spain	VLA-EC (ppm)	50 ppm
Switzerland	KZGW (mg/m <sup>3</sup> )	150 mg/m <sup>3</sup>
Switzerland	KZGW (ppm)	50 ppm
Switzerland	MAK (mg/m <sup>3</sup> )	150 mg/m <sup>3</sup>
Switzerland	MAK (ppm)	50 ppm
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	154 mg/m <sup>3</sup>
United Kingdom	WEL STEL (ppm)	50 ppm
Czech Republic	Expoziční limity (PEL) (mg/m <sup>3</sup> )	300 mg/m <sup>3</sup>
Finland	HTP-arvo (8h) (mg/m <sup>3</sup> )	150 mg/m <sup>3</sup>
Finland	HTP-arvo (8h) (ppm)	50 ppm
Finland	HTP-arvo (15 min)	230 mg/m <sup>3</sup>
Finland	HTP-arvo (15 min) (ppm)	75 ppm
Hungary	AK-érték	45 mg/m <sup>3</sup>
Hungary	CK-érték	90 mg/m <sup>3</sup>
Ireland	OEL (8 hours ref) (ppm)	20 ppm
Ireland	OEL (15 min ref) (ppm)	60 ppm (calculated)
Lithuania	IPRV (mg/m <sup>3</sup> )	45 mg/m <sup>3</sup>
Lithuania	IPRV (ppm)	15 ppm
Lithuania	NRV (mg/m <sup>3</sup> )	90 mg/m <sup>3</sup>
Lithuania	NRV (ppm)	30 ppm
Norway	Grenseverdier (Takverdi) (mg/m <sup>3</sup> )	75 mg/m <sup>3</sup>

# STRONTIUM ZIRCONIUM

## Safety Data Sheet

n-Butanol (71-36-3)		
Norway	Grønseverdier (Takverdi) (ppm)	25 ppm
Poland	NDS (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
Poland	NDSch (mg/m <sup>3</sup> )	150 mg/m <sup>3</sup>
Romania	OEL TWA (mg/m <sup>3</sup> )	100 mg/m <sup>3</sup>
Romania	OEL TWA (ppm)	33 ppm
Romania	OEL STEL (mg/m <sup>3</sup> )	200 mg/m <sup>3</sup>
Romania	OEL STEL (ppm)	66 ppm
Slovakia	NPHV (priemerná) (mg/m <sup>3</sup> )	310 mg/m <sup>3</sup>
Slovakia	NPHV (priemerná) (ppm)	100 ppm
Slovakia	NPHV (Hraničná) (mg/m <sup>3</sup> )	310 mg/m <sup>3</sup>
Sweden	nivågränsvärde (NVG) (mg/m <sup>3</sup> )	45 mg/m <sup>3</sup>
Sweden	nivågränsvärde (NVG) (ppm)	15 ppm
Sweden	takgränsvärde (TGV) (mg/m <sup>3</sup> )	90 mg/m <sup>3</sup>
Sweden	takgränsvärde (TGV) (ppm)	30 ppm
Canada (Quebec)	PLAFOND (mg/m <sup>3</sup> )	152 mg/m <sup>3</sup>
Canada (Quebec)	PLAFOND (ppm)	50 ppm
Portugal	OEL TWA (ppm)	20 ppm

### 8.2. Exposure controls

#### Appropriate engineering controls:

Provide local exhaust or general room ventilation.

#### Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

#### Hand protection:

Neoprene or nitrile rubber gloves

#### Eye protection:

Chemical goggles. Contact lenses should not be worn

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified organic vapor (black cartridge) respirator.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: Straw. Dark.
Odour	: Mild.
Odour threshold	: No data available
Refractive index	: No additional information available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: < 0 °C
Boiling point	: 117 °C initial
Flash point	: 29 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Flammable liquid and vapour.
Vapour pressure	: No data available

# STRONTIUM ZIRCONIUM

## Safety Data Sheet

Relative vapour density at 20 °C	: No data available
Relative density	: 0.96 - 1.01
% Volatiles	: > 25 %
Solubility	: Reacts with water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Stable in sealed containers.

### 10.3. Possibility of hazardous reactions

Moisture or water will slowly decompose product.

### 10.4. Conditions to avoid

Heat. Open flame. Sparks.

### 10.5. Incompatible materials

Oxidizing agent. Water.

### 10.6. Hazardous decomposition products

Organic acid vapors. Strontium oxides. Zirconium oxides.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

#### Methoxypropanol (107-98-2)

LC50 inhalation rat (mg/l)	> 6 mg/l/4h
----------------------------	-------------

#### n-Butanol (71-36-3)

LD50 oral rat	700 mg/kg
LD50 dermal rabbit	3402 mg/kg
LC50 inhalation rat (ppm)	> 8000 ppm/4h
ATE CLP (oral)	500 mg/kg bodyweight

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Symptoms/effects after inhalation	: May cause drowsiness or dizziness. May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: May be harmful if swallowed.
Reason for classification	: Expert judgment



# STRONTIUM ZIRCONIUM

## Safety Data Sheet

### SECTION 12: Ecological information

#### 12.1. Toxicity

Acute aquatic toxicity : Not classified  
Chronic aquatic toxicity : Not classified

#### Methoxypropanol (107-98-2)

LC50 fish 1	20.8 g/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	23300 mg/l (Exposure time: 48 h - Species: Daphnia magna)

#### n-Butanol (71-36-3)

LC50 fish 1	1730 - 1910 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	1983 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	1740 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 2	1897 - 2072 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])

#### 12.2. Persistence and degradability

No additional information available

#### 12.3. Bioaccumulative potential

#### Methoxypropanol (107-98-2)

BCF fish 1	< 2
Log Pow	-0.437

#### n-Butanol (71-36-3)

BCF fish 1	0.64
Log Pow	0.785 (at 25 °C)

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Results of PBT and vPvB assessment

No additional information available

#### 12.6. Other adverse effects

No additional information available

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Sewage disposal recommendations : Do not dispose of waste into sewer.  
Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to licensed waste disposal facility.  
Ecology - waste materials : Avoid release to the environment.

### SECTION 14: Transport information

#### 14.1. UN number

In accordance with ADR / RID / IMDG / IATA / ADN

#### 14.1. UN number

UN-No. (ADR) : 1993  
UN-No. (IMDG) : 1993  
UN-No. (IATA) : 1993  
UN-No. (ADN) : 1993  
UN-No. (RID) : 1993

#### 14.2. UN proper shipping name

Proper Shipping Name (ADR) : FLAMMABLE LIQUID, N.O.S.  
Proper Shipping Name (IMDG) : FLAMMABLE LIQUID, N.O.S.  
Proper Shipping Name (IATA) : Flammable liquid, n.o.s.  
Proper Shipping Name (ADN) : FLAMMABLE LIQUID, N.O.S.  
Proper Shipping Name (RID) : FLAMMABLE LIQUID, N.O.S.  
Transport document description (ADR) : UN 1993 FLAMMABLE LIQUID, N.O.S. (STRONTIUM ZIRCONIUM), 3, III, (D/E)  
Transport document description (IMDG) : UN 1993 FLAMMABLE LIQUID, N.O.S. (STRONTIUM ZIRCONIUM), 3, III  
Transport document description (IATA) : UN 1993 Flammable liquid, n.o.s. (STRONTIUM ZIRCONIUM), 3, III  
Transport document description (ADN) : UN 1993 FLAMMABLE LIQUID, N.O.S. (STRONTIUM ZIRCONIUM), 3, III  
Transport document description (RID) : UN 1993 FLAMMABLE LIQUID, N.O.S. (STRONTIUM ZIRCONIUM), 3, III

# STRONTIUM ZIRCONIUM

## Safety Data Sheet

### 14.3. Transport hazard class(es)

#### ADR

Transport hazard class(es) (ADR) : 3

Danger labels (ADR) : 3



#### IMDG

Transport hazard class(es) (IMDG) : 3

Danger labels (IMDG) : 3



#### IATA

Transport hazard class(es) (IATA) : 3

Hazard labels (IATA) : 3



#### ADN

Transport hazard class(es) (ADN) : 3

Danger labels (ADN) : 3



#### RID

Transport hazard class(es) (RID) : 3

Danger labels (RID) : 3



### 14.4. Packing group

Packing group (ADR) : III

Packing group (IMDG) : III

Packing group (IATA) : III

Packing group (ADN) : III

Packing group (RID) : III

### 14.5. Environmental hazards

Dangerous for the environment : No

Marine pollutant : No

Other information : No supplementary information available

# STRONTIUM ZIRCONIUM

## Safety Data Sheet

### 14.6. Special precautions for user

#### - Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 274, 601, 640E
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Operation (ADR)	: S2
Hazard identification number (Kemler No.)	: 30
Orange plates	:



Tunnel restriction code (ADR) : D/E

#### - Transport by sea

Special provisions (IMDG)	: 223, 274, 955
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP29
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-E
Stowage category (IMDG)	: A

#### - Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3
ERG code (IATA)	: 3L

#### - Inland waterway transport

Classification code (ADN)	: F1
Special provisions (ADN)	: 274, 601, 640E
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E1
Carriage permitted (ADN)	: T
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 0

# STRONTIUM ZIRCONIUM

## Safety Data Sheet

### - Rail transport

Classification code (RID)	: F1
Special provisions (RID)	: 274, 601, 640E
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T4
Portable tank and bulk container special provisions (RID)	: TP1, TP29
Tank codes for RID tanks (RID)	: LGBF
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W12
Colis express (express parcels) (RID)	: CE4
Hazard identification number (RID)	: 30

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.

Substance(s) are not subject to Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Directive 79/117/EEC.

Contains no REACH Annex XIV substances

% Volatiles : > 25 %

#### 15.1.2. National regulations

##### Germany

Reference to AwSV : Water hazard class (WGK) 3, Highly hazardous to water (Classification according to AwSV, Annex 1)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

##### Netherlands

SZW-lijst van kankerverwekkende stoffen : Methoxypropanol is listed

SZW-lijst van mutagene stoffen : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed

##### Denmark

Class for fire hazard : Class II-1

Store unit : 5 liter

Classification remarks : R10 <H226;H315;H318;H336>; Emergency management guidelines for the storage of flammable liquids must be followed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

### 15.2. Chemical safety assessment

No additional information available

# STRONTIUM ZIRCONIUM

## Safety Data Sheet

### SECTION 16: Other information

#### Abbreviations and acronyms:

Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor

Other information : Prepared by safety and environmental affairs.

#### Full text of H- and EUH-statements:

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

#### SDS EU (REACH Annex II) - Custom

*The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.*

© 2019 Gelest Inc. Morrisville, PA 19067