



# VINYL TERMINATED (18-22% DIETHYLSILOXANE)- DIMETHYLSILOXANE COPOLYMER

Safety Data Sheet EDV-2022

Date of issue: 06/10/2014

Version: 1.0

## SECTION 1: Identification

### 1.1. Identification

Product name : VINYL TERMINATED (18-22% DIETHYLSILOXANE)-DIMETHYLSILOXANE COPOLYMER  
 Product code : EDV-2022  
 Product form : Substance  
 Physical state : Liquid  
 Synonyms : VINYL TERMINATED DIMETHYL-DIETHYLSILOXANE COPOLYMER  
 Chemical family : ORGANOSILOXANE

### 1.2. Recommended use and restrictions on use

Recommended use : Chemical intermediate

### 1.3. Supplier

#### GELEST, INC.

11 East Steel Road  
 Morrisville, PA 19067

#### USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

[info@gelest.com](mailto:info@gelest.com) - [www.gelest.com](http://www.gelest.com)

### 1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

## SECTION 2: Hazard(s) identification

### 2.1. Classification of the substance or mixture

#### GHS-US classification

Not classified

### 2.2. GHS Label elements, including precautionary statements

#### GHS US labeling

No labeling applicable

### 2.3. Hazards not otherwise classified (HNOC)

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Substance type : Polymer  
 Name : VINYL TERMINATED (18-22% DIETHYLSILOXANE)-DIMETHYLSILOXANE COPOLYMER  
 CAS-No. : Not found

Name	Product identifier	%	GHS-US classification
Vinyl terminated (18-22% diethylsiloxane)-dimethylsiloxane copolymer	(CAS-No.) Not found	> 95	Not classified
Octamethylcyclotetrasiloxane	(CAS-No.) 556-67-2	< 2	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Eye Irrit. 2B, H320 Repr. 2, H361 Aquatic Chronic 4, H413

Full text of hazard classes and H-statements : see section 16

### 3.2. Mixtures

Not applicable

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.

# VINYL TERMINATED (18-22% DIETHYLSILOXANE)- DIMETHYLSILOXANE COPOLYMER

## Safety Data Sheet

First-aid measures after skin contact	: Wash with plenty of soap and water.
First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
First-aid measures after ingestion	: Never give anything by mouth to an unconscious person. Get medical advice/attention.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: No information available. Avoid any direct contact with the product.
Symptoms/effects after skin contact	: No information available. Avoid any direct contact with the product.
Symptoms/effects after eye contact	: May cause slight irritation.
Symptoms/effects after ingestion	: No information available. Avoid any direct contact with the product.

### 4.3. Immediate medical attention and special treatment, if necessary

No additional information available

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Water fog. Foam. Carbon dioxide. Dry chemical.

### 5.2. Specific hazards arising from the chemical

Fire hazard : Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.

### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection. Avoid all eye and skin contact and do not breathe vapor and mist.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or shovel spills into appropriate container for disposal.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling	: Avoid all eye and skin contact and do not breathe vapor and mist.
Hygiene measures	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Keep container tightly closed.
Incompatible materials	: Oxidizing agent.
Storage area	: Store in a well-ventilated place. Store away from heat.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Octamethylcyclotetrasiloxane (556-67-2)

AIHA	WEEL TWA (ppm)	10 ppm
------	----------------	--------

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation.

# VINYL TERMINATED (18-22% DIETHYLSILOXANE)- DIMETHYLSILOXANE COPOLYMER

## Safety Data Sheet

### 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

#### Hand protection:

Neoprene or nitrile rubber gloves

#### Eye protection:

Safety glasses. Contact lenses should not be worn

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear liquid.
Molecular mass	: 8000 - 12000 g/mol
Color	: No data available
Odor	: No data available
Odor threshold	: No data available
Refractive index	: 1.413
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: < -80 °C
Freezing point	: No data available
Boiling point	: > 205 °C
Flash point	: > 110 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: 0.953
% Volatiles	: < 3 %
Solubility	: Insoluble in water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: 150 - 300 cSt
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

No additional information available

# VINYL TERMINATED (18-22% DIETHYLSILOXANE)- DIMETHYLSILOXANE COPOLYMER

## Safety Data Sheet

### 10.4. Conditions to avoid

Heat. Open flame. Sparks.

### 10.5. Incompatible materials

Oxidizing agent.

### 10.6. Hazardous decomposition products

Organic acid vapors. Silicon dioxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

Octamethylcyclotetrasiloxane (556-67-2)	
LD50 oral rat	1540 mg/kg RTECS Number: GZ4397000
LD50 dermal rat	1770 mg/kg
LD50 dermal rabbit	794 µl/kg
LC50 inhalation rat (mg/l)	36 g/m <sup>3</sup> (Exposure time: 4 h)
ATE US (oral)	1540 mg/kg body weight
ATE US (dermal)	1770 mg/kg body weight
ATE US (vapors)	36 mg/l/4h
ATE US (dust, mist)	36 mg/l/4h

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity – single exposure : Not classified

Specific target organ toxicity – repeated exposure : Not classified

Aspiration hazard : Not classified

Symptoms/effects after inhalation : No information available. Avoid any direct contact with the product.

Symptoms/effects after skin contact : No information available. Avoid any direct contact with the product.

Symptoms/effects after eye contact : May cause slight irritation.

Symptoms/effects after ingestion : No information available. Avoid any direct contact with the product.

## SECTION 12: Ecological information

### 12.1. Toxicity

Octamethylcyclotetrasiloxane (556-67-2)	
LC50 fish 1	> 500 mg/l (Exposure time: 96 h - Species: Brachydanio rerio)
LC50 fish 2	> 1000 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

Octamethylcyclotetrasiloxane (556-67-2)	
BCF fish 1	12400
Log Pow	5.1

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

No additional information available

# VINYL TERMINATED (18-22% DIETHYLSILOXANE)-DIMETHYLSILOXANE COPOLYMER

## Safety Data Sheet

### SECTION 13: Disposal considerations

#### 13.1. Disposal methods

Product/Packaging disposal recommendations : Incinerate. Dispose in a safe manner in accordance with local/national regulations.  
Ecology - waste materials : Avoid release to the environment.

### SECTION 14: Transport information

#### 14.1. UN number

Not regulated for transport.

#### 14.2. UN proper shipping name

Not applicable

#### 14.3. Additional information

Other information : No supplementary information available.

#### Transport by sea

No additional information available

#### Air transport

No additional information available

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

##### VINYL TERMINATED (18-22% DIETHYLSILOXANE)-DIMETHYLSILOXANE COPOLYMER (Not found)

TSCA Exemption/Exclusion

CAUTION: This material is supplied for research and development purposes subject to the R&D exemption under TSCA, 40 CFR 720.36, and must meet the requirements of the exemption, including supervision by a "technically qualified individual" as defined by 40 CFR 720.3(ee). The use of this material for "commercial purposes" as defined by 40 CFR 720.3(r) is not permitted in the United States.

##### Octamethylcyclotetrasiloxane (556-67-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

EPA TSCA Regulatory Flag

T - T - indicates a substance that is the subject of a final TSCA section 4 test rule.

##### Vinyl terminated (18-22% diethylsiloxane)-dimethylsiloxane copolymer (Not found)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

#### 15.2. International regulations

##### CANADA

##### Octamethylcyclotetrasiloxane (556-67-2)

Listed on the Canadian DSL (Domestic Substances List)

##### EU-Regulations

##### Octamethylcyclotetrasiloxane (556-67-2)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

##### National regulations

##### Octamethylcyclotetrasiloxane (556-67-2)

Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on the Korean ECL (Existing Chemicals List)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Listed on INSQ (Mexican National Inventory of Chemical Substances)  
Listed on CICR (Turkish Inventory and Control of Chemicals)

#### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

### SECTION 16: Other information

# VINYL TERMINATED (18-22% DIETHYLSILOXANE)- DIMETHYLSILOXANE COPOLYMER

## Safety Data Sheet

Full text of H-phrases::

H226	Flammable liquid and vapor
H302	Harmful if swallowed
H312	Harmful in contact with skin
H320	Causes eye irritation
H361	Suspected of damaging fertility or the unborn child
H413	May cause long lasting harmful effects to aquatic life

Abbreviations and acronyms

: Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor.

### Hazard Rating

Health : 1 Slight Hazard - Irritation or minor reversible injury possible  
Flammability : 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)  
Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Prepared by safety and environmental affairs.

Date of issue: 06/10/2014 Version: 1.0

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

*The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.*

© 2019 Gelest Inc. Morrisville, PA 19067