



DIISOBUTYLALUMINUM HYDRIDE, 0.85M in tetrahydrofuran (14-16 wt%)

Safety Data Sheet OMAL021.5

Date of issue: 01/12/2017

Revision date: 03/05/2019

Version: 1.1

SECTION 1: Identification

1.1. Identification

Product name	: DIISOBUTYLALUMINUM HYDRIDE, 0.85M in tetrahydrofuran (14-16 wt%)
Product code	: OMAL021.5
Product form	: Mixture
Physical state	: Liquid
Formula	: C ₈ H ₁₉ Al
Synonyms	: DIBAL-H in tetrahydrofuran BIS(ISOBUTYL)HYDROALUMINUM in tetrahydrofuran HYDROBIS(2-METHYLPROPYL)ALUMINUM in tetrahydrofuran
Chemical family	: METAL ALKYL IN SOLVENT

1.2. Recommended use and restrictions on use

Recommended use	: Chemical intermediate
-----------------	-------------------------

1.3. Supplier

GELEST, INC.

11 East Steel Road
Morrisville, PA 19067
USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com

1.4. Emergency telephone number

Emergency number	: CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)
------------------	---

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable liquids Category 2
Substances and mixtures which in contact with water emit flammable gases Category 1
Acute toxicity (oral) Category 4
Skin corrosion/irritation Category 1B
Serious eye damage/eye irritation Category 1
Carcinogenicity Category 2
Specific target organ toxicity (single exposure) Category 3
Full text of H statements : see section 16

H225 Highly flammable liquid and vapor
H260 In contact with water releases flammable gases which may ignite spontaneously
H302 Harmful if swallowed
H314 Causes severe skin burns and eye damage
H318 Causes serious eye damage
H351 Suspected of causing cancer
H335 May cause respiratory irritation

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)



Signal word (GHS US)

: Danger

Hazard statements (GHS US)

: H225 - Highly flammable liquid and vapor
H260 - In contact with water releases flammable gases which may ignite spontaneously
H302 - Harmful if swallowed
H314 - Causes severe skin burns and eye damage
H318 - Causes serious eye damage
H335 - May cause respiratory irritation
H351 - Suspected of causing cancer

Precautionary statements (GHS US)

: P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P310 - Immediately call a POISON CENTER
P210 - Keep away from heat, sparks, open flames. - No smoking.
P223 - Do not allow contact with water.
P231+P232 - Handle under inert gas. Protect from moisture
P240 - Ground/Bond container and receiving equipment
P241 - Use explosion-proof electrical equipment
P242 - Use only non-sparking tools.

DIISOBUTYLALUMINUM HYDRIDE, 0.85M in tetrahydrofuran (14-16 wt%)

Safety Data Sheet

P243 - Take precautionary measures against static discharge.
P260 - Do not breathe vapors.
P264 - Wash hands thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.
P301+P312 - If swallowed: Call a POISON CENTER if you feel unwell.
P303+P361+P353 - If on skin (or hair): take off immediately all contaminated clothing. rinse skin with water/shower.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P321 - Specific treatment (see first aid instructions on this label).
P335+P334 - Brush off loose particles from skin. Immerse in cool water/wrap in wet bandages.
P363 - Wash contaminated clothing before reuse.
P370+P378 - In case of fire: Use dry chemical powder followed by sand or dolomite to extinguish.
P402+P404 - Store in a dry place. Store in a closed container.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P403+P235 - Keep in a cool place.
P405 - Store locked up.
P501 - Dispose of contents/container to licensed waste disposal facility.

2.3. Hazards not otherwise classified (HNOC)

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Tetrahydrofuran	(CAS-No.) 109-99-9	84 - 86	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Eye Irrit. 2A, H319 Carc. 2, H351 STOT SE 3, H335
Diisobutylaluminum hydride	(CAS-No.) 1191-15-7	14 - 16	Pyr. Liq. 1, H250 Water-react. 1, H260 Skin Corr. 1B, H314 Eye Dam. 1, H318

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician.
First-aid measures after skin contact	: Wash with plenty of soap and water. Get immediate medical advice/attention.
First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Get immediate medical advice/attention.
First-aid measures after ingestion	: Never give anything by mouth to an unconscious person. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects	: Causes severe skin burns and eye damage. Suspected of causing cancer.
Symptoms/effects after inhalation	: May cause respiratory irritation. The solvent, tetrahydrofuran, is mildly toxic by inhalation.
Symptoms/effects after skin contact	: Causes (severe) skin burns.
Symptoms/effects after eye contact	: Causes serious eye damage.
Symptoms/effects after ingestion	: Harmful if swallowed. Presumed to be a poison. Swallowing a small quantity of this material will result in serious health hazard.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

DIISOBUTYLALUMINUM HYDRIDE, 0.85M in tetrahydrofuran (14-16 wt%)

Safety Data Sheet

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Dry chemical powder followed by sand or dolomite.
- Unsuitable extinguishing media : Water.

5.2. Specific hazards arising from the chemical

- Fire hazard : Highly flammable liquid and vapor. In contact with water releases flammable gases which may ignite spontaneously.
- Explosion hazard : Container explosion may occur during fire conditions. May form flammable/explosive vapor-air mixture.

5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : If material is ignited, allow to burn. Exercise caution when fighting any chemical fire. In case of fire: Stop leak if safe to do so.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Avoid all eye and skin contact and do not breathe vapor and mist.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Eliminate every possible source of ignition. Use special care to avoid static electric charges. Laboratory and production areas must be equipped with special fire-extinguishing media for pyrophorics.

6.1.1. For non-emergency personnel

- Protective equipment : Wear protective equipment as described in Section 8.
- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

- Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Concentrate containment efforts to adjacent combustibles.
- Methods for cleaning up : Cover with dry chemical extinguishing powder, lime, sand or soda ash. Do not use water. Remove combustible materials in the vicinity of the spill. Allow time for decomposition or fire to burn out, then sweep material and transfer to a suitable container for disposal. Use only non-sparking tools.

6.4. Reference to other sections

- See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapors are flammable. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep away from any possible contact with water, because of violent reaction and possible flash fire.
- Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapor and mist. Do not allow contact with water. Handle under inert gas. Protect from moisture. Laboratory and production areas must be equipped with special fire-extinguishing media for pyrophorics. Take precautionary measures against static discharge. Ground/bond container and receiving equipment. Use only outdoors or in a well-ventilated area. Use only non-sparking tools.
- Hygiene measures : Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof electrical equipment.
- Storage conditions : Keep container tightly closed. Store in a dry place. Store in a closed container. Store locked up. Store in sealed containers under nitrogen or argon with <10ppm oxygen. Store < 10°C.
- Incompatible materials : Alkalis. Bromine. Chlorine. Metal salts. Oxidizing agent. Water. Dry residue has been reported to explode.
- Information on mixed storage : Flammable and combustible materials should not be stored in or near working areas for pyrophorics.

DIISOBUTYLALUMINUM HYDRIDE, 0.85M in tetrahydrofuran (14-16 wt%)

Safety Data Sheet

Storage area : Store in a well-ventilated place. Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Diisobutylaluminum hydride (1191-15-7)		
ACGIH	ACGIH TWA (mg/m ³)	2 mg/m ³
OSHA	OSHA PEL (TWA) (mg/m ³)	2 mg/m ³
Tetrahydrofuran (109-99-9)		
ACGIH	ACGIH TWA (ppm)	50 ppm
ACGIH	ACGIH STEL (ppm)	100 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	590 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	200 ppm
IDLH	US IDLH (ppm)	2000 ppm (10% LEL)
NIOSH	NIOSH REL (TWA) (mg/m ³)	590 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	200 ppm
NIOSH	NIOSH REL (STEL) (mg/m ³)	735 mg/m ³
NIOSH	NIOSH REL (STEL) (ppm)	250 ppm

8.2. Appropriate engineering controls

Appropriate engineering controls : Glove box or sealed system under inert atmosphere is required. Provide local exhaust or general room ventilation.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Hand protection:

Neoprene or nitrile rubber gloves

Eye protection:

Full face shield with chemical workers goggles. Contact lenses should not be worn

Skin and body protection:

Wear suitable protective clothing. Fire resistant laboratory jacket or apron should be worn.

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified organic vapor (black cartridge) respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear liquid. Fumes and ignites in air.
Molecular mass	: 142.22 g/mol
Color	: No data available
Odor	: No data available
Odor threshold	: No data available
Refractive index	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: < 0 °C
Freezing point	: No data available
Boiling point	: 65 °C initial (tetrahydrofuran)
Flash point	: -14 °C

DIISOBUTYLALUMINUM HYDRIDE, 0.85M in tetrahydrofuran (14-16 wt%)

Safety Data Sheet

Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Highly flammable liquid and vapor, In contact with water releases flammable gases which may ignite spontaneously
Vapor pressure	: No data available
Relative vapor density at 20 °C	: > 1
Relative density	: 0.84
Solubility	: Reacts violently with water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable in sealed containers under dry inert atmosphere when stored <10°C. Product activity decreases ~1%/month if stored at 20°C.

10.3. Possibility of hazardous reactions

The product can generate small amounts of hydrogen when exposed to alkalis and protic materials such as water and alcohol.

10.4. Conditions to avoid

Heat. Open flame. Sparks.

10.5. Incompatible materials

Alkalis. Bromine. Chlorine. Metal salts. Oxidizing agent. Water. Dry residue has been reported to explode.

10.6. Hazardous decomposition products

Aluminum oxides. Carbon monoxide. Formaldehyde. Hydrogen. Organic acid vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

DIISOBUTYLALUMINUM HYDRIDE, 0.85M in tetrahydrofuran (14-16 wt%) (1191-15-7)

ATE US (oral)	1918.605 mg/kg body weight
---------------	----------------------------

Tetrahydrofuran (109-99-9)

LD50 oral rat	1650 mg/kg
LC50 inhalation rat (ppm)	21000 ppm (Exposure time: 3 h)
ATE US (oral)	1650 mg/kg body weight

Skin corrosion/irritation	: Causes severe skin burns and eye damage.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.

Tetrahydrofuran (109-99-9)

National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity
--	---------------------------------

Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: May cause respiratory irritation.

Specific target organ toxicity – repeated exposure	: Not classified May cause damage to organs through prolonged or repeated exposure
--	---

Aspiration hazard	: Not classified
-------------------	------------------

DIISOBUTYLALUMINUM HYDRIDE, 0.85M in tetrahydrofuran (14-16 wt%)

Safety Data Sheet

Potential Adverse human health effects and symptoms	: The solvent, tetrahydrofuran affects liver and kidney function.
Symptoms/effects after inhalation	: May cause respiratory irritation. The solvent, tetrahydrofuran, is mildly toxic by inhalation.
Symptoms/effects after skin contact	: Causes (severe) skin burns.
Symptoms/effects after eye contact	: Causes serious eye damage.
Symptoms/effects after ingestion	: Harmful if swallowed. Presumed to be a poison. Swallowing a small quantity of this material will result in serious health hazard.
Reason for classification	: Expert judgment

SECTION 12: Ecological information

12.1. Toxicity

Tetrahydrofuran (109-99-9)	
LC50 fish 1	1970 - 2360 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 fish 2	2700 - 3600 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Tetrahydrofuran (109-99-9)	
BCF fish 1	(will not bioconcentrate)
Log Pow	0.45 (at 25 °C)

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other adverse effects	: This substance may be hazardous to the environment.
Effect on the ozone layer	: No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Sewage disposal recommendations	: Do not dispose of waste into sewer.
Product/Packaging disposal recommendations	: Incinerate. Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to licensed waste disposal facility. This is a RCRA hazardous waste: 40 CFR 261.21 (i.e. ignitable) 40 CFR 261.23 (i.e. reactive).
Additional information	: Handle empty containers with care because residual vapors are flammable.
Ecology - waste materials	: Avoid release to the environment.

SECTION 14: Transport information

14.1. UN number

UN-No.(DOT)	: 3399
DOT NA no.	UN3399

14.2. UN proper shipping name

Transport document description	: UN3399 Organometallic substance, liquid, water-reactive, flammable (DIISOBUTYLALUMINUM HYDRIDE, 0.85M in tetrahydrofuran (14-16 wt%)), 4.3 (3), I
Proper Shipping Name (DOT)	: Organometallic substance, liquid, water-reactive, flammable (DIISOBUTYLALUMINUM HYDRIDE, 0.85M in tetrahydrofuran (14-16 wt%))
Class (DOT)	: 4.3 - Class 4.3 - Dangerous when wet material 49 CFR 173.124
Packing group (DOT)	: I - Great Danger
Hazard labels (DOT)	: 4.3 - Dangerous when wet 3 - Flammable liquid



DOT Packaging Non Bulk (49 CFR 173.xxx)	: 201
DOT Packaging Bulk (49 CFR 173.xxx)	: 244
DOT Packaging Exceptions (49 CFR 173.xxx)	: None

DIISOBUTYLALUMINUM HYDRIDE, 0.85M in tetrahydrofuran (14-16 wt%)

Safety Data Sheet

DOT Symbols : G - Identifies PSN requiring a technical name

14.3. Additional information

Emergency Response Guide (ERG) Number : 138

Other information : No supplementary information available.

Transport by sea

DOT Vessel Stowage Location : D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger vessels in which the limiting number of passengers is exceeded.

DOT Vessel Stowage Other : 13 - Keep as dry as reasonably practicable, 40 - Stow "clear of living quarters", 52 - Stow "separated from" acids

Air transport

DOT Quantity Limitations Passenger aircraft/rail : Forbidden
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 1 L
CFR 175.75)

SECTION 15: Regulatory information

15.1. US Federal regulations

Diisobutylaluminum hydride (1191-15-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Tetrahydrofuran (109-99-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

EPA TSCA Regulatory Flag : T - T - indicates a substance that is the subject of a final TSCA section 4 test rule.

15.2. International regulations

CANADA

Diisobutylaluminum hydride (1191-15-7)

Listed on the Canadian NDSL (Non-Domestic Substances List)

Tetrahydrofuran (109-99-9)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification : Class B Division 2 - Flammable Liquid
Class D Division 2 Subdivision B - Toxic material causing other toxic effects

EU-Regulations

Diisobutylaluminum hydride (1191-15-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Tetrahydrofuran (109-99-9)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

Diisobutylaluminum hydride (1191-15-7)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

DIISOBUTYLALUMINUM HYDRIDE, 0.85M in tetrahydrofuran (14-16 wt%)

Safety Data Sheet

Tetrahydrofuran (109-99-9)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the Canadian IDL (Ingredient Disclosure List)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Diisobutylaluminum hydride (1191-15-7)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Tetrahydrofuran (109-99-9)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Full text of H-phrases::

H225	Highly flammable liquid and vapor
H250	Catches fire spontaneously if exposed to air
H260	In contact with water releases flammable gases which may ignite spontaneously
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H351	Suspected of causing cancer

Abbreviations and acronyms

: Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor.

Hazard Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

Flammability : 4 Severe Hazard - Flammable gases, or very volatile flammable liquids with flash points below 73 F, and boiling points below 100 F. Materials may ignite spontaneously with air. (Class IA)

Physical : 2 Moderate Hazard - Materials that are unstable and may undergo violent chemical changes at normal temperature and pressure with low risk for explosion. Materials may react violently with water or form peroxides upon exposure to air.

Prepared by safety and environmental affairs.

Date of issue: 01/12/2017 Revision date: 03/05/2019 Version: 1.1

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DIISOBUTYLALUMINUM HYDRIDE, 0.85M in tetrahydrofuran (14-16 wt%)

Safety Data Sheet

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2019 Gelest Inc. Morrisville, PA 19067

