



## TRIMETHYLALUMINUM, 2M in toluene (17-18 wgt%)

Safety Data Sheet OMAL086.4

Date of issue: 15/07/2015 Version: 1.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form	: Mixture
Physical state	: Liquid
Product name	: TRIMETHYLALUMINUM, 2M in toluene (17-18 wgt%)
Product code	: OMAL086.4
Formula	: C <sub>3</sub> H <sub>9</sub> Al
Synonyms	: TRIMETHYLALANE
Chemical family	: ORGANOMETAL

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Use of the substance/mixture : Chemical intermediate

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

##### GELEST, INC.

11 East Steel Road  
Morrisville, PA 19067

##### USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

[info@gelest.com](mailto:info@gelest.com) - [www.gelest.com](http://www.gelest.com)

##### GELEST INC.

Fritz-Klatte-Strasse 8  
65933 Frankfurt

##### Germany

T +49 (0) 69 3535106-500 - F +49 (0) 69 3535106-501 - (M-F): 8:00 AM - 4:00 PM

[info@gelestde.com](mailto:info@gelestde.com) - [www.gelestde.com](http://www.gelestde.com)

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2	H225
Pyrophoric Liquids, Category 1	H250
Substances and Mixtures which, in contact with water, emit flammable gases, Category 1	H260
Skin corrosion/irritation, Category 1B	H314
Serious eye damage/eye irritation, Category 1	H318
Reproductive toxicity, Category 2	H361
Specific target organ toxicity — Single exposure, Category 3, Narcosis	H336
Specific target organ toxicity — Repeated exposure, Category 2	H373
Hazardous to the aquatic environment — Chronic Hazard, Category 3	H412
Full text of H statements : see section 16	

##### Adverse physicochemical, human health and environmental effects

No additional information available

# TRIMETHYLALUMINUM, 2M in toluene (17-18 wgt%)

## Safety Data Sheet

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) :

Danger

Hazardous ingredients :

Trimethylaluminium; Toluene

Hazard statements (CLP) :

H225 - Highly flammable liquid and vapour.  
H250 - Catches fire spontaneously if exposed to air.  
H260 - In contact with water releases flammable gases which may ignite spontaneously.  
H314 - Causes severe skin burns and eye damage.  
H336 - May cause drowsiness or dizziness.  
H361 - Suspected of damaging fertility or the unborn child.  
H373 - May cause damage to organs through prolonged or repeated exposure.  
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) :

P202 - Do not handle until all safety precautions have been read and understood.  
P264 - Wash hands, forearms and face thoroughly after handling.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P223 - Do not allow contact with water.  
P231+P232 - Handle under inert gas. Protect from moisture.  
P310 - Immediately call a POISON CENTER or doctor/physician

EUH-statements

: EUH014 - Reacts violently with water.

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Toluene	(CAS-No.) 108-88-3 (EC-No.) 203-625-9 (EC Index-No.) 601-021-00-3 (REACH-no) 01-2119471310-51-0127	83 - 86	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
Trimethylaluminium	(CAS-No.) 75-24-1 (EC-No.) 200-853-0	14 - 17	Flam. Liq. 2, H225 Pyr. Liq. 1, H250 Water-react. 1, H260 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general

: Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.

First-aid measures after inhalation

: Remove person to fresh air and keep comfortable for breathing. If you feel unwell, seek medical advice.

First-aid measures after skin contact

: Wash with plenty of water/.... Get immediate medical advice/attention.

First-aid measures after eye contact

: Immediately flush eyes thoroughly with water for at least 15 minutes. Get immediate medical advice/attention.

# TRIMETHYLALUMINUM, 2M in toluene (17-18 wgt%)

## Safety Data Sheet

First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Get medical advice/attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Causes severe skin burns and eye damage. Causes damage to organs.  
Symptoms/effects after inhalation : May cause drowsiness or dizziness. May cause respiratory irritation. Direct respiratory contact is usually not possible, but will cause burns. Inhalation of combustion products can cause irritation. Vapor inhalation of toluene may lead to impairment of coordination mental alertness, and reaction times, leading to accident proneness. Exposure to levels around 500ppm leads to narcotic effects including nausea, headache and mental confusion. Overexposure may cause: Cough. Headache. Nausea.  
Symptoms/effects after skin contact : Causes (severe) skin burns. Causes skin irritation.  
Symptoms/effects after eye contact : Causes serious eye damage. Causes serious eye irritation.  
Symptoms/effects after ingestion : Presumed to be a poison.  
Chronic symptoms : Target organs presumed to be brain and liver.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Dry chemical powder followed by sand or dolomite.  
Unsuitable extinguishing media : Water.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Catches fire spontaneously if exposed to air. Pyrophoric liquid. Highly flammable liquid and vapour.  
Explosion hazard : Container explosion may occur during fire conditions. May form flammable/explosive vapour-air mixture.

### 5.3. Advice for firefighters

Firefighting instructions : If material is ignited, allow to burn. Exercise caution when fighting any chemical fire. In case of fire: stop leak if safe to do so.  
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Avoid all eye and skin contact and do not breathe vapour and mist.  
Other information : Can spontaneously ignite on contact with air.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Laboratory and production areas must be equipped with special fire-extinguishing media for pyrophorics. Eliminate every possible source of ignition. Use special care to avoid static electric charges.

#### 6.1.1. For non-emergency personnel

Protective equipment : Wear protective equipment as described in Section 8.  
Emergency procedures : Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".  
Emergency procedures : Stop release.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

For containment : Concentrate containment efforts to adjacent combustibles.  
Methods for cleaning up : Cover with dry chemical extinguishing powder, lime, sand or soda ash. Do not use water. Remove combustible materials in the vicinity of the spill. Allow time for decomposition or fire to burn out, then sweep material and transfer to a suitable container for disposal. Use only non-sparking tools.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapours are flammable. Catches fire spontaneously if exposed to air. Do not allow contact with water.

# TRIMETHYLALUMINUM, 2M in toluene (17-18 wgt%)

## Safety Data Sheet

Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapour and mist. Provide good ventilation in process area to prevent formation of vapour. Protect from moisture. Handle under inert gas. Use only outdoors or in a well-ventilated area. Take precautionary measures against static discharge. Use only non-sparking tools.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof electrical equipment.

Storage conditions : Keep container tightly closed. Store in sealed containers under nitrogen or argon with <10ppm oxygen. Flammable and combustible materials should not be stored in or near working areas for pyrophorics. Store in a dry place. Protect from moisture.

Incompatible materials : Alkalis. Bromine. Chlorine. Metal salts. Oxidizing agent. Precious metals. Water :

Information on mixed storage : Flammable and combustible materials should not be stored in or near working areas for pyrophorics.

Storage area : Store in a well-ventilated place. Store away from heat.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Trimethylaluminium (75-24-1)		
Italy - Portugal - USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
Toluene (108-88-3)		
EU	IOELV TWA (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup>
EU	IOELV TWA (ppm)	50 ppm
EU	IOELV STEL (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
EU	IOELV STEL (ppm)	100 ppm
Austria	MAK (mg/m <sup>3</sup> )	190 mg/m <sup>3</sup>
Austria	MAK (ppm)	50 ppm
Austria	MAK Short time value (mg/m <sup>3</sup> )	380 mg/m <sup>3</sup>
Austria	MAK Short time value (ppm)	100 ppm
Belgium	Limit value (mg/m <sup>3</sup> )	77 mg/m <sup>3</sup>
Belgium	Limit value (ppm)	20 ppm
Belgium	Short time value (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
Belgium	Short time value (ppm)	100 ppm
Bulgaria	OEL TWA (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup>
Bulgaria	OEL TWA (ppm)	50 ppm
Bulgaria	OEL STEL (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
Bulgaria	OEL STEL (ppm)	100 ppm
Cyprus	OEL TWA (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup>
Cyprus	OEL TWA (ppm)	50 ppm
Cyprus	OEL STEL (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
Cyprus	OEL STEL (ppm)	100 ppm
France	VLE (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup> (restrictive limit)
France	VLE (ppm)	100 ppm (restrictive limit)
France	VME (mg/m <sup>3</sup> )	76.8 mg/m <sup>3</sup> (restrictive limit)
France	VME (ppm)	20 ppm (restrictive limit)
Germany	TRGS 900 Occupational exposure limit value (mg/m <sup>3</sup> )	190 mg/m <sup>3</sup> (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Germany	TRGS 900 Occupational exposure limit value (ppm)	50 ppm (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Germany	TRGS 903 Biological limit value	600 µg/l (Medium: whole blood - Time: end of shift - Parameter: Toluene) 1.5 mg/l (Medium: urine - Time: end of several shifts - Parameter: o-Cresol (after hydrolysis))
Gibraltar	Eight hours mg/m <sup>3</sup>	192 mg/m <sup>3</sup>
Gibraltar	Eight hours ppm	50 ppm
Gibraltar	Short-term mg/m <sup>3</sup>	384 mg/m <sup>3</sup>

# TRIMETHYLALUMINUM, 2M in toluene (17-18 wgt%)

## Safety Data Sheet

Toluene (108-88-3)		
Gibraltar	Short-term ppm	100 ppm
Greece	OEL TWA (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup>
Greece	OEL TWA (ppm)	50 ppm
Greece	OEL STEL (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
Greece	OEL STEL (ppm)	100 ppm
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	20 ppm
Italy	OEL TWA (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup>
Italy	OEL TWA (ppm)	50 ppm
Latvia	OEL TWA (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
Latvia	OEL TWA (ppm)	14 ppm
USA IDLH	US IDLH (ppm)	500 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	375 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m <sup>3</sup> )	560 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (STEL) (ppm)	150 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
USA OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm
Spain	VLA-ED (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup> (indicative limit value; manufacturing, commercialization, and use restrictions under REACH)
Spain	VLA-ED (ppm)	50 ppm (indicative limit value; manufacturing, commercialization, and use restrictions under REACH)
Spain	VLA-EC (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
Spain	VLA-EC (ppm)	100 ppm
Switzerland	KZGW (mg/m <sup>3</sup> )	760 mg/m <sup>3</sup>
Switzerland	KZGW (ppm)	200 ppm
Switzerland	MAK (mg/m <sup>3</sup> )	190 mg/m <sup>3</sup>
Switzerland	MAK (ppm)	50 ppm
Netherlands	Grenswaarde TGG 8H (mg/m <sup>3</sup> )	150 mg/m <sup>3</sup>
Netherlands	Grenswaarde TGG 15MIN (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	191 mg/m <sup>3</sup>
United Kingdom	WEL TWA (ppm)	50 ppm
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
United Kingdom	WEL STEL (ppm)	100 ppm
Czech Republic	Expoziční limity (PEL) (mg/m <sup>3</sup> )	200 mg/m <sup>3</sup>
Denmark	Grænseværdie (langvarig) (mg/m <sup>3</sup> )	94 mg/m <sup>3</sup>
Denmark	Grænseværdie (langvarig) (ppm)	25 ppm
Finland	HTP-arvo (8h) (mg/m <sup>3</sup> )	81 mg/m <sup>3</sup>
Finland	HTP-arvo (8h) (ppm)	25 ppm
Finland	HTP-arvo (15 min)	380 mg/m <sup>3</sup>
Finland	HTP-arvo (15 min) (ppm)	100 ppm
Hungary	AK-érték	190 mg/m <sup>3</sup>
Hungary	CK-érték	380 mg/m <sup>3</sup>
Ireland	OEL (8 hours ref) (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup>
Ireland	OEL (8 hours ref) (ppm)	50 ppm
Ireland	OEL (15 min ref) (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
Ireland	OEL (15 min ref) (ppm)	100 ppm
Lithuania	IPRV (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup>
Lithuania	IPRV (ppm)	50 ppm
Lithuania	TPRV (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
Lithuania	TPRV (ppm)	100 ppm
Malta	OEL TWA (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup>
Malta	OEL TWA (ppm)	50 ppm

# TRIMETHYLALUMINUM, 2M in toluene (17-18 wgt%)

## Safety Data Sheet

Toluene (108-88-3)		
Malta	OEL STEL (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
Malta	OEL STEL (ppm)	100 ppm
Norway	Grenseverdier (AN) (mg/m <sup>3</sup> )	94 mg/m <sup>3</sup>
Norway	Grenseverdier (AN) (ppm)	25 ppm
Norway	Grenseverdier (Korttidsverdi) (mg/m <sup>3</sup> )	94 mg/m <sup>3</sup>
Norway	Grenseverdier (Korttidsverdi) (ppm)	25 ppm
Poland	NDS (mg/m <sup>3</sup> )	100 mg/m <sup>3</sup>
Poland	NDSch (mg/m <sup>3</sup> )	200 mg/m <sup>3</sup>
Romania	OEL TWA (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup>
Romania	OEL TWA (ppm)	50 ppm
Romania	OEL STEL (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
Romania	OEL STEL (ppm)	100 ppm
Slovakia	NPHV (priemerná) (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup>
Slovakia	NPHV (priemerná) (ppm)	50 ppm
Slovakia	NPHV (Hraničná) (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
Sweden	nivågränsvärde (NVG) (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup>
Sweden	nivågränsvärde (NVG) (ppm)	50 ppm
Sweden	kortidsvärde (KTV) (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
Sweden	kortidsvärde (KTV) (ppm)	100 ppm
Canada (Quebec)	VEMP (mg/m <sup>3</sup> )	188 mg/m <sup>3</sup>
Canada (Quebec)	VEMP (ppm)	50 ppm
Australia	TWA (mg/m <sup>3</sup> )	191 mg/m <sup>3</sup>
Australia	TWA (ppm)	50 ppm
Australia	STEL (mg/m <sup>3</sup> )	574 mg/m <sup>3</sup>
Australia	STEL (ppm)	150 ppm
Portugal	OEL TWA (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup> (indicative limit value)
Portugal	OEL TWA (ppm)	50 ppm (indicative limit value)
Portugal	OEL STEL (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup> (indicative limit value)
Portugal	OEL STEL (ppm)	100 ppm (indicative limit value)
Portugal	OEL chemical category (PT)	A4 - Not Classifiable as a Human Carcinogen, skin - potential for cutaneous exposure indicative limit value

### 8.2. Exposure controls

#### Appropriate engineering controls:

Glove box or sealed system under inert atmosphere is required. Provide local exhaust or general room ventilation.

#### Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

#### Hand protection:

Neoprene or nitrile rubber gloves

#### Eye protection:

Full face shield with chemical workers goggles. Contact lenses should not be worn

#### Skin and body protection:

Wear suitable protective clothing. Fire resistant laboratory jacket or apron should be worn.

#### Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified organic vapor (black cartridge) respirator.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Appearance : Clear liquid. Fumes and ignites in air.



# TRIMETHYLALUMINUM, 2M in toluene (17-18 wgt%)

## Safety Data Sheet

Molecular mass	: 72.09 g/mol
Colour	: No data available
Odour	: No data available
Odour threshold	: No data available
Refractive index	: No additional information available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: 15 °C (neat)
Freezing point	: No data available
Boiling point	: 125 - 126 °C (neat)
Flash point	: 4 °C
Auto-ignition temperature	: < 50 °C (Pyrophoric)
Decomposition temperature	: No data available
Flammability (solid, gas)	: Highly flammable liquid and vapour, Catches fire spontaneously if exposed to air.
Vapour pressure	: < 1 mm Hg
Relative vapour density at 20 °C	: > 1
Relative density	: 0.81
Solubility	: Reacts violently with water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Stable in sealed containers stored under a dry inert atmosphere.

### 10.3. Possibility of hazardous reactions

Catches fire spontaneously if exposed to air. In contact with water releases flammable gases which may ignite spontaneously. The product can generate small amounts of hydrogen when exposed to alkalis and protic materials such as water and alcohol.

### 10.4. Conditions to avoid

Heat. Sparks. Open flame.

### 10.5. Incompatible materials

Alkalis. Bromine. Chlorine. Metal salts. Oxidizing agent. Precious metals. Water :

### 10.6. Hazardous decomposition products

Aluminium oxides. Carbon monoxide. Formaldehyde. Hydrogen. Organic acid vapours.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

<b>Toluene (108-88-3)</b>	
LD50 oral rat	2600 mg/kg
LD50 dermal rabbit	12000 mg/kg
LC50 inhalation rat (mg/l)	12.5 mg/l/4h
ATE CLP (oral)	2600 mg/kg bodyweight
ATE CLP (dermal)	12000 mg/kg bodyweight
ATE CLP (vapours)	12.5 mg/l/4h
ATE CLP (dust,mist)	12.5 mg/l/4h

Skin corrosion/irritation : Causes severe skin burns and eye damage.

Serious eye damage/irritation : Causes serious eye damage.

# TRIMETHYLALUMINUM, 2M in toluene (17-18 wgt%)

## Safety Data Sheet

Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

### Toluene (108-88-3)

IARC group	3 - Not classifiable
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
Symptoms/effects after inhalation	: May cause drowsiness or dizziness. May cause respiratory irritation. Direct respiratory contact is usually not possible, but will cause burns. Inhalation of combustion products can cause irritation. Vapor inhalation of toluene may lead to impairment of coordination mental alertness, and reaction times, leading to accident proneness. Exposure to levels around 500ppm leads to narcotic effects including nausea, headache and mental confusion. Overexposure may cause: Cough. Headache. Nausea.
Symptoms/effects after skin contact	: Causes (severe) skin burns. Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye damage. Causes serious eye irritation.
Symptoms/effects after ingestion	: Presumed to be a poison.
Chronic symptoms	: Target organs presumed to be brain and liver.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: Harmful to aquatic life.
Acute aquatic toxicity	: Not classified
Chronic aquatic toxicity	: Harmful to aquatic life with long lasting effects.

### Toluene (108-88-3)

LC50 fish 1	15.22 - 19.05 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	5.46 - 9.83 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 fish 2	12.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	11.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

### Toluene (108-88-3)

Log Pow	2.65
---------	------

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

Other adverse effects	: This substance may be hazardous to the environment.
-----------------------	---

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product/Packaging disposal recommendations	: Incinerate. Dispose in a safe manner in accordance with local/national regulations. This is a RCRA hazardous waste: 40 CFR 261.21 (i.e. ignitable) 40 CFR 261.23 (i.e. reactive).
Additional information	: Handle empty containers with care because residual vapours are flammable.
Ecology - waste materials	: Avoid release to the environment.

## SECTION 14: Transport information

### 14.1. UN number

In accordance with ADR / RID / IMDG / IATA / ADN

### 14.1. UN number

UN-No. (ADR)	: 3394
UN-No. (IMDG)	: 3394
UN-No. (IATA)	: 3394



# TRIMETHYLALUMINUM, 2M in toluene (17-18 wgt%)

## Safety Data Sheet

UN-No. (ADN) : 3394  
UN-No. (RID) : 3394

### 14.2. UN proper shipping name

Proper Shipping Name (ADR) : ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATERREACTIVE  
Proper Shipping Name (IMDG) : ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE  
Proper Shipping Name (IATA) : Organometallic substance, liquid, pyrophoric, water-reactive  
Proper Shipping Name (ADN) : ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATERREACTIVE  
Proper Shipping Name (RID) : ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE  
Transport document description (ADR) : UN 3394 ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATERREACTIVE (TRIMETHYLALUMINUM, 2M in toluene (17-18 wgt%)), 4.2 (4.3), I, (B/E)  
Transport document description (IMDG) : UN 3394 ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE (TRIMETHYLALUMINUM, 2M in toluene (17-18 wgt%)), 4.2 (4.3), I  
Transport document description (IATA) : UN 3394 Organometallic substance, liquid, pyrophoric, water-reactive (TRIMETHYLALUMINUM, 2M in toluene (17-18 wgt%)), 4.2  
Transport document description (ADN) : UN 3394 ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATERREACTIVE (TRIMETHYLALUMINUM, 2M in toluene (17-18 wgt%)), 4.2 (4.3), I  
Transport document description (RID) : UN 3394 ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE (TRIMETHYLALUMINUM, 2M in toluene (17-18 wgt%)), 4.2 (4.3), I

### 14.3. Transport hazard class(es)

#### ADR

Transport hazard class(es) (ADR) : 4.2 (4.3)  
Danger labels (ADR) : 4.2, 4.3



#### IMDG

Transport hazard class(es) (IMDG) : 4.2 (4.3)  
Danger labels (IMDG) : 4.2, 4.3



#### IATA

Transport hazard class(es) (IATA) : 4.2 (4.3)

#### ADN

Transport hazard class(es) (ADN) : 4.2 (4.3)  
Danger labels (ADN) : 4.2, 4.3



#### RID

Transport hazard class(es) (RID) : 4.2 (4.3)  
Danger labels (RID) : 4.2, 4.3



# TRIMETHYLALUMINUM, 2M in toluene (17-18 wgt%)

## Safety Data Sheet

### 14.4. Packing group


Packing group (ADR)	: I
Packing group (IMDG)	: I
Packing group (IATA)	: Not applicable
Packing group (ADN)	: I
Packing group (RID)	: I

### 14.5. Environmental hazards

Dangerous for the environment	: No
Marine pollutant	: No
Other information	: No supplementary information available

### 14.6. Special precautions for user

#### - Overland transport

Classification code (ADR)	: SW
Special provisions (ADR)	: 274
Limited quantities (ADR)	: 0
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P400
Mixed packing provisions (ADR)	: MP2
Portable tank and bulk container instructions (ADR)	: T21
Portable tank and bulk container special provisions (ADR)	: TP2, TP7, TP36
Tank code (ADR)	: L21DH
Tank special provisions (ADR)	: TU4, TU14, TU22, TC1, TE21, TM1
Vehicle for tank carriage	: AT
Transport category (ADR)	: 0
Special provisions for carriage - Packages (ADR)	: V1
Special provisions for carriage - Operation (ADR)	: S20
Hazard identification number (Kemler No.)	: X333
Orange plates	: 
Tunnel restriction code (ADR)	: B/E
EAC code	: 4W

#### - Transport by sea

Special provisions (IMDG)	: 274
Limited quantities (IMDG)	: 0
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P400
Special packing provisions (IMDG)	: PP86
Tank instructions (IMDG)	: T21
Tank special provisions (IMDG)	: TP2, TP7, TP36, TP41
EmS-No. (Fire)	: F-G
EmS-No. (Spillage)	: S-M
Stowage category (IMDG)	: D
Stowage and handling (IMDG)	: H1
Segregation (IMDG)	: SG35, SG63, SG26
Properties and observations (IMDG)	: Highly flammable liquid. Liable to ignite spontaneously in air. In contact with air, evolve irritating and slightly toxic fumes. React violently with moisture, water and acids evolving flammable gas.

#### - Air transport

PCA Limited quantities (IATA)	: Forbidden
PCA limited quantity max net quantity (IATA)	: Forbidden
PCA packing instructions (IATA)	: Forbidden

# TRIMETHYLALUMINUM, 2M in toluene (17-18 wgt%)

## Safety Data Sheet

PCA max net quantity (IATA) : Forbidden  
CAO packing instructions (IATA) : Forbidden  
CAO max net quantity (IATA) : Forbidden  
ERG code (IATA) : 4W

### - Inland waterway transport

Classification code (ADN) : SW  
Special provisions (ADN) : 274  
Limited quantities (ADN) : 0  
Excepted quantities (ADN) : E0  
Equipment required (ADN) : PP, EX, A  
Ventilation (ADN) : VE01  
Number of blue cones/lights (ADN) : 0

### - Rail transport

Classification code (RID) : SW  
Special provisions (RID) : 274  
Limited quantities (RID) : 0  
Excepted quantities (RID) : E0  
Packing instructions (RID) : P400  
Special packing provisions (RID) : PP86  
Mixed packing provisions (RID) : MP2  
Portable tank and bulk container instructions (RID) : T21  
Portable tank and bulk container special provisions (RID) : TP2, TP7, TP36, TP41  
Tank codes for RID tanks (RID) : L21DH  
Special provisions for RID tanks (RID) : TU4, TU14, TU22, TU38, TC1, TE21, TE22, TE25, TM1  
Transport category (RID) : 0  
Special provisions for carriage – Packages (RID) : W1  
Hazard identification number (RID) : X333

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.

Substance(s) are not subject to Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Directive 79/117/EEC.

Contains no REACH Annex XIV substances

#### 15.1.2. National regulations

##### Germany

Reference to AwSV : Water hazard class (WGK) nwg, Non-hazardous to water (Classification according to AwSV, Annex 1)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

##### Netherlands

SZW-lijst van kankerverwekkende stoffen : Toluene is listed

SZW-lijst van mutagene stoffen : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed

# TRIMETHYLALUMINUM, 2M in toluene (17-18 wgt%)

## Safety Data Sheet

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Toluene is listed

### Denmark

Class for fire hazard : Class I-1

Store unit : 1 liter

Classification remarks : F <Flam. Liq. 2; Pyr. Liq. 1; Water-react. 1>; Emergency management guidelines for the storage of flammable liquids must be followed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product  
Pregnant/breastfeeding women working with the product must not be in direct contact with the product  
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

### 15.2. Chemical safety assessment

No additional information available

## SECTION 16: Other information

Abbreviations and acronyms:

Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor

Other information : Prepared by safety and environmental affairs.

Full text of H- and EUH-statements:

Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Pyr. Liq. 1	Pyrophoric Liquids, Category 1
Repr. 2	Reproductive toxicity, Category 2
Repr. 2	Reproductive toxicity, Category 2
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
Water-react. 1	Substances and Mixtures which, in contact with water, emit flammable gases, Category 1
H225	Highly flammable liquid and vapour.
H250	Catches fire spontaneously if exposed to air.
H260	In contact with water releases flammable gases which may ignite spontaneously.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
EUH014	Reacts violently with water.

# TRIMETHYLALUMINUM, 2M in toluene (17-18 wgt%)

## Safety Data Sheet

---

*The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.*

© 2019 Gelest Inc. Morrisville, PA 19067

