

METHYLTITANIUM TRIISOPROPOXIDE, 1M in tetrahydrofuran

Safety Data Sheet OMTI046

Date of issue: 30/03/2016

Revision date: 05/03/2019

Version: 1.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Mixture
Physical state	: Liquid
Product name	: METHYLTITANIUM TRIISOPROPOXIDE, 1M in tetrahydrofuran
Product code	: OMTI046
Formula	: C ₁₀ H ₂₄ O ₃ T
Synonyms	: METHYLTRIISOPROPOXYTITANIUM
Chemical family	: METAL ESTER

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Chemical intermediate

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

GELEST, INC.

11 East Steel Road
Morrisville, PA 19067

USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com

GELEST INC.

Fritz-Klatte-Strasse 8
65933 Frankfurt

Germany

T +49 (0) 69 3535106-500 - F +49 (0) 69 3535106-501 - (M-F): 8:00 AM - 4:00 PM

info@gelestde.com - www.gelestde.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2	H225
Serious eye damage/eye irritation, Category 2	H319
Carcinogenicity, Category 2	H351
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation	H335
Full text of H statements : see section 16	

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

GHS08

Signal word (CLP) : Danger

METHYLTITANIUM TRIISOPROPOXIDE, 1M in tetrahydrofuran

Safety Data Sheet

Hazardous ingredients	: Tetrahydrofuran
Hazard statements (CLP)	: H225 - Highly flammable liquid and vapour. H319 - Causes serious eye irritation. H335 - May cause respiratory irritation. H351 - Suspected of causing cancer.
Precautionary statements (CLP)	: P202 - Do not handle until all safety precautions have been read and understood. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P240 - Ground/bond container and receiving equipment. P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P308+P313 - IF exposed or concerned: Get medical advice/attention.
EUH-statements	: EUH019 - May form explosive peroxides.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Tetrahydrofuran	(CAS-No.) 109-99-9 (EC-No.) 203-726-8 (EC Index-No.) 603-025-00-0	> 75	Flam. Liq. 2, H225 Eye Irrit. 2, H319 Carc. 2, H351 STOT SE 3, H335
Methyltitanium triisopropoxide	(CAS-No.) 18006-13-8	< 25	Eye Irrit. 2, H319

Specific concentration limits:

Name	Product identifier	Specific concentration limits
Tetrahydrofuran	(CAS-No.) 109-99-9 (EC-No.) 203-726-8 (EC Index-No.) 603-025-00-0	(25 =C < 100) Eye Irrit. 2, H319 (25 =C < 100) STOT SE 3, H335

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If you feel unwell, seek medical advice.
First-aid measures after skin contact	: Wash with plenty of water/.... Get medical advice/attention.
First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
First-aid measures after ingestion	: Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause cancer.
Symptoms/effects after inhalation	: May cause respiratory irritation. Headache. Nausea.
Symptoms/effects after skin contact	: May cause skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: May be harmful if swallowed.
Chronic symptoms	: TETRAHYDROFURAN: Mildly toxic by inhalation. Mutagenic data has been reported. Reported as causing injury to liver and kidneys.

4.3. Indication of any immediate medical attention and special treatment needed

Note to physician: Activated charcoal slurry may be administered. Activated charcoal slurry is prepared by suspending 50 grams of activated charcoal in 400 ml water and mixing thoroughly. Administer 5 ml/kg.

METHYLTITANIUM TRIISOPROPOXIDE, 1M in tetrahydrofuran

Safety Data Sheet

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray. Water fog. Foam. Carbon dioxide. Dry chemical.
Unsuitable extinguishing media : Do not use straight streams.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Highly flammable liquid and vapour. Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.
Explosion hazard : May form flammable/explosive vapour-air mixture.

5.3. Advice for firefighters

- Firefighting instructions : Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Avoid all eye and skin contact and do not breathe vapour and mist.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Eliminate every possible source of ignition. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

- Protective equipment : Wear protective equipment as described in Section 8.
Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Ventilate area.

6.2. Environmental precautions

- Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or shovel spills into appropriate container for disposal. Use only non-sparking tools.

6.4. Reference to other sections

- See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapours are flammable. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid all eye and skin contact and do not breathe vapour and mist. Ground/bond container and receiving equipment. Take precautionary measures against static discharge. Use only outdoors or in a well-ventilated area. Use only non-sparking tools.
Hygiene measures : Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof electrical equipment.
Storage conditions : Keep container tightly closed. Store < 5°C. Keep in a cool place. Store locked up.
Incompatible materials : Oxidizing agent.
Storage area : Store in a well-ventilated place. Store away from heat.

7.3. Specific end use(s)

- No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Tetrahydrofuran (109-99-9)		
EU	IOELV TWA (mg/m ³)	150 mg/m ³
EU	IOELV TWA (ppm)	50 ppm

METHYLTITANIUM TRIISOPROPOXIDE, 1M in tetrahydrofuran

Safety Data Sheet

Tetrahydrofuran (109-99-9)		
EU	IOELV STEL (mg/m ³)	300 mg/m ³
EU	IOELV STEL (ppm)	100 ppm
Austria	MAK (mg/m ³)	150 mg/m ³
Austria	MAK (ppm)	50 ppm
Austria	MAK Short time value (mg/m ³)	300 mg/m ³
Austria	MAK Short time value (ppm)	100 ppm
Belgium	Limit value (mg/m ³)	150 mg/m ³
Belgium	Limit value (ppm)	50 ppm
Belgium	Short time value (mg/m ³)	300 mg/m ³
Belgium	Short time value (ppm)	100 ppm
Bulgaria	OEL TWA (mg/m ³)	150 mg/m ³
Bulgaria	OEL TWA (ppm)	50 ppm
Bulgaria	OEL STEL (mg/m ³)	100 mg/m ³
Bulgaria	OEL STEL (ppm)	300 ppm
Cyprus	OEL TWA (mg/m ³)	150 mg/m ³
Cyprus	OEL TWA (ppm)	50 ppm
Cyprus	OEL STEL (mg/m ³)	300 mg/m ³
Cyprus	OEL STEL (ppm)	100 ppm
France	VLE (mg/m ³)	300 mg/m ³ (restrictive limit)
France	VLE (ppm)	100 ppm (restrictive limit)
France	VME (mg/m ³)	150 mg/m ³ (restrictive limit)
France	VME (ppm)	50 ppm (restrictive limit)
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	150 mg/m ³ (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Germany	TRGS 900 Occupational exposure limit value (ppm)	50 ppm (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Germany	TRGS 903 Biological limit value	2 mg/l (Medium: urine - Time: end of shift - Parameter: Tetrahydrofuran)
Gibraltar	Eight hours mg/m ³	150 mg/m ³
Gibraltar	Eight hours ppm	50 ppm
Gibraltar	Short-term mg/m ³	300 mg/m ³
Gibraltar	Short-term ppm	100 ppm
Greece	OEL TWA (mg/m ³)	590 mg/m ³
Greece	OEL TWA (ppm)	200 ppm
Greece	OEL STEL (mg/m ³)	735 mg/m ³
Greece	OEL STEL (ppm)	250 ppm
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	50 ppm
Italy - Portugal - USA ACGIH	ACGIH STEL (ppm)	100 ppm
Italy	OEL TWA (mg/m ³)	150 mg/m ³
Italy	OEL TWA (ppm)	50 ppm
Italy	OEL STEL (mg/m ³)	300 mg/m ³
Italy	OEL STEL (ppm)	100 ppm
Latvia	OEL TWA (mg/m ³)	150 mg/m ³
Latvia	OEL TWA (ppm)	50 ppm
USA IDLH	US IDLH (ppm)	2000 ppm (10% LEL)
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	590 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	735 mg/m ³
USA NIOSH	NIOSH REL (STEL) (ppm)	250 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	590 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
Spain	VLA-ED (mg/m ³)	150 mg/m ³ (indicative limit value)
Spain	VLA-ED (ppm)	50 ppm (indicative limit value)
Spain	VLA-EC (mg/m ³)	300 mg/m ³
Spain	VLA-EC (ppm)	100 ppm

METHYLTITANIUM TRIISOPROPOXIDE, 1M in tetrahydrofuran

Safety Data Sheet

Tetrahydrofuran (109-99-9)		
Switzerland	KZGW (mg/m ³)	300 mg/m ³
Switzerland	KZGW (ppm)	100 ppm
Switzerland	MAK (mg/m ³)	150 mg/m ³
Switzerland	MAK (ppm)	50 ppm
Netherlands	Grenswaarde TGG 8H (mg/m ³)	300 mg/m ³
Netherlands	Grenswaarde TGG 15MIN (mg/m ³)	600 mg/m ³
United Kingdom	WEL TWA (mg/m ³)	150 mg/m ³
United Kingdom	WEL TWA (ppm)	50 ppm
United Kingdom	WEL STEL (mg/m ³)	300 mg/m ³
United Kingdom	WEL STEL (ppm)	100 ppm
Czech Republic	Expoziční limity (PEL) (mg/m ³)	150 mg/m ³
Denmark	Grænseværdie (langvarig) (mg/m ³)	150 mg/m ³
Denmark	Grænseværdie (langvarig) (ppm)	50 ppm
Finland	HTP-arvo (8h) (mg/m ³)	150 mg/m ³
Finland	HTP-arvo (8h) (ppm)	50 ppm
Finland	HTP-arvo (15 min)	300 mg/m ³
Finland	HTP-arvo (15 min) (ppm)	100 ppm
Hungary	AK-érték	150 mg/m ³
Hungary	CK-érték	300 mg/m ³
Ireland	OEL (8 hours ref) (mg/m ³)	150 mg/m ³
Ireland	OEL (8 hours ref) (ppm)	50 ppm
Ireland	OEL (15 min ref) (mg/m ³)	300 mg/m ³
Ireland	OEL (15 min ref) (ppm)	100 ppm
Lithuania	IPRV (mg/m ³)	150 mg/m ³
Lithuania	IPRV (ppm)	50 ppm
Lithuania	TPRV (mg/m ³)	300 mg/m ³
Lithuania	TPRV (ppm)	100 ppm
Malta	OEL TWA (mg/m ³)	150 mg/m ³
Malta	OEL TWA (ppm)	50 ppm
Malta	OEL STEL (mg/m ³)	300 mg/m ³
Malta	OEL STEL (ppm)	100 ppm
Norway	Grenseverdier (AN) (mg/m ³)	150 mg/m ³
Norway	Grenseverdier (AN) (ppm)	50 ppm
Norway	Grenseverdier (Korttidsverdi) (mg/m ³)	150 mg/m ³
Norway	Grenseverdier (Korttidsverdi) (ppm)	50 ppm
Poland	NDS (mg/m ³)	150 mg/m ³
Poland	NDSch (mg/m ³)	300 mg/m ³
Romania	OEL TWA (mg/m ³)	150 mg/m ³
Romania	OEL TWA (ppm)	50 ppm
Romania	OEL STEL (mg/m ³)	300 mg/m ³
Romania	OEL STEL (ppm)	100 ppm
Slovakia	NPHV (priemerná) (mg/m ³)	150 mg/m ³
Slovakia	NPHV (priemerná) (ppm)	50 ppm
Slovakia	NPHV (Hraničná) (mg/m ³)	300 mg/m ³
Sweden	nivågränsvärde (NVG) (mg/m ³)	150 mg/m ³
Sweden	nivågränsvärde (NVG) (ppm)	50 ppm
Sweden	kortidsvärde (KTV) (mg/m ³)	250 mg/m ³
Sweden	kortidsvärde (KTV) (ppm)	80 ppm
Canada (Quebec)	VEMP (mg/m ³)	300 mg/m ³
Canada (Quebec)	VEMP (ppm)	100 ppm
Australia	TWA (mg/m ³)	295 mg/m ³

METHYLTITANIUM TRIISOPROPOXIDE, 1M in tetrahydrofuran

Safety Data Sheet

Tetrahydrofuran (109-99-9)		
Australia	TWA (ppm)	100 ppm
Portugal	OEL TWA (mg/m ³)	150 mg/m ³ (indicative limit value)
Portugal	OEL TWA (ppm)	50 ppm (indicative limit value)
Portugal	OEL STEL (mg/m ³)	300 mg/m ³ (indicative limit value)
Portugal	OEL STEL (ppm)	100 ppm (indicative limit value)
Portugal	OEL chemical category (PT)	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans, skin - potential for cutaneous exposure indicative limit value

8.2. Exposure controls

Appropriate engineering controls:

Provide local exhaust or general room ventilation.

Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Hand protection:

Neoprene or nitrile rubber gloves

Eye protection:

Chemical goggles or face shield. Contact lenses should not be worn

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified organic vapor (black cartridge) respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear liquid.
Molecular mass	: 240.18 g/mol
Colour	: Pale yellow.
Odour	: No data available
Odour threshold	: No data available
Refractive index	: No additional information available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: 10 °C
Freezing point	: No data available
Boiling point	: 50 - 52 °C @ 0.02 mm Hg
Flash point	: -14 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Highly flammable liquid and vapour.
Vapour pressure	: 114 mm Hg @ 15°C (THF)
Relative vapour density at 20 °C	: > 1
Relative density	: 0.895
% Volatiles	: > 75 %
Solubility	: Reacts with water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

METHYLTITANIUM TRIISOPROPOXIDE, 1M in tetrahydrofuran

Safety Data Sheet

Explosive limits : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable when stored below 5°C. Slowly decomposes at room temperature.

10.3. Possibility of hazardous reactions

Material decomposes slowly in contact with oxygen and rapidly in contact moist air and water.

10.4. Conditions to avoid

Heat. Open flame. Sparks.

10.5. Incompatible materials

Oxidizing agent.

10.6. Hazardous decomposition products

Isopropanol. Organic acid vapors. Titanium oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Tetrahydrofuran (109-99-9)

LD50 oral rat	1650 mg/kg
LC50 inhalation rat (ppm)	21000 ppm (Exposure time: 3 h)
ATE CLP (oral)	1650 mg/kg bodyweight

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Suspected of causing cancer.

Tetrahydrofuran (109-99-9)

National Toxicology Program (NTP) Status : 1 - Evidence of Carcinogenicity

Reproductive toxicity : Not classified
STOT-single exposure : May cause respiratory irritation.
STOT-repeated exposure : Not classified
Aspiration hazard : Not classified
Potential adverse human health effects and symptoms : Material generates methane and isopropanol on contact with water or moisture in skin, eyes and mucous membranes and has an irritating, dehydrating effect on overexposed tissue.
Symptoms/effects after inhalation : May cause respiratory irritation. Headache. Nausea.
Symptoms/effects after skin contact : May cause skin irritation.
Symptoms/effects after eye contact : Causes serious eye irritation.
Symptoms/effects after ingestion : May be harmful if swallowed.
Chronic symptoms : TETRAHYDROFURAN: Mildly toxic by inhalation. Mutagenic data has been reported. Reported as causing injury to liver and kidneys.
Reason for classification : Expert judgment

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water : Toxic to aquatic life. Toxic to aquatic life with long lasting effects.
Acute aquatic toxicity : Not classified
Chronic aquatic toxicity : Not classified

Tetrahydrofuran (109-99-9)

LC50 fish 1	1970 - 2360 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 fish 2	2700 - 3600 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

METHYLTITANIUM TRIISOPROPOXIDE, 1M in tetrahydrofuran

Safety Data Sheet

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Tetrahydrofuran (109-99-9)	
BCF fish 1	(will not bioconcentrate)
Log Pow	0.45 (at 25 °C)

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Other adverse effects : This substance may be hazardous to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Sewage disposal recommendations : Do not dispose of waste into sewer.
Product/Packaging disposal recommendations : Incinerate. Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to licensed waste disposal facility.
Additional information : Handle empty containers with care because residual vapours are flammable.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

14.1. UN number

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR) : 2056
UN-No. (IMDG) : 2056
UN-No. (IATA) : 2056
UN-No. (ADN) : 2056
UN-No. (RID) : 2056

14.2. UN proper shipping name

Proper Shipping Name (ADR) : TETRAHYDROFURAN
Proper Shipping Name (IMDG) : TETRAHYDROFURAN
Proper Shipping Name (IATA) : Tetrahydrofuran
Proper Shipping Name (ADN) : TETRAHYDROFURAN
Proper Shipping Name (RID) : TETRAHYDROFURAN
Transport document description (ADR) : UN 2056 TETRAHYDROFURAN (METHYLTITANIUM TRIISOPROPOXIDE, 1M in tetrahydrofuran), 3, II, (D/E)
Transport document description (IMDG) : UN 2056 TETRAHYDROFURAN (METHYLTITANIUM TRIISOPROPOXIDE, 1M in tetrahydrofuran), 3, II (< -18°C c.c.)
Transport document description (IATA) : UN 2056 Tetrahydrofuran (METHYLTITANIUM TRIISOPROPOXIDE, 1M in tetrahydrofuran), 3, II
Transport document description (ADN) : UN 2056 TETRAHYDROFURAN (METHYLTITANIUM TRIISOPROPOXIDE, 1M in tetrahydrofuran), 3, II
Transport document description (RID) : UN 2056 TETRAHYDROFURAN (METHYLTITANIUM TRIISOPROPOXIDE, 1M in tetrahydrofuran), 3, II

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 3
Danger labels (ADR) : 3



IMDG

METHYLTITANIUM TRIISOPROPOXIDE, 1M in tetrahydrofuran

Safety Data Sheet

Transport hazard class(es) (IMDG) : 3
Danger labels (IMDG) : 3



IATA

Transport hazard class(es) (IATA) : 3
Hazard labels (IATA) : 3



ADN

Transport hazard class(es) (ADN) : 3
Danger labels (ADN) : 3



RID

Transport hazard class(es) (RID) : 3
Danger labels (RID) : 3



14.4. Packing group

Packing group (ADR) : II
Packing group (IMDG) : II
Packing group (IATA) : II
Packing group (ADN) : II
Packing group (RID) : II

14.5. Environmental hazards

Dangerous for the environment : No
Marine pollutant : No
Other information : No supplementary information available

14.6. Special precautions for user

- Overland transport

Classification code (ADR) : F1
Limited quantities (ADR) : 11
Excepted quantities (ADR) : E2
Packing instructions (ADR) : P001, IBC02, R001
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T4

METHYLTITANIUM TRIISOPROPOXIDE, 1M in tetrahydrofuran

Safety Data Sheet

Portable tank and bulk container special provisions (ADR) : TP1
Tank code (ADR) : LGBF
Vehicle for tank carriage : FL
Transport category (ADR) : 2
Special provisions for carriage - Operation (ADR) : S2, S20
Hazard identification number (Kemler No.) : 33
Orange plates :



Tunnel restriction code (ADR) : D/E

- Transport by sea

Limited quantities (IMDG) : 1 L
Excepted quantities (IMDG) : E2
Packing instructions (IMDG) : P001
IBC packing instructions (IMDG) : IBC02
Tank instructions (IMDG) : T4
Tank special provisions (IMDG) : TP1
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-D
Stowage category (IMDG) : B
Flash point (IMDG) : below -18°C c.c.
Properties and observations (IMDG) : Colourless liquid with an ethereal odour. Flashpoint: below -18°C c.c. Explosive limits: 1.5% to 12% Miscible with water.

- Air transport

PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y341
PCA limited quantity max net quantity (IATA) : 1L
PCA packing instructions (IATA) : 353
PCA max net quantity (IATA) : 5L
CAO packing instructions (IATA) : 364
CAO max net quantity (IATA) : 60L
ERG code (IATA) : 3H

- Inland waterway transport

Classification code (ADN) : F1
Limited quantities (ADN) : 1 L
Excepted quantities (ADN) : E2
Carriage permitted (ADN) : T
Equipment required (ADN) : PP, EX, A
Ventilation (ADN) : VE01
Number of blue cones/lights (ADN) : 1

- Rail transport

Classification code (RID) : F1
Limited quantities (RID) : 1L
Excepted quantities (RID) : E2
Packing instructions (RID) : P001, IBC02, R001
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T4
Portable tank and bulk container special provisions (RID) : TP1
Tank codes for RID tanks (RID) : LGBF
Transport category (RID) : 2
Colis express (express parcels) (RID) : CE7
Hazard identification number (RID) : 33

METHYLTITANIUM TRIISOPROPOXIDE, 1M in tetrahydrofuran

Safety Data Sheet

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.

Substance(s) are not subject to Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Directive 79/117/EEC.

Contains no REACH Annex XIV substances

% Volatiles : > 75 %

15.1.2. National regulations

Germany

Reference to AwSV : Water hazard class (WGK) 3, Highly hazardous to water (Classification according to AwSV, Annex 1)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen : Tetrahydrofuran is listed

SZW-lijst van mutagene stoffen : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Abbreviations and acronyms:

Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor

Other information : Prepared by safety and environmental affairs.

Full text of H- and EUH-statements:

Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H225	Highly flammable liquid and vapour.

METHYLTITANIUM TRIISOPROPOXIDE, 1M in tetrahydrofuran

Safety Data Sheet

H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
EUH019	May form explosive peroxides.

SDS EU (REACH Annex II) - Custom

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2019 Gelest Inc. Morrisville, PA 19067

