

**WHITE PIGMENT, 45% IN SILICONE OIL**

Safety Data Sheet PGWHT01

Date of issue: 06/01/2015

Revision date: 04/06/2018

Version: 1.1

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product form	: Mixture
Physical state	: Liquid
Product name	: WHITE PIGMENT, 45% IN SILICONE OIL
Product code	: PGWHT01
Synonyms	: WHITE PIGMENT DISPERSION in POLY(DIMETHYLSILOXANE), VINYL TERMINATED
Chemical family	: ORGANOSILOXANE

**1.2. Relevant identified uses of the substance or mixture and uses advised against****1.2.1. Relevant identified uses**

Use of the substance/mixture : Chemical intermediate

**1.2.2. Uses advised against**

No additional information available

**1.3. Details of the supplier of the safety data sheet****GELEST, INC.**11 East Steel Road  
Morrisville, PA 19067**USA**

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

[info@gelest.com](mailto:info@gelest.com) - [www.gelest.com](http://www.gelest.com)**GELEST INC.**Fritz-Klatte-Strasse 8  
65933 Frankfurt**Germany**

T +49 (0) 69 3535106-500 - F +49 (0) 69 3535106-501 - (M-F): 8:00 AM - 4:00 PM

[info@gelestde.com](mailto:info@gelestde.com) - [www.gelestde.com](http://www.gelestde.com)**1.4. Emergency telephone number**

Emergency number : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Carcinogenicity, Category 2	H351
Specific target organ toxicity — Repeated exposure, Category 2	H373
Full text of H statements : see section 16	

**Adverse physicochemical, human health and environmental effects**

No additional information available

**2.2. Label elements****Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP) :



GHS08

Signal word (CLP)	: Warning
Hazardous ingredients	: Titanium Dioxide
Hazard statements (CLP)	: H351 - Suspected of causing cancer. H373 - May cause damage to organs through prolonged or repeated exposure.
Precautionary statements (CLP)	: P280 - Wear protective gloves/protective clothing/eye protection/face protection. P202 - Do not handle until all safety precautions have been read and understood.

# WHITE PIGMENT, 45% IN SILICONE OIL

## Safety Data Sheet

P260 - Do not breathe mist.  
P314 - Get medical advice/attention if you feel unwell.  
P405 - Store locked up.  
P501 - Dispose of contents/container to licensed waste disposal facility.

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Monovinyl terminated polydimethylsiloxane	(CAS-No.) 68951-99-5	50 - 60	Not classified
Titanium Dioxide	(CAS-No.) 13463-67-7 (EC-No.) 236-675-5	40 - 50	Not classified

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If you feel unwell, seek medical advice.

First-aid measures after skin contact : Wash with plenty of water/....

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.

First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Get medical advice/attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : May cause irritation to the respiratory tract.

Symptoms/effects after skin contact : May cause skin irritation.

Symptoms/effects after eye contact : May cause eye irritation.

Symptoms/effects after ingestion : May be harmful if swallowed.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Water fog. Foam. Carbon dioxide. Dry chemical.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.

### 5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Avoid all eye and skin contact and do not breathe vapour and mist.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

# WHITE PIGMENT, 45% IN SILICONE OIL

## Safety Data Sheet

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or shovel spills into appropriate container for disposal.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapour and mist.  
Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container tightly closed.  
Incompatible materials : Acids. Oxidizing agent. Metal salts.  
Storage area : Store in a well-ventilated place. Store away from heat.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Titanium Dioxide (13463-67-7)		
Austria	MAK (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (alveolar dust, respirable fraction)
Austria	MAK Short time value (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (alveolar dust, respirable fraction)
Belgium	Limit value (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Bulgaria	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (respirable dust)
France	VME (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Greece	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (inhalable fraction) 5 mg/m <sup>3</sup> (respirable fraction)
Italy - Portugal - USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Latvia	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
USA IDLH	US IDLH (mg/m <sup>3</sup> )	5000 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> (total dust)
Spain	VLA-ED (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Switzerland	MAK (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup> (respirable dust)
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (total inhalable) 4 mg/m <sup>3</sup> (respirable)
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	30 mg/m <sup>3</sup> (calculated-total inhalable) 12 mg/m <sup>3</sup> (calculated-respirable)
Denmark	Grænseværdie (langvarig) (mg/m <sup>3</sup> )	6 mg/m <sup>3</sup>
Ireland	OEL (8 hours ref) (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (total inhalable dust) 4 mg/m <sup>3</sup> (respirable dust)
Ireland	OEL (15 min ref) (mg/m <sup>3</sup> )	30 mg/m <sup>3</sup> (calculated-total inhalable dust) 12 mg/m <sup>3</sup> (calculated-respirable dust)
Lithuania	IPRV (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
Norway	Grænseverdier (AN) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
Norway	Grænseverdier (Korttidsverdi) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
Poland	NDS (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (<2% free crystalline silica and containing no asbestos-inhalable fraction)
Romania	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Romania	OEL STEL (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup>
Sweden	nivågränsvärde (NVG) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (total dust)
Canada (Quebec)	VEMP (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (containing no Asbestos and <1% Crystalline silica-total dust)
Australia	TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (containing no asbestos and <1% crystalline silica-inhalable dust)
Portugal	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>

# WHITE PIGMENT, 45% IN SILICONE OIL

## Safety Data Sheet

### Titanium Dioxide (13463-67-7)

Portugal

OEL chemical category (PT)

A4 - Not Classifiable as a Human Carcinogen

### 8.2. Exposure controls

#### Appropriate engineering controls:

Provide local exhaust or general room ventilation.

#### Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

#### Hand protection:

Neoprene or nitrile rubber gloves

#### Eye protection:

Safety glasses. Contact lenses should not be worn

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified organic vapor (black cartridge) respirator.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Flowable. Paste.
Colour	: White.
Odour	: No data available
Odour threshold	: No data available
Refractive index	: No additional information available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: < -60 °C
Freezing point	: No data available
Boiling point	: > 205 °C
Flash point	: > 110 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: > 1
% Volatiles	: < 3 %
Solubility	: Insoluble in water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

# WHITE PIGMENT, 45% IN SILICONE OIL

## Safety Data Sheet

### 10.2. Chemical stability

Stable in sealed containers stored under a dry inert atmosphere.

### 10.3. Possibility of hazardous reactions

No additional information available

### 10.4. Conditions to avoid

Heat. Open flame. Sparks.

### 10.5. Incompatible materials

Acids. Oxidizing agent. Metal salts.

### 10.6. Hazardous decomposition products

Organic acid vapors.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

#### Titanium Dioxide (13463-67-7)

LD50 oral rat	> 10000 mg/kg
---------------	---------------

Skin corrosion/irritation : Not classified  
Serious eye damage/irritation : Not classified  
Respiratory or skin sensitisation : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Suspected of causing cancer.

#### Titanium Dioxide (13463-67-7)

IARC group	2B - Possibly carcinogenic to humans
------------	--------------------------------------

Reproductive toxicity : Not classified  
STOT-single exposure : Not classified  
STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.  
Aspiration hazard : Not classified  
Symptoms/effects after inhalation : May cause irritation to the respiratory tract.  
Symptoms/effects after skin contact : May cause skin irritation.  
Symptoms/effects after eye contact : May cause eye irritation.  
Symptoms/effects after ingestion : May be harmful if swallowed.

## SECTION 12: Ecological information

### 12.1. Toxicity

Acute aquatic toxicity : Not classified  
Chronic aquatic toxicity : Not classified

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

No additional information available

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product/Packaging disposal recommendations : Landfill. Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to licensed waste disposal facility.  
Ecology - waste materials : Avoid release to the environment.

# WHITE PIGMENT, 45% IN SILICONE OIL

## Safety Data Sheet

### SECTION 14: Transport information

#### 14.1. UN number

In accordance with ADR / RID / IMDG / IATA / ADN

#### 14.1. UN number

UN-No. (ADR)	: Not applicable
UN-No. (IMDG)	: Not applicable
UN-No. (IATA)	: Not applicable
UN-No. (ADN)	: Not applicable
UN-No. (RID)	: Not applicable

#### 14.2. UN proper shipping name

Proper Shipping Name (ADR)	: Not applicable
Proper Shipping Name (IMDG)	: Not applicable
Proper Shipping Name (IATA)	: Not applicable
Proper Shipping Name (ADN)	: Not applicable
Proper Shipping Name (RID)	: Not applicable

#### 14.3. Transport hazard class(es)

##### ADR

Transport hazard class(es) (ADR) : Not applicable

##### IMDG

Transport hazard class(es) (IMDG) : Not applicable

##### IATA

Transport hazard class(es) (IATA) : Not applicable

##### ADN

Transport hazard class(es) (ADN) : Not applicable

##### RID

Transport hazard class(es) (RID) : Not applicable

#### 14.4. Packing group

Packing group (ADR)	: Not applicable
Packing group (IMDG)	: Not applicable
Packing group (IATA)	: Not applicable
Packing group (ADN)	: Not applicable
Packing group (RID)	: Not applicable

#### 14.5. Environmental hazards

Dangerous for the environment	: No
Marine pollutant	: No
Other information	: No supplementary information available

#### 14.6. Special precautions for user

##### - Overland transport

No data available

##### - Transport by sea

No data available

##### - Air transport

No data available

##### - Inland waterway transport

No data available

##### - Rail transport

No data available

# WHITE PIGMENT, 45% IN SILICONE OIL

## Safety Data Sheet

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.

Substance(s) are not subject to Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Directive 79/117/EEC.

Contains no REACH Annex XIV substances

% Volatiles : < 3 %

#### 15.1.2. National regulations

##### Germany

Reference to AwSV : Water hazard class (WGK) 3, Highly hazardous to water (Classification according to AwSV, Annex 1)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

##### Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed

SZW-lijst van mutagene stoffen : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed

##### Denmark

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product  
Pregnant/breastfeeding women working with the product must not be in direct contact with the product  
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

### 15.2. Chemical safety assessment

No additional information available

## SECTION 16: Other information

Abbreviations and acronyms:

Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor

Other information : Prepared by safety and environmental affairs.

Full text of H- and EUH-statements:

Carc. 2	Carcinogenicity, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.

# WHITE PIGMENT, 45% IN SILICONE OIL

## Safety Data Sheet

---

SDS EU (REACH Annex II) - Custom

*The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.*

© 2019 Gelest Inc. Morrisville, PA 19067

