

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product form	: Mixture
Physical state	: Liquid
Product name	: AQUAPHILE® AQ
Product code	: PP1-AQAQ
Synonyms	: TRIMETHOXYSYLYLPROPYLPOLYETHYLENEIMINE), in isopropanol; AZIRIDINE, POLYMER WITH (3-CHLOROPROPYL)TRIMETHOXYSIANE
Chemical family	: ORGANOSILANE

**1.2. Relevant identified uses of the substance or mixture and uses advised against****1.2.1. Relevant identified uses**

Use of the substance/mixture : Chemical intermediate

**1.2.2. Uses advised against**

No additional information available

**1.3. Details of the supplier of the safety data sheet****GELEST, INC.**

11 East Steel Road  
Morrisville, PA 19067

**USA**

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

[info@gelest.com](mailto:info@gelest.com) - [www.gelest.com](http://www.gelest.com)

**GELEST INC.**

Fritz-Klatte-Strasse 8  
65933 Frankfurt

**Germany**

T +49 (0) 69 3535106-500 - F +49 (0) 69 3535106-501 - (M-F): 8:00 AM - 4:00 PM

[info@gelestde.com](mailto:info@gelestde.com) - [www.gelestde.com](http://www.gelestde.com)

**1.4. Emergency telephone number**

Emergency number : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Flammable liquids, Category 2	H225
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Specific target organ toxicity — Single exposure, Category 3, Narcosis	H336

Full text of H statements : see section 16

**Adverse physicochemical, human health and environmental effects**

No additional information available

**2.2. Label elements****Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP) :



# AQUAPHILE® AQ

## Safety Data Sheet

Signal word (CLP)	: Danger
Hazardous ingredients	: Isopropanol
Hazard statements (CLP)	: H225 - Highly flammable liquid and vapour. H315 - Causes skin irritation. H319 - Causes serious eye irritation. H336 - May cause drowsiness or dizziness.
Precautionary statements (CLP)	: P280 - Wear protective gloves/protective clothing/eye protection/face protection. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P240 - Ground/bond container and receiving equipment. P261 - Avoid breathing vapours. P264 - Wash hands thoroughly after handling. P312 - Call a doctor if you feel unwell.

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Isopropanol	(CAS-No.) 67-63-0 (EC-No.) 200-661-7 (EC Index-No.) 603-117-00-0	73 - 77	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
(N-Trimethoxysilylpropyl)poly-ethyleneimine	(CAS-No.) 75132-84-2	23 - 27	Skin Irrit. 2, H315 Eye Irrit. 2, H319

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label. IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If you feel unwell, seek medical advice.
First-aid measures after skin contact	: Wash with plenty of water/.... Get medical advice/attention.
First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
First-aid measures after ingestion	: Never give anything by mouth to an unconscious person. Get medical advice/attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: May cause drowsiness or dizziness. May cause irritation to the respiratory tract. Cough. Headache. Nausea. Overexposure may cause:
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: May be harmful if swallowed.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Foam. Carbon dioxide. Dry chemical.
Unsuitable extinguishing media	: Do not use straight streams.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapour. Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.
Explosion hazard	: May form flammable/explosive vapour-air mixture.

# AQUAPHILE® AQ

## Safety Data Sheet

### 5.3. Advice for firefighters

- Firefighting instructions : Use water spray to cool exposed surfaces. Exercise caution when fighting any chemical fire.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Avoid all eye and skin contact and do not breathe vapour and mist.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Eliminate every possible source of ignition. Use special care to avoid static electric charges.

#### 6.1.1. For non-emergency personnel

- Protective equipment : Wear protective equipment as described in Section 8.
- Emergency procedures : Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

- Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

- For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
- Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or shovel spills into appropriate container for disposal. Use only non-sparking tools.

### 6.4. Reference to other sections

- See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapours are flammable. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapour and mist. Provide good ventilation in process area to prevent formation of vapour. Ground/bond container and receiving equipment. Use only outdoors or in a well-ventilated area. Take precautionary measures against static discharge. Use only non-sparking tools.
- Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof electrical equipment.
- Storage conditions : Keep container tightly closed. Moisture causes product to gel.
- Incompatible materials : Acids. Oxidizing agent. Peroxides.
- Storage area : Store in a well-ventilated place. Store away from heat.

### 7.3. Specific end use(s)

- No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Isopropanol (67-63-0)		
Austria	MAK (mg/m <sup>3</sup> )	500 mg/m <sup>3</sup> (short time value for large casting)
Austria	MAK (ppm)	200 ppm (short time value for large casting)
Austria	MAK Short time value (mg/m <sup>3</sup> )	2000 mg/m <sup>3</sup> 2000 mg/m <sup>3</sup> (STEL for large casting valid till 12/31/2013)
Austria	MAK Short time value (ppm)	800 ppm 800 ppm (STEL for large casting valid till 12/31/2013)
Belgium	Limit value (mg/m <sup>3</sup> )	500 mg/m <sup>3</sup>
Belgium	Limit value (ppm)	200 ppm
Belgium	Short time value (mg/m <sup>3</sup> )	1000 mg/m <sup>3</sup>
Belgium	Short time value (ppm)	400 ppm
Bulgaria	OEL TWA (mg/m <sup>3</sup> )	980 mg/m <sup>3</sup>
Bulgaria	OEL STEL (mg/m <sup>3</sup> )	1225 mg/m <sup>3</sup>

# AQUAPHILE® AQ

## Safety Data Sheet

Isopropanol (67-63-0)		
France	VLE (mg/m <sup>3</sup> )	980 mg/m <sup>3</sup>
France	VLE (ppm)	400 ppm
Germany	TRGS 900 Occupational exposure limit value (mg/m <sup>3</sup> )	500 mg/m <sup>3</sup> (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Germany	TRGS 900 Occupational exposure limit value (ppm)	200 ppm (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Germany	TRGS 903 Biological limit value	25 mg/l (Medium: whole blood - Time: end of shift - Parameter: Acetone) 25 mg/l (Medium: urine - Time: end of shift - Parameter: Acetone)
Greece	OEL TWA (mg/m <sup>3</sup> )	980 mg/m <sup>3</sup>
Greece	OEL TWA (ppm)	400 ppm
Greece	OEL STEL (mg/m <sup>3</sup> )	1225 mg/m <sup>3</sup>
Greece	OEL STEL (ppm)	500 ppm
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	200 ppm
Italy - Portugal - USA ACGIH	ACGIH STEL (ppm)	400 ppm
Latvia	OEL TWA (mg/m <sup>3</sup> )	350 mg/m <sup>3</sup>
USA IDLH	US IDLH (ppm)	2000 ppm (10% LEL)
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	980 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (ppm)	400 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m <sup>3</sup> )	1225 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (STEL) (ppm)	500 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	980 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	400 ppm
Spain	VLA-ED (mg/m <sup>3</sup> )	500 mg/m <sup>3</sup> (it is prohibited the partial or complete commercialization or use of this substance as a phytosanitary or biocide compound)
Spain	VLA-ED (ppm)	200 ppm (it is prohibited the partial or complete commercialization or use of this substance as a phytosanitary or biocide compound)
Spain	VLA-EC (mg/m <sup>3</sup> )	1000 mg/m <sup>3</sup>
Spain	VLA-EC (ppm)	400 ppm
Switzerland	KZGW (mg/m <sup>3</sup> )	1000 mg/m <sup>3</sup>
Switzerland	KZGW (ppm)	400 ppm
Switzerland	MAK (mg/m <sup>3</sup> )	500 mg/m <sup>3</sup>
Switzerland	MAK (ppm)	200 ppm
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	999 mg/m <sup>3</sup>
United Kingdom	WEL TWA (ppm)	400 ppm
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	1250 mg/m <sup>3</sup>
United Kingdom	WEL STEL (ppm)	500 ppm
Czech Republic	Expoziční limity (PEL) (mg/m <sup>3</sup> )	500 mg/m <sup>3</sup>
Denmark	Grænseværdie (langvarig) (mg/m <sup>3</sup> )	490 mg/m <sup>3</sup>
Denmark	Grænseværdie (langvarig) (ppm)	200 ppm
Finland	HTP-arvo (8h) (mg/m <sup>3</sup> )	500 mg/m <sup>3</sup>
Finland	HTP-arvo (8h) (ppm)	200 ppm
Finland	HTP-arvo (15 min)	620 mg/m <sup>3</sup>
Finland	HTP-arvo (15 min) (ppm)	250 ppm
Hungary	AK-érték	500 mg/m <sup>3</sup>
Hungary	CK-érték	2000 mg/m <sup>3</sup>
Ireland	OEL (8 hours ref) (ppm)	200 ppm
Ireland	OEL (15 min ref) (ppm)	400 ppm
Lithuania	IPRV (mg/m <sup>3</sup> )	350 mg/m <sup>3</sup>
Lithuania	IPRV (ppm)	150 ppm
Lithuania	TPRV (mg/m <sup>3</sup> )	600 mg/m <sup>3</sup>

# AQUAPHILE® AQ

## Safety Data Sheet

Isopropanol (67-63-0)		
Lithuania	TPRV (ppm)	250 ppm
Norway	Grenseverdier (AN) (mg/m <sup>3</sup> )	245 mg/m <sup>3</sup>
Norway	Grenseverdier (AN) (ppm)	100 ppm
Norway	Grenseverdier (Korttidsverdi) (mg/m <sup>3</sup> )	245 mg/m <sup>3</sup>
Norway	Grenseverdier (Korttidsverdi) (ppm)	100 ppm
Poland	NDS (mg/m <sup>3</sup> )	900 mg/m <sup>3</sup>
Poland	NDSch (mg/m <sup>3</sup> )	1200 mg/m <sup>3</sup>
Romania	OEL TWA (mg/m <sup>3</sup> )	200 mg/m <sup>3</sup>
Romania	OEL TWA (ppm)	81 ppm
Romania	OEL STEL (mg/m <sup>3</sup> )	500 mg/m <sup>3</sup>
Romania	OEL STEL (ppm)	203 ppm
Slovakia	NPHV (priemerná) (mg/m <sup>3</sup> )	500 mg/m <sup>3</sup>
Slovakia	NPHV (priemerná) (ppm)	200 ppm
Slovakia	NPHV (Hraničná) (mg/m <sup>3</sup> )	1000 mg/m <sup>3</sup>
Sweden	nivågränsvärde (NVG) (mg/m <sup>3</sup> )	350 mg/m <sup>3</sup>
Sweden	nivågränsvärde (NVG) (ppm)	150 ppm
Sweden	kortidsvärde (KTV) (mg/m <sup>3</sup> )	600 mg/m <sup>3</sup>
Sweden	kortidsvärde (KTV) (ppm)	250 ppm
Canada (Quebec)	VECD (mg/m <sup>3</sup> )	1230 mg/m <sup>3</sup>
Canada (Quebec)	VECD (ppm)	500 ppm
Canada (Quebec)	VEMP (mg/m <sup>3</sup> )	985 mg/m <sup>3</sup>
Canada (Quebec)	VEMP (ppm)	400 ppm
Australia	TWA (mg/m <sup>3</sup> )	983 mg/m <sup>3</sup>
Australia	TWA (ppm)	400 ppm
Australia	STEL (mg/m <sup>3</sup> )	1230 mg/m <sup>3</sup>
Australia	STEL (ppm)	500 ppm
Portugal	OEL TWA (ppm)	200 ppm
Portugal	OEL STEL (ppm)	400 ppm
Portugal	OEL chemical category (PT)	A4 - Not Classifiable as a Human Carcinogen

### 8.2. Exposure controls

#### Appropriate engineering controls:

Provide local exhaust or general room ventilation.

#### Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

#### Hand protection:

Neoprene or nitrile rubber gloves

#### Eye protection:

Chemical goggles. Contact lenses should not be worn

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified combination organic vapor - amine gas (brown cartridge) respirator.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Solution.
Colour	: Pale yellow. Amber.
Odour	: No data available

# AQUAPHILE® AQ

## Safety Data Sheet

Odour threshold	: No data available
Refractive index	: No additional information available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: < 0 °C
Freezing point	: No data available
Boiling point	: 82 °C (initial, isopropanol)
Flash point	: 12 °C
Auto-ignition temperature	: 455 °C (isopropanol)
Decomposition temperature	: No data available
Flammability (solid, gas)	: Highly flammable liquid and vapour.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: > 2
Relative density	: 0.92
% Volatiles	: > 75 %
Solubility	: Reacts with water. Dissolves.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: 2.5 - 12 vol % (lower; upper: isopropanol)

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Stable in sealed containers stored under a dry atmosphere.

### 10.3. Possibility of hazardous reactions

Reacts with water and moisture in air, liberating methanol.

### 10.4. Conditions to avoid

Heat. Open flame. Sparks.

### 10.5. Incompatible materials

Acids. Oxidizing agent. Peroxides.

### 10.6. Hazardous decomposition products

Organic acid vapors.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

Isopropanol (67-63-0)	
LD50 oral rat	1870 mg/kg
LD50 dermal rabbit	4059 mg/kg
LC50 inhalation rat (mg/l)	72600 mg/m <sup>3</sup> (Exposure time: 4 h)
ATE CLP (oral)	4396 mg/kg bodyweight
ATE CLP (dermal)	12800 mg/kg bodyweight

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

Isopropanol (67-63-0)	
IARC group	3 - Not classifiable

# AQUAPHILE® AQ

## Safety Data Sheet

Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Symptoms/effects after inhalation	: May cause drowsiness or dizziness. May cause irritation to the respiratory tract. Cough. Headache. Nausea. Overexposure may cause:
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: May be harmful if swallowed.
Reason for classification	: Expert judgment

### SECTION 12: Ecological information

#### 12.1. Toxicity

Acute aquatic toxicity	: Not classified
Chronic aquatic toxicity	: Not classified

Isopropanol (67-63-0)	
LC50 fish 1	9640 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	13299 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	11130 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

#### 12.2. Persistence and degradability

No additional information available

#### 12.3. Bioaccumulative potential

Isopropanol (67-63-0)	
Log Pow	0.05 (at 25 °C)

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Results of PBT and vPvB assessment

No additional information available

#### 12.6. Other adverse effects

Other adverse effects : This substance may be hazardous to the environment.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Sewage disposal recommendations	: Do not dispose of waste into sewer.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to licensed waste disposal facility.
Additional information	: Handle empty containers with care because residual vapours are flammable.
Ecology - waste materials	: Avoid release to the environment.

### SECTION 14: Transport information

#### 14.1. UN number

In accordance with ADR / RID / IMDG / IATA / ADN

#### 14.1. UN number

UN-No. (ADR)	: 1993
UN-No. (IMDG)	: 1993
UN-No. (IATA)	: 1993
UN-No. (ADN)	: 1993
UN-No. (RID)	: 1993

#### 14.2. UN proper shipping name

Proper Shipping Name (ADR)	: FLAMMABLE LIQUID, N.O.S.
Proper Shipping Name (IMDG)	: FLAMMABLE LIQUID, N.O.S.
Proper Shipping Name (IATA)	: Flammable liquid, n.o.s.
Proper Shipping Name (ADN)	: FLAMMABLE LIQUID, N.O.S.
Proper Shipping Name (RID)	: FLAMMABLE LIQUID, N.O.S.



# AQUAPHILE® AQ

## Safety Data Sheet

Transport document description (ADR)	: UN 1993 FLAMMABLE LIQUID, N.O.S. (TRIMETHOXSILYLPROPYLPOLYETHYLENEIMINE), in isopropanol), 3, II, (D/E)
Transport document description (IMDG)	: UN 1993 FLAMMABLE LIQUID, N.O.S. (TRIMETHOXSILYLPROPYLPOLYETHYLENEIMINE), in isopropanol), 3, II
Transport document description (IATA)	: UN 1993 Flammable liquid, n.o.s. (TRIMETHOXSILYLPROPYLPOLYETHYLENEIMINE), in isopropanol), 3, II
Transport document description (ADN)	: UN 1993 FLAMMABLE LIQUID, N.O.S. (TRIMETHOXSILYLPROPYLPOLYETHYLENEIMINE), in isopropanol), 3, II
Transport document description (RID)	: UN 1993 FLAMMABLE LIQUID, N.O.S. (TRIMETHOXSILYLPROPYLPOLYETHYLENEIMINE), in isopropanol), 3, II

### 14.3. Transport hazard class(es)

#### ADR

Transport hazard class(es) (ADR) : 3  
Danger labels (ADR) : 3



#### IMDG

Transport hazard class(es) (IMDG) : 3  
Danger labels (IMDG) : 3



#### IATA

Transport hazard class(es) (IATA) : 3  
Hazard labels (IATA) : 3



#### ADN

Transport hazard class(es) (ADN) : 3  
Danger labels (ADN) : 3



#### RID

Transport hazard class(es) (RID) : 3  
Danger labels (RID) : 3





# AQUAPHILE® AQ

## Safety Data Sheet

### 14.4. Packing group

Packing group (ADR)	: II
Packing group (IMDG)	: II
Packing group (IATA)	: II
Packing group (ADN)	: II
Packing group (RID)	: II

### 14.5. Environmental hazards

Dangerous for the environment	: No
Marine pollutant	: No
Other information	: No supplementary information available

### 14.6. Special precautions for user

#### - Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 274, 601, 640C
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E2
Packing instructions (ADR)	: P001
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T7
Portable tank and bulk container special provisions (ADR)	: TP1, TP8, TP28
Tank code (ADR)	: L1.5BN
Vehicle for tank carriage	: FL
Transport category (ADR)	: 2
Special provisions for carriage - Operation (ADR)	: S2, S20
Hazard identification number (Kemler No.)	: 33
Orange plates	:



Tunnel restriction code (ADR)	: D/E
-------------------------------	-------

#### - Transport by sea

Special provisions (IMDG)	: 274
Limited quantities (IMDG)	: 1 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T7
Tank special provisions (IMDG)	: TP1, TP8, TP28
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-E
Stowage category (IMDG)	: B

#### - Air transport

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y341
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 353
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L
Special provisions (IATA)	: A3
ERG code (IATA)	: 3H

# AQUAPHILE® AQ

## Safety Data Sheet

### - Inland waterway transport

Classification code (ADN)	: F1
Special provisions (ADN)	: 274, 601, 640C
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E2
Carriage permitted (ADN)	: T
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 1

### - Rail transport

Classification code (RID)	: F1
Special provisions (RID)	: 274, 601, 640C
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E2
Packing instructions (RID)	: P001
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T7
Portable tank and bulk container special provisions (RID)	: TP1, TP8, TP28
Tank codes for RID tanks (RID)	: L1.5BN
Transport category (RID)	: 2
Colis express (express parcels) (RID)	: CE7
Hazard identification number (RID)	: 33

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions  
Contains no substance on the REACH candidate list  
Contains no REACH Annex XIV substances

% Volatiles : > 75 %

#### 15.1.2. National regulations

##### Germany

Reference to AwSV : Water hazard class (WGK) 3, severe hazard to water (Classification according to AwSV, Annex 1)  
12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

##### Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed  
SZW-lijst van mutagene stoffen : None of the components are listed  
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed  
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed  
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed

##### Denmark

Class for fire hazard : Class I-1  
Store unit : 1 liter  
Classification remarks : F <Flam. Liq. 2>; Emergency management guidelines for the storage of flammable liquids must be followed

# AQUAPHILE® AQ

## Safety Data Sheet

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

### 15.2. Chemical safety assessment

No additional information available

## SECTION 16: Other information

Abbreviations and acronyms:

Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor

Other information : Prepared by safety and environmental affairs.

Full text of H- and EUH-statements:

Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

SDS EU (REACH Annex II) - Custom

*The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.*

© 2018 Gelest Inc. Morrisville, PA 19067



## Gelest Aquaphile™ AQ

### Hydrophilic Treatment For Glass and Ceramics





Features: Provide water-wettable silicone molecular films with high durability for glass and vitreous surfaces.

Applications:

**optical lenses** provides an anti-fog coating

**clinical analysis** - provides non-specific (albumin-like) binding of proteins and DNA.

(Not for food or drug use.)

Capsular Description:	Thickness	 molecular	Cure	 air/moisture	Hardness	 low	Type	 solvent-borne 1-part
--------------------------	-----------	--	------	---	----------	--	------	--

#### Gelest Aquaphile™ AQ

Polyamine functional silane that provides low-contact angle surfaces

#### Description

Aquaphile™ AQ is a partially quaternized polyamine functional silane in isopropanol. Air-dried films bond tenaciously to glass and ceramic substrates by reacting with hydroxy and silanol groups.

#### Properties of Treated Surfaces

(Values reported are for glass slides dipped in solutions of Aquaphile™ AQ and cured at room temperature for 4 hours.)

#### Typical Properties of Aquaphile™ AQ

% active	25%
flashpoint	12°C
specific gravity	0.84-0.86
viscosity	

#### PP1-AQAQ Aquaphile™ AQ

100g/\$24.00

1kg/\$168.00

#### Cautions

Aquaphile™ AQ is dispersed in isopropanol, a flammable solvent. Avoid skin and eye contact. Use in a well ventilated area wearing gloves and safety glasses.

#### Application Methods

Aquaphile™ coatings are most frequently applied directly or as a 10-20% mixture with dry alcohol. Articles are dipped or wiped. Articles can be cured by air drying for 4 hours at conditions of <75% relative humidity. Heat curing at 90-100°C for 10-15 minutes in an exhausted oven provides the most effective surface treatment.

Over treatment results in a cloudy surface. The concentration should be reduced to eliminate this effect