

**AQUAPHOBE® CF**

## Safety Data Sheet PP1-AQCF

Date of issue: 11/24/2014

Revision date: 11/05/2018

Version: 2.0

**SECTION 1: Identification****1.1. Identification**

Product name	: AQUAPHOBE® CF
Product code	: PP1-AQCF
Product form	: Substance
Physical state	: Liquid
Synonyms	: CHLORINATED SILOXANE; CHLORINE TERMINATED FLUORINATED ALKYL METHYLSILOXANES
Chemical family	: ORGANOSILOXANE

**1.2. Recommended use and restrictions on use**

Recommended use	: Chemical intermediate
-----------------	-------------------------

**1.3. Supplier****GELEST, INC.**11 East Steel Road  
Morrisville, PA 19067**USA**

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

[info@gelest.com](mailto:info@gelest.com) - [www.gelest.com](http://www.gelest.com)**1.4. Emergency telephone number**

Emergency number	: CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)
------------------	---

**SECTION 2: Hazard(s) identification****2.1. Classification of the substance or mixture****GHS-US classification**

Skin corrosion/irritation Category 1C	H314 Causes severe skin burns and eye damage
Serious eye damage/eye irritation Category 1	H318 Causes serious eye damage

Full text of H statements : see section 16

**2.2. GHS Label elements, including precautionary statements****GHS US labeling**

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger

Hazard statements (GHS US)	: H314 - Causes severe skin burns and eye damage H318 - Causes serious eye damage
----------------------------	--

Precautionary statements (GHS US)	: P280 - Wear protective gloves/protective clothing/eye protection/face protection. P260 - Do not breathe vapors. P264 - Wash hands thoroughly after handling. P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting P303+P361+P353 - If on skin (or hair): take off immediately all contaminated clothing. rinse skin with water/shower P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P310 - Immediately call a doctor P363 - Wash contaminated clothing before reuse. P405 - Store locked up. P501 - Dispose of contents/container to licensed waste disposal facility.
-----------------------------------	---

**2.3. Hazards not otherwise classified (HNOC)**

No additional information available

**2.4. Unknown acute toxicity (GHS US)**

Not applicable

**SECTION 3: Composition/Information on ingredients****3.1. Substances**

Substance type	: Mono-constituent
----------------	--------------------

# AQUAPHOBE® CF

## Safety Data Sheet

Name : AQUAPHOBE® CF  
CAS-No. : 908858-79-7

Name	Product identifier	%	GHS-US classification
Chlorine terminated fluorinated alkylmethylsiloxanes	(CAS-No.) 908858-79-7	95 - 100	Skin Corr. 1C, H314 Eye Dam. 1, H318

Full text of hazard classes and H-statements : see section 16

### 3.2. Mixtures

Not applicable

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

- First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.
- First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention.
- First-aid measures after skin contact : Wash with plenty of soap and water. Get immediate medical advice/attention.
- First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.
- First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Get medical advice/attention.

### 4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects : Causes severe skin burns and eye damage.
- Symptoms/effects after inhalation : May cause irritation to the respiratory tract. Overexposure may cause: Coughing. Headache. Nausea.
- Symptoms/effects after skin contact : Causes (severe) skin burns.
- Symptoms/effects after eye contact : Causes serious eye damage.
- Symptoms/effects after ingestion : May be harmful if swallowed.

### 4.3. Immediate medical attention and special treatment, if necessary

No additional information available

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Water spray. Foam. Carbon dioxide. Dry chemical.
- Unsuitable extinguishing media : Water.

### 5.2. Specific hazards arising from the chemical

- Fire hazard : Irritating fumes of hydrochloric acid and organic acid vapors may develop when material is exposed to water or open flame.

### 5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Use water spray to cool exposed surfaces. Exercise caution when fighting any chemical fire.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Avoid all eye and skin contact and do not breathe vapor and mist.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

- Emergency procedures : Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or shovel spills into appropriate container for disposal.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

# AQUAPHOBE® CF

## Safety Data Sheet

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapor and mist. Provide good ventilation in process area to prevent accumulation of vapors.
- Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before reuse.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep container tightly closed.
- Incompatible materials : Alcohols. Amines. Oxidizing agent.
- Storage area : Store in a well-ventilated place. Store away from heat.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

No additional information available

#### 8.2. Appropriate engineering controls

- Appropriate engineering controls : Provide local exhaust or general room ventilation.

#### 8.3. Individual protection measures/Personal protective equipment

##### Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

##### Hand protection:

Neoprene or nitrile rubber gloves

##### Eye protection:

Chemical goggles or face shield. Contact lenses should not be worn

##### Skin and body protection:

Wear suitable protective clothing

##### Respiratory protection:

NIOSH-certified combination organic vapor/acid gas (yellow cartridge) respirator.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Appearance : Liquid.
- Color : Straw. Amber.
- Odor : Acrid.
- Odor threshold : No data available
- Refractive index : No data available
- pH : No data available
- Relative evaporation rate (butyl acetate=1) : No data available
- Melting point : No data available
- Freezing point : < -20 °C
- Boiling point : 190 °C (initial)
- Flash point : > 65 °C
- Auto-ignition temperature : No data available
- Decomposition temperature : No data available
- Flammability (solid, gas) : No data available
- Vapor pressure : < 5 mm Hg @ 25°C
- Relative vapor density at 20 °C : > 1
- Relative density : 1.41 - 1.42
- Solubility : Reacts with water.
- Log Pow : No data available
- Log Kow : No data available

# AQUAPHOBE® CF

## Safety Data Sheet

Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Stable in sealed containers stored under a dry inert atmosphere.

### 10.3. Possibility of hazardous reactions

Reacts with water and moisture in air, liberating hydrogen chloride.

### 10.4. Conditions to avoid

Heat. Open flame. Sparks.

### 10.5. Incompatible materials

Alcohols. Amines. Oxidizing agent.

### 10.6. Hazardous decomposition products

Organic acid vapors. Hydrogen chloride.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation	: Causes severe skin burns and eye damage.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
	None of the components in this product at concentrations >0.1% are listed by IARC, NTP, OSHA or ACGIH as a carcinogen.
Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: Not classified
Specific target organ toxicity – repeated exposure	: Not classified
Aspiration hazard	: Not classified
Symptoms/effects after inhalation	: May cause irritation to the respiratory tract. Overexposure may cause: Coughing. Headache. Nausea.
Symptoms/effects after skin contact	: Causes (severe) skin burns.
Symptoms/effects after eye contact	: Causes serious eye damage.
Symptoms/effects after ingestion	: May be harmful if swallowed.
Reason for classification	: Expert judgment

## SECTION 12: Ecological information

### 12.1. Toxicity

No additional information available

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

No additional information available

### 12.4. Mobility in soil

No additional information available

# AQUAPHOBE® CF

## Safety Data Sheet

### 12.5. Other adverse effects

Other adverse effects : This substance may be hazardous to the environment.  
Effect on the ozone layer : No additional information available

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Product/Packaging disposal recommendations : May be incinerated. Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to licensed waste disposal facility.  
Ecology - waste materials : Avoid release to the environment.

## SECTION 14: Transport information

### 14.1. UN number

UN-No.(DOT) : 1760  
DOT NA no. UN1760

### 14.2. UN proper shipping name

Transport document description : UN1760 Corrosive liquids, n.o.s. (CHLORINE TERMINATED FLUORINATED ALKYL METHYLSILOXANES), 8, III  
Proper Shipping Name (DOT) : Corrosive liquids, n.o.s. (CHLORINE TERMINATED FLUORINATED ALKYL METHYLSILOXANES)  
Class (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136  
Packing group (DOT) : III - Minor Danger  
Hazard labels (DOT) : 8 - Corrosive



DOT Packaging Non Bulk (49 CFR 173.xxx) : 203  
DOT Packaging Bulk (49 CFR 173.xxx) : 241  
DOT Packaging Exceptions (49 CFR 173.xxx) : 154  
DOT Symbols : G - Identifies PSN requiring a technical name

### 14.3. Additional information

Emergency Response Guide (ERG) Number : 154  
Other information : No supplementary information available.

### Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.  
DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

### Air transport

DOT Quantity Limitations Passenger aircraft/rail : 5 L (49 CFR 173.27)  
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### AQUAPHOBE® CF (908858-79-7)

TSCA Exemption/Exclusion

Low Volume Exemption in accordance with 40 CFR 723.50(c)(1). Use of this substance is restricted to use in surface modification. Anyone who intends to use this chemical substance for commercial purposes must comply with specific use restrictions and controls specified herein. This LVE limits site of manufacture of this substance to Gelest, Inc. unless otherwise approved by U.S. EPA

#### Chlorine terminated fluorinated alkylmethylsiloxanes (908858-79-7)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

# AQUAPHOBE® CF

## Safety Data Sheet

### 15.2. International regulations

#### CANADA

No additional information available

#### EU-Regulations

No additional information available

#### National regulations

No additional information available

### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

## SECTION 16: Other information

Full text of H-phrases::

H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage

Abbreviations and acronyms

: Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor.

### Hazard Rating

**Hazard Rating**  
Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given  
Flammability : 2 Moderate Hazard - Materials which must be moderately heated or exposed to high ambient temperatures before ignition will occur. Includes liquids having a flash point at or above 100 F but below 200 F. (Classes II & IIIA)  
Physical : 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.

Prepared by safety and environmental affairs.

Date of issue: 11/24/2014      Revision date: 11/05/2018      Version: 2.0

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

*The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.*

© 2019 Gelest Inc. Morrisville, PA 19067

## Hydrophobic and Oleophobic Treatments For Glass and Ceramics

Features: Provides water-repellent silicone, fluorinated silicone molecular films with high durability for glass and vitreous surfaces. Acidic byproducts remove surface alkali from soda-lime glass substrates.





Applications:

**microcontact printing**- provides durable release films for photocurable resins.

**optical fibers**- reduces moisture adsorption and surface fracture.

**clinical analysis**- reduces protein and lipid adsorption. (Not for food or drug use.)

**glass plate and glazing**- provides high water contact angle, facilitate forced air blow-off.

Capsular Description:	Thickness	 molecular	Cure	 air/moisture	Hardness	 low	Type	 100% active 1-part
-----------------------	-----------	---	------	--	----------	---	------	---

**Aquaphobe® CF** chlorinated fluoroalkylmethylsiloxane

### Description

Aquaphobe® CF is a chlorine terminated polyfluoroalkyl-methylsiloxane oligomer. The chlorines react with hydroxy and silanol groups of glass, siliceous surfaces and other metal oxide surfaces to form a chemically bound, low surface energy, fluorinated silicone surface.

### Properties of Treated Surfaces

(Values reported are for glass slides dipped in 1% solutions of Aquaphobe® CF and cured at 100°C.)

#### critical surface tension

untreated	$\gamma_c = 78$ dynes/cm
treated (hydrophobic)	$\gamma_c = 16-19$ dynes/cm

#### Typical Properties of Aquaphobe® CF

% active	100%
flashpoint	65°C
specific gravity	1.40-1.43
refractive index	1.358
viscosity	6-10 cSt.

#### Reference:

J. Taniguchi et al, Jpn. Soc. Appl. Phys., 41, 4194, Part 1, No. 6B, 2002

#### Standard Packaging

PP1-AQCF	<b>Aquaphobe® CF</b>
	25g/\$82.00
	100g/\$266.00

### Cautions

Aquaphobe® is a mixture of corrosive chlorinated polysiloxanes. Avoid skin and eye contact. Use in a well ventilated area. Wear gloves and safety glasses.

### Application Methods

1. Aquaphobe® coatings are most frequently applied as a 2-10% solution in dry solvents such as hexane, methylene chloride or toluene. Articles are dipped or wiped. Articles can be cured by air drying for 24 hours at conditions of <75% relative humidity. Heat curing at 110°C for 15-20 minutes in an exhausted oven provides the most effective surface treatment.
2. A master batch of Aquaphobe® in isopropanol or ethanol is desirable when large areas are to be treated and the acidic byproducts are difficult to handle. A 0.5-2.0% solution in isopropanol is prepared in a well-ventilated area. Hydrogen chloride fumes issue during this stage. Acidic character is reduced for subsequent surface treatment.

Over treatment results in a cloudy surface. The concentration should be reduced to eliminate this effect.



11 E. Steel Road  
Morrisville, PA 19067

215-547-1015 phone  
215-547-2484 fax  
[www.gelest.com](http://www.gelest.com)

**NOTICE OF TSCA USE RESTRICTIONS AND REQUIRED CONTROLS FOR  
PP1-AQCF  
AQUAPHOBE® CF**

Dear Customer:

The chemical product purchased, PP1-AQCF has been granted a Low Volume Exemption by the U.S. Environmental Protection Agency (EPA) under the Toxic Substances Control Act (TSCA) regulations (40 CFR 723.50). Any manufacturer or processor who intends to use this chemical substance for commercial purposes must comply with the specific use restrictions and controls specified as follows:

**USE OF THIS CHEMICAL SUBSTANCE IS RESTRICTED TO:** Surface modification

**CONTROLS:** Workers must use personal protection equipment to limit dermal and inhalation exposures as described in Section 8: Exposure Controls/Personal Protection of the Safety Data Sheet (SDS). These exposure controls include:

Hand protection: Impervious gloves (neoprene or nitrile rubber gloves)

Eye Protection: Chemical goggles. Contact lenses should not be worn.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: Air-purifying respirator with organic vapor/acid gas cartridge.

**WASTE DISPOSAL:** Collect and containerize all waste, residues and wash solvents for off-site disposal by incineration. Do not release to POTW via sewer or to surface waters.

If you have questions or need more information related to allowable use of this substance, contact Gelest Regulatory Affairs at 215-547-1015.

Best Regards,

Gelest, Inc.  
Regulatory Affairs Department