

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Mixture
Physical state	: Liquid
Product name	: AQUAPHOBE® CM
Product code	: PP1-AQCM
Synonyms	: CHLORINE TERMINATED POLYDIMETHYLSILOXANES
Chemical family	: ORGANOSILOXANE

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Chemical intermediate

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

GELEST, INC.

11 East Steel Road
Morrisville, PA 19067

USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com

GELEST INC.

Fritz-Klatte-Strasse 8

65933 Frankfurt

Germany

T +49 (0) 69 3535106-500 - F +49 (0) 69 3535106-501 - (M-F): 8:00 AM - 4:00 PM

info@gelestde.com - www.gelestde.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2	H225
Skin corrosion/irritation, Category 1B	H314
Serious eye damage/eye irritation, Category 1	H318

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS05

Signal word (CLP) : Danger

Hazardous ingredients : 1,3-Dichlorotetramethylidisiloxane; 1,5-Dichloro-1,1,3,3,5,5-hexamethyltrisiloxane; 1,7-Dichlorooctamethyltetrasiloxane

AQUAPHOBE® CM

Safety Data Sheet

Hazard statements (CLP)	: H225 - Highly flammable liquid and vapour. H314 - Causes severe skin burns and eye damage.
Precautionary statements (CLP)	: P280 - Wear protective gloves/protective clothing/eye protection/face protection. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P240 - Ground/bond container and receiving equipment. P260 - Do not breathe vapours. P264 - Wash hands thoroughly after handling. P310 - Immediately call a POISON CENTER or doctor/physician
EUH-statements	: EUH014 - Reacts violently with water.

2.3. Other hazards

Other hazards not contributing to the classification	: Hydrogen chloride may be formed by reaction with water and moisture in air. The US OSHA PEL (TWA) for hydrogen chloride is 5 ppm.
--	---

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
1,5-Dichloro-1,1,3,3,5,5-hexamethyltrisiloxane	(CAS-No.) 3582-71-6 (EC-No.) 222-707-5	30 - 60	Skin Corr. 1B, H314 Eye Dam. 1, H318
1,3-Dichlorotetramethyldisiloxane	(CAS-No.) 2401-73-2 (EC-No.) 219-278-1	20 - 50	Flam. Liq. 2, H225 Skin Corr. 1B, H314 Eye Dam. 1, H318
1,7-Dichlorooctamethyltetrasiloxane	(CAS-No.) 2474-02-4 (EC-No.) 219-597-6	20 - 50	Skin Corr. 1B, H314 Eye Dam. 1, H318

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label. IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If you feel unwell, seek medical advice.
First-aid measures after skin contact	: Wash with plenty of water/.... Get immediate medical advice/attention.
First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.
First-aid measures after ingestion	: Never give anything by mouth to an unconscious person. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Causes severe skin burns and eye damage.
Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: Causes (severe) skin burns.
Symptoms/effects after eye contact	: Causes serious eye damage.
Symptoms/effects after ingestion	: May be harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Foam. Carbon dioxide. Dry chemical.
Unsuitable extinguishing media	: Water.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapour. Irritating fumes of hydrogen chloride and organic acid vapors may develop when material is exposed to water or open flame.
Explosion hazard	: May form flammable/explosive vapour-air mixture.

AQUAPHOBE® CM

Safety Data Sheet

5.3. Advice for firefighters

- Firefighting instructions : Use water spray to cool exposed surfaces. Exercise caution when fighting any chemical fire.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Avoid all eye and skin contact and do not breathe vapour and mist.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Eliminate every possible source of ignition. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

- Protective equipment : Wear protective equipment as described in Section 8.
- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

- Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
- Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or shovel spills into appropriate container for disposal. Use only non-sparking tools.

6.4. Reference to other sections

- See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapours are flammable. Do not allow contact with water.
- Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapour and mist. Provide good ventilation in process area to prevent formation of vapour. Ground/bond container and receiving equipment. Take precautionary measures against static discharge. Use only non-sparking tools.
- Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof electrical equipment.
- Storage conditions : Keep container tightly closed. Keep in a cool place. Store locked up.
- Incompatible materials : alcohols. Amines. Oxidizing agent.
- Storage area : Store in a well-ventilated place. Store away from heat.

7.3. Specific end use(s)

- No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

- No additional information available

8.2. Exposure controls

Appropriate engineering controls:

- Provide local exhaust or general room ventilation.

Personal protective equipment:

- Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Hand protection:

- Neoprene or nitrile rubber gloves

Eye protection:

- Chemical goggles or face shield. Contact lenses should not be worn

AQUAPHOBE® CM

Safety Data Sheet

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified combination organic vapor/acid gas (yellow cartridge) respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Molecular mass	: 203 - 353 g/mol
Colour	: Straw. Amber.
Odour	: Acrid.
Odour threshold	: No data available
Refractive index	: No additional information available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: < -20 °C
Boiling point	: 138 °C initial
Flash point	: 15 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Highly flammable liquid and vapour.
Vapour pressure	: 8 mm Hg @ 25°C
Relative vapour density at 20 °C	: > 1
Relative density	: 0.99 - 1.01
Solubility	: Reacts with water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable in sealed containers stored under a dry inert atmosphere.

10.3. Possibility of hazardous reactions

Reacts with water and moisture in air, liberating hydrogen chloride.

10.4. Conditions to avoid

Heat. Open flame. Sparks.

10.5. Incompatible materials

alcohols. Amines. Oxidizing agent.

10.6. Hazardous decomposition products

Hydrogen chloride. Organic acid vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

AQUAPHOBE® CM

Safety Data Sheet

Skin corrosion/irritation	: Causes severe skin burns and eye damage.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: Causes (severe) skin burns.
Symptoms/effects after eye contact	: Causes serious eye damage.
Symptoms/effects after ingestion	: May be harmful if swallowed.
Reason for classification	: Expert judgment

SECTION 12: Ecological information

12.1. Toxicity

Acute aquatic toxicity	: Not classified
Chronic aquatic toxicity	: Not classified

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Other adverse effects : This substance may be hazardous to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Sewage disposal recommendations	: Do not dispose of waste into sewer.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to licensed waste disposal facility.
Additional information	: Handle empty containers with care because residual vapours are flammable.
Ecology - waste materials	: Avoid release to the environment.

SECTION 14: Transport information

14.1. UN number

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR)	: 2924
UN-No. (IMDG)	: 2924
UN-No. (IATA)	: 2924
UN-No. (ADN)	: 2924
UN-No. (RID)	: 2924

14.2. UN proper shipping name

Proper Shipping Name (ADR)	: FLAMMABLE LIQUID, CORROSIVE, N.O.S.
Proper Shipping Name (IMDG)	: FLAMMABLE LIQUID, CORROSIVE, N.O.S.
Proper Shipping Name (IATA)	: Flammable liquid, corrosive, n.o.s.
Proper Shipping Name (ADN)	: FLAMMABLE LIQUID, CORROSIVE, N.O.S.
Proper Shipping Name (RID)	: FLAMMABLE LIQUID, CORROSIVE, N.O.S.
Transport document description (ADR)	: UN 2924 FLAMMABLE LIQUID, CORROSIVE, N.O.S. (CHLORINE TERMINATED POLYDIMETHYLSILOXANES), 3 (8), II, (D/E)

AQUAPHOBE® CM

Safety Data Sheet

Transport document description (IMDG)	: UN 2924 FLAMMABLE LIQUID, CORROSIVE, N.O.S. (CHLORINE TERMINATED POLYDIMETHYLSILOXANES), 3 (8), II
Transport document description (IATA)	: UN 2924 Flammable liquid, corrosive, n.o.s. (CHLORINE TERMINATED POLYDIMETHYLSILOXANES), 3 (8), II
Transport document description (ADN)	: UN 2924 FLAMMABLE LIQUID, CORROSIVE, N.O.S. (CHLORINE TERMINATED POLYDIMETHYLSILOXANES), 3 (8), II
Transport document description (RID)	: UN 2924 FLAMMABLE LIQUID, CORROSIVE, N.O.S. (CHLORINE TERMINATED POLYDIMETHYLSILOXANES), 3 (8), II

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR)	: 3 (8)
Danger labels (ADR)	: 3, 8



IMDG

Transport hazard class(es) (IMDG)	: 3 (8)
Danger labels (IMDG)	: 3, 8



IATA

Transport hazard class(es) (IATA)	: 3 (8)
Hazard labels (IATA)	: 3, 8



ADN

Transport hazard class(es) (ADN)	: 3 (8)
Danger labels (ADN)	: 3, 8



RID

Transport hazard class(es) (RID)	: 3 (8)
Danger labels (RID)	: 3, 8



14.4. Packing group

Packing group (ADR)	: II
Packing group (IMDG)	: II

AQUAPHOBE® CM

Safety Data Sheet

Packing group (IATA)	: II
Packing group (ADN)	: II
Packing group (RID)	: II

14.5. Environmental hazards

Dangerous for the environment	: No
Marine pollutant	: No
Other information	: No supplementary information available

14.6. Special precautions for user

- Overland transport

Classification code (ADR)	: FC		
Special provisions (ADR)	: 274		
Limited quantities (ADR)	: 1I		
Excepted quantities (ADR)	: E2		
Packing instructions (ADR)	: P001, IBC02		
Mixed packing provisions (ADR)	: MP19		
Portable tank and bulk container instructions (ADR)	: T11		
Portable tank and bulk container special provisions (ADR)	: TP2, TP27		
Tank code (ADR)	: L4BH		
Vehicle for tank carriage	: FL		
Transport category (ADR)	: 2		
Special provisions for carriage - Operation (ADR)	: S2, S20		
Hazard identification number (Kemler No.)	: 338		
Orange plates	: <table border="1"><tr><td>338</td></tr><tr><td>2924</td></tr></table>	338	2924
338			
2924			
Tunnel restriction code (ADR)	: D/E		

- Transport by sea

Special provisions (IMDG)	: 274
Limited quantities (IMDG)	: 1 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T11
Tank special provisions (IMDG)	: TP2, TP27
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-C
Stowage category (IMDG)	: B
Stowage and handling (IMDG)	: SW2
Properties and observations (IMDG)	: Causes burns to skin, eyes and mucous membranes.

- Air transport

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y340
PCA limited quantity max net quantity (IATA)	: 0.5L
PCA packing instructions (IATA)	: 352
PCA max net quantity (IATA)	: 1L
CAO packing instructions (IATA)	: 363
CAO max net quantity (IATA)	: 5L
Special provisions (IATA)	: A3
ERG code (IATA)	: 3CH

- Inland waterway transport

Classification code (ADN)	: FC
---------------------------	------

AQUAPHOBE® CM

Safety Data Sheet

Special provisions (ADN)	: 274
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E2
Carriage permitted (ADN)	: T
Equipment required (ADN)	: PP, EP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 1

- Rail transport

Classification code (RID)	: FC
Special provisions (RID)	: 274
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E2
Packing instructions (RID)	: P001, IBC02
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T11
Portable tank and bulk container special provisions (RID)	: TP2, TP27
Tank codes for RID tanks (RID)	: L4BH
Transport category (RID)	: 2
Colis express (express parcels) (RID)	: CE7
Hazard identification number (RID)	: 338

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions
Contains no substance on the REACH candidate list
Contains no REACH Annex XIV substances

15.1.2. National regulations

Germany

Reference to AwSV : Water hazard class (WGK) 3, severe hazard to water (Classification according to AwSV, Annex 1)
12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed
SZW-lijst van mutagene stoffen : None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed

Denmark

Class for fire hazard : Class I-1
Store unit : 1 liter
Classification remarks : F <Flam. Liq. 2>; Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

15.2. Chemical safety assessment

No additional information available

AQUAPHOBE® CM

Safety Data Sheet

SECTION 16: Other information

Abbreviations and acronyms:

Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor

Other information : Prepared by safety and environmental affairs.

Full text of H- and EUH-statements:

Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
H225	Highly flammable liquid and vapour.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
EUH014	Reacts violently with water.

SDS EU (REACH Annex II) - Custom

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2018 Gelest Inc. Morrisville, PA 19067

The logo for Gelest, featuring the word "Gelest" in a large, white, serif font. The letters "e", "l", "e", and "s" are partially overlaid by a large, light purple triangle that points to the right.

Hydrophobic Treatments For Glass and Ceramics

Features: Provides water-repellent silicone, molecular films with high durability for glass and vitreous surfaces. Acidic byproducts remove surface alkali from soda-lime glass substrates.





Applications:

laboratory glassware- improves drainage, reduce breakage.

optical fibers- reduces moisture adsorption and surface fracture.

clinical analysis- reduces protein and lipid adsorption. (Not for food or drug use.)

glass plate and glazing- provides high water contact angle, facilitate forced air blow-off.

Capsular Description:	Thickness	 molecular	Cure	 air/moisture	Hardness	 low	Type	 100% active 1-part
-----------------------	-----------	---	------	--	----------	---	------	---

Aquaphobe® CM chlorinated polydimethylsiloxane

Description

Aquaphobe® CM is a chlorine terminated polydimethylsiloxane oligomer. The chlorines react with hydroxy and silanol groups of glass, siliceous surfaces and other metal oxide surfaces to form a chemically bound polydimethylsiloxane “siliconized” surface.

Properties of Treated Surfaces

(Values reported are for glass slides dipped in 1% solutions of Aquaphobe® CM and cured at 100°C.)

critical surface tension

untreated	$\gamma_c = 78$ dynes/cm
treated (hydrophobic)	$\gamma_c = 25$ dynes/cm

Typical Properties of Aquaphobe™ CM

% active	100%
flashpoint	15°C
specific gravity	0.99-1.01
viscosity	3-6 cSt.

Standard Packaging

PP1-AQCM Aquaphobe® CM
100g/\$26.00
1kg/\$196.00
18kg/commercial package

Cautions

Aquaphobe® is a mixture of corrosive chlorinated polysiloxanes. Avoid skin and eye contact. Use in a well ventilated area. Wear gloves and safety glasses.

Application Methods

1. Aquaphobe® coatings are most frequently applied as a 2-10% solution in dry solvents such as hexane, methylene chloride or toluene. Articles are dipped or wiped. Articles can be cured by air drying for 24 hours at conditions of <75% relative humidity. Heat curing at 110°C for 15-20 minutes in an exhausted oven provides the most effective surface treatment.

2. A master batch of Aquaphobe® in isopropanol or ethanol is desirable when large areas are to be treated and the acidic byproducts are difficult to handle. A 0.5-2.0% solution in isopropanol is prepared in a well-ventilated area. Hydrogen chloride fumes issue during this stage. Acidic character is reduced for subsequent surface treatment.

Over treatment results in a cloudy surface. The concentration should be reduced to eliminate this effect.