

**GLASSCLAD® 18**

Safety Data Sheet PP1-GC18

Date of issue: 06/01/2015

Revision date: 05/03/2019

Version: 1.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product form	: Mixture
Physical state	: Liquid
Product name	: GLASSCLAD® 18
Product code	: PP1-GC18
Synonyms	: Octadecyl functional silane, 20% in t-butanol/diacetone alcohol
Chemical family	: ORGANOSILANE

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.2.1. Relevant identified uses**

Use of the substance/mixture : Chemical intermediate

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet**GELEST, INC.**11 East Steel Road
Morrisville, PA 19067**USA**

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com**GELEST INC.**Fritz-Klatte-Strasse 8
65933 Frankfurt**Germany**

T +49 (0) 69 3535106-500 - F +49 (0) 69 3535106-501 - (M-F): 8:00 AM - 4:00 PM

info@gelestde.com - www.gelestde.com**1.4. Emergency telephone number**

Emergency number : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Flammable liquids, Category 2	H225
Acute toxicity (inhalation:vapour) Category 4	H332
Serious eye damage/eye irritation, Category 2	H319
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation	H335
Full text of H statements : see section 16	

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP) :



GHS02

GHS07

Signal word (CLP) : Danger

Hazardous ingredients : 2-Methyl-2-propan-2-ol

GLASSCLAD® 18

Safety Data Sheet

Hazard statements (CLP)	: H225 - Highly flammable liquid and vapour. H319 - Causes serious eye irritation. H332 - Harmful if inhaled. H335 - May cause respiratory irritation.
Precautionary statements (CLP)	: P280 - Wear protective gloves/protective clothing/eye protection/face protection. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P240 - Ground/bond container and receiving equipment. P261 - Avoid breathing vapours. P264 - Wash hands thoroughly after handling. P312 - Call a doctor if you feel unwell.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
2-Methyl-2-propan-2-ol	(CAS-No.) 75-65-0 (EC-No.) 200-889-7 (EC Index-No.) 603-005-00-1	> 35	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2, H319 STOT SE 3, H335
4-Hydroxy-4-methyl-2-pentanone	(CAS-No.) 123-42-2 (EC-No.) 204-626-7 (EC Index-No.) 603-016-00-1	> 35	Eye Irrit. 2, H319
Octadecyl functional silane		> 20	Not classified

Specific concentration limits:

Name	Product identifier	Specific concentration limits
4-Hydroxy-4-methyl-2-pentanone	(CAS-No.) 123-42-2 (EC-No.) 204-626-7 (EC Index-No.) 603-016-00-1	(10 =<C < 100) Eye Irrit. 2, H319

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If you feel unwell, seek medical advice.
First-aid measures after skin contact	: Wash with plenty of water/.... Get medical advice/attention.
First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
First-aid measures after ingestion	: Never give anything by mouth to an unconscious person. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: May be harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Water fog. Foam. Carbon dioxide. Dry chemical.

GLASSCLAD® 18

Safety Data Sheet

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Highly flammable liquid and vapour. Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.
- Explosion hazard : May form flammable/explosive vapour-air mixture.

5.3. Advice for firefighters

- Firefighting instructions : Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Avoid all eye and skin contact and do not breathe vapour and mist.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Eliminate every possible source of ignition. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.

6.2. Environmental precautions

- Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or shovel spills into appropriate container for disposal. Use only non-sparking tools.

6.4. Reference to other sections

- See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapours are flammable.
- Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapour and mist. Containers and transfer lines require grounding during use. Provide good ventilation in process area to prevent formation of vapour. Use only non-sparking tools. Use only outdoors or in a well-ventilated area.
- Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof electrical equipment.
- Storage conditions : Keep container tightly closed. Store under N₂.
- Incompatible materials : Moist air. Oxidizing agent. Water :
- Storage area : Store in a well-ventilated place. Store away from heat.

7.3. Specific end use(s)

- No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2-Methyl-2-propan-2-ol (75-65-0)		
Austria	MAK (mg/m ³)	62 mg/m ³
Austria	MAK (ppm)	20 ppm
Austria	MAK Short time value (mg/m ³)	248 mg/m ³
Austria	MAK Short time value (ppm)	80 ppm
Belgium	Limit value (mg/m ³)	307 mg/m ³
Belgium	Limit value (ppm)	100 ppm
France	VME (mg/m ³)	300 mg/m ³
France	VME (ppm)	100 ppm
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	62 mg/m ³
Germany	TRGS 900 Occupational exposure limit value (ppm)	20 ppm
Greece	OEL TWA (mg/m ³)	300 mg/m ³
Greece	OEL TWA (ppm)	100 ppm
Greece	OEL STEL (mg/m ³)	450 mg/m ³

GLASSCLAD® 18

Safety Data Sheet

2-Methyl-2-propan-2-ol (75-65-0)		
Greece	OEL STEL (ppm)	150 ppm
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	100 ppm
Latvia	OEL TWA (mg/m ³)	10 mg/m ³
USA IDLH	US IDLH (ppm)	1600 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	300 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	450 mg/m ³
USA NIOSH	NIOSH REL (STEL) (ppm)	150 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	300 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm
Spain	VLA-ED (mg/m ³)	308 mg/m ³ (it is prohibited the partial or complete commercialization or use of this substance as a phytosanitary or biocide compound)
Spain	VLA-ED (ppm)	100 ppm (it is prohibited the partial or complete commercialization or use of this substance as a phytosanitary or biocide compound)
Switzerland	KZGW (mg/m ³)	240 mg/m ³
Switzerland	KZGW (ppm)	80 ppm
Switzerland	MAK (mg/m ³)	60 mg/m ³
Switzerland	MAK (ppm)	20 ppm
United Kingdom	WEL TWA (mg/m ³)	308 mg/m ³
United Kingdom	WEL TWA (ppm)	100 ppm
United Kingdom	WEL STEL (mg/m ³)	462 mg/m ³
United Kingdom	WEL STEL (ppm)	150 ppm
Czech Republic	Expoziční limity (PEL) (mg/m ³)	300 mg/m ³
Finland	HTP-arvo (8h) (mg/m ³)	150 mg/m ³
Finland	HTP-arvo (8h) (ppm)	50 ppm
Finland	HTP-arvo (15 min)	230 mg/m ³
Finland	HTP-arvo (15 min) (ppm)	75 ppm
Ireland	OEL (8 hours ref) (mg/m ³)	300 mg/m ³
Ireland	OEL (8 hours ref) (ppm)	100 ppm
Ireland	OEL (15 min ref) (mg/m ³)	450 mg/m ³
Ireland	OEL (15 min ref) (ppm)	150 ppm
Lithuania	IPRV (mg/m ³)	150 mg/m ³
Lithuania	IPRV (ppm)	50 ppm
Lithuania	TPRV (mg/m ³)	250 mg/m ³
Lithuania	TPRV (ppm)	75 ppm
Norway	Grenseverdier (Takverdi) (mg/m ³)	75 mg/m ³
Norway	Grenseverdier (Takverdi) (ppm)	25 ppm
Poland	NDS (mg/m ³)	300 mg/m ³
Poland	NDSch (mg/m ³)	450 mg/m ³
Slovakia	NPHV (priemerná) (mg/m ³)	62 mg/m ³
Slovakia	NPHV (priemerná) (ppm)	20 ppm
Slovakia	NPHV (Hraničná) (mg/m ³)	250 mg/m ³
Sweden	nivågränsvärde (NVG) (mg/m ³)	150 mg/m ³
Sweden	nivågränsvärde (NVG) (ppm)	50 ppm
Sweden	kortidsvärde (KTV) (mg/m ³)	250 mg/m ³
Sweden	kortidsvärde (KTV) (ppm)	75 ppm
Canada (Quebec)	VEMP (mg/m ³)	303 mg/m ³
Canada (Quebec)	VEMP (ppm)	100 ppm
Australia	TWA (mg/m ³)	303 mg/m ³
Australia	TWA (ppm)	100 ppm

GLASSCLAD® 18

Safety Data Sheet

2-Methyl-2-propan-2-ol (75-65-0)		
Australia	STEL (mg/m ³)	455 mg/m ³
Australia	STEL (ppm)	150 ppm
Portugal	OEL TWA (ppm)	100 ppm
Portugal	OEL chemical category (PT)	A4 - Not Classifiable as a Human Carcinogen
4-Hydroxy-4-methyl-2-pentanone (123-42-2)		
Austria	MAK (mg/m ³)	240 mg/m ³
Austria	MAK (ppm)	50 ppm
Belgium	Limit value (mg/m ³)	241 mg/m ³
Belgium	Limit value (ppm)	50 ppm
France	VME (mg/m ³)	240 mg/m ³
France	VME (ppm)	50 ppm
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	96 mg/m ³
Germany	TRGS 900 Occupational exposure limit value (ppm)	20 ppm
Greece	OEL TWA (mg/m ³)	240 mg/m ³
Greece	OEL TWA (ppm)	50 ppm
Greece	OEL STEL (mg/m ³)	360 mg/m ³
Greece	OEL STEL (ppm)	75 ppm
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	50 ppm
USA IDLH	US IDLH (ppm)	1800 ppm (10% LEL)
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	240 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	50 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	240 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm
Spain	VLA-ED (mg/m ³)	241 mg/m ³
Spain	VLA-ED (ppm)	50 ppm
Switzerland	KZGW (mg/m ³)	192 mg/m ³
Switzerland	KZGW (ppm)	40 ppm
Switzerland	MAK (mg/m ³)	96 mg/m ³
Switzerland	MAK (ppm)	20 ppm
United Kingdom	WEL TWA (mg/m ³)	241 mg/m ³
United Kingdom	WEL TWA (ppm)	50 ppm
United Kingdom	WEL STEL (mg/m ³)	362 mg/m ³
United Kingdom	WEL STEL (ppm)	75 ppm
Czech Republic	Expoziční limity (PEL) (mg/m ³)	200 mg/m ³
Denmark	Grænseværdie (langvarig) (mg/m ³)	240 mg/m ³
Denmark	Grænseværdie (langvarig) (ppm)	50 ppm
Finland	HTP-arvo (8h) (mg/m ³)	240 mg/m ³
Finland	HTP-arvo (8h) (ppm)	50 ppm
Finland	HTP-arvo (15 min)	360 mg/m ³
Finland	HTP-arvo (15 min) (ppm)	75 ppm
Ireland	OEL (8 hours ref) (mg/m ³)	240 mg/m ³
Ireland	OEL (8 hours ref) (ppm)	50 ppm
Ireland	OEL (15 min ref) (mg/m ³)	360 mg/m ³
Ireland	OEL (15 min ref) (ppm)	75 ppm
Lithuania	IPRV (mg/m ³)	120 mg/m ³
Lithuania	IPRV (ppm)	25 ppm
Lithuania	TPRV (mg/m ³)	240 mg/m ³
Lithuania	TPRV (ppm)	50 ppm
Norway	Grenseverdier (AN) (mg/m ³)	120 mg/m ³
Norway	Grenseverdier (AN) (ppm)	25 ppm
Norway	Grenseverdier (Korttidsverdi) (mg/m ³)	120 mg/m ³
Norway	Grenseverdier (Korttidsverdi) (ppm)	25 ppm

GLASSCLAD® 18

Safety Data Sheet

4-Hydroxy-4-methyl-2-pentanone (123-42-2)		
Poland	NDS (mg/m ³)	240 mg/m ³
Romania	OEL TWA (mg/m ³)	150 mg/m ³
Romania	OEL TWA (ppm)	32 ppm
Romania	OEL STEL (mg/m ³)	250 mg/m ³
Romania	OEL STEL (ppm)	53 ppm
Sweden	nivågränsvärde (NVG) (mg/m ³)	120 mg/m ³
Sweden	nivågränsvärde (NVG) (ppm)	25 ppm
Sweden	kortidsvärde (KTV) (mg/m ³)	240 mg/m ³
Sweden	kortidsvärde (KTV) (ppm)	50 ppm
Canada (Quebec)	VEMP (mg/m ³)	238 mg/m ³
Canada (Quebec)	VEMP (ppm)	50 ppm
Australia	TWA (mg/m ³)	238 mg/m ³
Australia	TWA (ppm)	50 ppm
Portugal	OEL TWA (ppm)	50 ppm

8.2. Exposure controls

Appropriate engineering controls:

Provide local exhaust or general room ventilation.

Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Hand protection:

Neoprene or nitrile rubber gloves

Eye protection:

Chemical goggles. Contact lenses should not be worn

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

NIOSH-certified organic vapor (black cartridge) respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Hazy liquid.
Colour	: Amber.
Odour	: No data available
Odour threshold	: No data available
Refractive index	: No additional information available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: -30 °C (Solidification Point)
Boiling point	: 100 °C (initial)
Flash point	: 10 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Highly flammable liquid and vapour.
Vapour pressure	: 45 mm Hg @ 25°C
Relative vapour density at 20 °C	: > 1
Relative density	: 0.88
% Volatiles	: > 75 °C
Solubility	: Insoluble in water. Reacts with water.

GLASSCLAD® 18

Safety Data Sheet

Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable in sealed bottles under a dry nitrogen for six months.

10.3. Possibility of hazardous reactions

Undergoes non-hazardous polymerization.

10.4. Conditions to avoid

Heat. Open flame. Sparks.

10.5. Incompatible materials

Moist air. Oxidizing agent. Water :

10.6. Hazardous decomposition products

Organic acid vapors. Silicon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Harmful if inhaled.

GLASSCLAD® 18

ATE CLP (vapours)	11 mg/l/4h
-------------------	------------

2-Methyl-2-propan-2-ol (75-65-0)

LD50 oral rat	2200 mg/kg
LD50 dermal rabbit	> 2 g/kg
LC50 inhalation rat (ppm)	> 10000 ppm/4h
ATE CLP (oral)	2200 mg/kg bodyweight
ATE CLP (vapours)	11 mg/l/4h

4-Hydroxy-4-methyl-2-pentanone (123-42-2)

LD50 oral rat	4 g/kg
ATE CLP (oral)	4000 mg/kg bodyweight

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

2-Methyl-2-propan-2-ol (75-65-0)

National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity
--	---------------------------------

Reproductive toxicity	: Not classified
STOT-single exposure	: May cause respiratory irritation.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: May be harmful if swallowed.

GLASSCLAD® 18

Safety Data Sheet

SECTION 12: Ecological information

12.1. Toxicity

Acute aquatic toxicity : Not classified
Chronic aquatic toxicity : Not classified

2-Methyl-2-propan-2-ol (75-65-0)

LC50 fish 1	6130 - 6700 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	933 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 Daphnia 2	4607 - 6577 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])

4-Hydroxy-4-methyl-2-pentanone (123-42-2)

LC50 fish 1	420 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
LC50 fish 2	420 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

2-Methyl-2-propan-2-ol (75-65-0)

BCF fish 1	1.09
Log Pow	0.35

4-Hydroxy-4-methyl-2-pentanone (123-42-2)

Log Pow	1.03
---------	------

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Incinerate. Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to licensed waste disposal facility.
Additional information : Handle empty containers with care because residual vapours are flammable.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

14.1. UN number

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR)	: 1993
UN-No. (IMDG)	: 1993
UN-No. (IATA)	: 1993
UN-No. (ADN)	: 1993
UN-No. (RID)	: 1993

14.2. UN proper shipping name

Proper Shipping Name (ADR)	: FLAMMABLE LIQUID, N.O.S.
Proper Shipping Name (IMDG)	: FLAMMABLE LIQUID, N.O.S.
Proper Shipping Name (IATA)	: Flammable liquid, n.o.s.
Proper Shipping Name (ADN)	: FLAMMABLE LIQUID, N.O.S.
Proper Shipping Name (RID)	: FLAMMABLE LIQUID, N.O.S.
Transport document description (ADR)	: UN 1993 FLAMMABLE LIQUID, N.O.S. (2-METHYL-2-PROPAN-2-OL), 3, II, (D/E)
Transport document description (IMDG)	: UN 1993 FLAMMABLE LIQUID, N.O.S. (2-METHYL-2-PROPAN-2-OL), 3, II
Transport document description (IATA)	: UN 1993 Flammable liquid, n.o.s. (2-METHYL-2-PROPAN-2-OL), 3, II
Transport document description (ADN)	: UN 1993 FLAMMABLE LIQUID, N.O.S. (2-METHYL-2-PROPAN-2-OL), 3, II
Transport document description (RID)	: UN 1993 FLAMMABLE LIQUID, N.O.S. (2-METHYL-2-PROPAN-2-OL), 3, II

14.3. Transport hazard class(es)

ADR

GLASSCLAD® 18

Safety Data Sheet

Transport hazard class(es) (ADR) : 3
Danger labels (ADR) : 3



IMDG

Transport hazard class(es) (IMDG) : 3
Danger labels (IMDG) : 3



IATA

Transport hazard class(es) (IATA) : 3
Hazard labels (IATA) : 3



ADN

Transport hazard class(es) (ADN) : 3
Danger labels (ADN) : 3



RID

Transport hazard class(es) (RID) : 3
Danger labels (RID) : 3



14.4. Packing group

Packing group (ADR) : II
Packing group (IMDG) : II
Packing group (IATA) : II
Packing group (ADN) : II
Packing group (RID) : II

14.5. Environmental hazards

Dangerous for the environment : No
Marine pollutant : No
Other information : No supplementary information available


GLASSCLAD® 18

Safety Data Sheet

14.6. Special precautions for user

- Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 274, 601, 640D
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E2
Packing instructions (ADR)	: P001, IBC02, R001
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T7
Portable tank and bulk container special provisions (ADR)	: TP1, TP8, TP28
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 2
Special provisions for carriage - Operation (ADR)	: S2, S20
Hazard identification number (Kemler No.)	: 33
Orange plates	:



Tunnel restriction code (ADR) : D/E

- Transport by sea

Special provisions (IMDG)	: 274
Limited quantities (IMDG)	: 1 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T7
Tank special provisions (IMDG)	: TP1, TP8, TP28
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-E
Stowage category (IMDG)	: B

- Air transport

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y341
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 353
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L
Special provisions (IATA)	: A3
ERG code (IATA)	: 3H

- Inland waterway transport

Classification code (ADN)	: F1
Special provisions (ADN)	: 274, 601, 640C
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E2
Carriage permitted (ADN)	: T
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 1

- Rail transport

Classification code (RID)	: F1
Special provisions (RID)	: 274, 601, 640C

GLASSCLAD® 18

Safety Data Sheet

Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E2
Packing instructions (RID)	: P001
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T7
Portable tank and bulk container special provisions (RID)	: TP1, TP8, TP28
Tank codes for RID tanks (RID)	: L1.5BN
Transport category (RID)	: 2
Colis express (express parcels) (RID)	: CE7
Hazard identification number (RID)	: 33

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.

Substance(s) are not subject to Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Directive 79/117/EEC.

Contains no REACH Annex XIV substances

% Volatiles : > 75 °C

15.1.2. National regulations

Germany

Reference to AwSV : Water hazard class (WGK) 3, Highly hazardous to water (Classification according to AwSV, Annex 1)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed

SZW-lijst van mutagene stoffen : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed

Denmark

Class for fire hazard : Class I-1

Store unit : 1 liter

Classification remarks : F <Flam. Liq. 2>; Emergency management guidelines for the storage of flammable liquids must be followed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Abbreviations and acronyms:

GLASSCLAD® 18

Safety Data Sheet

Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor

Other information : Prepared by safety and environmental affairs.

Full text of H- and EUH-statements:

Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.

SDS EU (REACH Annex II) - Custom

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2019 Gelest Inc. Morrisville, PA 19067

The logo features the word "Gelest" in a large, light blue, serif font. The letters are partially overlaid by a large, light blue triangle pointing to the right, which is also semi-transparent.



Gelest Glassclad® 18

Hydrophobic Water-Dispersible Coatings For Glass and Ceramics

Features: Provides water-repellency, lubricity, surface resistivity to glass and vitreous surfaces.

Applications:




laboratory glassware - improves drainage, reduces breakage.

optical fibers - provides lubricity and reduces breakage during fabrication and operational flexing.

clinical analysis - decreases protein adsorption of analytical and diagnostic equipment, decreases hemolysis and increases clotting time of blood. Glassclad®18 is not for food or drug use.

fluorescent light bulbs - increases scratch resistance, reducing breakage, increases surface resistivity.

porcelain ware - provides a glide surface and reduces adhesion to other porcelain ware.

Capsular Description:	Thickness	 molecular	Cure	 air/moisture	Hardness	 low	Type	 solvent-borne 1-part
-----------------------	-----------	---	------	--	----------	---	------	--

Glassclad®18 Hydrophobic Coating

Description

Glassclad®18 is a monomeric octadecylsilane derivative in a mixture of t-butanol and diacetone alcohol that reacts with water to form a silanol-rich prepolymer. The silanol-rich prepolymer condenses with available hydroxyl groups of siliceous substrates to form a chemically bound alkylsilicone.

Properties of Treated Surfaces

Values reported are for glass slides dipped in 1% solutions of Glassclad®18 and cured 5 minutes at 100°C.

Critical Surface Tension

untreated $\gamma_c = 78$ dynes/cm
treated (hydrophobic) $\gamma_c = 31$ dynes/cm

Surface Resistivity

untreated 1×10^{12} ohms
treated 1.2×10^{13} ohms

Coefficient of Friction, Static (glass slide on glass slide)

untreated 0.9-1.0
treated 0.2-0.3

Blood Protein Adsorption

(comparative 100 hour adsorption value for whole human blood on borosilicate glass surfaces)

untreated 0.13mg/mm²
treated 0.01-0.02mg/mm²

Solution Properties of Glassclad®18

solids 20%
color, gardner scale 8
specific gravity 0.88
flashpoint 10°C
viscosity 8-20 cSt.

Reference:

B. Arkles et al in "Silanes, Surfaces, Interfaces" D. Leyden ed, Gordon & Breach, 1986, p91.

Shelf Life of Glassclad®18

The shelf life of Glassclad®18 is six months in sealed containers. The product is normally hazy. A small amount of precipitate does not affect the performance of the solution.

Standard Packaging

PPI-GC18 Glassclad®18
100g/\$19.00
1.5kg/\$148.00
15kg/commercial package
180kg/commercial package

Application Methods

Glassclad®18 is most frequently used as a dilute aqueous dispersion containing 0.1-1.0% of reactive silane. A 0.2% solution of active chemical can be easily prepared by adding one part by weight of the product as supplied to 99 parts of water while stirring. The following treatment method is frequently employed.

1. Thoroughly clean objects with an alkaline detergent. Used or old glass surfaces may require immersion in 2-3% sodium hydroxide. All detergent and alkali should be removed with a final rinse.
2. Prepare a 1% solution of Glassclad®18 in water. Ordinary tap water is acceptable. "Hard water" or "fluoridated water," is not acceptable.
3. Immerse the glass or vitreous surface in the solution for 5-10 seconds, ensuring that all surfaces are wetted by the solution. Agitation of the solution or the object generally results in more uniform deposition. After immersion, remove the part and gently but thoroughly rinse with water to remove excess Glassclad®18 from the surface.
4. Cure Glassclad®18 by bringing surface temperature to 100°C for 3-5 minutes. Room temperature cure may be accomplished by air drying for 24 hours if relative humidity is 65% or less.

Each liter of solution will coat approximately 80 one liter beakers, 600 15cm test tubes, or approximately 250 m² of surface.

Stability of Glassclad®18 Solutions

Aqueous solutions are not stable and will turn cloudy and precipitate after standing for several days. The solution stability can be optimized by adjusting pH to 4.5-5.