

**GLASSCLAD® 18**

Safety Data Sheet PP1-GC18

Date of issue: 01/06/2015

Revision date: 03/05/2019

Version: 1.1

SECTION 1: Identification**1.1. Identification**

Product name	: GLASSCLAD® 18
Product code	: PP1-GC18
Product form	: Mixture
Physical state	: Liquid
Synonyms	: Octadecyl functional silane, 20% in t-butanol/diacetone alcohol
Chemical family	: ORGANOSILANE

1.2. Recommended use and restrictions on use

Recommended use	: Chemical intermediate
-----------------	-------------------------

1.3. Supplier**GELEST, INC.**11 East Steel Road
Morrisville, PA 19067**USA**

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com**1.4. Emergency telephone number**

Emergency number	: CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)
------------------	---

SECTION 2: Hazard(s) identification**2.1. Classification of the substance or mixture****GHS-US classification**

Flammable liquids Category 2	H225 Highly flammable liquid and vapor
Skin corrosion/irritation Category 2	H315 Causes skin irritation
Serious eye damage/eye irritation Category 2A	H319 Causes serious eye irritation
Specific target organ toxicity (single exposure) Category 3	H335 May cause respiratory irritation
Full text of H statements : see section 16	

2.2. GHS Label elements, including precautionary statements**GHS US labeling**

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger

Hazard statements (GHS US) :

H225 - Highly flammable liquid and vapor
 H315 - Causes skin irritation
 H319 - Causes serious eye irritation
 H335 - May cause respiratory irritation

Precautionary statements (GHS US) :

P280 - Wear protective gloves/protective clothing/eye protection/face protection.
 P261 - Avoid breathing vapors.
 P243 - Take precautionary measures against static discharge.
 P210 - Keep away from heat, open flames, sparks. - No smoking.
 P240 - Ground/Bond container and receiving equipment
 P241 - Use explosion-proof electrical equipment
 P242 - Use only non-sparking tools.
 P264 - Wash hands thoroughly after handling.
 P271 - Use only outdoors or in a well-ventilated area.
 P303+P361+P353 - If on skin (or hair): take off immediately all contaminated clothing. rinse skin with water/shower
 P332+P313 - If skin irritation occurs: Get medical advice/attention.
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 P337+P313 - If eye irritation persists: Get medical advice/attention.
 P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
 P312 - Call a doctor if you feel unwell
 P362 - Take off contaminated clothing and wash before reuse.
 P370+P378 - In case of fire: Use water spray or fog, foam, carbon dioxide, dry chemical to extinguish.
 P403+P235 - Keep in a cool place

GLASSCLAD® 18

Safety Data Sheet

P405 - Store locked up.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P501 - Dispose of contents/container to licensed waste disposal facility.

2.3. Hazards not otherwise classified (HNOC)

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
2-Methyl-2-propan-2-ol	(CAS-No.) 75-65-0	> 35	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H335
4-Hydroxy-4-methyl-2-pentanone	(CAS-No.) 123-42-2	> 35	Flam. Liq. 4, H227 Skin Irrit. 2, H315 Eye Irrit. 2A, H319
Octadecyl functional silane*	(CAS-No.) Trade Secret	> 20	Not classified

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.
- First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.
- First-aid measures after skin contact : Wash with plenty of soap and water. Get medical advice/attention.
- First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
- First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Get medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects after inhalation : May cause respiratory irritation.
- Symptoms/effects after skin contact : Causes skin irritation.
- Symptoms/effects after eye contact : Causes serious eye irritation.
- Symptoms/effects after ingestion : May be harmful if swallowed.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Water fog. Foam. Carbon dioxide. Dry chemical.

5.2. Specific hazards arising from the chemical

- Fire hazard : Highly flammable liquid and vapor. Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.
- Explosion hazard : May form flammable/explosive vapor-air mixture.

5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Avoid all eye and skin contact and do not breathe vapor and mist.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Eliminate every possible source of ignition. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

GLASSCLAD® 18

Safety Data Sheet

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or shovel spills into appropriate container for disposal. Use only non-sparking tools.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.
Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapor and mist. Containers and transfer lines require grounding during use. Provide good ventilation in process area to prevent accumulation of vapors. Use only non-sparking tools. Use only outdoors or in a well-ventilated area.
Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof electrical equipment.
Storage conditions : Keep container tightly closed. Store under N2.
Incompatible materials : Moist air. Oxidizing agent. Water.
Storage area : Store in a well-ventilated place. Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2-Methyl-2-propan-2-ol (75-65-0)		
ACGIH	ACGIH TWA (ppm)	100 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	300 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
IDLH	US IDLH (ppm)	1600 ppm
NIOSH	NIOSH REL (TWA) (mg/m ³)	300 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
NIOSH	NIOSH REL (STEL) (mg/m ³)	450 mg/m ³
NIOSH	NIOSH REL (STEL) (ppm)	150 ppm
4-Hydroxy-4-methyl-2-pentanone (123-42-2)		
ACGIH	ACGIH TWA (ppm)	50 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	240 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	50 ppm
IDLH	US IDLH (ppm)	1800 ppm (10% LEL)
NIOSH	NIOSH REL (TWA) (mg/m ³)	240 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	50 ppm

8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Hand protection:

Neoprene or nitrile rubber gloves

Eye protection:

GLASSCLAD® 18

Safety Data Sheet

Chemical goggles. Contact lenses should not be worn

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

NIOSH-certified organic vapor (black cartridge) respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Hazy liquid.
Color	: Amber.
Odor	: No data available
Odor threshold	: No data available
Refractive index	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: -30 °C (Solidification Point)
Boiling point	: 100 °C (initial)
Flash point	: 10 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Highly flammable liquid and vapor
Vapor pressure	: 45 mm Hg @ 25°C
Relative vapor density at 20 °C	: > 1
Relative density	: 0.88
% Volatiles	: > 75 °C
Solubility	: Insoluble in water. Reacts with water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable in sealed bottles under a dry nitrogen for six months.

10.3. Possibility of hazardous reactions

Undergoes non-hazardous polymerization.

10.4. Conditions to avoid

Heat. Open flame. Sparks.

10.5. Incompatible materials

Moist air. Oxidizing agent. Water.

10.6. Hazardous decomposition products

Organic acid vapors. Silicon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

GLASSCLAD® 18

Safety Data Sheet

2-Methyl-2-propan-2-ol (75-65-0)	
LD50 oral rat	2200 mg/kg
LD50 dermal rabbit	> 2 g/kg
LC50 inhalation rat (ppm)	> 10000 ppm/4h
ATE US (oral)	2200 mg/kg body weight

4-Hydroxy-4-methyl-2-pentanone (123-42-2)	
LD50 oral rat	4 g/kg

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

2-Methyl-2-propan-2-ol (75-65-0)	
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity

Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: May cause respiratory irritation.

Specific target organ toxicity – repeated exposure	: Not classified
--	------------------

Aspiration hazard	: Not classified
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: May be harmful if swallowed.

SECTION 12: Ecological information

12.1. Toxicity

2-Methyl-2-propan-2-ol (75-65-0)	
LC50 fish 1	6130 - 6700 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	933 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 Daphnia 2	4607 - 6577 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])

4-Hydroxy-4-methyl-2-pentanone (123-42-2)	
LC50 fish 1	420 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
LC50 fish 2	420 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

2-Methyl-2-propan-2-ol (75-65-0)	
BCF fish 1	1.09
Log Pow	0.35

4-Hydroxy-4-methyl-2-pentanone (123-42-2)	
Log Pow	1.03

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the ozone layer	: No additional information available
---------------------------	---------------------------------------

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations	: Incinerate. Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to licensed waste disposal facility.
Additional information	: Handle empty containers with care because residual vapors are flammable.
Ecology - waste materials	: Avoid release to the environment.

GLASSCLAD® 18

Safety Data Sheet

SECTION 14: Transport information

14.1. UN number

UN-No.(DOT) : 1993
DOT NA no. UN1993

14.2. UN proper shipping name

Transport document description : UN1993 Flammable liquids, n.o.s. (2-METHYL-2-PROPAN-2-OL), 3, II
Proper Shipping Name (DOT) : Flammable liquids, n.o.s.
(2-METHYL-2-PROPAN-2-OL)
Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Packing group (DOT) : II - Medium Danger
Hazard labels (DOT) : 3 - Flammable liquid



DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Symbols : G - Identifies PSN requiring a technical name

14.3. Additional information

Emergency Response Guide (ERG) Number : 128
Other information : No supplementary information available.

Transport by sea

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 5 L
(49 CFR 173.27)
DOT Quantity Limitations Cargo aircraft only (49 : 60 L
CFR 175.75)

SECTION 15: Regulatory information

15.1. US Federal regulations

2-Methyl-2-propan-2-ol (75-65-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313

SARA Section 313 - Emission Reporting	1 %
---------------------------------------	-----

4-Hydroxy-4-methyl-2-pentanone (123-42-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a final TSCA section 4 test rule.
--------------------------	--

Octadecyl functional silane

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

2-Methyl-2-propan-2-ol (75-65-0)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	--

GLASSCLAD® 18

Safety Data Sheet

4-Hydroxy-4-methyl-2-pentanone (123-42-2)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification

Class B Division 3 - Combustible Liquid
Class D Division 2 Subdivision B - Toxic material causing other toxic effects

EU-Regulations

2-Methyl-2-propan-2-ol (75-65-0)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

4-Hydroxy-4-methyl-2-pentanone (123-42-2)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

2-Methyl-2-propan-2-ol (75-65-0)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the Canadian IDL (Ingredient Disclosure List)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)

4-Hydroxy-4-methyl-2-pentanone (123-42-2)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the Canadian IDL (Ingredient Disclosure List)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

2-Methyl-2-propan-2-ol (75-65-0)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List

4-Hydroxy-4-methyl-2-pentanone (123-42-2)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Full text of H-phrases::

H225	Highly flammable liquid and vapor
H227	Combustible liquid
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation

Abbreviations and acronyms

: Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor.

GLASSCLAD® 18

Safety Data Sheet

Hazard Rating

Health	: 2 Moderate Hazard - Temporary or minor injury may occur
Flammability	: 4 Severe Hazard - Flammable gases, or very volatile flammable liquids with flash points below 73 F, and boiling points below 100 F. Materials may ignite spontaneously with air. (Class IA)
Physical	: 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.

Prepared by safety and environmental affairs.


Date of issue: 01/06/2015 Revision date: 03/05/2019 Version: 1.1

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2019 Gelest Inc. Morrisville, PA 19067





Hydrophobic Water-Dispersible Coatings For Glass and Ceramics

Features: Provides water-repellency, lubricity, surface resistivity to glass and vitreous surfaces.

Applications:





laboratory glassware - improves drainage, reduces breakage.

optical fibers - provides lubricity and reduces breakage during fabrication and operational flexing.

clinical analysis - decreases protein adsorption of analytical and diagnostic equipment, decreases hemolysis and increases clotting time of blood. Glassclad®18 is not for food or drug use.

fluorescent light bulbs - increases scratch resistance, reducing breakage, increases surface resistivity.

porcelain ware - provides a glide surface and reduces adhesion to other porcelain ware.

Capsular Description:	Thickness	 molecular	Cure	 air/moisture	Hardness	 low	Type	 solvent-borne 1-part
-----------------------	-----------	---	------	--	----------	---	------	--

Glassclad®18 Hydrophobic Coating

Description

Glassclad®18 is a monomeric octadecylsilane derivative in a mixture of t-butanol and diacetone alcohol that reacts with water to form a silanol-rich prepolymer. The silanol-rich prepolymer condenses with available hydroxyl groups of siliceous substrates to form a chemically bound alkylsilicone.

Properties of Treated Surfaces

Values reported are for glass slides dipped in 1% solutions of Glassclad®18 and cured 5 minutes at 100°C.

Critical Surface Tension

untreated $\gamma_c = 78$ dynes/cm
treated (hydrophobic) $\gamma_c = 31$ dynes/cm

Surface Resistivity

untreated 1×10^{12} ohms
treated 1.2×10^{13} ohms

Coefficient of Friction, Static (glass slide on glass slide)

untreated 0.9-1.0
treated 0.2-0.3

Blood Protein Adsorption

(comparative 100 hour adsorption value for whole human blood on borosilicate glass surfaces)

untreated 0.13mg/mm²
treated 0.01-0.02mg/mm²

Solution Properties of Glassclad®18

solids 20%
color, gardner scale 8
specific gravity 0.88
flashpoint 10°C
viscosity 8-20 cSt.

Reference:

B. Arkles et al in "Silanes, Surfaces, Interfaces" D. Leyden ed, Gordon & Breach, 1986, p91.

Shelf Life of Glassclad®18

The shelf life of Glassclad®18 is six months in sealed containers. The product is normally hazy. A small amount of precipitate does not affect the performance of the solution.

Standard Packaging

PPI-GC18 Glassclad®18
100g/\$19.00
1.5kg/\$148.00
15kg/commercial package
180kg/commercial package

Application Methods

Glassclad®18 is most frequently used as a dilute aqueous dispersion containing 0.1-1.0% of reactive silane. A 0.2% solution of active chemical can be easily prepared by adding one part by weight of the product as supplied to 99 parts of water while stirring. The following treatment method is frequently employed.

1. Thoroughly clean objects with an alkaline detergent. Used or old glass surfaces may require immersion in 2-3% sodium hydroxide. All detergent and alkali should be removed with a final rinse.
2. Prepare a 1% solution of Glassclad®18 in water. Ordinary tap water is acceptable. "Hard water" or "fluoridated water," is not acceptable.
3. Immerse the glass or vitreous surface in the solution for 5-10 seconds, ensuring that all surfaces are wetted by the solution. Agitation of the solution or the object generally results in more uniform deposition. After immersion, remove the part and gently but thoroughly rinse with water to remove excess Glassclad®18 from the surface.
4. Cure Glassclad®18 by bringing surface temperature to 100°C for 3-5 minutes. Room temperature cure may be accomplished by air drying for 24 hours if relative humidity is 65% or less.

Each liter of solution will coat approximately 80 one liter beakers, 600 15cm test tubes, or approximately 250 m² of surface.

Stability of Glassclad®18 Solutions

Aqueous solutions are not stable and will turn cloudy and precipitate after standing for several days. The solution stability can be optimized by adjusting pH to 4.5-5.