



# GELEST OPTICAL ENCAPSULANT 41 LOW VOLATILITY GRADE 1 KG KIT

Safety Data Sheet PP2-OE41.6

Date of issue: 08/25/2016 Version: 1.0

## SECTION 1: Identification

### 1.1. Identification

Product name	: GELEST OPTICAL ENCAPSULANT 41 LOW VOLATILITY GRADE 1 KG KIT
Product code	: PP2-OE41.6
Product form	: Mixture
Physical state	: Liquid
Synonyms	: Gelest OE™ 41.6 2-part Low Volatility Optical Encapsulant VINYL MODIFIED SILICA Q RESIN in POLY(DIMETHYLSILOXANE), VINYL TERMINATED with (part B) HYDRIDE FUNCTIONAL CROSSLINKER RESIN REINFORCED VINYL TERMINATED POLYDIMETHYLSILOXANE
Chemical family	: ORGANOSILOXANE

### 1.2. Recommended use and restrictions on use

Recommended use	: Chemical intermediate
-----------------	-------------------------

### 1.3. Supplier

**GELEST, INC.**  
11 East Steel Road  
Morrisville, PA 19067  
**USA**  
T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST  
[info@gelest.com](mailto:info@gelest.com) - [www.gelest.com](http://www.gelest.com)

### 1.4. Emergency telephone number

Emergency number	: CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)
------------------	---

## SECTION 2: Hazard(s) identification

### 2.1. Classification of the substance or mixture

#### GHS-US classification

Not classified

### 2.2. GHS Label elements, including precautionary statements

#### GHS US labeling

No labeling applicable

### 2.3. Hazards not otherwise classified (HNOC)

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Part A: Monovinyl terminated polydimethylsiloxane	(CAS-No.) 68951-99-5	> 70	Not classified
Vinyl modified Q silica resin	(CAS-No.) 68584-83-8	< 30	Not classified
Part B: Methylhydrosiloxane-dimethylsiloxane copolymer, trimethylsiloxane terminated	(CAS-No.) 68037-59-2	< 10	Not classified

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.
First-aid measures after skin contact	: Wash with plenty of soap and water. Get medical advice/attention.
First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.

# GELEST OPTICAL ENCAPSULANT 41 LOW VOLATILITY GRADE 1 KG KIT

## Safety Data Sheet

First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Get medical advice/attention.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : No information available.  
Symptoms/effects after skin contact : May cause skin irritation.  
Symptoms/effects after eye contact : May cause eye irritation.  
Symptoms/effects after ingestion : No information available.

### 4.3. Immediate medical attention and special treatment, if necessary

No additional information available

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Water fog. Foam. Carbon dioxide. Dry chemical.  
Unsuitable extinguishing media : None known.

### 5.2. Specific hazards arising from the chemical

Fire hazard : Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.

### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers.  
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Avoid all eye and skin contact and do not breathe vapor and mist.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Protective equipment : Wear protective equipment as described in Section 8.  
Emergency procedures : Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.  
Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or shovel spills into appropriate container for disposal.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapor and mist.  
Hygiene measures : Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container tightly closed.  
Incompatible materials : Alkalis. Metal salts. Oxidizing agent. Precious metals.  
Storage area : Store in a well-ventilated place. Store away from heat.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

No additional information available

# GELEST OPTICAL ENCAPSULANT 41 LOW VOLATILITY GRADE 1 KG KIT

## Safety Data Sheet

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation.

### 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

#### Hand protection:

Neoprene or nitrile rubber gloves

#### Eye protection:

Chemical goggles. Contact lenses should not be worn

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified organic vapor (black cartridge) respirator.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear liquid.
Molecular mass	: (mixture)
Color	: No data available
Odor	: No data available
Odor threshold	: No data available
Refractive index	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: < -60 °C
Freezing point	: No data available
Boiling point	: > 205 °C
Flash point	: 220 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: < 1 mm Hg @ 20°C
Relative vapor density at 20 °C	: No data available
Relative density	: 1.01
% Volatiles	: < 3 %
Solubility	: Insoluble in water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: 1000 - 4000 cSt
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

# GELEST OPTICAL ENCAPSULANT 41 LOW VOLATILITY GRADE 1 KG KIT

## Safety Data Sheet

### 10.2. Chemical stability

Stable in sealed containers stored under a dry inert atmosphere.

### 10.3. Possibility of hazardous reactions

No additional information available

### 10.4. Conditions to avoid

Heat. Open flame. Sparks.

### 10.5. Incompatible materials

Alkalis. Metal salts. Oxidizing agent. Precious metals.

### 10.6. Hazardous decomposition products

Organic acid vapors. Silicon dioxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified  
Skin corrosion/irritation : Not classified  
Serious eye damage/irritation : Not classified  
Respiratory or skin sensitization : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified

Reproductive toxicity : Not classified  
Specific target organ toxicity – single exposure : Not classified

Specific target organ toxicity – repeated exposure : Not classified

Aspiration hazard : Not classified  
Symptoms/effects after inhalation : No information available.  
Symptoms/effects after skin contact : May cause skin irritation.  
Symptoms/effects after eye contact : May cause eye irritation.  
Symptoms/effects after ingestion : No information available.

## SECTION 12: Ecological information

### 12.1. Toxicity

No additional information available

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

No additional information available

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Effect on the ozone layer : No additional information available

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Sewage disposal recommendations : Do not dispose of waste into sewer.  
Product/Packaging disposal recommendations : Incinerate. Dispose in a safe manner in accordance with local/national regulations.  
Ecology - waste materials : Avoid release to the environment.

## SECTION 14: Transport information

### 14.1. UN number

Not regulated for transport.

### 14.2. UN proper shipping name

Not applicable

# GELEST OPTICAL ENCAPSULANT 41 LOW VOLATILITY GRADE 1 KG KIT

## Safety Data Sheet

### 14.3. Additional information

Other information : No supplementary information available.

#### Transport by sea

No additional information available

#### Air transport

No additional information available

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### Part A: Monovinyl terminated polydimethylsiloxane (68951-99-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### Vinyl modified Q silica resin (68584-83-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### Part B: Methylhydrosiloxane-dimethylsiloxane copolymer, trimethylsiloxane terminated (68037-59-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

### 15.2. International regulations

#### CANADA

#### Part A: Monovinyl terminated polydimethylsiloxane (68951-99-5)

Listed on the Canadian DSL (Domestic Substances List)

#### Vinyl modified Q silica resin (68584-83-8)

Listed on the Canadian DSL (Domestic Substances List)

#### Part B: Methylhydrosiloxane-dimethylsiloxane copolymer, trimethylsiloxane terminated (68037-59-2)

Listed on the Canadian DSL (Domestic Substances List)

#### EU-Regulations

No additional information available

#### Vinyl modified Q silica resin (68584-83-8)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

#### National regulations

#### Part A: Monovinyl terminated polydimethylsiloxane (68951-99-5)

Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the Korean ECL (Existing Chemicals List)  
Listed on NZIoC (New Zealand Inventory of Chemicals)

#### Vinyl modified Q silica resin (68584-83-8)

Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the Korean ECL (Existing Chemicals List)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

#### Part B: Methylhydrosiloxane-dimethylsiloxane copolymer, trimethylsiloxane terminated (68037-59-2)

Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on the Korean ECL (Existing Chemicals List)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Listed on INSQ (Mexican National Inventory of Chemical Substances)

### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

## SECTION 16: Other information

# GELEST OPTICAL ENCAPSULANT 41 LOW VOLATILITY GRADE 1 KG KIT

## Safety Data Sheet

### Abbreviations and acronyms

: Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor.

### Hazard Rating

Health : 1 Slight Hazard - Irritation or minor reversible injury possible  
Flammability : 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)  
Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Prepared by safety and environmental affairs.

Date of issue: 08/25/2016      Version: 1.0

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

*The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.*

© 2019 Gelest Inc. Morrisville, PA 19067



# Gelest Flexible Optical Encapsulant Series

## Filler-Free 2-part Silicone Elastomers

Features: Provide rapid-cure pure silicone elastomers with high optical transmission They have relatively low viscosity and extended pot-life, allowing potting, embedding and coating. Systems are vinyl-addition (platinum) cure.

Applications:

**electronic devices** - provide mechanical and chemical protection to electronic components, free of abrasive silica.

**optical devices** - index matching, cladding or transmission media applications.

**supported membranes** - filler-free silicone allows maximum transport of gases.

Capsular Description:	Thickness		Cure	<b>Pt</b>	Hardness		Type	
	thick		catalyst		medium		100% active 2-part	

**Gelest OE™ 41** 1.41 refractive index 2-part silicone RTV encapsulant, supplied as 1:1 kit

### Description

Gelest OE™ 41 is a flexible, optically clear molding, encapsulation and coating compound. The low viscosity of the catalyzed mix, long pot-life at room temperature and moderate cure temperature make this extremely useful in laboratory, prototype and small production run applications.

### Cured Properties


Refractive Index	1.407
Tensile Strength	>300psi
Elongation	140-200%
Durometer, Shore A	15-30
Tear Strength	5-15pli

### Uncured Properties of Gelest OE™ 41

Viscosity (1:1) catalyzed: 1750-2500 cSt.

### Application Methods

Thoroughly mix Part A with Part B in a 1:1 ratio. De-air mix under vacuum for about 20 minutes. The pot-life is 18 hours at 25°C. Pot-life may be extended by storing at 5°C. Pour into mold or apply to substrate. Avoid entrapping air. Cure at 55°C for 4 hours or at room temperature over 72 hours.



### Standard Packaging

PP2-OE41 <b>Gelest OE™ 41</b>	
1 kg kit (500g OE41A, 500g OE41B):	\$84.00
6 kg kit (3kg OE41A, 3kg OE41B):	\$384.00

**Gelest OE™ 41 is available in other versions in which cure speed or volatile content has been varied to match special requirements.**

### Gelest OE™ 41.2 Accelerated Cure

Rapid cure version of standard Gelest OE™ 41, cures in less than 1 hour at room temperature, has a working time of about 10 minutes.

PP2-OE41.2 <b>Gelest OE™ 41.2</b>	
1 kg kit (500g OE41.2A, 500g OE41.2B):	\$96.00
6 kg kit (3kg OE41.2A, 3kg OE41.2B):	\$384.00

### Gelest OE™ 41.4 Extended Cure

Slow cure version of standard Gelest OE™ 41, offers a pot-life of 48 hours at room temperature. Cures in one hour at 120°C

PP2-OE41.4 <b>Gelest OE™ OE41.4B</b>	
1 kg kit (500g OE41.4A, 500g OE41B):	\$96.00
6 kg kit (3kg OE41.4A, 3kg OE41.4B):	\$384.00

### Gelest OE™ 41.6 Low Volatility

Low volatility content of **Gelest OE™ 41.6** offers advantages in electrical and high vacuum where bleed or migration of low molecular weight species can have deleterious effects.

PP2-OE41.6 <b>Gelest OE™ 41.6</b>	
1 kg kit (500g OE41.6A, 500g OE41.6B):	\$160.00

### Gelest OE™ 41.7 Low Volatility in solution

A single component solution version in toluene which cures after evaporation of solvent i 24 ours to form optically clear films. Product must be stored <5°C

PP1-OE41.7 <b>Gelest OE™ 41.7</b>	100g/\$85.00
-----------------------------------	--------------