



Enabling Your Technology

GELEST RG® 03 HYDROPHILIC REPROGRAPHIC SILICONE

Safety Data Sheet PP2-RG03

Date of issue: 06/02/2016 Version: 1.0

SECTION 1: Identification**1.1. Identification**

Product name : GELEST RG® 03 HYDROPHILIC REPROGRAPHIC SILICONE
 Product code : PP2-RG03
 Product form : Mixture
 Physical state : Liquid
 Synonyms : 2-COMPONENT SILICONE RTV; VINYL, METHYL MODIFIED SILICA in POLY(DIMETHYLSILOXANE), VINYLTERMINATED with (part B) HYDRIDE FUNCTIONAL CROSSLINKER
 Chemical family : ORGANOSILOXANE

1.2. Recommended use and restrictions on use

Recommended use : Chemical intermediate

1.3. Supplier**GELEST, INC.**

11 East Steel Road
 Morrisville, PA 19067

USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

SECTION 2: Hazard(s) identification**2.1. Classification of the substance or mixture****GHS-US classification**

Not classified

2.2. GHS Label elements, including precautionary statements**GHS US labeling**

No labeling applicable

2.3. Hazards not otherwise classified (HNOC)

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients**3.1. Substances**

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Part A: Vinyl terminated polydimethylsiloxane	(CAS-No.) 68083-19-2	> 70	Not classified
Part B: Methylhydrosiloxane-dimethylsiloxane copolymer, trimethylsiloxane terminated	(CAS-No.) 68037-59-2	< 50	Not classified
Part A: Vinyl, methyl modified silica	(CAS-No.) 68988-89-6	< 30	Not classified
Part A: Vinyl functional polydimethylsiloxane, methoxy(diethyleneoxide)propyl terminated	(CAS-No.) 1586018-77-0	< 20	Not classified

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures**4.1. Description of first aid measures**

First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.

First-aid measures after skin contact : Wash with plenty of soap and water. Get medical advice/attention.

GELEST RG® 03 HYDROPHILIC REPROGRAPHIC SILICONE

Safety Data Sheet

First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
First-aid measures after ingestion	: Never give anything by mouth to an unconscious person. Get medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: No information available.
Symptoms/effects after skin contact	: May cause mild skin irritation.
Symptoms/effects after eye contact	: May cause mild eye irritation.
Symptoms/effects after ingestion	: No information available.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Water fog. Foam. Carbon dioxide. Dry chemical.
Unsuitable extinguishing media	: None known.

5.2. Specific hazards arising from the chemical

Fire hazard	: Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.
-------------	---

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection. Avoid all eye and skin contact and do not breathe vapor and mist.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment	: Wear protective equipment as described in Section 8.
Emergency procedures	: Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	--

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up	: Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or shovel spills into appropriate container for disposal.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Avoid all eye and skin contact and do not breathe vapor and mist. Use only in well ventilated areas.
Hygiene measures	: Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Keep container tightly closed.
Incompatible materials	: Alkalis. Metal salts. Oxidizing agent. Precious metals.
Storage area	: Store in a well-ventilated place. Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

GELEST RG® 03 HYDROPHILIC REPROGRAPHIC SILICONE

Safety Data Sheet

8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Hand protection:

Neoprene or nitrile rubber gloves

Eye protection:

Chemical goggles. Contact lenses should not be worn

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified organic vapor (black cartridge) respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear liquid. Viscous.
Molecular mass	: (mixture)
Color	: Translucent.
Odor	: No data available
Odor threshold	: No data available
Refractive index	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: < -60 °C
Freezing point	: No data available
Boiling point	: > 205 °C
Flash point	: 121 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: < 1 mm Hg @ 20°C
Relative vapor density at 20 °C	: No data available
Relative density	: 1.04
% Volatiles	: < 3 %
Solubility	: Insoluble in water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: A: 3000-5000 cSt; B: 50-125 cSt
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable in sealed containers stored under a dry inert atmosphere.

GELEST RG® 03 HYDROPHILIC REPROGRAPHIC SILICONE

Safety Data Sheet

10.3. Possibility of hazardous reactions

B-part is reactive with metal salts and precious metals.

10.4. Conditions to avoid

Heat. Open flame. Sparks.

10.5. Incompatible materials

Alkalis. Metal salts. Oxidizing agent. Precious metals.

10.6. Hazardous decomposition products

Formaldehyde. Organic acid vapors. Silicon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Part A: Vinyl terminated polydimethylsiloxane (68083-19-2)

LD50 oral rat	> 16 ml/kg
LD50 dermal rabbit	> 16 ml/kg

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

None of the components in this product at concentrations >0.1% are listed by IARC, NTP, OSHA or ACGIH as a carcinogen.

Reproductive toxicity : Not classified

Specific target organ toxicity – single exposure : Not classified

Specific target organ toxicity – repeated exposure : Not classified

Aspiration hazard : Not classified

Symptoms/effects after inhalation : No information available.

Symptoms/effects after skin contact : May cause mild skin irritation.

Symptoms/effects after eye contact : May cause mild eye irritation.

Symptoms/effects after ingestion : No information available.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the ozone layer : No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Sewage disposal recommendations : Do not dispose of waste into sewer.

Product/Packaging disposal recommendations : Incinerate. Dispose in a safe manner in accordance with local/national regulations.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

14.1. UN number

Not regulated for transport.

GELEST RG® 03 HYDROPHILIC REPROGRAPHIC SILICONE

Safety Data Sheet

14.2. UN proper shipping name

Not applicable

14.3. Additional information

Other information : No supplementary information available.

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

Part A: Vinyl terminated polydimethylsiloxane (68083-19-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Part A: Vinyl, methyl modified silica (68988-89-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Part A: Vinyl functional polydimethylsiloxane, methoxy(diethyleneoxide)propyl terminated (1586018-77-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Part B: Methylhydrosiloxane-dimethylsiloxane copolymer, trimethylsiloxane terminated (68037-59-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

Part A: Vinyl terminated polydimethylsiloxane (68083-19-2)

Listed on the Canadian DSL (Domestic Substances List)

Part A: Vinyl, methyl modified silica (68988-89-6)

Listed on the Canadian DSL (Domestic Substances List)

Part B: Methylhydrosiloxane-dimethylsiloxane copolymer, trimethylsiloxane terminated (68037-59-2)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Part A: Vinyl terminated polydimethylsiloxane (68083-19-2)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Part A: Vinyl, methyl modified silica (68988-89-6)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Part B: Methylhydrosiloxane-dimethylsiloxane copolymer, trimethylsiloxane terminated (68037-59-2)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

GELEST RG® 03 HYDROPHILIC REPROGRAPHIC SILICONE

Safety Data Sheet

SECTION 16: Other information

Abbreviations and acronyms : Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor.

Hazard Rating

Health : 1 Slight Hazard - Irritation or minor reversible injury possible
Flammability : 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)
Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Prepared by safety and environmental affairs.

Date of issue: 06/02/2016 Version: 1.0




SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2019 Gelest Inc. Morrisville, PA 19067

Gelest® RG 03 2-Part Hydrophilic Reprographic Silicone Elastomer (10:1 kit)

Capsular Description:	Thickness  thick	Cure Pt catalyst	Hardness  medium	Type  100% active 2-part
-----------------------	---	-------------------------	---	---

Description

Gelest® RG 03 is a clear to translucent, high definition molding and encapsulation compound with improved surface wettability and reduced coefficient of friction compared to conventional silicones. Microfluidic features exhibit lower hydrodynamic back-pressures.

Cured Properties

Tensile Strength	4.0-6.0 MPa
Elongation	100-200%
Durometer, Shore A	40-60
Refractive Index (25°C)	1.43

Coefficient of Friction

(aqueous environment, 37°C) **1.0-1.5**

Tear Strength	1.75-2.10 kN/m
Specific Gravity	1.04
Contact Angle, water	85°

<u>Standard Reprographic PDMS</u>	
Coefficient of Friction	≈2
Contact Angle, water	110°

Uncured Properties of Gelest® RG 03

Viscosity	(10:1) catalyzed: 3000-4000 cSt
	Part A (base): 3500-4500 cSt
	Part B (crosslinker): 50-75 cSt

Application Methods

Thoroughly mix Part A and Part B in a 10:1 ratio. Try to avoid introducing bubbles. For critical applications, de-air mix under vacuum for about 20 minutes. The pot-life is 12 hours at 25°C. Pot-life may be extended by storing at 5°C. Apply to substrate. Avoid entrapping air during transfer and casting. Cure at 80°C for 4 hours or at room temperature for 36 hours.

Standard Packaging

PP2-RG03 Gelest® RG 03
100 g SpeedMixer™ kit:
220 g kit (200g RG03-A, 20g RG03-B)
1.1 kg kit (1000g RG03-A, 100g RG03-B)

Application and Reference Data

1. Goff, J. et al. *MRS Proceedings* **2014**, 1626.