

Safety Data Sheet SIA0200.0

Issue date: 01/13/2015 Revision date: 02/05/2024 Version: 5.1

# **SECTION 1: Identification**

#### 1.1. Identification

Product name : (3-ACRYLOXYPROPYL)TRIMETHOXYSILANE, 96%

Product code : SIA0200.0
Product form : Substance
Physical state : Liquid
Formula : C9H1805Si

Synonyms : 3-(TRIMETHOXYSILYL)PROPYLACRYLATE

ACRYLIC ACID, 3-(TRIMETHOXYSILYL)PROPYL ESTER 2-PROPENOIC ACID, 3-(TRIMETHOXYSILYL)PROPYL ESTER

Chemical family : ORGANOMETHOXYSILANE

#### 1.2. Recommended use and restrictions on use

Recommended use : Chemical intermediate

### 1.3. Supplier

#### **GELEST. INC.**

11 East Steel Road Morrisville, PA 19067

USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com

## 1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

# SECTION 2: Hazard(s) identification

## 2.1. Classification of the substance or mixture

#### **GHS US classification**

Acute toxicity (dermal) Category 4 H312 Harmful in contact with skin

Acute toxicity (inhalation) Category 4 H332 Harmful if inhaled Acute toxicity (inhalation:vapor) Category 4 H332 Harmful if inhaled

Skin corrosion/irritation Category 1B H314 Causes severe skin burns and eye damage

Serious eye damage/eye irritation Category 1 H318 Causes serious eye damage
Skin sensitization, Category 1 H317 May cause an allergic skin reaction

Hazardous to the aquatic environment – Chronic H412 Harmful to aquatic life with long lasting effects

Hazard Category 3

Full text of H statements : see section 16

# 2.2. GHS Label elements, including precautionary statements

## **GHS US labeling**

Hazard pictograms (GHS US)





Signal word (GHS US) : Danger

Hazard statements (GHS US)

: H312+H332 - Harmful in contact with skin or if inhaled
H314 - Causes severe skin burns and eye damage

Print date: 02/05/2024 EN (English US) SDS ID: **SIA0200.0** 1/13

# Safety Data Sheet

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H412 - Harmful to aquatic life with long lasting effects

Precautionary statements (GHS US) : P260 - Do not breathe vapors.

P261 - Avoid breathing vapors.

P264 - Wash hands thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P272 - Contaminated work clothing must not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.

P302+P352 - If on skin: Wash with plenty of water.

P303+P361+P353 - If on skin (or hair): take off immediately all contaminated clothing. rinse skin

with water/shower

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a doctor.

P312 - Call a doctor if you feel unwell.

P321 - Specific treatment (see first aid instructions on this label).

P322 - Specific treatment (see supplemental first aid instruction on this label)

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P363 - Wash contaminated clothing before reuse.

P405 - Store locked up.

P501 - Dispose of contents/container to licensed waste disposal facility...

# 2.3. Hazards not otherwise classified (HNOC)

No additional information available

# 2.4. Unknown acute toxicity (GHS US)

Not applicable

# **SECTION 3: Composition/Information on ingredients**

## 3.1. Substances

Substance type : Multi-constituent

Name : (3-ACRYLOXYPROPYL)TRIMETHOXYSILANE, 96%

CAS-No. : 4369-14-6

Name	Product identifier	%	GHS US classification
(3-Acryloxypropyl)trimethoxysilane	CAS-No.: 4369-14-6	> 96	Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Chronic 3, H412
3-Chloropropyltrimethoxysilane	CAS-No.: 2530-87-2	< 2	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2A, H319
Methanol	CAS-No.: 67-56-1	< 1	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 STOT SE 1, H370

Full text of hazard classes and H-statements : see section 16

Print date: 02/05/2024 EN (English US) SDS ID: **SIA0200.0** 2/13

# Safety Data Sheet

#### 3.2. Mixtures

Not applicable

## **SECTION 4: First-aid measures**

# 4.1. Description of first aid measures

First-aid measures general

: Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.

First-aid measures after inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.

First-aid measures after skin contact First-aid measures after eye contact

First-aid measures after ingestion

: Wash with plenty of soap and water. Get immediate medical advice/attention.

: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

: Never give anything by mouth to an unconscious person. Get medical advice/attention.

# 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects

: Causes severe skin burns and eye damage.

Symptoms/effects after inhalation

: Harmful if inhaled. May cause irritation to the respiratory tract.

Symptoms/effects after skin contact

: May cause an allergic skin reaction. Acrylates can have a sensitizing effect. May be harmful in contact with skin.

Symptoms/effects after eye contact Symptoms/effects after ingestion

: Causes serious eye damage.: May be harmful if swallowed.

Chronic symptoms

: On contact with water this compound liberates methanol which is known to have a chronic effect on the central nervous system. Methanol may effect the central nervous system resulting in persistent or recurring headaches or impaired vision.

## 4.3. Immediate medical attention and special treatment, if necessary

NOTE TO PHYSICIAN: This product reacts with water in the acid contents of the stomach to form methanol. The combination of visual disturbances, metabolic acidosis and formic acid in urine is evidence of methanol poisoning. The therapeutic intravenous administration of ethanol (10 mls/hour) allows methanol to be preferentially oxidized and reduces production of methanol metabolites. Acidosis must be treated with intravenous administration of sodium bicarbonate and methanol elimination may be increased by hemodialysis, as indicated. Treatment should be based on blood methanol levels and acid-base balance.

# **SECTION 5: Fire-fighting measures**

# 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Foam. Carbon dioxide. Dry chemical.

Unsuitable extinguishing media : Do not use straight streams.

# 5.2. Specific hazards arising from the chemical

Fire hazard : Irritating fumes and organic acid vapors may develop when material is exposed to elevated

temperatures or open flame.

# 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Use water spray to cool exposed surfaces.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Avoid

all eye and skin contact and do not breathe vapor and mist.

### **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Protective equipment : Wear protective equipment as described in Section 8.

Print date: 02/05/2024 EN (English US) SDS ID: **SIA0200.0** 3/13

# Safety Data Sheet

Emergency procedures : Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with

proper protection. For further information refer to section 8: "Exposure controls/personal

protection".

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or

streams.

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it.

#### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapor and mist. Use only outdoors or in a well-

ventilated area.

Hygiene measures : Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap

and water before eating, drinking or smoking and when leaving work.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container tightly closed. Store locked up. Store cold.

Incompatible materials : Moisture. Water.

Storage area : Store in a well-ventilated place. Store away from heat.

### **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

Methanol (67-56-1)		
USA - ACGIH - Occupational Exposure Limits		
Local name	Methanol	
ACGIH OEL TWA	200 ppm	
ACGIH OEL STEL	250 ppm	
Remark (ACGIH)	TLV® Basi	is: Headache; eye dam; dizziness; nausea. Notations: Skin; BEI
ACGIH chemical category	Skin - potential significant contribution to overall exposure by the cutaneous route	
Regulatory reference	ACGIH 2024	
USA - ACGIH - Biological Exposure Indices		
Local name	Methanol	
BEI (BLV)	15 mg/l (M	ledium: urine - Time: end of shift - Parameter: Methanol (background, nonspecific)
Regulatory reference	ACGIH 202	24
USA - OSHA - Occupational Exposure Limits		
Local name	Methyl alco	ohol

Print date: 02/05/2024 EN (English US) SDS ID: **SIA0200.0** 4/13

# Safety Data Sheet

Methanol (67-56-1)		
OSHA PEL TWA	260 mg/m³	
	200 ppm	
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1	
USA - IDLH - Occupational Exposure Limits		
IDLH	6000 ppm	
USA - NIOSH - Occupational Exposure Limits		
NIOSH REL (TWA)	260 mg/m³	
	200 ppm	
NIOSH REL (STEL)	325 mg/m³	
	250 ppm	
US-NIOSH chemical category	Potential for dermal absorption	

# 8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation.

### 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

#### Hand protection:

Neoprene or nitrile rubber gloves

# Eye protection:

Odor threshold

Chemical goggles or face shield. Contact lenses should not be worn

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified combination organic vapor/acid gas (yellow cartridge) respirator.

No data available

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state: LiquidAppearance: Clear liquid.Molecular mass: 234.32 g/molColor: Straw.Odor: Mild.

pH : No data available
Relative evaporation rate (butyl acetate=1) : No data available
Melting point : No data available
Fronzing point : 20°C

Freezing point : < -20 °C

Boiling point :  $68 \, ^{\circ}\text{C} \ @ 0.4 \, \text{mm Hg}$ 

Flash point : 123 °C

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Flammability (solid, gas) : No data available

Vapor pressure : < 0.1 mm Hg @ 25°C

Print date: 02/05/2024 EN (English US) SDS ID: **SIA0200.0** 5/13

# Safety Data Sheet

Relative vapor density at 20°C : > 1
Relative density : 1.06

Solubility : Insoluble in water. Reacts with water.

Partition coefficient n-octanol/water (Log Pow) : No data available Partition coefficient n-octanol/water (Log Kow) : No data available Viscosity, kinematic : No data available Viscosity, dynamic : No data available Explosive properties : No data available Oxidizing properties : No data available Explosion limits : No data available : No data available

### 9.2. Other information

No additional information available

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Stable in sealed containers stored in the dark at 0-5°C. Polymerization can occur when stored at elevated temperature.

# 10.3. Possibility of hazardous reactions

Reacts with water and moisture in air, liberating methanol.

### 10.4. Conditions to avoid

Heat. Open flame. Sparks.

# 10.5. Incompatible materials

Moisture. Water.

# 10.6. Hazardous decomposition products

Methanol. Organic acid vapors.

LC50 Inhalation - Rat

# **SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Harmful in contact with skin.

Acute toxicity (inhalation) : Harmful if inhaled. Inhalation:vapor: Harmful if inhaled.

(3-ACRYLOXYPROPYL)TRIMETHOXYSILANE, 96% (4369-14-6)		
ATE US (dermal)	1096.021 mg/kg body weight	
ATE US (gases)	4500 ppmV/4h	
ATE US (vapors)	11 mg/l/4h	
ATE US (dust, mist)	1.5 mg/l/4h	
(3-Acryloxypropyl)trimethoxysilane (4369-14-6)		
LD50 oral rat	> 2000 mg/kg Source: ECHA	
LD50 dermal rabbit	1060 mg/kg Source: GESTIS	

Print date: 02/05/2024 EN (English US) SDS ID: **SIA0200.0** 6/13

3,2 - 4,48

3.79 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), 95% CL:

# Safety Data Sheet

3-Chloropropyltrimethoxysilane (253	30-87-2)
LD50 oral rat	> 2000 mg/kg Source: SIDS
LD50 dermal rat	> 2000 mg/kg Source: SIDS
LD50 dermal rabbit	2830 µl/kg
Methanol (67-56-1)	
LD50 oral rat	100 mg/kg Source: National Institute of Environmental Research NCIS
LD50 dermal rabbit	300 mg/kg Source: ECHA
LC50 Inhalation - Rat [ppm]	22500 ppm (Exposure time: 8 h)
Skin corrosion/irritation	: Causes severe skin burns.
Serious eye damage/irritation	: Causes serious eye damage.
	Eye Irritation - rabbit: 100 uL: severe irritation effect
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
	None of the components in this product at concentrations >0.1% are listed by IARC, NTP, OSHA or ACGIH as a carcinogen.
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Symptoms/effects after inhalation	: Harmful if inhaled. May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: May cause an allergic skin reaction. Acrylates can have a sensitizing effect. May be harmful in
	contact with skin.
Symptoms/effects after eye contact	: Causes serious eye damage.
Symptoms/effects after ingestion	: May be harmful if swallowed.
Chronic symptoms	: On contact with water this compound liberates methanol which is known to have a chronic effect
	on the central nervous system. Methanol may effect the central nervous system resulting in
	persistent or recurring headaches or impaired vision.

# SECTION 12: Ecological information

# 12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

(3-Acryloxypropyl)trimethoxysilane (4369-14-6)				
LC50 - Fish [1]	75 mg/l Source: ECHA			
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna			
EC50 72h - Algae [1]	87 mg/l Source: ECHA			
EC50 72h - Algae [2]	87 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)			
EC50 96h - Algae [1]	70 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)			
3-Chloropropyltrimethoxysilane (2530-87-2)				
LC50 - Fish [1]	> 100 mg/l Source: SIDS			
EC50 - Crustacea [1]	869 mg/l Source: SIDS			
EC50 72h - Algae [1]	> 833 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)			

Print date: 02/05/2024 EN (English US) SDS ID: **SIA0200.0** 7/13

# Safety Data Sheet

3-Chloropropyltrimethoxysilane (2530-87-2)	
EC50 72h - Algae [2]	> 883 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
ErC50 algae	> 883 mg/l Source: SIDS
LOEC (chronic)	> 100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 66 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
Methanol (67-56-1)	
LC50 - Fish [1]	28200 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 - Fish [2]	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 96h - Algae [1]	22000 mg/l Source: ECHA
NOEC (chronic)	208 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	446.7 mg/l Test organisms (species): Pimephales promelas Duration: '28 d'

# 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

(3-Acryloxypropyl)trimethoxysilane (4369-14-6)					
Partition coefficient n-octanol/water (Log Pow)	2.18 Source: ECHA				
3-Chloropropyltrimethoxysilane (2530-87-2)					
Partition coefficient n-octanol/water (Log Pow)	0.56				
Methanol (67-56-1)					
BCF - Fish [1]	< 10				
Partition coefficient n-octanol/water (Log Pow)	-0.77				

# 12.4. Mobility in soil

Methanol (67-56-1)	
Mobility in soil	2.75 Source: HSDB

# 12.5. Other adverse effects

Effect on the ozone layer : No additional information available

# **SECTION 13: Disposal considerations**

# 13.1. Disposal methods

Sewage disposal recommendations : Do not dispose of waste into sewer.

Product/Packaging disposal recommendations : May be incinerated. Dispose in a safe manner in accordance with local/national regulations.

Dispose of contents/container to licensed waste disposal facility..

Ecological information : Avoid release to the environment.

# **SECTION 14: Transport information**

In accordance with DOT / TDG / IMDG / IATA

Print date: 02/05/2024 EN (English US) SDS ID: **SIA0200.0** 8/13

Safety Data Sheet

DOT	TDG	IMDG	IATA	
14.1. UN number				
1760	Not applicable	1760	1760	
14.2. Proper Shipping Name				
Corrosive liquids, n.o.s. (((3- ACRYLOXYPROPYL)TRIMETHOX YSILANE))	Not applicable	CORROSIVE LIQUID, N.O.S. ((3- ACRYLOXYPROPYL)TRIMETHOX YSILANE)	Corrosive liquid, n.o.s. ((3- ACRYLOXYPROPYL)TRIMETHOX YSILANE)	
Transport document description				
UN1760 Corrosive liquids, n.o.s. ((3-ACRYLOXYPROPYL)TRIMETHOX YSILANE), 8, III	Not applicable	UN 1760 CORROSIVE LIQUID, N.O.S. ((3- ACRYLOXYPROPYL)TRIMETHOX YSILANE), 8, III	UN 1760 Corrosive liquid, n.o.s. ((3- ACRYLOXYPROPYL)TRIMETHOX YSILANE), 8, III	
14.3. Transport hazard class(es	)			
8	Not applicable	8	8	
CORROSIVE 8	Not applicable	8	8	
14.4. Packing group				
III	Not applicable	III	III	
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	
No supplementary information availab	le			

## 14.6. Special precautions for user

DOT

UN-No.(DOT) : UN1760

DOT Special Provisions (49 CFR 172.102)

: IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) 154 DOT Packaging Non Bulk (49 CFR 173.xxx) 203 DOT Packaging Bulk (49 CFR 173.xxx) 241 DOT Quantity Limitations Passenger aircraft/rail (49 : 5 L CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L

CFR 175.75)

Print date: 02/05/2024 EN (English US) SDS ID: SIA0200.0 9/13

# Safety Data Sheet

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

**TDG** 

Emergency Response Guide (ERG) Number : 154

**IMDG** 

Special provision (IMDG): 223, 274Packing instructions (IMDG): P001, LP01IBC packing instructions (IMDG): IBC03Tank instructions (IMDG): T7Tank special provisions (IMDG): TP1, TP28

EmS-No. (Fire) : F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE

EmS-No. (Spillage) : S-B - SPILLAGE SCHEDULE Bravo - CORROSIVE SUBSTANCES

Stowage category (IMDG) : A
Stowage and handling (IMDG) : SW2

Properties and observations (IMDG) : Causes burns to skin, eyes and mucous membranes.

**IATA** 

: E1 PCA Excepted quantities (IATA) PCA Limited quantities (IATA) : Y841 PCA limited quantity max net quantity (IATA) 1L PCA packing instructions (IATA) 852 PCA max net quantity (IATA) 5L : 856 CAO packing instructions (IATA) : 60L CAO max net quantity (IATA) Special provision (IATA) A3, A803 ERG code (IATA) 8L

# 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

# **SECTION 15: Regulatory information**

## 15.1. US Federal regulations

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

Name	CAS-No.	Listing	Commercial status	Flags
(3-Acryloxypropyl)trimethoxysilane	4369-14-6	Present	Active	PMN
3-Chloropropyltrimethoxysilane	2530-87-2	Present	Active	
Methanol	67-56-1	Present	Active	

### Methanol (67-56-1)

Subject to reporting requirements of United States SARA Section 313

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ 5000 lb

# 15.2. International regulations

# CANADA

# (3-ACRYLOXYPROPYL)TRIMETHOXYSILANE, 96% (4369-14-6)

Listed on the Canadian NDSL (Non-Domestic Substances List)

Print date: 02/05/2024 EN (English US) SDS ID: **SIA0200.0** 10/13

# Safety Data Sheet

### (3-Acryloxypropyl)trimethoxysilane (4369-14-6)

Listed on the Canadian NDSL (Non-Domestic Substances List)

#### 3-Chloropropyltrimethoxysilane (2530-87-2)

Listed on the Canadian DSL (Domestic Substances List)

#### Methanol (67-56-1)

Listed on the Canadian DSL (Domestic Substances List)

#### **EU-Regulations**

#### (3-ACRYLOXYPROPYL)TRIMETHOXYSILANE, 96% (4369-14-6)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)- Directive 79/831/EEC, sixth Amendment of Directive 67/548/EEC (dangerous substances)

#### (3-Acryloxypropyl)trimethoxysilane (4369-14-6)

Listed on ELINCS (European List of Notified Chemical Substances)

### 3-Chloropropyltrimethoxysilane (2530-87-2)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

#### Methanol (67-56-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

#### National regulations

### (3-ACRYLOXYPROPYL)TRIMETHOXYSILANE, 96% (4369-14-6)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

# (3-Acryloxypropyl)trimethoxysilane (4369-14-6)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing New Chemical Substances) inventory

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the TCSI (Taiwan Chemical Substance Inventory)

Listed on the NCI (Vietnam - National Chemical Inventory)

Listed on Thailand Existing Chemicals Inventory (DIW)

Listed on KECL/KECI (Korean Existing Chemicals Inventory)

# 3-Chloropropyltrimethoxysilane (2530-87-2)

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing New Chemical Substances) inventory

Listed on KECL/KECI (Korean Existing Chemicals Inventory)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the TCSI (Taiwan Chemical Substance Inventory)

Listed on Thailand Existing Chemicals Inventory (DIW)

Listed on the NCI (Vietnam - National Chemical Inventory)

Print date: 02/05/2024 EN (English US) SDS ID: **SIA0200.0** 11/13

# Safety Data Sheet

# Methanol (67-56-1)

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing New Chemical Substances) inventory

Listed on KECL/KECI (Korean Existing Chemicals Inventory)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Japanese Poisonous and Deleterious Substances Control Law

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Listed on CICR (Turkish Inventory and Control of Chemicals)

Listed on the TCSI (Taiwan Chemical Substance Inventory)

Listed on Thailand Existing Chemicals Inventory (DIW)

Listed on the NCI (Vietnam - National Chemical Inventory)

### 15.3. US State regulations



This product can expose you to Methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Methanol (67-56-1)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
No	Yes	No	No		47000 μg/day (inhalation); 23,000 μg/day (oral)

# Methanol (67-56-1)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

# **SECTION 16: Other information**

#### Full text of H-phrases::

H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H301	Toxic if swallowed
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H331	Toxic if inhaled
H332	Harmful if inhaled
H370	Causes damage to organs
H412	Harmful to aquatic life with long lasting effects

Print date: 02/05/2024 EN (English US) SDS ID: **SIA0200.0** 12/13

# Safety Data Sheet

Abbreviations and acronyms

Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemcial Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor.

Hazard Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is

given

Flammability : 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids,

solids and semi solids having a flash point above 200 F. (Class IIIB)

Physical : 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high

 $temperatures \ and \ pressures. \ Materials \ may \ react \ non-violently \ with \ water \ or \ undergo \ hazardous$ 

polymerization in the absence of inhibitors.

Prepared by safety and environmental affairs.

Issue date: 01/13/2015 Revision date: 02/05/2024 Version: 5.1

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist.

Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2023 Gelest Inc. Morrisville, PA 19067

Print date: 02/05/2024 EN (English US) SDS ID: **SIA0200.0** 13/13