



## ACRYLOXYTRIISOPROPYLSILANE

Safety Data Sheet SIA0315.0

Date of issue: 09/28/2016

Revision date: 04/08/2019

Version: 1.2

### SECTION 1: Identification

#### 1.1. Identification

Product name	: ACRYLOXYTRIISOPROPYLSILANE
Product code	: SIA0315.0
Product form	: Substance
Physical state	: Liquid
Formula	: C <sub>12</sub> H <sub>24</sub> O <sub>2</sub> Si
Synonyms	: TIPSA O-TRIISOPROPYLSILYLACRYLATE TRIS(1-METHYLETHYL)SILYL 2-PROPENOATE 2-PROPENOIC ACID, TRIS(1-METHYLETHYL)SILYL ESTER
Chemical family	: ORGANOSILANE

#### 1.2. Recommended use and restrictions on use

Recommended use	: Chemical intermediate
-----------------	-------------------------

#### 1.3. Supplier

##### GELEST, INC.

11 East Steel Road

Morrisville, PA 19067

##### USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

[info@gelest.com](mailto:info@gelest.com) - [www.gelest.com](http://www.gelest.com)

#### 1.4. Emergency telephone number

Emergency number	: CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)
------------------	---

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Flammable liquids Category 4	H227 Combustible liquid
Skin corrosion/irritation Category 2	H315 Causes skin irritation
Serious eye damage/eye irritation Category 2A	H319 Causes serious eye irritation
Skin sensitization, Category 1	H317 May cause an allergic skin reaction

Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

##### GHS US labeling

Hazard pictograms (GHS US)



Signal word (GHS US)

: Warning

Hazard statements (GHS US)

: H227 - Combustible liquid  
H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H319 - Causes serious eye irritation

Precautionary statements (GHS US)

: P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
P210 - Keep away from heat, open flames, sparks. - No smoking.  
P261 - Avoid breathing vapors.  
P264 - Wash hands thoroughly after handling.  
P272 - Contaminated work clothing must not be allowed out of the workplace  
P302+P352 - If on skin: Wash with plenty of soap and water  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P321 - Specific treatment (see first aid instructions on this label)  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P363 - Wash contaminated clothing before reuse.  
P370+P378 - In case of fire: Use water spray, foam, carbon dioxide, dry chemical to extinguish.  
P403+P235 - Keep in a cool place  
P501 - Dispose of contents/container to licensed waste disposal facility.

# ACRYLOXYTRIIISOPROPYLSILANE

## Safety Data Sheet

### 2.3. Hazards not otherwise classified (HNOC)

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Substance type : Mono-constituent  
Name : ACRYLOXYTRIIISOPROPYLSILANE  
CAS-No. : 157859-20-6

Name	Product identifier	%	GHS-US classification
Acryloxytrisopropylsilane	(CAS-No.) 157859-20-6	95 - 100	Flam. Liq. 4, H227 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317
Hydroquinone monomethyl ether	(CAS-No.) 150-76-5	< 0.05	Acute Tox. 4 (Oral), H302 Eye Irrit. 2B, H320 Skin Sens. 1, H317

Full text of hazard classes and H-statements : see section 16

### 3.2. Mixtures

Not applicable

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.

First-aid measures after skin contact : Wash with plenty of soap and water. Get medical advice/attention.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.

First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Get medical advice/attention.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : May cause irritation to the respiratory tract.

Symptoms/effects after skin contact : Causes skin irritation. May cause an allergic skin reaction. Acrylate esters in general are known to cause sensitization reactions.

Symptoms/effects after eye contact : Causes serious eye irritation.

Symptoms/effects after ingestion : May be harmful if swallowed.

### 4.3. Immediate medical attention and special treatment, if necessary

No additional information available

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Foam. Carbon dioxide. Dry chemical.

Unsuitable extinguishing media : Do not use straight streams.

### 5.2. Specific hazards arising from the chemical

Fire hazard : Combustible liquid. Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.

### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Use water spray to cool exposed surfaces.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Avoid all eye and skin contact and do not breathe vapor and mist.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges.

#### 6.1.1. For non-emergency personnel

Protective equipment : Wear protective equipment as described in Section 8.

Emergency procedures : Evacuate unnecessary personnel.

# ACRYLOXYTRIISOPROPYLSILANE

## Safety Data Sheet

### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.  
Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Use only non-sparking tools.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : Keep away from heat, open flames, sparks. - No smoking.  
Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapor and mist. Ground/bond container and receiving equipment. Provide good ventilation in process area to prevent accumulation of vapors. Use only non-sparking tools.  
Hygiene measures : Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container tightly closed. Keep in a cool place. Store < 5°C.  
Incompatible materials : Alcohols. Amines. Oxidizing agent. Peroxides.  
Storage area : Store in a well-ventilated place. Store away from heat.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Hydroquinone monomethyl ether (150-76-5)		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation.

### 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

#### Hand protection:

Neoprene or nitrile rubber gloves

#### Eye protection:

Chemical goggles. Contact lenses should not be worn

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified combination organic vapor/acid gas (yellow cartridge) respirator.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Appearance : Clear liquid.  
Molecular mass : 228.41 g/mol  
Color : No data available

# ACRYLOXYTRIISOPROPYLSILANE

## Safety Data Sheet

Odor	: Pungent. Vinegar-like.
Odor threshold	: No data available
Refractive index	: 1.4485
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: < 0 °C
Boiling point	: 94 - 96 °C @ 7 mm Hg
Flash point	: > 65 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Combustible liquid
Vapor pressure	: < 5 mm Hg @ 20°C
Relative vapor density at 20 °C	: > 1
Relative density	: 0.91
Solubility	: Reacts with water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Stable in sealed containers in a cool dark place.

### 10.3. Possibility of hazardous reactions

Reacts with water and moisture in air liberating acrylic acid. Hazardous polymerization may occur if stored at elevated temperature or under UV exposure.

### 10.4. Conditions to avoid

Heat. Open flame. Sparks.

### 10.5. Incompatible materials

Alcohols. Amines. Oxidizing agent. Peroxides.

### 10.6. Hazardous decomposition products

Acrylic acid. Organic acid vapors.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

#### ACRYLOXYTRIISOPROPYLSILANE (157859-20-6)

Toxicity information	250 (Acrylic acid toxicity oral-rat, LD50)
----------------------	--

#### Hydroquinone monomethyl ether (150-76-5)

LD50 oral rat	1600 mg/kg
---------------	------------

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

None of the components in this product at concentrations >0.1% are listed by IARC, NTP, OSHA or ACGIH as a carcinogen.

# ACRYLOXYTRIISOPROPYLSILANE

## Safety Data Sheet

Reproductive toxicity	: Not classified Acrylic acid, the hydrolysis product is an experimental teratogen with other observed reproductive effects.
Specific target organ toxicity – single exposure	: Not classified
Specific target organ toxicity – repeated exposure	: Not classified
Aspiration hazard	: Not classified
Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: Causes skin irritation. May cause an allergic skin reaction. Acrylate esters in general are known to cause sensitization reactions.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: May be harmful if swallowed.
Reason for classification	: Expert judgment

## SECTION 12: Ecological information

### 12.1. Toxicity

Hydroquinone monomethyl ether (150-76-5)	
LC50 fish 1	84.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 fish 2	28.5 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

Hydroquinone monomethyl ether (150-76-5)	
Log Pow	1.34

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Other adverse effects	: This substance may be hazardous to the environment.
Effect on the ozone layer	: No additional information available

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Sewage disposal recommendations	: Do not dispose of waste into sewer.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to licensed waste disposal facility.
Ecology - waste materials	: Avoid release to the environment.

## SECTION 14: Transport information

### 14.1. UN number

DOT NA no.	NA1993
------------	--------

### 14.2. UN proper shipping name

Transport document description	: NA1993 Combustible liquid, n.o.s. (ACRYLOXYTRIISOPROPYLSILANE), 3, III
Proper Shipping Name (DOT)	: Combustible liquid, n.o.s. (ACRYLOXYTRIISOPROPYLSILANE)
Class (DOT)	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Packing group (DOT)	: III - Minor Danger
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 241
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Symbols	: D - Proper shipping name for domestic use only, or to and from Canada, G - Identifies PSN requiring a technical name

### 14.3. Additional information

Other information	: This product is Combustible as defined by the US Department of Transportation (DOT). It is regulated for transport in the US in container > 119 gallons (450 liters). The product is not regulated for transport by the IATA, ADR/RID, ADNR or the IMDG regulations.
-------------------	--

# ACRYLOXYTRIISOPROPYLSILANE

## Safety Data Sheet

### Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

### Air transport

DOT Quantity Limitations Passenger aircraft/rail : 60 L  
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L  
CFR 175.75)

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### ACRYLOXYTRIISOPROPYLSILANE (157859-20-6)

TSCA Exemption/Exclusion

CAUTION: This material is supplied for research and development purposes subject to the R&D exemption under TSCA, 40 CFR 720.36, and must meet the requirements of the exemption, including supervision by a "technically qualified individual" as defined by 40 CFR 720.3(ee). The use of this material for "commercial purposes" as defined by 40 CFR 720.3(r) is not permitted in the United States.

#### Hydroquinone monomethyl ether (150-76-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

EPA TSCA Regulatory Flag

T - T - indicates a substance that is the subject of a final TSCA section 4 test rule.

#### Acryloxytriisopropylsilane (157859-20-6)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

### 15.2. International regulations

#### CANADA

#### Hydroquinone monomethyl ether (150-76-5)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification

Class D Division 2 Subdivision B - Toxic material causing other toxic effects

#### EU-Regulations

#### Hydroquinone monomethyl ether (150-76-5)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

#### Acryloxytriisopropylsilane (157859-20-6)

Listed on ELINCS (European List of Notified Chemical Substances)

#### National regulations

#### Hydroquinone monomethyl ether (150-76-5)

Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on the Korean ECL (Existing Chemicals List)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Listed on the Canadian IDL (Ingredient Disclosure List)  
Listed on INSQ (Mexican National Inventory of Chemical Substances)  
Listed on CICR (Turkish Inventory and Control of Chemicals)

#### Acryloxytriisopropylsilane (157859-20-6)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

#### Hydroquinone monomethyl ether (150-76-5)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

## SECTION 16: Other information

# ACRYLOXYTRIISOPROPYLSILANE

## Safety Data Sheet

Full text of H-phrases::

H227	Combustible liquid
H302	Harmful if swallowed
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H320	Causes eye irritation

Abbreviations and acronyms

: Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor.

### Hazard Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

Flammability : 2 Moderate Hazard - Materials which must be moderately heated or exposed to high ambient temperatures before ignition will occur. Includes liquids having a flash point at or above 100 F but below 200 F. (Classes II & IIIA)

Physical : 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.

Prepared by safety and environmental affairs.

Date of issue: 09/28/2016      Revision date: 04/08/2019      Version: 1.2

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

*The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.*

© 2019 Gelest Inc. Morrisville, PA 19067