

Safety Data Sheet SIA0540.0

Issue date: 12/29/2014 Revision date: 02/05/2024 Version: 2.2

### **SECTION 1: Identification**

#### 1.1. Identification

Product name : ALLYLTRIMETHOXYSILANE

Product code : SIA0540.0
Product form : Substance
Physical state : Liquid
Formula : C6H14O3Si

Synonyms : 1-TRIMETHOXYSILYLPROP-2-ENE
Chemical family : ORGANOMETHOXYSILANE

### 1.2. Recommended use and restrictions on use

Recommended use Chemical intermediate

### 1.3. Supplier

#### GELEST, INC.

11 East Steel Road Morrisville. PA 19067

USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com

### 1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

### **SECTION 2: Hazard(s) identification**

## 2.1. Classification of the substance or mixture

#### **GHS US classification**

Flammable liquids Category 3 H226 Flammable liquid and vapor Serious eye damage/eye irritation Category 2A H319 Causes serious eye irritation

Full text of H statements : see section 16

### 2.2. GHS Label elements, including precautionary statements

### **GHS US labeling**

Hazard pictograms (GHS US)





Signal word (GHS US) : Warning

Hazard statements (GHS US) : H226 - Flammable liquid and vapor

H319 - Causes serious eye irritation

Precautionary statements (GHS US) : P210 - Keep away from heat, open flames, sparks. - No smoking.

P233 - Keep container tightly closed.

P240 - Ground/Bond container and receiving equipment.
P241 - Use explosion-proof electrical equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P264 - Wash hands thoroughly after handling.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Print date: 02/05/2024 EN (English US) SDS ID: **SIA0540.0** 1/9

# Safety Data Sheet

P303+P361+P353 - If on skin (or hair): take off immediately all contaminated clothing. rinse skin with water/shower

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing

P337+P313 - If eye irritation persists: Get medical advice/attention.

P370+P378 - In case of fire: Use water spray, foam, carbon dioxide, dry chemical to extinguish.

P403+P235 - Keep in a cool place

P501 - Dispose of contents/container to licensed waste disposal facility...

### 2.3. Hazards not otherwise classified (HNOC)

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## **SECTION 3: Composition/Information on ingredients**

### 3.1. Substances

Substance type : Mono-constituent

Name : ALLYLTRIMETHOXYSILANE

CAS-No. : 2551-83-9

Name	Product identifier	%	GHS US classification
Allyltrimethoxysilane	CAS-No.: 2551-83-9	95 – 100	Flam. Liq. 3, H226 Eye Irrit. 2A, H319

Full text of hazard classes and H-statements : see section 16

### 3.2. Mixtures

Not applicable

### **SECTION 4: First-aid measures**

### 4.1. Description of first aid measures

First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available

show packaging or label.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If you feel unwell, seek medical

advice.

First-aid measures after skin contact : Wash with plenty of soap and water. Get medical advice/attention.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical advice/attention.

First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Get medical advice/attention.

## 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : May cause irritation to the respiratory tract. Overexposure may cause: Coughing. Headache.

Nausea.

Symptoms/effects after skin contact : May cause skin irritation.
Symptoms/effects after eye contact : Causes serious eye irritation.

Symptoms/effects after ingestion : Oral toxicity is associated with methanol, the solvent and a hydrolysis product which causes

nausea, vomiting, headache, visual effects including blindness.

Chronic symptoms : On contact with water this compound liberates methanol which is known to have a chronic effect

on the central nervous system.

Print date: 02/05/2024 EN (English US) SDS ID: **SIA0540.0** 2/9

# Safety Data Sheet

### 4.3. Immediate medical attention and special treatment, if necessary

NOTE TO PHYSICIAN: This product reacts with water in the acid contents of the stomach to form methanol. The combination of visual disturbances, metabolic acidosis and formic acid in urine is evidence of methanol poisoning. The therapeutic intravenous administration of ethanol (10 mls/hour) allows methanol to be preferentially oxidized and reduces production of methanol metabolites. Acidosis must be treated with intravenous administration of sodium bicarbonate and methanol elimination may be increased by hemodialysis, as indicated. Treatment should be based on blood methanol levels and acid-base balance.

## **SECTION 5: Fire-fighting measures**

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Foam. Carbon dioxide. Dry chemical.

Unsuitable extinguishing media : Do not use straight streams.

### 5.2. Specific hazards arising from the chemical

Fire hazard : Flammable liquid and vapor. Irritating fumes and organic acid vapors may develop when material

is exposed to elevated temperatures or open flame.

Explosion hazard : May form flammable/explosive vapor-air mixture.

### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Use water spray to cool exposed surfaces.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Avoid

all eye and skin contact and do not breathe vapor and mist.

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Eliminate ignition sources. Use special care to avoid static electric charges.

#### 6.1.1. For non-emergency personnel

Protective equipment : Wear protective equipment as described in Section 8.

Emergency procedures : Evacuate unnecessary personnel.

### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with

proper protection. For further information refer to section 8: "Exposure controls/personal

protection".

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or

streams.

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Use only non-

sparking tools.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable. Keep away from

heat/sparks/open flames/hot surfaces. - No smoking.

Print date: 02/05/2024 EN (English US) SDS ID: **SIA0540.0** 3/9

# Safety Data Sheet

Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapor and mist. Ground/bond container and

receiving equipment. Provide good ventilation in process area to prevent accumulation of vapors.

Take precautionary measures against static discharge. Use only non-sparking tools.

Hygiene measures : Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap

and water before eating, drinking or smoking and when leaving work.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment. Proper grounding procedures to avoid static

electricity should be followed. Use explosion-proof electrical equipment.

Storage conditions : Keep container tightly closed. Keep in a cool place.

Incompatible materials : Water. Moisture.

Storage area : Store in a well-ventilated place. Store away from heat.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

No additional information available

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation.

### 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

#### Hand protection:

Neoprene or nitrile rubber gloves

### Eye protection:

Chemical goggles. Contact lenses should not be worn

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

NIOSH-certified organic vapor (black cartridge) respirator.

## **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state: LiquidAppearance: Clear liquid.Molecular mass: 162.26 g/molColor: Straw.Odor: Mild.

Odor threshold : No data available pH : No data available Relative evaporation rate (butyl acetate=1) : No data available Melting point : No data available

Freezing point : < 0 °C Boiling point : 146 - 148 °C Flash point : 46 °C

Auto-ignition temperature : No data available Decomposition temperature : No data available

Flammability (solid, gas) : Flammable liquid and vapor.

Vapor pressure : < 2 mm Hg @ 20°C

Relative vapor density at  $20^{\circ}$ C : > 1 Relative density : 0.963

Print date: 02/05/2024 EN (English US) SDS ID: **SIA0540.0** 4/9

# Safety Data Sheet

Solubility : Insoluble in water. Reacts with water.

Partition coefficient n-octanol/water (Log Pow) : No data available Partition coefficient n-octanol/water (Log Kow) : No data available Viscosity, kinematic : No data available Viscosity, dynamic : No data available Explosive properties : No data available Oxidizing properties : No data available Explosion limits : No data available Explosion limits : No data available

### 9.2. Other information

No additional information available

### **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Stable in sealed containers.

### 10.3. Possibility of hazardous reactions

Reacts with water and moisture in air, liberating methanol.

### 10.4. Conditions to avoid

Heat. Sparks. Open flame.

# 10.5. Incompatible materials

Water. Moisture.

## 10.6. Hazardous decomposition products

Organic acid vapors. Methanol.

### **SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified
Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified

None of the components in this product at concentrations >0.1% are listed by IARC, NTP, OSHA  $\,$ 

or ACGIH as a carcinogen.

Reproductive toxicity : Not classified STOT-single exposure : Not classified STOT-repeated exposure : Not classified Aspiration hazard : Not classified

Symptoms/effects after inhalation : May cause irritation to the respiratory tract. Overexposure may cause: Coughing. Headache.

Nausea.

Symptoms/effects after skin contact : May cause skin irritation.
Symptoms/effects after eye contact : Causes serious eye irritation.

Print date: 02/05/2024 EN (English US) SDS ID: **SIA0540.0** 5/9

# Safety Data Sheet

Symptoms/effects after ingestion : Oral toxicity is associated with methanol, the solvent and a hydrolysis product which causes

nausea, vomiting, headache, visual effects including blindness.

Chronic symptoms On contact with water this compound liberates methanol which is known to have a chronic effect

on the central nervous system.

# **SECTION 12: Ecological information**

### 12.1. Toxicity

No additional information available

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

No additional information available

## 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Other adverse effects : This substance may be hazardous to the environment.

Effect on the ozone layer No additional information available

## **SECTION 13: Disposal considerations**

#### 13.1. Disposal methods

Sewage disposal recommendations Do not dispose of waste into sewer.

Product/Packaging disposal recommendations May be incinerated. Dispose in a safe manner in accordance with local/national regulations.

Dispose of contents/container to licensed waste disposal facility...

Additional information : Handle empty containers with care because residual vapors are flammable. **Ecological information** 

: Avoid release to the environment.

### **SECTION 14: Transport information**

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA	
14.1. UN number				
1993	Not applicable	1993	1993	
14.2. Proper Shipping Name				
Flammable liquids, n.o.s. ((ALLYLTRIMETHOXYSILANE))	Not applicable	FLAMMABLE LIQUID, N.O.S.	Flammable liquid, n.o.s.	
Transport document description				
UN1993 Flammable liquids, n.o.s. (ALLYLTRIMETHOXYSILANE), 3, III	Not applicable	UN 1993 FLAMMABLE LIQUID, N.O.S., 3, III	UN 1993 Flammable liquid, n.o.s., 3, III	
14.3. Transport hazard class(es)				
3	Not applicable	3	3	
FLAMMABE LIQUID	Not applicable	3	3	

Print date: 02/05/2024 EN (English US) SDS ID: SIA0540.0 6/9

# Safety Data Sheet

DOT	TDG	IMDG	IATA	
14.4. Packing group				
III	Not applicable	III	III	
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	
No supplementary information availab	ble			

### 14.6. Special precautions for user

DOT

UN-No.(DOT) : UN1993

DOT Special Provisions (49 CFR 172.102) B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the

bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.

B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table

2 for UN2672).

T4 - 2.65 178.274(d)(2) Normal...... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous

materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the

MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) 150 DOT Packaging Non Bulk (49 CFR 173.xxx) 203 DOT Packaging Bulk (49 CFR 173.xxx) 242 DOT Quantity Limitations Passenger aircraft/rail (49 : 60 L

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L

CFR 175.75)

**DOT Vessel Stowage Location** : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

TDG

Emergency Response Guide (ERG) Number : 128

**IMDG** 

Special provision (IMDG) : 223, 274, 955

Limited quantities (IMDG) : 5 L Excepted quantities (IMDG) : E1

: LP01, P001 Packing instructions (IMDG) : IBC03 IBC packing instructions (IMDG) Tank instructions (IMDG) : T4 Tank special provisions (IMDG) : TP1, TP29

EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS EmS-No. (Spillage) : S-E - SPILLAGE SCHEDULE Echo - FLAMMABLE LIQUIDS, FLOATING ON WATER

Stowage category (IMDG) Α

Print date: 02/05/2024 EN (English US) SDS ID: SIA0540.0 7/9

# Safety Data Sheet

#### **IATA**

: E1 PCA Excepted quantities (IATA) PCA Limited quantities (IATA) : Y344 PCA limited quantity max net quantity (IATA) 10L PCA packing instructions (IATA) 355 : 60L PCA max net quantity (IATA) : 366 CAO packing instructions (IATA) CAO max net quantity (IATA) : 220L Special provision (IATA) : A3 ERG code (IATA) 3L

# 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

### **SECTION 15: Regulatory information**

### 15.1. US Federal regulations

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

Name	CAS-No.	Listing	Commercial status	Flags
Allyltrimethoxysilane	2551-83-9	Present	Active	

# 15.2. International regulations

#### **CANADA**

### Allyltrimethoxysilane (2551-83-9)

Listed on the Canadian DSL (Domestic Substances List)

### **EU-Regulations**

#### Allyltrimethoxysilane (2551-83-9)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

### **National regulations**

### Allyltrimethoxysilane (2551-83-9)

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing New Chemical Substances) inventory

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the TCSI (Taiwan Chemical Substance Inventory)

Listed on the NCI (Vietnam - National Chemical Inventory)

Listed on KECL/KECI (Korean Existing Chemicals Inventory)

### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

# **SECTION 16: Other information**

#### Full text of H-phrases::

H226	Flammable liquid and vapor
H319	Causes serious eye irritation

Print date: 02/05/2024 EN (English US) SDS ID: **SIA0540.0** 8/9

# Safety Data Sheet

Abbreviations and acronyms

Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemcial Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor.

Hazard Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is

given

Flammability : 2 Moderate Hazard - Materials which must be moderately heated or exposed to high ambient temperatures before ignition will occur. Includes liquids having a flash point at or above 100 F

but below 200 F. (Classes II IIIA)

Physical : 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous

polymerization in the absence of inhibitors.

Prepared by safety and environmental affairs.

Issue date: 12/29/2014 Revision date: 02/05/2024 Version: 2.2

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist.

Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2023 Gelest Inc. Morrisville, PA 19067

Print date: 02/05/2024 EN (English US) SDS ID: **SIA0540.0** 9/9