



3-AMINOPROPYLDIISOPROPYLETHOXSILANE

Safety Data Sheet SIA0602.0

Date of issue: 01/07/2015 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product name : 3-AMINOPROPYLDIISOPROPYLETHOXSILANE
 Product code : SIA0602.0
 Product form : Substance
 Physical state : Liquid
 Formula : C₁₁H₂₇NOSi
 Synonyms : 3-(DIISOPROPYLETHOXSILYL)PROPYLAMINE
 Chemical family : ORGANOETHOXSILANE

1.2. Recommended use and restrictions on use

Recommended use : Chemical intermediate

1.3. Supplier

GELEST, INC.

11 East Steel Road
 Morrisville, PA 19067

USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Skin corrosion/irritation Category 1B H314 Causes severe skin burns and eye damage
 Serious eye damage/eye irritation Category 1 H318 Causes serious eye damage
 Specific target organ toxicity (single exposure) Category 3 H335 May cause respiratory irritation
 Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger

Hazard statements (GHS US) : H314 - Causes severe skin burns and eye damage
 H318 - Causes serious eye damage
 H335 - May cause respiratory irritation

Precautionary statements (GHS US) : P280 - Wear protective gloves/protective clothing/eye protection/face protection.
 P260 - Do not breathe vapors.
 P264 - Wash hands thoroughly after handling.
 P271 - Use only outdoors or in a well-ventilated area.
 P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting
 P303+P361+P353 - If on skin (or hair): take off immediately all contaminated clothing. rinse skin with water/shower
 P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 P310 - Immediately call a doctor
 P363 - Wash contaminated clothing before reuse.
 P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
 P405 - Store locked up.
 P501 - Dispose of contents/container to licensed waste disposal facility.

2.3. Hazards not otherwise classified (HNOC)

Other hazards not contributing to the classification : The hydrolysis product of this compound is ethanol. Overexposure to ethanol by skin absorption, inhalation or ingestion may have a narcotic effect (headache, nausea, drowsiness). Ethanol is metabolized to acetaldehyde and acetic acid which in large quantities result in metabolic acidosis, CNS depression and death due to respiratory arrest. This product contains

3-AMINOPROPYLDIISOPROPYLETHOXSILANE

Safety Data Sheet

ethanol which is classified as a carcinogen by IARC in alcoholic beverages.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Substance type : Mono-constituent
Name : 3-AMINOPROPYLDIISOPROPYLETHOXSILANE
CAS-No. : 117559-36-1

Name	Product identifier	%	GHS-US classification
3-Aminopropyldiisopropylethoxysilane	(CAS-No.) 117559-36-1	> 95	Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335
Ethanol	(CAS-No.) 64-17-5		Flam. Liq. 2, H225 Eye Irrit. 2A, H319

Full text of hazard classes and H-statements : see section 16

3.2. Mixtures

Not applicable

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.

First-aid measures after skin contact : Wash with plenty of soap and water. Get immediate medical advice/attention.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Get medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : Causes severe skin burns and eye damage.

Symptoms/effects after inhalation : May cause respiratory irritation. Overexposure may cause: Coughing. Headache. Nausea.

Symptoms/effects after skin contact : Causes burns.

Symptoms/effects after eye contact : Causes serious eye damage.

Symptoms/effects after ingestion : May be harmful if swallowed.

Chronic symptoms : On contact with water this compound liberates ethanol which is known to have a chronic effect on the central nervous system.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Foam. Carbon dioxide. Dry chemical.

5.2. Specific hazards arising from the chemical

Fire hazard : Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use water spray to cool exposed surfaces. Exercise caution when fighting any chemical fire.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Avoid all eye and skin contact and do not breathe vapor and mist.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

3-AMINOPROPYLDIISOPROPYLETHOXSILANE

Safety Data Sheet

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or shovel spills into appropriate container for disposal.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapor and mist. Provide good ventilation in process area to prevent accumulation of vapors.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container tightly closed.

Incompatible materials : Acids. Alcohols. Moisture. Oxidizing agent. Peroxides. Water.

Storage area : Store in a well-ventilated place. Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Ethanol (64-17-5)		
ACGIH	ACGIH STEL (ppm)	1000 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	1900 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
IDLH	US IDLH (ppm)	3300 ppm (10% LEL)
NIOSH	NIOSH REL (TWA) (mg/m ³)	1900 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	1000 ppm

8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Hand protection:

Neoprene or nitrile rubber gloves

Eye protection:

Chemical goggles. Contact lenses should not be worn

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

NIOSH-certified combination organic vapor - amine gas (brown cartridge) respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear liquid.
Molecular mass	: 217.43 g/mol
Color	: Straw.
Odor	: Amine. Ammonia-like.
Odor threshold	: No data available
Refractive index	: 1.4489
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: < 1

3-AMINOPROPYLDIISOPROPYLETHOXSILANE

Safety Data Sheet

Melting point	: No data available
Freezing point	: < 0 °C
Boiling point	: 78 - 80 °C @ 0.4 mm Hg
Flash point	: > 100 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: < 0.1 mm Hg @ 20°C
Relative vapor density at 20 °C	: > 1
Relative density	: 0.872
% Volatiles	: < 30 %
Solubility	: Reacts with water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable when stored in sealed containers.

10.3. Possibility of hazardous reactions

Reacts with water and moisture in air, liberating ethanol.

10.4. Conditions to avoid

Heat. Open flame. Sparks.

10.5. Incompatible materials

Acids. Alcohols. Moisture. Oxidizing agent. Peroxides. Water.

10.6. Hazardous decomposition products

Ethanol. Organic acid vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

3-AMINOPROPYLDIISOPROPYLETHOXSILANE (117559-36-1)	
LD50 oral rat	9280 mg/kg
Ethanol (64-17-5)	
LD50 oral rat	7060 mg/kg
LC50 inhalation rat (mg/l)	124.7 mg/l/4h
LC50 inhalation rat (ppm)	20000 ppm 10 hrs.
LDLo oral rat	1400 mg/kg (Human)
ATE US (oral)	7060 mg/kg body weight
ATE US (vapors)	124.7 mg/l/4h
ATE US (dust, mist)	124.7 mg/l/4h

Skin corrosion/irritation : Causes severe skin burns and eye damage.

Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Ethanol (64-17-5)	
IARC group	1 - Carcinogenic to humans

3-AMINOPROPYLDIISOPROPYLETHOXSILANE

Safety Data Sheet

Ethanol (64-17-5)	
In OSHA Hazard Communication Carcinogen list	Yes

Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: May cause respiratory irritation.
Specific target organ toxicity – repeated exposure	: Not classified
Aspiration hazard	: Not classified
Symptoms/effects after inhalation	: May cause respiratory irritation. Overexposure may cause: Coughing. Headache. Nausea.
Symptoms/effects after skin contact	: Causes burns.
Symptoms/effects after eye contact	: Causes serious eye damage.
Symptoms/effects after ingestion	: May be harmful if swallowed.
Chronic symptoms	: On contact with water this compound liberates ethanol which is known to have a chronic effect on the central nervous system.
Reason for classification	: Expert judgment

SECTION 12: Ecological information

12.1. Toxicity

Ethanol (64-17-5)	
LC50 fish 1	> 10000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
LC50 fish 2	> 13400 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Ethanol (64-17-5)	
Log Pow	-0.32

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other adverse effects	: This substance may be hazardous to the environment.
Effect on the ozone layer	: No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations	: May be incinerated. Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to licensed waste disposal facility.
Ecology - waste materials	: Avoid release to the environment.

SECTION 14: Transport information

14.1. UN number

UN-No.(DOT)	: 1760
DOT NA no.	UN1760

14.2. UN proper shipping name

Transport document description	: UN1760 Corrosive liquids, n.o.s. (3-AMINOPROPYLDIISOPROPYLETHOXSILANE), 8, III
Proper Shipping Name (DOT)	: Corrosive liquids, n.o.s. (3-AMINOPROPYLDIISOPROPYLETHOXSILANE)
Class (DOT)	: 8 - Class 8 - Corrosive material 49 CFR 173.136
Packing group (DOT)	: III - Minor Danger
Hazard labels (DOT)	: 8 - Corrosive



DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
---	-------

3-AMINOPROPYLDIISOPROPYLETHOXYSILANE

Safety Data Sheet

DOT Packaging Bulk (49 CFR 173.xxx) : 241
DOT Packaging Exceptions (49 CFR 173.xxx) : 154
DOT Symbols : G - Identifies PSN requiring a technical name

14.3. Additional information

Emergency Response Guide (ERG) Number : 154

Other information : No supplementary information available.

Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 5 L
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L
CFR 175.75)

SECTION 15: Regulatory information

15.1. US Federal regulations

3-AMINOPROPYLDIISOPROPYLETHOXYSILANE (117559-36-1)

TSCA Exemption/Exclusion

CAUTION: This material is supplied for research and development purposes subject to the R&D exemption under TSCA, 40 CFR 720.36, and must meet the requirements of the exemption, including supervision by a "technically qualified individual" as defined by 40 CFR 720.3(ee). The use of this material for "commercial purposes" as defined by 40 CFR 720.3(r) is not permitted in the United States.

Ethanol (64-17-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

3-Aminopropyl-diisopropylethoxysilane (117559-36-1)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

Ethanol (64-17-5)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification

Class B Division 2 - Flammable Liquid
Class D Division 2 Subdivision B - Toxic material causing other toxic effects

EU-Regulations

Ethanol (64-17-5)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

Ethanol (64-17-5)

Listed on IARC (International Agency for Research on Cancer)
Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the Canadian IDL (Ingredient Disclosure List)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)

15.3. US State regulations

⚠ WARNING: This product can expose you to Ethanol, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

3-AMINOPROPYLDIISOPROPYLETHOXSILANE

Safety Data Sheet

Ethanol (64-17-5)					
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	Yes	No	No		

Ethanol (64-17-5)
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Full text of H-phrases::

H225	Highly flammable liquid and vapor
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H319	Causes serious eye irritation
H335	May cause respiratory irritation

Abbreviations and acronyms

: Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor.

Hazard Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

Flammability : 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)

Physical : 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.

Prepared by safety and environmental affairs.

Date of issue: 01/07/2015 Version: 1.0

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2019 Gelest Inc. Morrisville, PA 19067