

Safety Data Sheet SIB1048.0

Issue date: 03/08/2016 Revision date: 03/06/2024 Version: 2.1

SECTION 1: Identification

1.1. Identification

Product name : 1,8-BIS(CHLORODIMETHYLSILYL)OCTANE, 95%

Product code : SIB1048.0
Product form : Substance
Physical state : Liquid
Formula : C12H28Cl2Si2

Synonyms : 2,11-DICHLORO-2,11-DIMETHYL-2,11-DISILADODECANE; OCTANE-1,8-

DIYLBIS[CHLORODIMETHYLSILANE]

Chemical family : ORGANOCHLOROSILANE

1.2. Recommended use and restrictions on use

Recommended use : Chemical intermediate

1.3. Supplier

GELEST, INC.

11 East Steel Road Morrisville, PA 19067

USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation Category 1B H314 Causes severe skin burns and eye damage

Serious eye damage/eye irritation Category 1 H318 Causes serious eye damage

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)



Signal word (GHS US) : Danger

Hazard statements (GHS US) : H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

Precautionary statements (GHS US) : P260 - Do not breathe vapors.

 $\ensuremath{\mathsf{P264}}$ - Wash hands thoroughly after handling.

P280 - Wear protective gloves/protective clothing/eye protection/face protection. P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.

P303+P361+P353 - If on skin (or hair): take off immediately all contaminated clothing, rinse skin

with water/shower

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.

Print date: 04/01/2024 EN (English US) SDS ID: **SIB1048.0** 1/9

Safety Data Sheet

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a doctor.

P321 - Specific treatment (see first aid instructions on this label).

P363 - Wash contaminated clothing before reuse.

P405 - Store locked up.

P501 - Dispose of contents/container to licensed waste disposal facility...

2.3. Hazards not otherwise classified (HNOC)

Other hazards which do not result in classification

: Hydrogen chloride may be formed by reaction with water and moisture in air. The US OSHA PEL

(TWA) for hydrogen chloride is 5 ppm.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Substance type : Multi-constituent

Name : 1,8-BIS(CHLORODIMETHYLSILYL)OCTANE, 95%

CAS-No. : 5089-28-1

Name	Product identifier	%	GHS US classification
1,8-Bis(chlorodimethylsilyl)octane	CAS-No.: 5089-28-1	95 – 100	Skin Corr. 1B, H314 Eye Dam. 1, H318
Bis(chlorodimethylsilyl)octane isomers	CAS-No.: Not found	0 – 5	Skin Corr. 1B, H314 Eye Dam. 1, H318

Full text of hazard classes and H-statements : see section 16

3.2. Mixtures

Not applicable

SECTION 4: First-aid measures

4.1. Description of first aid measures

4.1. Description of met ala measures

First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available

show packaging or label.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel

unwell, seek medical advice.

First-aid measures after skin contact : Wash with plenty of soap and water. Get immediate medical advice/attention.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get immediate medical advice/attention.

First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel

unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : Causes severe skin burns and eye damage.

Symptoms/effects after inhalation : May cause irritation to the respiratory tract.

Symptoms/effects after skin contact : Causes (severe) skin burns. Symptoms/effects after eye contact : Causes serious eye damage.

Symptoms/effects after ingestion : May be harmful if swallowed.

Print date: 04/01/2024 EN (English US) SDS ID: **SIB1048.0** 2/9

Safety Data Sheet

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Foam. Carbon dioxide. Dry chemical.

Unsuitable extinguishing media : Water

5.2. Specific hazards arising from the chemical

Fire hazard : Irritating fumes of hydrogen chloride and organic acid vapors may develop when material is

exposed to water or open flame.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Use water spray to cool exposed surfaces.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Avoid

all eye and skin contact and do not breathe vapor and mist.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Wear protective equipment as described in Section 8.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with

proper protection. For further information refer to section 8: "Exposure controls/personal

protection".

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or

streams.

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or

shovel spills into appropriate container for disposal.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapor and mist. Provide good ventilation in

process area to prevent accumulation of vapors.

Hygiene measures : Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap

and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container tightly closed. Store locked up.

Incompatible materials : Alcohols. Amines. Oxidizing agent.

Print date: 04/01/2024 EN (English US) SDS ID: **SIB1048.0** 3/9

Safety Data Sheet

Storage area : Store in a well-ventilated place. Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Hand protection:

Neoprene or nitrile rubber gloves

Eye protection:

Chemical goggles or face shield. Contact lenses should not be worn

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified combination organic vapor/acid gas (yellow cartridge) respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Liquid.
Molecular mass : 299.43 g/mol
Color : Clear to pale yellow.

Odor : Acrid.

Odor threshold : No data available pH : No data available Relative evaporation rate (butyl acetate=1) : No data available Melting point : No data available

Freezing point : < 0 °C

Boiling point : 106 - 107 °C @ 0.4 mm Hg

Flash point : 180 °C

Auto-ignition temperature : No data available
Decomposition temperature : No data available
Flammability (solid, gas) : No data available
Vapor pressure : < 0.1 mm Hg @ 25°C

Relative vapor density at 20°C : > 1
Relative density : 0.946

Solubility Reacts with water. Partition coefficient n-octanol/water (Log Pow) : No data available Partition coefficient n-octanol/water (Log Kow) : No data available Viscosity, kinematic : No data available Viscosity, dynamic No data available No data available Explosive properties Oxidizing properties No data available **Explosion limits** No data available

Print date: 04/01/2024 EN (English US) SDS ID: **SIB1048.0** 4/9

Safety Data Sheet

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable in sealed containers stored under a dry inert atmosphere.

10.3. Possibility of hazardous reactions

Reacts with water and moisture in air, liberating hydrogen chloride.

10.4. Conditions to avoid

Heat. Open flame. Sparks.

10.5. Incompatible materials

Alcohols. Amines. Oxidizing agent.

10.6. Hazardous decomposition products

Hydrogen chloride. Organic acid vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Skin corrosion/irritation : Causes severe skin burns.
Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Not classified
STOT-repeated exposure : Not classified
Aspiration hazard : Not classified

Symptoms/effects after inhalation : May cause irritation to the respiratory tract.

Symptoms/effects after skin contact : Causes (severe) skin burns.
Symptoms/effects after eye contact : Causes serious eye damage.
Symptoms/effects after ingestion : May be harmful if swallowed.

Reason for classification : Expert judgment

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

Print date: 04/01/2024 EN (English US) SDS ID: **SIB1048.0** 5/9

Safety Data Sheet

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other adverse effects : This substance may be hazardous to the environment.

Effect on the ozone layer : No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Sewage disposal recommendations : Do not dispose of waste into sewer.

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of

contents/container to licensed waste disposal facility..

Ecological information : Avoid release to the environment.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

In accordance with DOT / TDG / IMDG / IATA					
DOT	TDG		IMDG	IATA	
14.1. UN number					
2987	Not applicable		2987	2987	
14.2. Proper Shipping Name					
Chlorosilanes, corrosive, n.o.s. ((1,8- BIS(CHLORODIMETHYLSILYL)OC TANE))	Not applicable		CHLOROSILANES, CORROSIVE, N.O.S. (1,8- BIS(CHLORODIMETHYLSILYL)OC TANE)	Chlorosilanes, corrosive, n.o.s. (1,8- BIS(CHLORODIMETHYLSILYL)OC TANE)	
Transport document description					
UN2987 Chlorosilanes, corrosive, n.o.s. (1,8- BIS(CHLORODIMETHYLSILYL)OC TANE), 8, II	Not applicable		UN 2987 CHLOROSILANES, CORROSIVE, N.O.S. (1,8- BIS(CHLORODIMETHYLSILYL)OC TANE), 8, II	UN 2987 Chlorosilanes, corrosive, n.o.s. (1,8- BIS(CHLORODIMETHYLSILYL)OC TANE), 8, II	
14.3. Transport hazard class(es)				
8	Not applicable		8	8	
CORROSTVE 8	Not applicable		8	8	
14.4. Packing group					
II	Not applicable		II	II	
14.5. Environmental hazards					
Dangerous for the environment: No	Dangerous for the environment: No		Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	
No supplementary information availab	le				

Print date: 04/01/2024 EN (English US) SDS ID: **SIB1048.0** 6/9

Safety Data Sheet

14.6. Special precautions for user

DOT

UN-No.(DOT) : UN2987

DOT Special Provisions (49 CFR 172.102) : B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are

not authorized.

T14 - 6 6 mm Prohibited 178.275(g)(3).

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

TP7 - The vapor space must be purged of air by nitrogen or other means.

TP13 - Self-contained breathing apparatus must be provided when this hazardous material is

transported by sea.

TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : None
DOT Packaging Non Bulk (49 CFR 173.xxx) : 206
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Quantity Limitations Passenger aircraft/rail (49 : Forbidden

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 30 L

CFR 175.75)

DOT Vessel Stowage Location : C - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

TDG

Emergency Response Guide (ERG) Number : 156

IMDG

Limited quantities (IMDG) : 0
Excepted quantities (IMDG) : E0
Packing instructions (IMDG) : P010
Tank instructions (IMDG) : T14

Tank special provisions (IMDG) : TP2, TP7, TP13, TP27

EmS-No. (Fire) : F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE EmS-No. (Spillage) : S-B - SPILLAGE SCHEDULE Bravo - CORROSIVE SUBSTANCES

Stowage category (IMDG) : C
Stowage and handling (IMDG) : SW2

Properties and observations (IMDG) : Colourless liquids with a pungent odour. Immiscible with water. React violently with water or

steam, evolving hydrogen chloride, an irritating and corrosive gas apparent as white fumes. When involved in a fire, evolve toxic gases. In the presence of moisture, highly corrosive to most

metals. Cause burns to skin, eyes and mucous membranes.

IATA

PCA Excepted quantities (IATA) E0 PCA Limited quantities (IATA) Forbidden Forbidden PCA limited quantity max net quantity (IATA) PCA packing instructions (IATA) Forbidden PCA max net quantity (IATA) Forbidden 876 CAO packing instructions (IATA) 30L CAO max net quantity (IATA) Special provision (IATA) : A1 ERG code (IATA) 8L

Print date: 04/01/2024 EN (English US) SDS ID: **SIB1048.0** 7/9

Safety Data Sheet

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

1,8-BIS(CHLORODIMETHYLSILYL)OCTANE, 95% (5089-28-1)

TSCA Exemption/Exclusion

CAUTION: This material is supplied for research and development purposes subject to the RD exemption under TSCA, 40 CFR 720.36, and must meet the requirements of the exemption, including supervision by a "technically qualified individual" as defined by 40 CFR 720.3(ee). The use of this material for "commercial purposes" as defined by 40 CFR 720.3(r) is not permitted in the United States.

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

1,8-Bis(chlorodimethylsilyl)octane	CAS-No. 5089-28-1	95 – 100%
Bis(chlorodimethylsilyl)octane isomers	CAS-No. Not found	0 – 5%

15.2. International regulations

CANADA

No additional information available

EU-Regulations

1,8-Bis(chlorodimethylsilyl)octane (5089-28-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

1,8-Bis(chlorodimethylsilyl)octane (5089-28-1)

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

Full text of H-phrases::

H314	Causes severe skin burns and eye damage	
H318	Causes serious eye damage	

Abbreviations and acronyms

: Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemcial Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor.

Hazard Rating

Print date: 04/01/2024 EN (English US) SDS ID: **SIB1048.0** 8/9

Safety Data Sheet

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is

Flammability : 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids,

solids and semi solids having a flash point above 200 F. (Class IIIB)

Physical : 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous

polymerization in the absence of inhibitors.

Prepared by safety and environmental affairs.

Issue date: 03/08/2016 Revision date: 03/06/2024 Version: 2.1

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist.

Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2023 Gelest Inc. Morrisville, PA 19067



Print date: 04/01/2024 EN (English US) SDS ID: **SIB1048.0** 9/9