

Safety Data Sheet SIB1906.0
Date of issue: 01/06/2015 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product name : 3-BROMOPROPYLTRIMETHOXYSILANE

Product code : SIB1906.0
Product form : Substance
Physical state : Liquid
Formula : C6H15BrO3Si

Synonyms : 1-BROMO-3-(TRIMETHOXYSILYL)PROPANE

Chemical family : ORGANOMETHOXYSILANE

1.2. Recommended use and restrictions on use

Recommended use : Chemical intermediate

1.3. Supplier

GELEST, INC.

11 East Steel Road Morrisville, PA 19067

USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable liquids Category 4 H227 Combustible liquid
Skin corrosion/irritation Category 2 H315 Causes skin irritation
Serious eye damage/eye irritation Category 2A H319 Causes serious eye irritation

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)



Signal word (GHS US) : Warning

Hazard statements (GHS US)

: H227 - Combustible liquid
H315 - Causes skin irritation

H319 - Causes serious eye irritation

Precautionary statements (GHS US) : P280 - Wear eye protection, protective gloves, protective clothing.

P210 - Keep away from heat, open flames, sparks. - No smoking.

P264 - Wash hands thoroughly after handling. P302+P352 - If on skin: Wash with plenty of water

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing P337+P313 - If eye irritation persists: Get medical advice/attention. P362 - Take off contaminated clothing and wash before reuse.

P370+P378 - In case of fire: Use water spray, foam, carbon dioxide, dry chemical to extinguish.

P403+P235 - Keep in a cool place

P501 - Dispose of contents/container to licensed waste disposal facility.

2.3. Hazards not otherwise classified (HNOC)

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

Print date: 04/12/2019 EN (English US) SDS ID: **SIB1906.0** Page 1

Safety Data Sheet

SECTION 3: Composition/Information on ingredients

3.1. Substances

Substance type : Mono-constituent

Name : 3-BROMOPROPYLTRIMETHOXYSILANE

CAS-No. : 51826-90-5

Name	Product identifier	%	GHS-US classification
3-Bromopropyltrimethoxysilane	(CAS-No.) 51826-90-5	> 95	Flam. Liq. 4, H227 Skin Irrit. 2, H315 Eye Irrit. 2A, H319
Methanol	(CAS-No.) 67-56-1		Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 1, H370 STOT SE 3, H336

Full text of hazard classes and H-statements : see section 16

3.2 Mixtures

Not applicable

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not

available show packaging or label.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel

unwell, seek medical advice.

First-aid measures after skin contact : Wash with plenty of soap and water.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. Get medical advice/attention.

First-aid measures after ingestion : Immediately call a poison center or doctor/physician. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : May cause irritation to the respiratory tract. Overexposure may cause: Coughing. Headache.

Nausea.

Symptoms/effects after skin contact : Causes skin irritation.

Symptoms/effects after eye contact : Causes serious eye irritation.

Symptoms/effects after ingestion : Oral toxicity is associated with methanol, the solvent and a hydrolysis product which causes

nausea, vomiting, headache, visual effects including blindness.

Chronic symptoms : On contact with water this compound liberates methanol which is known to have a chronic

effect on the central nervous system.

4.3. Immediate medical attention and special treatment, if necessary

NOTE TO PHYSICIAN: This product reacts with water in the acid contents of the stomach to form methanol. The combination of visual disturbances, metabolic acidosis and formic acid in urine is evidence of methanol poisoning. The therapeutic intravenous administration of ethanol (10 mls/hour) allows methanol to be preferentially oxidized and reduces production of methanol metabolites. Acidosis must be treated with intravenous administration of sodium bicarbonate and methanol elimination may be increased by hemodialysis, as indicated. Treatment should be based on blood methanol levels and acid-base balance.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Foam. Carbon dioxide. Dry chemical.

5.2. Specific hazards arising from the chemical

Fire hazard : Combustible liquid. Irritating fumes and organic acid vapors may develop when material is

exposed to elevated temperatures or open flame.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use water spray to cool exposed surfaces. Exercise caution when fighting any chemical fire.

Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Avoid all eye and skin contact and do not breathe vapor and mist.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges.

Print date: 04/12/2019 EN (English US) SDS ID: SIB1906.0 2/7

Safety Data Sheet

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Clean up any spills

: Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or shovel spills into appropriate container for disposal. Use only non-sparking tools.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

: Keep away from heat, open flames, sparks. - No smoking.

Precautions for safe handling

: Provide good ventilation in process area to prevent accumulation of vapors. Avoid all eye and skin contact and do not breathe vapor and mist. Containers and transfer lines require grounding

during use. Use only non-sparking tools.

Hygiene measures

: Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Keep container tightly closed.

Incompatible materials : Acids. Alcohols. Lewis acids. Oxidizing agent. Peroxides. Moisture. Water.

Storage area : Store in a well-ventilated place. Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Methanol (67-56-1)			
ACGIH	ACGIH TWA (ppm)	200 ppm	
ACGIH	ACGIH STEL (ppm)	250 ppm	
OSHA	OSHA PEL (TWA) (mg/m³)	260 mg/m³	
OSHA	OSHA PEL (TWA) (ppm)	200 ppm	
IDLH	US IDLH (ppm)	6000 ppm	
NIOSH	NIOSH REL (TWA) (mg/m³)	260 mg/m³	
NIOSH	NIOSH REL (TWA) (ppm)	200 ppm	
NIOSH	NIOSH REL (STEL) (mg/m³)	325 mg/m³	
NIOSH	NIOSH REL (STEL) (ppm)	250 ppm	

8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Hand protection:

Neoprene or nitrile rubber gloves

Eye protection:

Chemical goggles. Contact lenses should not be worn

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Print date: 04/12/2019 EN (English US) SDS ID: SIB1906.0 3/7

Safety Data Sheet

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Clear liquid.
Molecular mass : 243.17 g/mol
Color : Straw.
Odor : Mild.

Odor threshold : No data available

Refractive index : 1.44

pH : No data available Relative evaporation rate (butyl acetate=1) : No data available Melting point : No data available

Freezing point : < 0 °C

Boiling point : 130 °C @ 45 mm Hg

Flash point : 82 °C

Auto-ignition temperature : No data available
Decomposition temperature : No data available
Flammability (solid, gas) : Combustible liquid
Vapor pressure : < 10 mm Hg

Relative vapor density at 20 °C : > 1
Relative density : 1.293

Solubility Reacts with water. Log Pow No data available No data available Log Kow No data available Viscosity, kinematic Viscosity, dynamic No data available Explosive properties No data available Oxidizing properties No data available **Explosion limits** No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable in sealed containers stored under dry nitrogen.

10.3. Possibility of hazardous reactions

Reacts with water and moisture in air, liberating methanol.

10.4. Conditions to avoid

Heat. Sparks. Open flame.

10.5. Incompatible materials

Acids. Alcohols. Lewis acids. Oxidizing agent. Peroxides. Moisture. Water.

10.6. Hazardous decomposition products

Hydrogen bromide. Methanol. Organic acid vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Methanol (67-56-1)		
LC50 inhalation rat (ppm)	22500 ppm (Exposure time: 8 h)	
ATE US (oral)	100 mg/kg body weight	
ATE US (dermal)	300 mg/kg body weight	
ATE US (vapors)	3 mg/l/4h	

Print date: 04/12/2019 EN (English US) SDS ID: SIB1906.0 4/7

Safety Data Sheet

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified

A recent study indicated that the related compound, chloropropyltrimethoxysilane, is a genetically active material via inhalation in a bone marrow micronucleus assay in female rats exposed to 200ppm daily over a 28 day period. However, using the same assay, no evidence of genetic activity was found in mice exposed to 500, 1000, or 1625 mg/kg by intraperitoneal injection. The relevance of this information to humans has not yet been determined.

Carcinogenicity : Not classified

Reproductive toxicity : Not classified Specific target organ toxicity – single exposure : Not classified

Specific target organ toxicity - repeated

exposure

: Not classified

Aspiration hazard : Not classified

Symptoms/effects after inhalation : May cause irritation to the respiratory tract. Overexposure may cause: Coughing. Headache.

Nausea.

Symptoms/effects after skin contact : Causes skin irritation.

Symptoms/effects after eye contact : Causes serious eye irritation.

Symptoms/effects after ingestion : Oral toxicity is associated with methanol, the solvent and a hydrolysis product which causes

nausea, vomiting, headache, visual effects including blindness.

Chronic symptoms : On contact with water this compound liberates methanol which is known to have a chronic

effect on the central nervous system.

SECTION 12: Ecological information

12.1. Toxicity

Methanol (67-56-1)				
LC50 fish 1	28200 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])			
LC50 fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])			

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Methanol (67-56-1)		
BCF fish 1	< 10	
Log Pow	-0.77	

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other adverse effects : This substance may be hazardous to the environment.

Effect on the ozone layer : No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of

contents/container to licensed waste disposal facility. May be incinerated.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

14.1. UN number

DOT NA no. NA1993

14.2. UN proper shipping name

Transport document description : NA1993 Combustible liquid, n.o.s. (3-BROMOPROPYLTRIMETHOXYSILANE), 3, III

Proper Shipping Name (DOT) : Combustible liquid, n.o.s.

(3-BROMOPROPYLTRIMETHOXYSILANE)

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Packing group (DOT) : III - Minor Danger

Print date: 04/12/2019 EN (English US) SDS ID: **SIB1906.0** 5/7

Safety Data Sheet

DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
DOT Packaging Bulk (49 CFR 173.xxx) : 241
DOT Packaging Exceptions (49 CFR 173.xxx) : 150

DOT Symbols : D - Proper shipping name for domestic use only, or to and from Canada,G - Identifies PSN

requiring a technical name

14.3. Additional information

Other information : This product is Combustible as defined by the US Department of Transportation (DOT). It is

regulated for transport in the US in container > 119 gallons (450 liters). The product is not

regulated for transport by the IATA, ADR/RID, ADNR or the IMDG regulations.

Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 60 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L

CFR 175.75)

SECTION 15: Regulatory information

15.1. US Federal regulations

3-BROMOPROPYLTRIMETHOXYSILANE (51826-90-5)

TSCA Exemption/Exclusion

CAUTION: This material is supplied for research and development purposes subject to the R&D exemption under TSCA, 40 CFR 720.36, and must meet the requirements of the exemption, including supervision by a "technically qualified individual" as defined by 40 CFR 720.3(ee). The use of this material for "commercial purposes" as defined by 40 CFR 720.3(r) is not permitted in the United States.

Methanol (67-56-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Subject to reporting requirements of United States SARA Section 313

SARA Section 313 - Emission Reporting 1 %

3-Bromopropyltrimethoxysilane (51826-90-5)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

Methanol (67-56-1)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification Class B Division 2 - Flammable Liquid

Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects

Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects

EU-Regulations

Methanol (67-56-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

3-Bromopropyltrimethoxysilane (51826-90-5)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

Methanol (67-56-1)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Japanese Poisonous and Deleterious Substances Control Law

Listed on the Canadian IDL (Ingredient Disclosure List)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Listed on CICR (Turkish Inventory and Control of Chemicals)

Print date: 04/12/2019 EN (English US) SDS ID: **SIB1906.0** 6/7

Safety Data Sheet

3-Bromopropyltrimethoxysilane (51826-90-5)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

15.3. US State regulations

MARNING:

This product can expose you to Methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Methanol (67-56-1)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
No	Yes	No	No		

Methanol (67-56-1)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

SECTION 16: Other information

Full text of H-phrases::

on in philadee		
H225		Highly flammable liquid and vapor
H227		Combustible liquid
H301		Toxic if swallowed
H311		Toxic in contact with skin
H315		Causes skin irritation
H318		Causes serious eye damage
H319		Causes serious eye irritation
H331		Toxic if inhaled
H336	1	May cause drowsiness or dizziness
H370	V 1600	Causes damage to organs

Abbreviations and acronyms

Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemcial Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor.

Hazard Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

: 2 Moderate Hazard - Materials which must be moderately heated or exposed to high ambient Flammability temperatures before ignition will occur. Includes liquids having a flash point at or above 100 F

but below 200 F. (Classes II & IIIA)

1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high Physical temperatures and pressures. Materials may react non-violently with water or undergo

hazardous polymerization in the absence of inhibitors.

Prepared by safety and environmental affairs.

Date of issue: 01/06/2015 Version: 1.0

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. The information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2019 Gelest Inc. Morrisville, PA 19067

Print date: 04/12/2019 EN (English US) SDS ID: SIB1906.0 7/7