

Safety Data Sheet SIC2298.6

Date of issue: 06/02/2015 Revision date: 11/01/2018 Version: 1.1

SECTION 1: Identification

1.1. Identification

Product name : CHLOROMETHYLTRIMETHOXYSILANE

Product code : SIC2298.6
Product form : Substance
Physical state : Liquid
Formula : C4H11CIO3Si

Synonyms : TRIMETHOXYCHLOROMETHYLSILANE

Chemical family : ORGANOMETHOXYSILANE

1.2. Recommended use and restrictions on use

Recommended use : Chemical intermediate

1.3. Supplier

GELEST, INC.

11 East Steel Road Morrisville, PA 19067

USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable liquids Category 3

Acute toxicity (oral) Category 4

Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2A

Specific target organ toxicity (single exposure) Category 3

H226

Flammable liquid and vapor

H302

Hamful if swallowed

H315

Causes skin irritation

H319

Causes serious eye irritation

H335

May cause respiratory irritation

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)





Signal word (GHS US) : Warning

Hazard statements (GHS US) : H226 - Flammable liquid and vapor

H302 - Harmful if swallowed H315 - Causes skin irritation H319 - Causes serious eye irritation H335 - May cause respiratory irritation

Precautionary statements (GHS US) : P210 - Keep away from heat, open flames, sparks. - No smoking.

P240 - Ground/Bond container and receiving equipment

P241 - Use explosion-proof ventilating equipment

P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.

P261 - Avoid breathing vapors.

P264 - Wash hands thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear eye protection, face protection, protective gloves. P301+P312 - If swallowed: Call a doctor if you feel unwell

P303+P361+P353 - If on skin (or hair): take off immediately all contaminated clothing. rinse

skin with water/shower

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing

P312 - Call a doctor if you feel unwell

Print date: 04/11/2019 EN (English US) SDS ID: **SIC2298.6** Page 1

Safety Data Sheet

P330 - Rinse mouth.

P332+P313 - If skin irritation occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P362 - Take off contaminated clothing and wash before reuse.

P370+P378 - In case of fire: Use foam, dry powder, carbon dioxide (CO2), Water spray to

extinguish.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P403+P235 - Keep in a cool place

P405 - Store locked up.

P501 - Dispose of contents/container to licensed waste disposal facility.

Hazards not otherwise classified (HNOC) 23

Other hazards not contributing to the classification

: On contact with water this compound liberates methanol which is known to have a chronic effect on the central nervous system.

Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

Substances

Substance type : Mono-constituent

: CHLOROMETHYLTRIMETHOXYSILANE Name

CAS-No. 5926-26-1

Name	Product identifier	%	GHS-US classification
Silane, chloromethyl-trimethoxy-	(CAS-No.) 5926-26-1	> 95	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
Methanol	(CAS-No.) 67-56-1		Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 1, H370 STOT SE 3, H336

Full text of hazard classes and H-statements : see section 16

Mixtures

Not applicable

SECTION 4: First-aid measures

Description of first aid measures

First-aid measures general

: Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.

First-aid measures after inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.

First-aid measures after skin contact

Wash with plenty of soap and water.

First-aid measures after eye contact

Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.

First-aid measures after ingestion

: Never give anything by mouth to an unconscious person. Get medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation

: May cause irritation to the respiratory tract. Overexposure may cause: Coughing. Headache. Nausea.

Symptoms/effects after skin contact

: Causes skin irritation.

Symptoms/effects after eye contact

: Causes serious eye irritation.

Symptoms/effects after ingestion

Oral toxicity is associated with methanol, the solvent and a hydrolysis product which causes

nausea, vomiting, headache, visual effects including blindness.

Chronic symptoms

On contact with water this compound liberates methanol which is known to have a chronic effect on the central nervous system. Methanol may effect the central nervous system resulting in persistent or recurring headaches or impaired vision.

Immediate medical attention and special treatment, if necessary

NOTE TO PHYSICIAN: This product reacts with water in the acid contents of the stomach to form methanol. The combination of visual disturbances, metabolic acidosis and formic acid in urine is evidence of methanol poisoning. The therapeutic intravenous administration of ethanol (10 mls/hour) allows methanol to be preferentially oxidized and reduces production of methanol metabolites. Acidosis must be treated with intravenous administration of sodium bicarbonate and methanol elimination may be increased by hemodialysis, as indicated. Treatment should be based on blood methanol levels and acid-base balance.

Print date: 04/11/2019 EN (English US) SDS ID: SIC2298.6 2/8

Safety Data Sheet

SECTION 5: Fire-fighting measures

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Foam. Carbon dioxide. Dry chemical.

Specific hazards arising from the chemical 5.2.

Fire hazard

: Highly flammable liquid and vapor. Irritating fumes and organic acid vapors may develop when

material is exposed to elevated temperatures or open flame.

Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use water spray to cool exposed surfaces. Exercise caution when fighting any chemical fire.

Do not enter fire area without proper protective equipment, including respiratory protection. Protection during firefighting

Avoid all eye and skin contact and do not breathe vapor and mist.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

: Eliminate every possible source of ignition. Use special care to avoid static electric charges. General measures

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

Methods and material for containment and cleaning up

Methods for cleaning up

Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or

shovel spills into appropriate container for disposal.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

Precautions for safe handling 7.1.

Additional hazards when processed

: Handle empty containers with care because residual vapors are flammable.

Precautions for safe handling

Provide local exhaust or general room ventilation. Avoid all eye and skin contact and do not breathe vapor and mist. Ground/bond container and receiving equipment. Take precautionary measures against static discharge. Use only non-sparking tools.

Hygiene measures

Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof

electrical equipment.

Storage conditions : Keep container tightly closed. Incompatible materials : Oxidizing agent. Moisture. Water.

Storage area : Store in a well-ventilated place. Store away from heat.

SECTION 8: Exposure controls/personal protection

Control parameters

Methanol (67-56-1)		
ACGIH	ACGIH TWA (ppm)	200 ppm
ACGIH	ACGIH STEL (ppm)	250 ppm
OSHA	OSHA PEL (TWA) (mg/m³)	260 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	200 ppm
IDLH	US IDLH (ppm)	6000 ppm
NIOSH	NIOSH REL (TWA) (mg/m³)	260 mg/m³
NIOSH	NIOSH REL (TWA) (ppm)	200 ppm
NIOSH	NIOSH REL (STEL) (mg/m³)	325 mg/m³
NIOSH	NIOSH REL (STEL) (ppm)	250 ppm

Print date: 04/11/2019 EN (English US) SDS ID: SIC2298.6 3/8

Safety Data Sheet

8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Hand protection:

Neoprene or nitrile rubber gloves

Eye protection:

Chemical goggles or face shield. Contact lenses should not be worn

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified combination organic vapor/acid gas (yellow cartridge) respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Clear liquid.
Molecular mass : 170.67 g/mol
Color : Straw.

Odor : Characteristic.
Odor threshold : No data available

Refractive index : 1.407

pH : No data available Relative evaporation rate (butyl acetate=1) : No data available Melting point : No data available

Freezing point : $< 0 \, ^{\circ}\text{C}$ Boiling point : $156 \, ^{\circ}\text{C}$ Flash point : $26 \, ^{\circ}\text{C}$

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Flammability (solid, gas) : Highly flammable liquid and vapor

Vapor pressure : No data available Relative vapor density at 20 °C : No data available

Relative density : 1.125 % Volatiles : 100 %

Solubility : Insoluble in water. Reacts with water.

Log Pow : No data available
Log Kow : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidizing properties : No data available
Explosion limits : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable in sealed containers.

Print date: 04/11/2019 EN (English US) SDS ID: SIC2298.6 4/8

Safety Data Sheet

10.3. Possibility of hazardous reactions

Reacts with water and moisture in air, liberating methanol.

10.4. Conditions to avoid

Heat. Sparks. Open flame.

10.5. Incompatible materials

Oxidizing agent. Moisture. Water.

10.6. Hazardous decomposition products

Methanol. Organic acid vapors. Silicon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

CHLOROMETHYLTRIMETHOXYSILANE (5926-26-1)			
ATE US (oral) 526.316 mg/kg body weight			
Methanol (67-56-1)			
LC50 inhalation rat (ppm) 22500 ppm (Exposure time: 8 h)			
ATE US (oral) 100 mg/kg body weight			
ATE US (dermal) 300 mg/kg body weight			
ATE US (vapors) 3 mg/l/4h			
Silane, chloromethyl-trimethoxy- (5926-26-1)			

Silane, chloromethyl-trimethoxy- (5926-26-1)				
LD50 oral rat	500 mg/kg			
LC50 inhalation rat (ppm)	3600 ppm/4h			
ATE US (oral)	500 mg/kg body weight			
ATE US (gases)	3600 ppmV/4h			

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

None of the components in this product at concentrations >0.1% are listed by IARC, NTP,

OSHA or ACGIH as a carcinogen.

Reproductive toxicity : Not classified

Specific target organ toxicity – single exposure : May cause respiratory irritation.

Specific target organ toxicity - repeated

exposure

: Not classified

Aspiration hazard : Not classified

Symptoms/effects after inhalation : May cause irritation to the respiratory tract. Overexposure may cause: Coughing. Headache.

Nausea.

Symptoms/effects after skin contact : Causes skin irritation.

Symptoms/effects after eye contact : Causes serious eye irritation.

Symptoms/effects after ingestion : Oral toxicity is associated with methanol, the solvent and a hydrolysis product which causes

nausea, vomiting, headache, visual effects including blindness.

Chronic symptoms : On contact with water this compound liberates methanol which is known to have a chronic

effect on the central nervous system. Methanol may effect the central nervous system resulting

in persistent or recurring headaches or impaired vision.

SECTION 12: Ecological information

12.1. Toxicity

Methanol (67-56-1)		
LC50 fish 1	28200 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])	
LC50 fish 2 > 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])		

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Print date: 04/11/2019 EN (English US) SDS ID: SIC2298.6 5/8

Safety Data Sheet

Methanol (67-56-1)	
BCF fish 1	< 10
Log Pow	-0.77

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other adverse effects : This substance may be hazardous to the environment.

Effect on the ozone layer : No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : May be incinerated. Dispose of contents/container to licensed waste disposal facility.

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

14.1. UN number

UN-No.(DOT) : 1993 DOT NA no. UN1993

14.2. UN proper shipping name

Transport document description : UN1993 Flammable liquids, n.o.s. (CHLOROMETHYLTRIMETHOXYSILANE), 3, III

Proper Shipping Name (DOT) : Flammable liquids, n.o.s.

(CHLOROMETHYLTRIMETHOXYSILANE)

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Packing group (DOT) : III - Minor Danger
Hazard labels (DOT) : 3 - Flammable liquid



DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Packaging Exceptions (49 CFR 173.xxx) : 150

DOT Symbols : G - Identifies PSN requiring a technical name

14.3. Additional information

Emergency Response Guide (ERG) Number : 128

Other information : No supplementary information available.

Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 60 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L

CFR 175.75)

SECTION 15: Regulatory information

15.1. US Federal regulations

CHLOROMETHYLTRIMETHOXYSILANE (5926-26-1)		
TSCA Exemption/Exclusion	Low Volume Exemption in accordance with 40 CFR 723.50(c)(1). Use of this substance is restricted to use in modification of inorganic surfaces. Anyone who intends to use this chemical substance for commercial purposes must comply with specific use restrictions and controls specified herein. This LVE limits site of manufacture of this substance to Gelest, Inc. unless otherwise approved by U.S. EPA	

Print date: 04/11/2019 EN (English US) SDS ID: SIC2298.6 6/8

Safety Data Sheet

Me	ethanol (67-56-1)		
	Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313		
SA	ARA Section 313 - Emission Reporting	1 %	

15.2. International regulations

CANADA

Methanol (67-56-1)			
Listed on the Canadian DSL (Domestic Substances List)			
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects		

EU-Regulations

Methanol (67-56-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

Methanol (67-56-1)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Japanese Poisonous and Deleterious Substances Control Law

Listed on the Canadian IDL (Ingredient Disclosure List)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Listed on CICR (Turkish Inventory and Control of Chemicals)

Silane, chloromethyl-trimethoxy- (5926-26-1)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

15.3. US State regulations



This product can expose you to Methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Methanol (67-56-1)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
No	Yes	No	No		

Methanol (67-56-1)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

SECTION 16: Other information

Full text of H-phrases::

H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H331	Toxic if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H370	Causes damage to organs

Print date: 04/11/2019 EN (English US) SDS ID: **SIC2298.6** 7/8

Safety Data Sheet

Abbreviations and acronyms

: Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemcial Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor.

Hazard Rating

Flammability

Physical

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is

given

: 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 F and boiling points above

100 F. as well as liquids with flash points between 73 F and 100 F. (Classes IB & IC)

: 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo

hazardous polymerization in the absence of inhibitors.

Prepared by safety and environmental affairs.

Date of issue: 06/02/2015 Revision date: 11/01/2018 Version: 1.1

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2019 Gelest Inc. Morrisville, PA 19067

Print date: 04/11/2019 EN (English US) SDS ID: SIC2298.6 8/8



11 E. Steel Road Morrisville, PA 19067

215-547-1015 phone 215-547-2484 fax www.gelest.com

NOTICE OF TSCA USE RESTRICTIONS AND REQUIRED CONTROLS FOR SIC2298.6 CHLOROMETHYLTRIMETHOXYSILANE

Dear Customer:

The chemical product purchased, SIC2298.6 has been granted a Low Volume Exemption by the U.S. Environmental Protection Agency (EPA) under the Toxic Substances Control Act (TSCA) regulations (40 CFR 723.50). Any manufacturer or processor who intends to use this chemical substance for commercial purposes must comply with the specific use restrictions and controls specified as follows:

USE OF THIS CHEMICAL SUBSTANCE IS RESTRICTED TO: Modification of inorganic surfaces

CONTROLS: Workers must use personal protection equipment to limit dermal and inhalation exposures as described in Section 8: Exposure Controls/Personal Protection of the Safety Data Sheet (SDS). These exposure controls include:

Hand protection: Impervious gloves (neoprene or nitrile rubber gloves) Eye Protection: Chemical goggles. Contact lenses should not be worn.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: Air-purifying respirator with organic vapor/acid gas cartridge.

WASTE DISPOSAL: Collect and containerize all waste, residues and wash solvents for off-site disposal by incineration. Do not release to POTW via sewer or to surface waters.

If you have questions or need more information related to allowable use of this substance, contact Gelest Regulatory Affairs at 215-547-1015.

Best Regards,

Gelest, Inc.

Regulatory Affairs Department