

Safety Data Sheet SIC2355.0 Date of issue: 01/05/2015 Version: 1.0

SECTION 1: Identification

Identification

Product name : 3-CHLOROPROPYLMETHYLDIMETHOXYSILANE

Product code : SIC2355.0 Product form : Substance Physical state : Liquid Formula : C6H15ClO2Si

1-CHLORO-3-(METHYLDIMETHOXYSILYL)PROPANE; (3-Synonyms

CHLOROPROPYL)DIMETHOXYMETHYLSILANE

: ORGANOMETHOXYSILANE Chemical family

Recommended use and restrictions on use

Recommended use : Chemical intermediate

Supplier

GELEST, INC.

11 East Steel Road Morrisville, PA 19067

USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com

Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

SECTION 2: Hazard(s) identification

Classification of the substance or mixture

GHS-US classification

Flammable liquids Category 4 Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2A H319 Causes serious eye irritation

H227 Combustible liquid H315 Causes skin irritation

Full text of H statements : see section 16

GHS Label elements, including precautionary statements 2.2.

GHS US labeling

Hazard pictograms (GHS US)



Signal word (GHS US) : Warning

Hazard statements (GHS US) H227 - Combustible liquid H315 - Causes skin irritation

H319 - Causes serious eye irritation

P280 - Wear protective gloves/protective clothing/eye protection/face protection. Precautionary statements (GHS US)

P210 - Keep away from heat, open flames, sparks. - No smoking.

P370+P378 - In case of fire: Use water spray, foam, carbon dioxide, dry chemical to extinguish. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing P337+P313 - If eye irritation persists: Get medical advice/attention.

P302+P352 - If on skin: Wash with plenty of water

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P264 - Wash hands thoroughly after handling

P362 - Take off contaminated clothing and wash before reuse.

P403+P235 - Keep in a cool place

P501 - Dispose of contents/container to licensed waste disposal facility.

Hazards not otherwise classified (HNOC)

No additional information available

Unknown acute toxicity (GHS US)

Not applicable

Print date: 04/11/2019 EN (English US) SDS ID: SIC2355.0 Page 1

Safety Data Sheet

SECTION 3: Composition/Information on ingredients

Substances

Substance type : Mono-constituent

3-CHLOROPROPYLMETHYLDIMETHOXYSILANE Name

CAS-No. 18171-19-2

Name	Product identifier	%	GHS-US classification
3-Chloropropylmethyldimethyloxysilane	(CAS-No.) 18171-19-2	> 95	Flam. Liq. 4, H227 Skin Irrit. 2, H315 Eye Irrit. 2A, H319
Methanol	(CAS-No.) 67-56-1		Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 1, H370 STOT SE 3. H336

Full text of hazard classes and H-statements : see section 16

Mixtures

Not applicable

SECTION 4: First-aid measures

Description of first aid measures

First-aid measures general Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not

available show packaging or label.

First-aid measures after inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel

unwell, seek medical advice.

First-aid measures after skin contact : Wash with plenty of soap and water. Get medical advice/attention.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical advice/attention.

First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Get medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation May cause irritation to the respiratory tract. Overexposure may cause: Cough. Headache.

Nausea

Symptoms/effects after skin contact Causes skin irritation.

Symptoms/effects after eye contact Causes serious eye irritation.

Oral toxicity is associated with methanol, the solvent and a hydrolysis product which causes Symptoms/effects after ingestion

nausea, vomiting, headache, visual effects including blindness. Onset of symptoms may be

delayed up to 48 hours.

On contact with water this compound liberates methanol which is known to have a chronic Chronic symptoms

effect on the central nervous system.

Immediate medical attention and special treatment, if necessary

NOTE TO PHYSICIAN: This product reacts with water in the acid contents of the stomach to form methanol. The combination of visual disturbances, metabolic acidosis and formic acid in urine is evidence of methanol poisoning. The therapeutic intravenous administration of ethanol (10 mls/hour) allows methanol to be preferentially oxidized and reduces production of methanol metabolites. Acidosis must be treated with intravenous administration of sodium bicarbonate and methanol elimination may be increased by hemodialysis, as indicated. Treatment should be based on blood methanol levels and acid-base balance.

SECTION 5: Fire-fighting measures

Suitable (and unsuitable) extinguishing media 5.1.

Suitable extinguishing media : Water spray. Foam. Carbon dioxide. Dry chemical.

5.2. Specific hazards arising from the chemical

Fire hazard : Combustible liquid. Irritating fumes and organic acid vapors may develop when material is

exposed to elevated temperatures or open flame.

Explosion hazard : May form flammable/explosive vapor-air mixture.

Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use water spray to cool exposed surfaces. Exercise caution when fighting any chemical fire.

: Do not enter fire area without proper protective equipment, including respiratory protection. Protection during firefighting Avoid all eye and skin contact and do not breathe vapor and mist.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges.

Print date: 04/11/2019 EN (English US) SDS ID: SIC2355.0 2/8

Safety Data Sheet

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or

shovel spills into appropriate container for disposal.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Keep away from heat, open flames, sparks. - No smoking.

Precautions for safe handling : Provide good ventilation in process area to prevent accumulation of vapors. Avoid breathing

vapors, mist. Take precautionary measures against static discharge.

Hygiene measures : Wash hands thoroughly after handling. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Keep container tightly closed.

Incompatible materials : Acids. Alcohols. Lewis acids. Oxidizing agent. Peroxides. Moisture. Water.

Storage area : Store in a well-ventilated place. Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Methanol (67-56-1)				
ACGIH	ACGIH TWA (ppm)	7 DY	200 ppm	
ACGIH	ACGIH STEL (ppm)		250 ppm	-
OSHA	OSHA PEL (TWA) (mg/m³)		260 mg/m³	
OSHA	OSHA PEL (TWA) (ppm)		200 ppm	
IDLH	US IDLH (ppm)		6000 ppm	
NIOSH	NIOSH REL (TWA) (mg/m³)		260 mg/m³	
NIOSH	NIOSH REL (TWA) (ppm)		200 ppm	
NIOSH	NIOSH REL (STEL) (mg/m³)		325 mg/m³	
NIOSH	NIOSH REL (STEL) (ppm)		250 ppm	

8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Hand protection:

Neoprene or nitrile rubber gloves

Eye protection:

Chemical goggles. Contact lenses should not be worn

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

NIOSH-certified combination organic vapor/acid gas (yellow cartridge) respirator.

Print date: 04/11/2019 EN (English US) SDS ID: SIC2355.0 3/8

Safety Data Sheet

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Clear liquid.
Molecular mass : 182.72 g/mol
Color : Straw.
Odor : Mild.

Odor threshold : No data available

Refractive index : 1.4253

pH : No data available Relative evaporation rate (butyl acetate=1) : No data available Melting point : No data available

Freezing point : < 0 °C

Boiling point : 70 - 72 °C @ 11 mm Hg

Flash point : 80 °C

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Flammability (solid, gas) : Combustible liquid

Vapor pressure : 5 mm Hg @ 25°C

Relative vapor density at 20 °C : > 1
Relative density : 1.025

Solubility : Reacts with water. Log Pow : No data available No data available Log Kow Viscosity, kinematic No data available : No data available Viscosity, dynamic No data available **Explosive** properties No data available Oxidizing properties **Explosion limits** : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable in sealed containers stored under a dry inert atmosphere.

10.3. Possibility of hazardous reactions

Reacts with water and moisture in air, liberating methanol.

10.4. Conditions to avoid

Heat. Open flame. Sparks.

10.5. Incompatible materials

Acids. Alcohols. Lewis acids. Oxidizing agent. Peroxides. Moisture. Water.

10.6. Hazardous decomposition products

Methanol. Organic acid vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Methanol (67-56-1)			
LC50 inhalation rat (ppm)	22500 ppm (Exposure time: 8 h)		
ATE US (oral)	100 mg/kg body weight		
ATE US (dermal)	rmal) 300 mg/kg body weight		
ATE US (vapors) 3 mg/l/4h			

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.

Print date: 04/11/2019 EN (English US) SDS ID: **SIC2355.0** 4/8

Safety Data Sheet

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified

> A recent study indicated that the related compound, chloropropyltrimethoxysilane, is a genetically active material via inhalation in a bone marrow micronucleus assay in female rats exposed to 200ppm daily over a 28 day period. However, using the same assay, no evidence of genetic activity was found in mice exposed to 500, 1000, or 1625 mg/kg by intraperitoneal

injection. The relevance of this information to humans has not yet been determined.

Carcinogenicity : Not classified

Reproductive toxicity : Not classified Specific target organ toxicity - single exposure : Not classified

Specific target organ toxicity - repeated

exposure

: Not classified

Aspiration hazard : Not classified

Symptoms/effects after inhalation : May cause irritation to the respiratory tract. Overexposure may cause: Cough. Headache.

Nausea.

: Causes skin irritation. Symptoms/effects after skin contact Symptoms/effects after eye contact : Causes serious eye irritation.

: Oral toxicity is associated with methanol, the solvent and a hydrolysis product which causes Symptoms/effects after ingestion

nausea, vomiting, headache, visual effects including blindness. Onset of symptoms may be

Chronic symptoms On contact with water this compound liberates methanol which is known to have a chronic

effect on the central nervous system.

SECTION 12: Ecological information

12.1. **Toxicity**

Methanol (67-56-1)	
LC50 fish 1	28200 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

12.2. Persistence and degradability

No additional information available

Bioaccumulative potential 12.3.

Methanol (67-56-1)		
BCF fish 1	< 10	
Log Pow	-0.77	

Mobility in soil

No additional information available

Other adverse effects

Other adverse effects : This substance may be hazardous to the environment.

: No additional information available Effect on the ozone layer

SECTION 13: Disposal considerations

Disposal methods

: Dispose in a safe manner in accordance with local/national regulations. Dispose of Product/Packaging disposal recommendations

contents/container to licensed waste disposal facility.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

14.1. **UN** number

DOT NA no. NA1993

UN proper shipping name 14.2.

Transport document description : NA1993 COMBUSTIBLE LIQUID, N.O.S. (3-CHLOROPROPYLMETHYLDIMETHOXYSILANE),

Proper Shipping Name (DOT) : COMBUSTIBLE LIQUID, N.O.S.

(3-CHLOROPROPYLMETHYLDIMETHOXYSILANE)

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Packing group (DOT) : III - Minor Danger

SDS ID: SIC2355.0 Print date: 04/11/2019 EN (English US) 5/8

Safety Data Sheet

DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
DOT Packaging Bulk (49 CFR 173.xxx) : 241
DOT Packaging Exceptions (49 CFR 173.xxx) : 150

DOT Symbols : D - Proper shipping name for domestic use only, or to and from Canada,G - Identifies PSN

requiring a technical name

14.3. Additional information

Other information : This product is Combustible as defined by the US Department of Transportation (DOT). It is

regulated for transport in the US in container > 119 gallons (450 liters). The product is not

regulated for transport by the IATA, ADR/RID, ADNR or the IMDG regulations.

Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 60 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L

CFR 175.75)

SECTION 15: Regulatory information

15.1. US Federal regulations

Methanol (67-56-1)				
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313				
SARA Section 313 - Emission Reporting	1 %			
0.011				

3-Chloropropylmethyldimethyloxysilane (18171-19-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

	CANADA						
	Methanol (67-56-1)						
Listed on the Canadian DSL (Domestic Substances List)							
	WHMIS Classificat	tion			Class D	B Division 2 - Flammable Liquid D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects D Division 2 Subdivision A - Very toxic material causing other toxic effects	
						D Division 2 Subdivision B - Toxic material causing other toxic effects	

3-Chloropropylmethyldimethyloxysilane (18171-19-2)

Listed on the Canadian NDSL (Non-Domestic Substances List)

EU-Regulations

Methanol (67-56-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

3-Chloropropylmethyldimethyloxysilane (18171-19-2)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

Methanol (67-56-1)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Japanese Poisonous and Deleterious Substances Control Law

Listed on the Canadian IDL (Ingredient Disclosure List)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Listed on CICR (Turkish Inventory and Control of Chemicals)

Print date: 04/11/2019 EN (English US) SDS ID: SIC2355.0 6/8

Safety Data Sheet

3-Chloropropylmethyldimethyloxysilane (18171-19-2)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

15.3. US State regulations

MARNING:

This product can expose you to Methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Methanol (67-56					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
No	Yes	No	No		

Methanol (67-56-1)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

SECTION 16: Other information

Full text of H-phrases::

	a ci i i pinaccon		
	H225		Highly flammable liquid and vapor
	H227		Combustible liquid
	H301		Toxic if swallowed
	H311		Toxic in contact with skin
4	H315		Causes skin irritation
	H318		Causes serious eye damage
	H319	7 6	Causes serious eye irritation
	H331	7	Toxic if inhaled
	H336		May cause drowsiness or dizziness
	H370	1	Causes damage to organs

Abbreviations and acronyms

: Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemcial Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor.

Hazard Rating

Health

: 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

Flammability

: 2 Moderate Hazard - Materials which must be moderately heated or exposed to high ambient temperatures before ignition will occur. Includes liquids having a flash point at or above 100 F but below 200 F. (Classes II & IIIA)

Physical

: 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.

Prepared by safety and environmental affairs.

Date of issue: 01/05/2015 Version: 1.0

SDS US (GHS HazCom 2012) - Custom


According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Print date: 04/11/2019 EN (English US) SDS ID: SIC2355.0 7/8

Safety Data Sheet

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2019 Gelest Inc. Morrisville, PA 19067



Print date: 04/11/2019 EN (English US) SDS ID: **SIC2355.0** 8/8