

Safety Data Sheet SIC2568.0

Issue date: 06/15/2015 Revision date: 11/22/2023 Version: 2.1

SECTION 1: Identification

1.1. Identification

Product name : CYCLOTRIMETHYLENEDICHLOROSILANE

Product code : SIC2568.0
Product form : Substance
Physical state : Liquid
Formula : C3H6Cl2Si

Synonyms : 1,1-DICHLOROSILACYCLOBUTANE

Chemical family : ORGANOCHLOROSILANE

1.2. Recommended use and restrictions on use

Recommended use : Chemical intermediate

1.3. Supplier

GELEST, INC.

11 East Steel Road Morrisville. PA 19067

USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 2 H225 Highly flammable liquid and vapor Serious eye damage/eye irritation Category 2A H319 Causes serious eye irritation

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)





Signal word (GHS US) : Danger

Hazard statements (GHS US) : H225 - Highly flammable liquid and vapor

H319 - Causes serious eye irritation

Precautionary statements (GHS US) : P210 - Keep away from heat, hot surfaces, ignition sources, open flames, sparks. - No smoking.

P233 - Keep container tightly closed.

P240 - Ground/Bond container and receiving equipment. P241 - Use explosion-proof ventilating equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P264 - Wash hands thoroughly after handling.

P280 - Wear eye protection, face protection, face shield, protective clothing, protective gloves.

Print date: 12/22/2023 EN (English US) SDS ID: **SIC2568.0** 1/9

Safety Data Sheet

P303+P361+P353 - If on skin (or hair): take off immediately all contaminated clothing. rinse skin with water/shower

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing

P337+P313 - If eye irritation persists: Get medical advice/attention.

P370+P378 - In case of fire: Use Water spray, carbon dioxide (CO2), foam, dry extinguishing

powder to extinguish.

P403+P235 - Keep in a cool place

P501 - Dispose of contents/container to licensed waste disposal facility...

2.3. Hazards not otherwise classified (HNOC)

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Substance type : Mono-constituent

Name : CYCLOTRIMETHYLENEDICHLOROSILANE

CAS-No. : 2351-33-9

Name	Product identifier	%	GHS US classification
Silacyclobutane, 1,1-dichloro-	CAS-No.: 2351-33-9	> 97	Flam. Liq. 2, H225
			Eye Irrit. 2A, H319

Full text of hazard classes and H-statements : see section 16

3.2. Mixtures

Not applicable

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available

show packaging or label.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel

unwell, seek medical advice.

First-aid measures after skin contact : Wash with plenty of soap and water. Get immediate medical advice/attention.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get immediate medical advice/attention.

First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel

unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : May cause irritation to the respiratory tract.

Symptoms/effects after skin contact : May cause skin irritation.

Symptoms/effects after eye contact : Causes eye irritation.

Symptoms/effects after ingestion : May be harmful if swallowed.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

Print date: 12/22/2023 EN (English US) SDS ID: **SIC2568.0** 2/9

Safety Data Sheet

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Foam. Carbon dioxide. Dry chemical.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : Flammable liquid and vapor. Irritating fumes of hydrogen chloride and organic acid vapors may

develop when material is exposed to elevated temperatures or open flame.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Exercise caution when fighting any chemical fire.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Avoid

all eye and skin contact and do not breathe vapor and mist.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use special care to avoid static electric charges. Eliminate every possible source of ignition.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or

shovel spills into appropriate container for disposal. Use only non-sparking tools.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.

Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapor and mist. Provide good ventilation in

process area to prevent accumulation of vapors. Containers must be properly grounded before

beginning transfer. Use only non-sparking tools.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Keep container tightly closed.

Incompatible materials : Acids. Alcohols. Oxidizing agent. Moisture. Water. Storage area : Store in a well-ventilated place. Store away from heat.

Print date: 12/22/2023 EN (English US) SDS ID: **SIC2568.0** 3/9

Safety Data Sheet

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Hand protection:

Neoprene or nitrile rubber gloves

Eye protection:

Chemical goggles or face shield. Contact lenses should not be worn

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified combination organic vapor/acid gas (yellow cartridge) respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Clear.
Molecular mass : 141.07 g/mol
Color : Straw.

Odor : Acrid. Similar to hydrogen chloride.

Odor threshold : No data available pH : No data available Relative evaporation rate (butyl acetate=1) : No data available Melting point : No data available

Freezing point : <0 °C
Boiling point : 113 – 114 °C
Flash point : 9 °C

Auto-ignition temperature : No data available Decomposition temperature : No data available

Flammability (solid, gas) : Highly flammable liquid and vapor.

Vapor pressure : No data available Relative vapor density at 20°C : No data available

Relative density : 1.201

Solubility Reacts with water. Partition coefficient n-octanol/water (Log Pow) No data available Partition coefficient n-octanol/water (Log Kow) No data available No data available Viscosity, kinematic : No data available Viscosity, dynamic Explosive properties No data available Oxidizing properties No data available **Explosion limits** No data available

9.2. Other information

No additional information available

Print date: 12/22/2023 EN (English US) SDS ID: **SIC2568.0** 4/9

Safety Data Sheet

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable in sealed containers stored under a dry inert atmosphere.

10.3. Possibility of hazardous reactions

Reacts with water and moisture in air, liberating hydrogen chloride.

10.4. Conditions to avoid

Heat. Open flame. Sparks.

10.5. Incompatible materials

Acids. Alcohols. Oxidizing agent. Moisture. Water.

10.6. Hazardous decomposition products

Hydrogen chloride. Organic acid vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified
Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Not classified
STOT-repeated exposure : Not classified
Aspiration hazard : Not classified

Symptoms/effects after inhalation : May cause irritation to the respiratory tract.

Symptoms/effects after skin contact : May cause skin irritation.

Symptoms/effects after eye contact : Causes eye irritation.

Symptoms/effects after ingestion : May be harmful if swallowed.

Reason for classification : Expert judgment

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

Print date: 12/22/2023 EN (English US) SDS ID: **SIC2568.0** 5/9

Safety Data Sheet

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other adverse effects : This substance may be hazardous to the environment.

Effect on the ozone layer : No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of

contents/container to licensed waste disposal facility..

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecological information : Avoid release to the environment.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG		IATA	
14.1. UN number					
2985	Not applicable	2985		2985	
14.2. Proper Shipping Name					
Chlorosilanes, flammable, corrosive, n.o.s.	Not applicable		CHLOROSILANES, FLAMMABLE, CORROSIVE, N.O.S.	Chlorosilanes, flammable, corrosive, n.o.s.	
Transport document description					
UN2985 Chlorosilanes, flammable, corrosive, n.o.s., 3 (8), II	Not applicable		UN 2985 CHLOROSILANES, FLAMMABLE, CORROSIVE, N.O.S., 3 (8), II	UN 2985 Chlorosilanes, flammable, corrosive, n.o.s., 3 (8), II	
14.3. Transport hazard class(es)					
3 (8)	Not applicable		3 (8)	3 (8)	
FLAMMABLE LIQUID CORROSIVE 8	Not applicable		3 8	3 8	
14.4. Packing group					
II	Not applicable		II	II	
14.5. Environmental hazards					
Dangerous for the environment: No	Dangerous for the environ	ment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	
No supplementary information available				1	

14.6. Special precautions for user

DOT

UN-No.(DOT) : UN2985

Print date: 12/22/2023 EN (English US) SDS ID: **SIC2568.0** 6/9

Safety Data Sheet

DOT Special Provisions (49 CFR 172.102) : T14 - 6 6 mm Prohibited 178.275(q)(3).

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

TP7 - The vapor space must be purged of air by nitrogen or other means.

TP13 - Self-contained breathing apparatus must be provided when this hazardous material is

transported by sea.

TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : none
DOT Packaging Non Bulk (49 CFR 173.xxx) : 206
DOT Packaging Bulk (49 CFR 173.xxx) : 243
DOT Quantity Limitations Passenger aircraft/rail (49 : Forbidden

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 5 L

CFR 175.75)

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this

section is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

TDG

Emergency Response Guide (ERG) Number : 155

IMDG

 Limited quantities (IMDG)
 : 0

 Excepted quantities (IMDG)
 : E0

 Packing instructions (IMDG)
 : P010

 Tank instructions (IMDG)
 : T14

Tank special provisions (IMDG) : TP2, TP7, TP13, TP27

EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS EmS-No. (Spillage) : S-C - SPILLAGE SCHEDULE Charlie - FLAMMABLE CORROSIVE LIQUIDS

Stowage category (IMDG) : B
Stowage and handling (IMDG) : SW2

Properties and observations (IMDG) : White or slightly yellowish deliquescent crystals or sticks. Soluble in water. Mixtures with

combustible material are readily ignited and may burn fiercely. Mixtures with ammonium

compounds or cyanides may explode. Harmful if swallowed.

IATA

PCA Excepted quantities (IATA) E0 PCA Limited quantities (IATA) Forbidden PCA limited quantity max net quantity (IATA) : Forbidden PCA packing instructions (IATA) : Forbidden Forbidden PCA max net quantity (IATA) CAO packing instructions (IATA) 377 51 CAO max net quantity (IATA) . ERG code (IATA) 3C

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

Print date: 12/22/2023 EN (English US) SDS ID: **SIC2568.0** 7/9

Safety Data Sheet

SECTION 15: Regulatory information

15.1. US Federal regulations

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

Name	CAS-No.	Listing	Commercial status	Flags
Silacyclobutane, 1,1-dichloro-	2351-33-9	Present	Active	

15.2. International regulations

CANADA

Silacyclobutane, 1,1-dichloro- (2351-33-9)

Listed on the Canadian NDSL (Non-Domestic Substances List)

EU-Regulations

Silacyclobutane, 1,1-dichloro- (2351-33-9)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

Silacyclobutane, 1,1-dichloro- (2351-33-9)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

Full text of H-phrases::

1 0	ext of Figure 200	
	H225	Highly flammable liquid and vapor
	H319	Causes serious eve irritation

Abbreviations and acronyms

: Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemcial Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor.

Hazard Rating

Health

: 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

Flammability

: 4 Severe Hazard - Flammable gases, or very volatile flammable liquids with flash points below 73 F, and boiling points below 100 F. Materials may ignite spontaneously with air. (Class IA)

Physical

: 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.

Prepared by safety and environmental affairs.

 Print date: 12/22/2023
 EN (English US)
 SDS ID: SIC2568.0
 8/9

Safety Data Sheet


Issue date: 06/15/2015 Revision date: 11/22/2023 Version: 2.1

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2023 Gelest Inc. Morrisville, PA 19067



Print date: 12/22/2023 EN (English US) SDS ID: **SIC2568.0** 9/9