

**DI-t-BUTYLDIFLUOROSILANE**

Safety Data Sheet SID3207.0

Date of issue: 17/09/2015      Version: 1.0

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product form	: Substance
Physical state	: Liquid
Substance name	: DI-t-BUTYLDIFLUOROSILANE
Product code	: SID3207.0
Formula	: C <sub>8</sub> H <sub>18</sub> F <sub>2</sub> Si
Synonyms	: DIFLUORODI-t-BUTYLSILANE
Chemical family	: ORGANOFLUOROSILANE

**1.2. Relevant identified uses of the substance or mixture and uses advised against****1.2.1. Relevant identified uses**

Use of the substance/mixture : Chemical intermediate

**1.2.2. Uses advised against**

No additional information available

**1.3. Details of the supplier of the safety data sheet****GELEST, INC.**11 East Steel Road  
Morrisville, PA 19067**USA**

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

[info@gelest.com](mailto:info@gelest.com) - [www.gelest.com](http://www.gelest.com)**GELEST INC.**Fritz-Klatte-Strasse 8  
65933 Frankfurt**Germany**

T +49 (0) 69 3535106-500 - F +49 (0) 69 3535106-501 - (M-F): 8:00 AM - 4:00 PM

[info@gelestde.com](mailto:info@gelestde.com) - [www.gelestde.com](http://www.gelestde.com)**1.4. Emergency telephone number**

Emergency number : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Flammable liquids, Category 3	H226
Skin corrosion/irritation, Category 1B	H314
Serious eye damage/eye irritation, Category 1	H318
Full text of H statements : see section 16	

**Adverse physicochemical, human health and environmental effects**

No additional information available

**2.2. Label elements****Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP) :



GHS02

GHS05

Signal word (CLP) :

: Danger

Hazard statements (CLP) :

: H226 - Flammable liquid and vapour.  
H314 - Causes severe skin burns and eye damage.

# DI-t-BUTYLDIFLUOROSILANE

## Safety Data Sheet

Precautionary statements (CLP) : P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P240 - Ground/bond container and receiving equipment.  
P260 - Do not breathe vapours.  
P264 - Wash hands thoroughly after handling.  
P310 - Immediately call a POISON CENTER or doctor/physician

### 2.3. Other hazards

Other hazards not contributing to the classification : Hydrogen fluoride may be formed by reaction with water and moisture in air. The US OSHA PEL (TWA) for hydrogen fluoride is 3 ppm.

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Substance type : Mono-constituent  
Name : DI-t-BUTYLDIFLUOROSILANE  
CAS-No. : 558-63-4

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Di-t-butylidifluorosilane	(CAS-No.) 558-63-4	95 - 100	Flam. Liq. 3, H226 Skin Corr. 1B, H314 Eye Dam. 1, H318

Full text of H-statements: see section 16

### 3.2. Mixtures

Not applicable

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label. IF exposed or concerned: Get medical advice/attention.  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If you feel unwell, seek medical advice.  
First-aid measures after skin contact : Flush with water, then wash with saturated solution of sodium carbonate or 3% aqueous ammonia. Get immediate medical advice/attention.  
First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.  
First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Causes severe skin burns and eye damage.  
Symptoms/effects after inhalation : May cause irritation to the respiratory tract.  
Symptoms/effects after skin contact : Causes (severe) skin burns.  
Symptoms/effects after eye contact : Causes serious eye damage.  
Symptoms/effects after ingestion : May be harmful if swallowed.  
Symptoms/effects upon intravenous administration : For ingestion, calcium gluconate intravenously and calcium lactate orally may be considered.  
Chronic symptoms : Hydrofluoric acid, the hydrolysis product has demonstrated mutagenicity and teratogenicity in laboratory bioassay.

### 4.3. Indication of any immediate medical attention and special treatment needed

NOTE TO PHYSICIAN: This product reacts with water and human tissues to form hydrofluoric acid. Massage a paste of 20% magnesium oxide in glycerol onto the burned areas. Inject 2-5 cc of 10% calcium gluconate beneath and around the burned areas. Gastric lavage, if swallowed, using 5% calcium chloride followed by saline catharsis.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Foam. Carbon dioxide. Dry chemical.  
Unsuitable extinguishing media : Do not use straight streams.

# DI-t-BUTYLDIFLUOROSILANE

## Safety Data Sheet

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapour. Irritating fumes, hydrogen fluoride and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.

### 5.3. Advice for firefighters

Firefighting instructions : Use water spray to cool exposed surfaces. Exercise caution when fighting any chemical fire.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Avoid all eye and skin contact and do not breathe vapour and mist.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Eliminate ignition sources. Use special care to avoid static electric charges.

#### 6.1.1. For non-emergency personnel

Protective equipment : Wear protective equipment as described in Section 8.

Emergency procedures : Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or shovel spills into appropriate container for disposal. Use only non-sparking tools.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapour and mist. Provide good ventilation in process area to prevent formation of vapour. Ground/bond container and receiving equipment. Take precautionary measures against static discharge. Use only non-sparking tools.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Use explosion-proof electrical equipment.

Storage conditions : Keep container tightly closed. Keep in a cool place. Store locked up. Store in sealed chemically resistant plastic containers.

Incompatible materials : Moisture. Water.

Storage area : Store in a well-ventilated place. Store away from heat.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

No additional information available

### 8.2. Exposure controls

#### Appropriate engineering controls:

Provide local exhaust or general room ventilation.

#### Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

#### Hand protection:

# DI-t-BUTYLDIFLUOROSILANE

## Safety Data Sheet

Neoprene or nitrile rubber gloves

### Eye protection:

Chemical goggles or face shield. Contact lenses should not be worn

### Skin and body protection:

Wear suitable protective clothing

### Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified combination organic vapor/acid gas (yellow cartridge) respirator.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear liquid.
Molecular mass	: 180.31 g/mol
Colour	: Straw.
Odour	: Acrid.
Odour threshold	: No data available
Refractive index	: No additional information available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: < 0 °C
Boiling point	: 134 °C
Flash point	: < 60 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Flammable liquid and vapour.
Vapour pressure	: < 10 mm Hg @ 20°C
Relative vapour density at 20 °C	: > 1
Relative density	: 0.896
Solubility	: Insoluble in water. Reacts with water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Stable in sealed plastic containers.

### 10.3. Possibility of hazardous reactions

Reacts with water and moisture in air liberating hydrogen fluoride.

### 10.4. Conditions to avoid

Heat. Open flame. Sparks.

### 10.5. Incompatible materials

Moisture. Water.

### 10.6. Hazardous decomposition products

Hydrogen fluoride. Organic acid vapors.

# DI-t-BUTYLDIFLUOROSILANE

## Safety Data Sheet

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation	: Causes severe skin burns and eye damage.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Potential adverse human health effects and symptoms	: On contact with water and human tissue this compound liberates hydrogen fluoride (hydrofluoric acid).
Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: Causes (severe) skin burns.
Symptoms/effects after eye contact	: Causes serious eye damage.
Symptoms/effects after ingestion	: May be harmful if swallowed.
Symptoms/effects upon intravenous administration	: For ingestion, calcium gluconate intravenously and calcium lactate orally may be considered.
Chronic symptoms	: Hydrofluoric acid, the hydrolysis product has demonstrated mutagenicity and teratogenicity in laboratory bioassay.
Reason for classification	: Expert judgment

### SECTION 12: Ecological information

#### 12.1. Toxicity

Acute aquatic toxicity	: Not classified
Chronic aquatic toxicity	: Not classified

#### 12.2. Persistence and degradability

No additional information available

#### 12.3. Bioaccumulative potential

No additional information available

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Results of PBT and vPvB assessment

No additional information available

#### 12.6. Other adverse effects

Other adverse effects : This substance may be hazardous to the environment.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Sewage disposal recommendations	: Do not dispose of waste into sewer.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to licensed waste disposal facility.
Ecology - waste materials	: Avoid release to the environment.

### SECTION 14: Transport information

#### 14.1. UN number

In accordance with ADR / RID / IMDG / IATA / ADN

#### 14.1. UN number

UN-No. (ADR)	: 2920
UN-No. (IMDG)	: 2920
UN-No. (IATA)	: 2920
UN-No. (ADN)	: 2920
UN-No. (RID)	: 2920

# DI-t-BUTYLDIFLUOROSILANE

## Safety Data Sheet

### 14.2. UN proper shipping name

Proper Shipping Name (ADR)	: CORROSIVE LIQUID, FLAMMABLE, N.O.S.
Proper Shipping Name (IMDG)	: CORROSIVE LIQUID, FLAMMABLE, N.O.S.
Proper Shipping Name (IATA)	: Corrosive liquid, flammable, n.o.s.
Proper Shipping Name (ADN)	: CORROSIVE LIQUID, FLAMMABLE, N.O.S.
Proper Shipping Name (RID)	: CORROSIVE LIQUID, FLAMMABLE, N.O.S.
Transport document description (ADR)	: UN 2920 CORROSIVE LIQUID, FLAMMABLE, N.O.S. (DI-t-BUTYLDIFLUOROSILANE), 8 (3), II, (D/E)
Transport document description (IMDG)	: UN 2920 CORROSIVE LIQUID, FLAMMABLE, N.O.S. (DI-t-BUTYLDIFLUOROSILANE), 8 (3), II
Transport document description (IATA)	: UN 2920 Corrosive liquid, flammable, n.o.s. (DI-t-BUTYLDIFLUOROSILANE), 8 (3), II
Transport document description (ADN)	: UN 2920 CORROSIVE LIQUID, FLAMMABLE, N.O.S. (DI-t-BUTYLDIFLUOROSILANE), 8 (3), II
Transport document description (RID)	: UN 2920 CORROSIVE LIQUID, FLAMMABLE, N.O.S. (DI-t-BUTYLDIFLUOROSILANE), 8 (3), II

### 14.3. Transport hazard class(es)

#### ADR

Transport hazard class(es) (ADR)	: 8 (3)
Danger labels (ADR)	: 8, 3



#### IMDG

Transport hazard class(es) (IMDG)	: 8 (3)
Danger labels (IMDG)	: 8, 3



#### IATA

Transport hazard class(es) (IATA)	: 8 (3)
Hazard labels (IATA)	: 8, 3



#### ADN

Transport hazard class(es) (ADN)	: 8 (3)
Danger labels (ADN)	: 8, 3



#### RID

Transport hazard class(es) (RID)	: 8 (3)
Danger labels (RID)	: 8, 3



# DI-t-BUTYLDIFLUOROSILANE

## Safety Data Sheet



### 14.4. Packing group

Packing group (ADR)	: II
Packing group (IMDG)	: II
Packing group (IATA)	: II
Packing group (ADN)	: II
Packing group (RID)	: II

### 14.5. Environmental hazards

Dangerous for the environment	: No
Marine pollutant	: No
Other information	: No supplementary information available

### 14.6. Special precautions for user

#### - Overland transport

Classification code (ADR)	: CF1
Special provisions (ADR)	: 274
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E2
Packing instructions (ADR)	: P001, IBC02
Mixed packing provisions (ADR)	: MP15
Portable tank and bulk container instructions (ADR)	: T11
Portable tank and bulk container special provisions (ADR)	: TP2, TP27
Tank code (ADR)	: L4BN
Vehicle for tank carriage	: FL
Transport category (ADR)	: 2
Special provisions for carriage - Operation (ADR)	: S2
Hazard identification number (Kemler No.)	: 83
Orange plates	:



Tunnel restriction code (ADR)	: D/E
-------------------------------	-------

#### - Transport by sea

Special provisions (IMDG)	: 274
Limited quantities (IMDG)	: 1 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T11
Tank special provisions (IMDG)	: TP2, TP27
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-C
Stowage category (IMDG)	: C
Stowage and handling (IMDG)	: SW1, SW2
Properties and observations (IMDG)	: Causes burns to skin, eyes and mucous membranes.

#### - Air transport

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y840
PCA limited quantity max net quantity (IATA)	: 0.5L
PCA packing instructions (IATA)	: 851

# DI-t-BUTYLDIFLUOROSILANE

## Safety Data Sheet

PCA max net quantity (IATA) : 1L  
CAO packing instructions (IATA) : 855  
CAO max net quantity (IATA) : 30L  
ERG code (IATA) : 8F

### - Inland waterway transport

Classification code (ADN) : CF1  
Special provisions (ADN) : 274  
Limited quantities (ADN) : 1 L  
Excepted quantities (ADN) : E2  
Carriage permitted (ADN) : T  
Equipment required (ADN) : PP, EP, EX, A  
Ventilation (ADN) : VE01  
Number of blue cones/lights (ADN) : 1

### - Rail transport

Classification code (RID) : CF1  
Special provisions (RID) : 274  
Limited quantities (RID) : 1L  
Excepted quantities (RID) : E2  
Packing instructions (RID) : P001, IBC02  
Mixed packing provisions (RID) : MP15  
Portable tank and bulk container instructions (RID) : T11  
Portable tank and bulk container special provisions (RID) : TP2, TP27  
Tank codes for RID tanks (RID) : L4BN  
Transport category (RID) : 2  
Colis express (express parcels) (RID) : CE6  
Hazard identification number (RID) : 83

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

No REACH Annex XVII restrictions

DI-t-BUTYLDIFLUOROSILANE is not on the REACH Candidate List

DI-t-BUTYLDIFLUOROSILANE is not on the REACH Annex XIV List

DI-t-BUTYLDIFLUOROSILANE is not subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL OF 4 July 2012 concerning the export and import of hazardous chemicals.

DI-t-BUTYLDIFLUOROSILANE is not subject to Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Directive 79/117/EEC

#### 15.1.2. National regulations

##### Germany

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

##### Netherlands

SZW-lijst van kankerverwekkende stoffen : The substance is not listed

SZW-lijst van mutagene stoffen : The substance is not listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : The substance is not listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : The substance is not listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : The substance is not listed

##### Denmark



# DI-t-BUTYLDIFLUOROSILANE

## Safety Data Sheet

Class for fire hazard	: Class III-1
Store unit	: 50 liter
Classification remarks	: Flammable according to the Danish Ministry of Justice; Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations	: Young people below the age of 18 years are not allowed to use the product

### 15.2. Chemical safety assessment

No additional information available

## SECTION 16: Other information

Abbreviations and acronyms:

Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor

Other information : Prepared by safety and environmental affairs.

Full text of H- and EUH-statements:

Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Flam. Liq. 3	Flammable liquids, Category 3
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
H226	Flammable liquid and vapour.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.

SDS EU (REACH Annex II) - Custom

*The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.*

© 2019 Gelest Inc. Morrisville, PA 19067