

**DI-t-BUTYLISOBUTYLSILANE**

Safety Data Sheet SID3224.0

Date of issue: 01/07/2016 Version: 1.0

SECTION 1: Identification**1.1. Identification**

Product name : DI-t-BUTYLISOBUTYLSILANE
 Product code : SID3224.0
 Product form : Substance
 Physical state : Liquid
 Formula : C₁₂H₂₈Si
 Synonyms : ISOBUTYLDI-t-BUTYLSILYLHYDRIDE
 Chemical family : ORGANOHYDRIDOSILANE

1.2. Recommended use and restrictions on use

Recommended use : Chemical intermediate

1.3. Supplier**GELEST, INC.**

11 East Steel Road
 Morrisville, PA 19067

USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

SECTION 2: Hazard(s) identification**2.1. Classification of the substance or mixture****GHS-US classification**

Flammable liquids Category 4 H227 Combustible liquid

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements**GHS US labeling**

Signal word (GHS US) : Warning
 Hazard statements (GHS US) : H227 - Combustible liquid
 Precautionary statements (GHS US) : P280 - Wear protective gloves/protective clothing/eye protection/face protection.
 P210 - Keep away from heat, open flames, sparks. - No smoking.
 P370+P378 - In case of fire: Use water spray or fog, foam, carbon dioxide, dry chemical to extinguish.
 P403+P235 - Keep in a cool place
 P501 - Dispose of contents/container to licensed waste disposal facility.

2.3. Hazards not otherwise classified (HNOC)

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients**3.1. Substances**

Substance type : Mono-constituent
 Name : DI-t-BUTYLISOBUTYLSILANE
 CAS-No. : 1314639-85-4

Name	Product identifier	%	GHS-US classification
Di-t-butylisobutylsilane	(CAS-No.) 1314639-85-4	95 - 100	Flam. Liq. 4, H227

Full text of hazard classes and H-statements : see section 16

3.2. Mixtures

Not applicable

DI-t-BUTYLISOBUTYLSILANE

Safety Data Sheet

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.
First-aid measures after skin contact	: Wash with plenty of soap and water. Get medical advice/attention.
First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
First-aid measures after ingestion	: Never give anything by mouth to an unconscious person. Get medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: No information available.
Symptoms/effects after skin contact	: May cause skin irritation.
Symptoms/effects after eye contact	: May cause eye irritation.
Symptoms/effects after ingestion	: No information available.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Water fog. Foam. Carbon dioxide. Dry chemical.
Unsuitable extinguishing media	: None known.

5.2. Specific hazards arising from the chemical

Fire hazard	: Combustible liquid. Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.
-------------	---

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection. Avoid all eye and skin contact and do not breathe vapor and mist.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment	: Wear protective equipment as described in Section 8.
Emergency procedures	: Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	--

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up	: Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or shovel spills into appropriate container for disposal.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Precautions for safe handling	: Avoid all eye and skin contact and do not breathe vapor and mist. Ground/bond container and receiving equipment. Provide good ventilation in process area to prevent accumulation of vapors.
Hygiene measures	: Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

DI-t-BUTYLISOBUTYLSILANE

Safety Data Sheet

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Keep container tightly closed. Keep in a cool place.
Incompatible materials	: Alkalis. Metal salts. Oxidizing agent. Precious metals.
Storage area	: Store in a well-ventilated place. Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Hand protection:

Neoprene or nitrile rubber gloves

Eye protection:

Chemical goggles. Contact lenses should not be worn

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified organic vapor (black cartridge) respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear liquid.
Molecular mass	: 200.44 g/mol
Color	: No data available
Odor	: No data available
Odor threshold	: No data available
Refractive index	: 1.4411
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: ~ 1
Melting point	: < 20 °C
Freezing point	: No data available
Boiling point	: 65 - 70 °C @ 5 mm Hg
Flash point	: > 65 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Combustible liquid
Vapor pressure	: No data available
Relative vapor density at 20 °C	: > 1
Relative density	: 0.788
% Volatiles	: > 95 %
Solubility	: Insoluble in water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available

DI-t-BUTYLISOBUTYLSILANE

Safety Data Sheet

Oxidizing properties : No data available
Explosion limits : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable in sealed containers under dry inert atmosphere.

10.3. Possibility of hazardous reactions

The product can generate small amounts of hydrogen when exposed to alkalis and protic materials such as water and alcohol in combination with metal salts such as aluminum chloride or precious metals such as platinum.

10.4. Conditions to avoid

Heat. Open flame. Sparks.

10.5. Incompatible materials

Alkalis. Metal salts. Oxidizing agent. Precious metals.

10.6. Hazardous decomposition products

Carbon monoxide. Hydrogen. Organic acid vapors. Silicon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified
Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
Specific target organ toxicity – single exposure : Not classified

Specific target organ toxicity – repeated exposure : Not classified

Aspiration hazard : Not classified
Symptoms/effects after inhalation : No information available.
Symptoms/effects after skin contact : May cause skin irritation.
Symptoms/effects after eye contact : May cause eye irritation.
Symptoms/effects after ingestion : No information available.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the ozone layer : No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Sewage disposal recommendations : Do not dispose of waste into sewer.

DI-t-BUTYLISOBUTYLSILANE

Safety Data Sheet

Product/Packaging disposal recommendations : Incinerate. Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to licensed waste disposal facility.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

14.1. UN number

DOT NA no. NA1993

14.2. UN proper shipping name

Transport document description : NA1993 Combustible liquid, n.o.s. (DI-t-BUTYLISOBUTYLSILANE), 3, III

Proper Shipping Name (DOT) : Combustible liquid, n.o.s.
(DI-t-BUTYLISOBUTYLSILANE)

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Packing group (DOT) : III - Minor Danger

DOT Packaging Non Bulk (49 CFR 173.xxx) : 203

DOT Packaging Bulk (49 CFR 173.xxx) : 241

DOT Packaging Exceptions (49 CFR 173.xxx) : 150

DOT Symbols : D - Proper shipping name for domestic use only, or to and from Canada, G - Identifies PSN requiring a technical name

14.3. Additional information

Other information : This product is Combustible as defined by the US Department of Transportation (DOT). It is regulated for transport in the US in container > 119 gallons (450 liters). The product is not regulated for transport by the IATA, ADR/RID, ADNR or the IMDG regulations.

Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 60 L
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L
CFR 175.75)

SECTION 15: Regulatory information

15.1. US Federal regulations

DI-t-BUTYLISOBUTYLSILANE (1314639-85-4)

TSCA Exemption/Exclusion

CAUTION: This material is supplied for research and development purposes subject to the R&D exemption under TSCA, 40 CFR 720.36, and must meet the requirements of the exemption, including supervision by a "technically qualified individual" as defined by 40 CFR 720.3(ee). The use of this material for "commercial purposes" as defined by 40 CFR 720.3(r) is not permitted in the United States.

Di-t-butylisobutylsilane (1314639-85-4)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

DI-t-BUTYLISOBUTYLSILANE

Safety Data Sheet

Full text of H-phrases::

H227

Combustible liquid

Abbreviations and acronyms

: Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor.

Hazard Rating

Health

: 2 Moderate Hazard - Temporary or minor injury may occur

Flammability

: 2 Moderate Hazard - Materials which must be moderately heated or exposed to high ambient temperatures before ignition will occur. Includes liquids having a flash point at or above 100 F but below 200 F. (Classes II & IIIA)

Physical

: 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.

Prepared by safety and environmental affairs.

Date of issue: 01/07/2016 Version: 1.0

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2019 Gelest Inc. Morrisville, PA 19067