

Safety Data Sheet SID3391.0

Date of issue: 11/07/2014 Revision date: 04/12/2014 Version: 1.1

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **Product identifier**

Product form : Substance Physical state : Liquid

: DICYCLOPENTYLDIMETHOXYSILANE Substance name

Product code SID3391 0 Formula C12H24O2Si

: DIMETHOXYDICYCLOPENTYLCYCLOHEXANE Synonyms

Chemical family : ORGANOMETHOXYSILANE

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1 Relevant identified uses

Use of the substance/mixture : Chemical intermediate

#### Uses advised against 1.2.2.

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

#### **GELEST, INC.**

11 East Steel Road Morrisville, PA 19067

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com

#### **GELEST INC.**

Fritz-Klatte-Strasse 8 65933 Frankfurt

#### Germany

T +49 (0) 69 3535106-500 - F +49 (0) 69 3535106-501 - (M-F): 8:00 AM - 4:00 PM

info@gelestde.com - www.gelestde.com

# **Emergency telephone number**

: CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International) **Emergency number** 

#### **SECTION 2: Hazards identification**

#### Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2 H315 Serious eye damage/eye irritation, Category 1 H318 Hazardous to the aquatic environment — Acute Hazard, Category 1 H400 Hazardous to the aquatic environment — Chronic Hazard, Category 1 H410

Full text of H statements: see section 16

#### Adverse physicochemical, human health and environmental effects

No additional information available

#### 22 Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS05



GHS09

Signal word (CLP) Danger

Hazard statements (CLP) H315 - Causes skin irritation.

H318 - Causes serious eye damage.

Print date: 11/04/2019 EN (English) SDS ID: SID3391.0 1/10

# Safety Data Sheet

H410 - Very toxic to aquatic life with long lasting effects.

Precautionary statements (CLP) : P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P264 - Wash hands thoroughly after handling.

P310 - Immediately call a POISON CENTER or doctor/physician

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P302+P352 - IF ON SKIN: Wash with plenty of water.

P273 - Avoid release to the environment.

#### 2.3. Other hazards

Other hazards not contributing to the classification

Note: The hydrolysis product of this product is methanol. Swallowing methanol can cause

drowsiness, unconsciousness, blindness and death.

### **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

Substance type : Multi-constituent

Name : DICYCLOPENTYLDIMETHOXYSILANE

CAS-No. : 126990-35-0 EC-No. : 404-370-8 EC Index-No. : 014-032-00-8

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Dicyclopentyldimethoxysilane	(CAS-No.) 126990-35-0 (EC-No.) 404-370-8 (EC Index-No.) 014-032-00-8	> 95	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Methanol	(CAS-No.) 67-56-1 (EC-No.) 200-659-6 (EC Index-No.) 603-001-00-X	< 0.5	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 STOT SE 1, H370

#### Specific concentration limits:

Name	Product identifier	Specific concentration limits
Methanol	(CAS-No.) 67-56-1 (EC-No.) 200-659-6 (EC Index-No.) 603-001-00-X	( 3 = <c 10)="" 2,="" <="" h371<br="" se="" stot="">( 10 =<c 1,="" 100)="" <="" h370<="" se="" stot="" th=""></c></c>

Full text of H-statements; see section 16

#### 3.2. Mixtures

Not applicable

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not

available show packaging or label.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If you feel unwell, seek medical

advice.

First-aid measures after skin contact : Wash with plenty of water/....

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical advice/attention.

First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Get medical advice/attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : May cause irritation to the respiratory tract. Overexposure may cause: Cough. Headache.

Nausea.

Symptoms/effects after skin contact : Causes skin irritation.

Symptoms/effects after eye contact : Causes serious eye irritation. Symptoms/effects after ingestion : May be harmful if swallowed.

Chronic symptoms : On contact with water this compound liberates methanol which is known to have a chronic

effect on the central nervous system.

Print date: 11/04/2019 EN (English) SDS ID: **SID3391.0** 2/10

# Safety Data Sheet

#### 4.3. Indication of any immediate medical attention and special treatment needed

NOTE TO PHYSICIAN: This product reacts with water in the acid contents of the stomach to form methanol. The combination of visual disturbances, metabolic acidosis and formic acid in urine is evidence of methanol poisoning. The therapeutic intravenous administration of ethanol (10 mls/hour) allows methanol to be preferentially oxidized and reduces production of methanol metabolites. Acidosis must be treated with intravenous administration of sodium bicarbonate and methanol elimination may be increased by hemodialysis, as indicated. Treatment should be based on blood methanol levels and acid-base balance.

### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Foam. Carbon dioxide. Dry chemical.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Irritating fumes and organic acid vapors may develop when material is exposed to elevated

temperatures or open flame.

#### 5.3. Advice for firefighters

Firefighting instructions : Use water spray to cool exposed surfaces. Exercise caution when fighting any chemical fire.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Avoid all eye and skin contact and do not breathe vapour and mist.

## **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or

shovel spills into appropriate container for disposal.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

#### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapour and mist. Provide good ventilation in

process area to prevent formation of vapour.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container tightly closed.

Incompatible materials : Moisture. Water :

Storage area : Store in a well-ventilated place. Store away from heat.

#### 7.3. Specific end use(s)

No additional information available

## **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

Methanol (67-56-1)		
EU	IOELV TWA (mg/m³)	260 mg/m³
EU	IOELV TWA (ppm)	200 ppm
Austria	MAK (mg/m³)	260 mg/m³
Austria	MAK (ppm)	200 ppm
Austria	MAK Short time value (mg/m³)	1040 mg/m³
Austria	MAK Short time value (ppm)	800 ppm
Belgium	Limit value (mg/m³)	266 mg/m³
Belgium	Limit value (ppm)	200 ppm
Belgium	Short time value (mg/m³)	333 mg/m³
Belgium	Short time value (ppm)	250 ppm
Bulgaria	OEL TWA (mg/m³)	260 mg/m³

Print date: 11/04/2019 EN (English) SDS ID: **SID3391.0** 3/10

Safety Data Sheet

Methanol (67-56-1)		
Bulgaria	OEL TWA (ppm)	200 ppm
Cyprus	OEL TWA (mg/m³)	260 mg/m³
Cyprus	OEL TWA (ppm)	200 ppm
France	VLE (mg/m³)	1300 mg/m³
France	VLE (ppm)	1000 ppm
France	VME (mg/m³)	260 mg/m³ (restrictive limit)
France	VME (ppm)	200 ppm (restrictive limit)
Germany	TRGS 900 Occupational exposure limit value (mg/m³)	270 mg/m³ (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Germany	TRGS 900 Occupational exposure limit value (ppm)	200 ppm (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Germany	TRGS 903 Biological limit value	30 mg/l (Medium: urine - Time: end of shift - Parameter: Methanol) 30 mg/l (Medium: urine - Time: end of several shifts - Parameter: Methanol (for long-term exposures)
Gibraltar	Eight hours mg/m3	260 mg/m³
Gibraltar	Eight hours ppm	200 ppm
Greece	OEL TWA (mg/m³)	260 mg/m³
Greece	OEL TWA (ppm)	200 ppm
Greece	OEL STEL (mg/m³)	325 mg/m³
Greece	OEL STEL (ppm)	250 ppm
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	200 ppm
Italy - Portugal - USA ACGIH	ACGIH STEL (ppm)	250 ppm
Italy	OEL TWA (mg/m³)	260 mg/m <sup>3</sup>
Italy	OEL TWA (ppm)	200 ppm
Latvia	OEL TWA (mg/m³)	260 mg/m³
Latvia	OEL TWA (ppm)	200 ppm
USA IDLH	US IDLH (ppm)	6000 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m³)	260 mg/m³
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m³)	325 mg/m³
USA NIOSH	NIOSH REL (STEL) (ppm)	250 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	260 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
Spain	VLA-ED (mg/m³)	266 mg/m³ (indicative limit value)
Spain	VLA-ED (ppm)	200 ppm (indicative limit value)
Switzerland	KZGW (mg/m³)	1040 mg/m³
Switzerland	KZGW (ppm)	800 ppm
Switzerland	MAK (mg/m³)	260 mg/m³
Switzerland	MAK (ppm)	200 ppm
Netherlands	Grenswaarde TGG 8H (mg/m³)	133 mg/m³
Netherlands	Grenswaarde TGG 8H (ppm)	100 ppm
United Kingdom	WEL TWA (mg/m³)	266 mg/m³
United Kingdom	WEL TWA (ppm)	200 ppm
United Kingdom	WEL STEL (mg/m³)	333 mg/m³
United Kingdom	WEL STEL (ppm)	250 ppm
Czech Republic	Expoziční limity (PEL) (mg/m³)	250 mg/m³
Denmark	Grænseværdie (langvarig) (mg/m³)	260 mg/m³
Denmark	Grænseværdie (langvarig) (ppm)	200 ppm
Finland	HTP-arvo (8h) (mg/m³)	270 mg/m³
Finland	HTP-arvo (8h) (ppm)	200 ppm
Finland	HTP-arvo (15 min)	330 mg/m³
Finland	HTP-arvo (15 min) (ppm)  AK-érték	250 ppm 260 mg/m³
Hungary	AL-GIEK	260 mg/m³

Print date: 11/04/2019 EN (English) SDS ID: **SID3391.0** 4/10

# Safety Data Sheet

Methanol (67-56-1)		
Ireland	OEL (8 hours ref) (mg/m³)	260 mg/m³
Ireland	OEL (8 hours ref) (ppm)	200 ppm
Ireland	OEL (15 min ref) (mg/m3)	780 mg/m³ (calculated)
Ireland	OEL (15 min ref) (ppm)	600 ppm (calculated)
Lithuania	IPRV (mg/m³)	260 mg/m³
Lithuania	IPRV (ppm)	200 ppm
Malta	OEL TWA (mg/m³)	260 mg/m³
Malta	OEL TWA (ppm)	200 ppm
Norway	Grenseverdier (AN) (mg/m³)	130 mg/m³
Norway	Grenseverdier (AN) (ppm)	100 ppm
Norway	Grenseverdier (Korttidsverdi) (mg/m3)	130 mg/m³
Norway	Grenseverdier (Korttidsverdi) (ppm)	100 ppm
Poland	NDS (mg/m³)	100 mg/m³
Poland	NDSCh (mg/m³)	300 mg/m³
Romania	OEL TWA (mg/m³)	260 mg/m³
Romania	OEL TWA (ppm)	200 ppm
Romania	OEL STEL (ppm)	5 ppm
Slovakia	NPHV (priemerná) (mg/m³)	260 mg/m³
Slovakia	NPHV (priemerná) (ppm)	200 ppm
Sweden	nivågränsvärde (NVG) (mg/m³)	250 mg/m³
Sweden	nivågränsvärde (NVG) (ppm)	200 ppm
Sweden	kortidsvärde (KTV) (mg/m³)	350 mg/m³
Sweden	kortidsvärde (KTV) (ppm)	250 ppm
Canada (Quebec)	VECD (mg/m³)	328 mg/m³
Canada (Quebec)	VECD (ppm)	250 ppm
Canada (Quebec)	VEMP (mg/m³)	262 mg/m³
Canada (Quebec)	VEMP (ppm)	200 ppm
Australia	TWA (mg/m³)	262 mg/m³
Australia	TWA (ppm)	200 ppm
Australia	STEL (mg/m³)	328 mg/m³
Australia	STEL (ppm)	250 ppm
Portugal	OEL TWA (mg/m³)	260 mg/m³ (indicative limit value)
Portugal	OEL TWA (ppm)	200 ppm (indicative limit value)
Portugal	OEL STEL (ppm)	250 ppm
Portugal	OEL chemical category (PT)	skin - potential for cutaneous exposure indicative limit value

### 8.2. Exposure controls

## Appropriate engineering controls:

Provide local exhaust or general room ventilation.

#### Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

### Hand protection:

Neoprene or nitrile rubber gloves

# Eye protection:

Chemical goggles. Contact lenses should not be worn

### Skin and body protection:

Wear suitable protective clothing

# Respiratory protection:

NIOSH-certified organic vapor (black cartridge) respirator.

Print date: 11/04/2019 EN (English) SDS ID: **SID3391.0** 5/10

# Safety Data Sheet

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Clear liquid.
Molecular mass : 228.4 g/mol
Colour : Straw.
Odour : Mild.

Odour threshold : No data available

Refractive index : 1.4663

pH : No data available Relative evaporation rate (butylacetate=1) : No data available Melting point : No data available

Freezing point : < 0 °C

Boiling point :  $120 \, ^{\circ}\text{C} \, @ \, 6 \, \text{mm Hg}$ 

Flash point : 102 °C
Auto-ignition temperature : 235 °C

Decomposition temperature : No data available
Flammability (solid, gas) : No data available
Vapour pressure : < 1 mm Hg @ 25°C

Relative vapour density at 20 °C : > 1
Relative density : 1

Solubility : Insoluble in water. Reacts with water.

Log Pow : No data available
Log Kow : No data available

Viscosity, kinematic : 2.5 cSt

Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidising properties : No data available
Explosive limits : No data available

# 9.2. Other information

No additional information available

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No additional information available

#### 10.2. Chemical stability

Stable in sealed containers.

#### 10.3. Possibility of hazardous reactions

Reacts with water and moisture in air, liberating methanol.

#### 10.4. Conditions to avoid

Heat. Open flame. Sparks.

### 10.5. Incompatible materials

Moisture. Water:

#### 10.6. Hazardous decomposition products

Methanol. Organic acid vapors.

### **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

Acute toxicity : Not classified

Methanol (67-56-1)		
LC50 inhalation rat (ppm)	22500 ppm (Exposure time: 8 h)	
ATE CLP (oral)	100 mg/kg bodyweight	
ATE CLP (dermal)	300 mg/kg bodyweight	
ATE CLP (vapours)	3 mg/l/4h	
Dicyclopentyldimethoxysilane (126990-35-0)		
LD50 oral rat	> 2000 mg/kg	

Print date: 11/04/2019 EN (English) SDS ID: **SID3391.0** 6/10

# Safety Data Sheet

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Not classified
STOT-repeated exposure : Not classified
Aspiration hazard : Not classified

Symptoms/effects after inhalation : May cause irritation to the respiratory tract. Overexposure may cause: Cough. Headache.

Nausea.

Symptoms/effects after skin contact : Causes skin irritation.

Symptoms/effects after eye contact : Causes serious eye irritation.

Symptoms/effects after ingestion : May be harmful if swallowed.

Chronic symptoms : On contact with water this compound liberates methanol which is known to have a chronic

effect on the central nervous system.

Reason for classification : Expert judgment

### **SECTION 12: Ecological information**

#### 12.1. Toxicity

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

Methanol (67-56-1)	
LC50 fish 1	28200 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

#### 12.2. Persistence and degradability

No additional information available

#### 12.3. Bioaccumulative potential

Methanol (67-56-1)	
BCF fish 1	< 10
Log Pow	-0.77

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

Other adverse effects : This substance may be hazardous to the environment.

# **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

Product/Packaging disposal recommendations : May be incinerated. Dispose in a safe manner in accordance with local/national regulations.

Ecology - waste materials : Avoid release to the environment.

### **SECTION 14: Transport information**

#### 14.1. UN number

In accordance with ADR / RID / IMDG / IATA / ADN

#### 14.1. UN number

UN-No. (ADR) : Not applicable
UN-No. (IMDG) : Not applicable
UN-No. (IATA) : Not applicable
UN-No. (ADN) : Not applicable
UN-No. (RID) : Not applicable

## 14.2. UN proper shipping name

Proper Shipping Name (ADR) : Not applicable
Proper Shipping Name (IMDG) : Not applicable

Print date: 11/04/2019 EN (English) SDS ID: **SID3391.0** 7/10

# Safety Data Sheet

Proper Shipping Name (IATA) : Not applicable
Proper Shipping Name (ADN) : Not applicable
Proper Shipping Name (RID) : Not applicable

# 14.3. Transport hazard class(es)

#### ADR

Transport hazard class(es) (ADR) : Not applicable

\*\*\*

#### **IMDG**

Transport hazard class(es) (IMDG) : Not applicable



#### IATA

Transport hazard class(es) (IATA) : Not applicable



#### ADN

Transport hazard class(es) (ADN) : Not applicable



#### RID

Transport hazard class(es) (RID) : Not applicable



# 14.4. Packing group

Packing group (ADR) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable
Packing group (ADN) : Not applicable
Packing group (RID) : Not applicable

### 14.5. Environmental hazards

Dangerous for the environment : Yes
Marine pollutant : Yes

Other information : No supplementary information available

# 14.6. Special precautions for user

#### - Overland transport

No data available

# - Transport by sea

No data available

Print date: 11/04/2019 EN (English) SDS ID: **SID3391.0** 8/10

# Safety Data Sheet

#### - Air transport

No data available

#### - Inland waterway transport

No data available

#### - Rail transport

No data available

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

#### **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

No REACH Annex XVII restrictions

DICYCLOPENTYLDIMETHOXYSILANE is not on the REACH Candidate List

DICYCLOPENTYLDIMETHOXYSILANE is not on the REACH Annex XIV List

DICYCLOPENTYLDIMETHOXYSILANE is not subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.

DICYCLOPENTYLDIMETHOXYSILANE is not subject to Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Directive 79/117/EEC

#### 15.1.2. National regulations

#### Germany

Reference to AwSV

: Water hazard class (WGK) 2, Significantly hazardous to water (Classification according to VwVwS, Annex 3; ID No. 5574)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV

: Is not subject of the 12. BlmSchV (Hazardous Incident Ordinance)

#### Netherlands

SZW-lijst van kankerverwekkende stoffen

SZW-lijst van mutagene stoffen

NIET-limitatieve lijst van voor de voortplanting

giftige stoffen – Borstvoeding

NIET-limitatieve lijst van voor de voortplanting

giftige stoffen – Vruchtbaarheid

NIET-limitatieve lijst van voor de voortplanting

giftige stoffen - Ontwikkeling

: The substance is not listed

The substance is not listed

: The substance is not listed

: The substance is not listed

: The substance is not listed

#### Denmark

**Danish National Regulations** 

: Young people below the age of 18 years are not allowed to use the product

Pregnant/breastfeeding women working with the product must not be in direct contact with the

product

#### 15.2. Chemical safety assessment

No additional information available

#### **SECTION 16: Other information**

Indication of changes:

Applied changes to section 4.

Abbreviations and acronyms:

Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemcial Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor

Other information

: Prepared by safety and environmental affairs.

Full text of H- and EUH-statements:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3

Print date: 11/04/2019 EN (English) SDS ID: **SID3391.0** 9/10

# Safety Data Sheet

Acute Tox. 3 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 1	Specific target organ toxicity — Single exposure, Category 1
STOT SE 2	Specific target organ toxicity — Single exposure, Category 2
H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H370	Causes damage to organs.
H371	May cause damage to organs.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

#### SDS EU (REACH Annex II) - Custom

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2019 Gelest Inc. Morrisville, PA 19067

Print date: 11/04/2019 EN (English) SDS ID: **SID3391.0** 10/10