

Safety Data Sheet SIG5836.0

Date of issue: 01/12/2015 Revision date: 11/01/2018 Version: 2.3

## **SECTION 1: Identification**

#### Identification

Product name : (3-GLYCIDOXYPROPYL)METHYLDIMETHOXYSILANE

: SIG5836.0 Product code Product form : Substance Physical state : Liquid Formula C9H20O4Si

3-(2,3-EPOXYPROPOXYPROPYL)METHYLDIMETHOXYSILANE Synonyms

[3-(2,3-EPOXYPROPOXY)PROPYL]DIMETHOXYMETHYLSILANE

Chemical family : ORGANOMETHOXYSILANE

#### Recommended use and restrictions on use 1.2.

Recommended use : Chemical intermediate

#### Supplier

## **GELEST, INC.**

11 East Steel Road Morrisville, PA 19067

USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com

#### **Emergency telephone number**

**Emergency number** : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

## SECTION 2: Hazard(s) identification

## Classification of the substance or mixture

## **GHS-US** classification

Skin corrosion/irritation Category 2 H315 Causes skin irritation Serious eye damage/eye irritation Category 2A H319 Causes serious eye irritation

Full text of H statements : see section 16

#### 2.2. **GHS Label elements, including precautionary statements**

## **GHS US labeling**

Hazard pictograms (GHS US)



Signal word (GHS US) : Warning

Hazard statements (GHS US) H315 - Causes skin irritation

H319 - Causes serious eye irritation

Precautionary statements (GHS US) P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P264 - Wash hands thoroughly after handling. P302+P352 - If on skin: Wash with plenty of water

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing P337+P313 - If eye irritation persists: Get medical advice/attention. P362 - Take off contaminated clothing and wash before reuse.

## Hazards not otherwise classified (HNOC)

Other hazards not contributing to the classification

Additional methanol may be formed by reaction with moisture and water. The US OSHA PEL

(TWA) for methanol is 200 ppm.

## **Unknown acute toxicity (GHS US)**

Not applicable

## **SECTION 3: Composition/Information on ingredients**

## Substances

Substance type : Multi-constituent

: (3-GLYCIDOXYPROPYL)METHYLDIMETHOXYSILANE Name

65799-47-5 CAS-No.

Print date: 04/10/2019 EN (English US) SDS ID: SIG5836.0 Page 1

## Safety Data Sheet

Name	Product identifier	%	GHS-US classification
[3-(2,3-Epoxypropoxy)propyl]dimethoxymethylsilane	(CAS-No.) 65799-47-5	95 - 100	Skin Irrit. 2, H315 Eye Irrit. 2A, H319
Other Organosilanes		0 - 2	Not classified

Full text of hazard classes and H-statements : see section 16

#### 3.2 Mixtures

Not applicable

#### **SECTION 4: First-aid measures**

## 4.1. Description of first aid measures

First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not

available show packaging or label.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel

unwell, seek medical advice.

First-aid measures after skin contact : Wash with plenty of soap and water. Get medical advice/attention.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.

First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Get medical advice/attention.

## 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : May cause irritation to the respiratory tract.

Symptoms/effects after skin contact : Causes skin irritation.

Symptoms/effects after eye contact : Causes eye irritation.

Symptoms/effects after ingestion : Oral toxicity is associated with methanol, the solvent and a hydrolysis product which causes

nausea, vomiting, headache, visual effects including blindness. Onset of symptoms may be

delayed up to 48 hours.

Chronic symptoms : On contact with water this compound liberates methanol which is known to have a chronic effect on the central nervous system. Methanol may effect the central nervous system resulting

in persistent or recurring headaches or impaired vision.

## 4.3. Immediate medical attention and special treatment, if necessary

NOTE TO PHYSICIAN: This product reacts with water in the acid contents of the stomach to form methanol. The combination of visual disturbances, metabolic acidosis and formic acid in urine is evidence of methanol poisoning. The therapeutic intravenous administration of ethanol (10 mls/hour) allows methanol to be preferentially oxidized and reduces production of methanol metabolites. Acidosis must be treated with intravenous administration of sodium bicarbonate and methanol elimination may be increased by hemodialysis, as indicated. Treatment should be based on blood methanol levels and acid-base balance.

## **SECTION 5: Fire-fighting measures**

## 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Foam. Carbon dioxide. Dry chemical.

Unsuitable extinguishing media : Do not use straight streams.

## 5.2. Specific hazards arising from the chemical

Fire hazard : Irritating fumes and organic acid vapors may develop when material is exposed to elevated

temperatures or open flame.

Reactivity : Can react exothermically with amines.

## 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Use water spray to cool exposed surfaces.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Avoid all eye and skin contact and do not breathe vapor and mist.

## **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

## 6.1.1. For non-emergency personnel

Protective equipment : Wear protective equipment as described in Section 8.

Emergency procedures : Evacuate unnecessary personnel.

## 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with

proper protection. For further information refer to section 8: "Exposure controls/personal protection".

## 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

Print date: 04/10/2019 EN (English US) SDS ID: **SIG5836.0** 2/6

## Safety Data Sheet

## 6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or

streams.

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it.

#### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapor and mist. Provide good ventilation in

process area to prevent accumulation of vapors.

Hygiene measures : Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild

soap and water before eating, drinking or smoking and when leaving work.

## 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container tightly closed. Incompatible materials : Amines. Moisture. Water.

Storage area : Store in a well-ventilated place. Store away from heat.

## SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

No additional information available

## 8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation.

## 8.3. Individual protection measures/Personal protective equipment

## Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

## Hand protection:

Impervious gloves such as neoprene or nitrile rubber gloves

## Eye protection:

Goggles. Contact lenses should not be worn

## Skin and body protection:

Wear suitable protective clothing

## Respiratory protection:

Where exposure through inhalation may occur from use, use full face NIOSH-certified respirator with APF of 50; organic vapor (black cartridge) is recommended, if air-purifying respirator selected.

## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Clear liquid.
Molecular mass : 220.34 g/mol
Color : Straw.
Odor : Mild.

Odor threshold : No data available

Refractive index : 1.431

pH : No data available
Relative evaporation rate (butyl acetate=1) : No data available
Melting point : No data available

Freezing point : < 0 °C

Boiling point :  $100 \, ^{\circ}\text{C} \, @ \, 4 \, \text{mm Hg}$ 

Flash point : 105 °C

Auto-ignition temperature : No data available

Print date: 04/10/2019 EN (English US) SDS ID: **SIG5836.0** 3/6

## Safety Data Sheet

Decomposition temperature : No data available
Flammability (solid, gas) : No data available
Vapor pressure : < 1 mm Hg @ 25°C

Relative vapor density at 20 °C : > 1
Relative density : 1.02

Solubility : Reacts with water. Log Pow : No data available Log Kow No data available Viscosity, kinematic No data available : No data available Viscosity, dynamic : No data available Explosive properties : No data available Oxidizing properties : No data available **Explosion limits** 

## 9.2. Other information

No additional information available

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Can react exothermically with amines.

#### 10.2. Chemical stability

Stable in sealed containers.

## 10.3. Possibility of hazardous reactions

Reacts with water and moisture in air, liberating methanol.

## 10.4. Conditions to avoid

Heat. Open flame. Sparks.

## 10.5. Incompatible materials

Amines. Moisture. Water.

## 10.6. Hazardous decomposition products

Methanol. Organic acid vapors.

## **SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects

Acute toxicity : Not classified

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

None of the components in this product at concentrations >0.1% are listed by IARC, NTP,

OSHA or ACGIH as a carcinogen.

Reproductive toxicity : Not classified Specific target organ toxicity – single exposure : Not classified

Specific target organ toxicity - repeated

exposure

: Not classified

: Not classified

Aspiration hazard

Potential Adverse human health effects and

symptoms

: This material liberates small amounts of methanol on contact with moisture. Material generates methanol on contact with water or moisture in skin, eyes and mucous membranes and has an

irritating, dehydrating effect on overexposed tissue.

Symptoms/effects after inhalation : May cause irritation to the respiratory tract.

Symptoms/effects after skin contact : Causes skin irritation.

Symptoms/effects after eye contact : Causes eye irritation.

Symptoms/effects after ingestion : Oral toxicity is associated with methanol, the solvent and a hydrolysis product which causes nausea vomiting headache visual effects including blindness. Onset of symptoms may be

nausea, vomiting, headache, visual effects including blindness. Onset of symptoms may be delayed up to 48 hours.

Print date: 04/10/2019 EN (English US) SDS ID: **SIG5836.0** 4/6

## Safety Data Sheet

Chronic symptoms : On contact with water this compound liberates methanol which is known to have a chronic

effect on the central nervous system. Methanol may effect the central nervous system resulting

in persistent or recurring headaches or impaired vision.

Reason for classification : Expert judgment

## **SECTION 12: Ecological information**

#### 12.1. Toxicity

No additional information available

## 12.2. Persistence and degradability

No additional information available

#### 12.3. Bioaccumulative potential

No additional information available

## 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

Effect on the ozone layer : No additional information available

## **SECTION 13: Disposal considerations**

## 13.1. Disposal methods

Sewage disposal recommendations : Do not dispose of waste into sewer.

Product/Packaging disposal recommendations : May be incinerated. Dispose in a safe manner in accordance with local/national regulations.

Ecology - waste materials : Avoid release to the environment.

## **SECTION 14: Transport information**

#### 14.1. UN number

Not regulated for transport.

## 14.2. UN proper shipping name

Not applicable

## 14.3. Additional information

Other information : No supplementary information available.

## Transport by sea

No additional information available

## Air transport

No additional information available

## **SECTION 15: Regulatory information**

## 15.1. US Federal regulations

## (3-GLYCIDOXYPROPYL)METHYLDIMETHOXYSILANE (65799-47-5)

TSCA Exemption/Exclusion

Low Volume Exemption in accordance with 40 CFR 723.50(c)(1). Use of this substance is restricted to use in coating and adhesion promoter. Anyone who intends to use this chemical substance for commercial purposes must comply with specific use restrictions and controls specified herein. This LVE limits site of manufacture of this substance to Gelest, Inc. unless otherwise approved by U.S. EPA

## 15.2. International regulations

## CANADA

No additional information available

## **EU-Regulations**

No additional information available

## [3-(2,3-Epoxypropoxy)propyl]dimethoxymethylsilane (65799-47-5)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

## **National regulations**

Print date: 04/10/2019 EN (English US) SDS ID: **SIG5836.0** 5/6

## Safety Data Sheet

## [3-(2,3-Epoxypropoxy)propyl]dimethoxymethylsilane (65799-47-5)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

## 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

## **SECTION 16: Other information**

Full text of H-phrases::

	H315	Causes skin irritation		
	H319	Causes serious eye irritation		

Abbreviations and acronyms

: Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemcial Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor.

## **Hazard Rating**

Health

: 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

Flammability

: 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)

Physical

: 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.

Prepared by safety and environmental affairs.

Date of issue: 01/12/2015 Revision date: 11/01/2018 Version: 2.3

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2019 Gelest Inc. Morrisville, PA 19067

Print date: 04/10/2019 EN (English US) SDS ID: **SIG5836.0** 6/6



11 E. Steel Road Morrisville, PA 19067

215-547-1015 phone 215-547-2484 fax www.gelest.com

# NOTICE OF TSCA USE RESTRICTIONS AND REQUIRED CONTROLS FOR SIG5836.0 (3-GLYCIDOXYPROPYL)METHYL-DIMETHOXYSILANE

## Dear Customer:

The chemical product purchased, SIG5836.0 has been granted a Low Volume Exemption by the U.S. Environmental Protection Agency (EPA) under the Toxic Substances Control Act (TSCA) regulations (40 CFR 723.50). Any manufacturer or processor who intends to use this chemical substance for commercial purposes must comply with the specific use restrictions and controls specified as follows:

**USE OF THIS CHEMICAL SUBSTANCE IS RESTRICTED TO**: Coating and adhesion promoter

**CONTROLS:** Workers must use personal protection equipment to limit dermal and inhalation exposures as described in Section 8: Exposure Controls/Personal Protection of the Safety Data Sheet (SDS). These exposure controls include:

Hand protection: Impervious gloves (neoprene or nitrile rubber gloves) Eye Protection: Chemical goggles. Contact lenses should not be worn.

Skin and Body Protection: Wear suitable protective clothing. Respiratory Protection: Air-purifying respirator with APF of 50.

**WASTE DISPOSAL:** Collect and containerize all waste, residues and wash solvents for off-site disposal by incineration. Do not release to POTW via sewer or to surface waters.

If you have questions or need more information related to allowable use of this substance, contact Gelest Regulatory Affairs at 215-547-1015.

Best Regards,

Gelest, Inc.
Regulatory Affairs Department