



[HYDROXY(POLYETHYLENEOXY)PROPYL]TRIETHOXYSILANE, (8-12 EO), 50% in ethanol

Safety Data Sheet SIH6188.0

Date of issue: 11/20/2014 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product name	: [HYDROXY(POLYETHYLENEOXY)PROPYL]TRIETHOXYSILANE, (8-12 EO), 50% in ethanol
Product code	: SIH6188.0
Product form	: Mixture
Physical state	: Liquid
Synonyms	: TRIETHOXYSILYLPROPYLPOYETHYLENEGLYCOL
Chemical family	: ORGANOETHOXYSILANE

1.2. Recommended use and restrictions on use

Recommended use	: Chemical intermediate
-----------------	-------------------------

1.3. Supplier

GELEST, INC.

11 East Steel Road
Morrisville, PA 19067

USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com

1.4. Emergency telephone number

Emergency number	: CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)
------------------	---

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable liquids Category 2	H225 Highly flammable liquid and vapor
Serious eye damage/eye irritation Category 2A	H319 Causes serious eye irritation
Specific target organ toxicity (single exposure) Category 3	H335 May cause respiratory irritation
Full text of H statements : see section 16	

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger

Hazard statements (GHS US) : H225 - Highly flammable liquid and vapor
H319 - Causes serious eye irritation
H335 - May cause respiratory irritation

Precautionary statements (GHS US) :

- P280 - Wear protective gloves/protective clothing/eye protection/face protection.
- P261 - Avoid breathing vapors.
- P264 - Wash hands thoroughly after handling.
- P312 - Call a POISON CENTER if you feel unwell
- P210 - Keep away from heat, open flames, sparks. - No smoking.
- P240 - Ground/Bond container and receiving equipment
- P241 - Use explosion-proof electrical equipment
- P242 - Use only non-sparking tools.
- P243 - Take precautionary measures against static discharge.
- P271 - Use only outdoors or in a well-ventilated area.
- P303+P361+P353 - If on skin (or hair): take off immediately all contaminated clothing. rinse skin with water/shower
- P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
- P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- P337+P313 - If eye irritation persists: Get medical advice/attention.
- P370+P378 - In case of fire: Use water spray or fog, foam, carbon dioxide, dry chemical to extinguish.
- P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
- P403+P235 - Keep in a cool place
- P405 - Store locked up.
- P501 - Dispose of contents/container to licensed waste disposal facility.

[HYDROXY(POLYETHYLENEOXY)PROPYL]TRIETHOXYSILANE, (8-12 EO), 50% in ethanol

Safety Data Sheet

2.3. Hazards not otherwise classified (HNOC)

Other hazards not contributing to the classification : Overexposure to ethanol by skin absorption, inhalation or ingestion may have a narcotic effect (headache, nausea, drowsiness). Ethanol is metabolized to acetaldehyde and acetic acid which in large quantities result in metabolic acidosis, CNS depression and death due to respiratory arrest. This product contains ethanol which is classified as a carcinogen by IARC in alcoholic beverages.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Ethanol	(CAS-No.) 64-17-5	< 50	Flam. Liq. 2, H225 Eye Irrit. 2A, H319
[Hydroxy(polyethyleneoxy)propyl]triethoxysilane	(CAS-No.) Not found	> 50	Eye Irrit. 2A, H319

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.

First-aid measures after skin contact : Wash with plenty of soap and water.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.

First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Get medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : May cause respiratory irritation. Overexposure may cause: Coughing. Headache. Nausea.

Symptoms/effects after skin contact : May cause skin irritation.

Symptoms/effects after eye contact : Causes serious eye irritation.

Symptoms/effects after ingestion : May be harmful if swallowed.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Foam. Carbon dioxide. Dry chemical.

Unsuitable extinguishing media : None known.

5.2. Specific hazards arising from the chemical

Fire hazard : Highly flammable liquid and vapor. Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.

Explosion hazard : May form flammable/explosive vapor-air mixture.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use water spray to cool exposed surfaces. Exercise caution when fighting any chemical fire.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Avoid all eye and skin contact and do not breathe vapor and mist.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Eliminate ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

[HYDROXY(POLYETHYLENEOXY)PROPYL]TRIETHOXYSILANE, (8-12 EO), 50% in ethanol

Safety Data Sheet

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or shovel spills into appropriate container for disposal. Use only non-sparking tools.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.
Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapor and mist. Provide good ventilation in process area to prevent accumulation of vapors. Take precautionary measures against static discharge. Containers and transfer lines require grounding during use. Use only non-sparking tools.
Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.
Storage conditions : Keep container tightly closed.
Incompatible materials : Moisture. Water.
Storage area : Store in a well-ventilated place. Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Ethanol (64-17-5)		
ACGIH	ACGIH STEL (ppm)	1000 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	1900 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
IDLH	US IDLH (ppm)	3300 ppm (10% LEL)
NIOSH	NIOSH REL (TWA) (mg/m ³)	1900 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	1000 ppm

8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Hand protection:

Neoprene or nitrile rubber gloves

Eye protection:

Chemical goggles. Contact lenses should not be worn

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

NIOSH-certified organic vapor (black cartridge) respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Clear liquid.

[HYDROXY(POLYETHYLENEOXY)PROPYL]TRIETHOXYSILANE, (8-12 EO), 50% in ethanol

Safety Data Sheet

Molecular mass	: 575 - 750 g/mol
Color	: Straw.
Odor	: Mild. Alcohol.
Odor threshold	: No data available
Refractive index	: 1.401
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: < 0 °C
Boiling point	: 76 °C - initial (ethanol)
Flash point	: 12 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Highly flammable liquid and vapor
Vapor pressure	: No data available
Relative vapor density at 20 °C	: > 1
Relative density	: 0.889
Solubility	: Soluble in water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: 3.3 - 19 vol % (lower; upper)

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable in sealed containers.

10.3. Possibility of hazardous reactions

Reacts with water and moisture in air, liberating ethanol.

10.4. Conditions to avoid

Heat. Open flame. Sparks.

10.5. Incompatible materials

Moisture. Water.

10.6. Hazardous decomposition products

Ethanol. Organic acid vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Ethanol (64-17-5)	
LD50 oral rat	7060 mg/kg
LC50 inhalation rat (mg/l)	124.7 mg/l/4h
LC50 inhalation rat (ppm)	20000 ppm 10 hrs.
LDLo oral rat	1400 mg/kg (Human)
ATE US (oral)	7060 mg/kg body weight
ATE US (vapors)	124.7 mg/l/4h
ATE US (dust, mist)	124.7 mg/l/4h

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Causes serious eye irritation.

[HYDROXY(POLYETHYLENEOXY)PROPYL]TRIETHOXYSILANE, (8-12 EO), 50% in ethanol

Safety Data Sheet

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified.

Ethanol (64-17-5)	
IARC group	1 - Carcinogenic to humans
In OSHA Hazard Communication Carcinogen list	Yes

Reproductive toxicity : Not classified
Specific target organ toxicity – single exposure : May cause respiratory irritation.

Specific target organ toxicity – repeated exposure : Not classified

Aspiration hazard : Not classified
Symptoms/effects after inhalation : May cause respiratory irritation. Overexposure may cause: Coughing. Headache. Nausea.
Symptoms/effects after skin contact : May cause skin irritation.
Symptoms/effects after eye contact : Causes serious eye irritation.
Symptoms/effects after ingestion : May be harmful if swallowed.
Reason for classification : Expert judgment

SECTION 12: Ecological information

12.1. Toxicity

Ethanol (64-17-5)	
LC50 fish 1	> 10000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
LC50 fish 2	> 13400 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Ethanol (64-17-5)	
Log Pow	-0.32

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the ozone layer : No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : May be incinerated. Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to licensed waste disposal facility.
Additional information : Handle empty containers with care because residual vapors are flammable.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

14.1. UN number

UN-No.(DOT) : 1993
DOT NA no. : UN1993

14.2. UN proper shipping name

Transport document description : UN1993 Flammable liquids, n.o.s.
([HYDROXY(POLYETHYLENEOXY)PROPYL]TRIETHOXYSILANE, (8-12 EO), 50% in ethanol), 3, II
Proper Shipping Name (DOT) : Flammable liquids, n.o.s.
([HYDROXY(POLYETHYLENEOXY)PROPYL]TRIETHOXYSILANE, (8-12 EO), 50% in ethanol)
Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Packing group (DOT) : II - Medium Danger

[HYDROXY(POLYETHYLENEOXY)PROPYL]TRIETHOXSILANE, (8-12 EO), 50% in ethanol

Safety Data Sheet

Hazard labels (DOT) : 3 - Flammable liquid



DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Symbols : G - Identifies PSN requiring a technical name

14.3. Additional information

Emergency Response Guide (ERG) Number : 128
Other information : No supplementary information available.

Transport by sea

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

Air transport

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L

SECTION 15: Regulatory information

15.1. US Federal regulations

[HYDROXY(POLYETHYLENEOXY)PROPYL]TRIETHOXSILANE, (8-12 EO), 50% in ethanol

TSCA Exemption/Exclusion

CAUTION: This material is supplied for research and development purposes subject to the R&D exemption under TSCA, 40 CFR 720.36, and must meet the requirements of the exemption, including supervision by a "technically qualified individual" as defined by 40 CFR 720.3(ee). The use of this material for "commercial purposes" as defined by 40 CFR 720.3(r) is not permitted in the United States.

Ethanol (64-17-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

[Hydroxy(polyethyleneoxy)propyl]triethoxysilane (Not found)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

Ethanol (64-17-5)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification

Class B Division 2 - Flammable Liquid
Class D Division 2 Subdivision B - Toxic material causing other toxic effects

EU-Regulations

Ethanol (64-17-5)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

[HYDROXY(POLYETHYLENEOXY)PROPYL]TRIETHOXYSILANE, (8-12 EO), 50% in ethanol

Safety Data Sheet

Ethanol (64-17-5)

Listed on IARC (International Agency for Research on Cancer)
Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the Canadian IDL (Ingredient Disclosure List)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)

15.3. US State regulations

WARNING: This product can expose you to Ethanol, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Ethanol (64-17-5)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	Yes	No	No		

Ethanol (64-17-5)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Full text of H-phrases::

H225	Highly flammable liquid and vapor
H319	Causes serious eye irritation
H335	May cause respiratory irritation

Abbreviations and acronyms

: Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor.

Hazard Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur
Flammability : 4 Severe Hazard - Flammable gases, or very volatile flammable liquids with flash points below 73 F, and boiling points below 100 F. Materials may ignite spontaneously with air. (Class IA)
Physical : 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.

Prepared by safety and environmental affairs.

Date of issue: 11/20/2014 Version: 1.0

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2019 Gelest Inc. Morrisville, PA 19067