

Safety Data Sheet SII6453.7 Date of issue: 15/06/2015 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Substance
Physical state : Liquid

Substance name : ISOBUTYLTRIMETHOXYSILANE

Product code : SII6453.7
Formula : C7H18O3Si

Synonyms : TRIMETHOXYSILYL-2-METHYLPROPANE

Chemical family : ORGANOSILANE

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Chemical intermediate

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

GELEST, INC.

11 East Steel Road Morrisville, PA 19067

USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com

GELEST INC.

Fritz-Klatte-Strasse 8 65933 Frankfurt

Germany

T +49 (0) 69 3535106-500 - F +49 (0) 69 3535106-501 - (M-F): 8:00 AM - 4:00 PM

info@gelestde.com - www.gelestde.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3

Acute toxicity (oral), Category 4

Skin corrosion/irritation, Category 2

Serious eye damage/eye irritation, Category 2

Specific target organ toxicity — Single exposure, Category 3,

H335

Respiratory tract irritation

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)





GHS02

GHS07

Print date: 10/04/2019 EN (English) SDS ID: **SII6453.7** 1/12

Safety Data Sheet

Signal word (CLP) : Warning

Hazard statements (CLP) : H226 - Flammable liquid and vapour.

H302 - Harmful if swallowed.
H315 - Causes skin irritation.

H319 - Causes serious eye irritation. H335 - May cause respiratory irritation.

Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P240 - Ground/bond container and receiving equipment.

P261 - Avoid breathing vapours.

P264 - Wash hands thoroughly after handling.

P280 - Wear protective clothing, protective gloves, eye protection.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

2.3. Other hazards

Other hazards not contributing to the classification

: On contact with water this compound liberates methanol which is known to have a chronic effect on the central nervous system.

SECTION 3: Composition/information on ingredients

3.1. Substances

Substance type : Mono-constituent

Name : ISOBUTYLTRIMETHOXYSILANE

CAS-No. : 18395-30-7 EC-No. : 242-272-5

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Isobutyltrimethoxysilane	(CAS-No.) 18395-30-7 (EC-No.) 242-272-5	> 96	Flam. Liq. 3, H226 Eye Dam. 1, H318
Methanol	(CAS-No.) 67-56-1 (EC-No.) 200-659-6 (EC Index-No.) 603-001-00-X		Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 STOT SE 1, H370

Specific concentration limits:

Name	Product identifier	Specific concentration limits
Methanol	(CAS-No.) 67-56-1 (EC-No.) 200-659-6	(3 = <c 10)="" 2,="" <="" h371<br="" se="" stot="">(10 =<c 1,="" 100)="" <="" h370<="" se="" stot="" th=""></c></c>
	(EC Index-No.) 603-001-00-X	

Full text of H-statements: see section 16

3.2. Mixtures

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not

available show packaging or label.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If you feel unwell, seek medical

advice.

First-aid measures after skin contact : Wash with plenty of water/....

First-aid measures after eye contact : Consult an eye specialist. Immediately flush eyes thoroughly with water for at least 15 minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : May cause irritation to the respiratory tract. Overexposure may cause: Cough. Headache.

Nausea.

Symptoms/effects after skin contact : May cause skin irritation.

Symptoms/effects after eye contact : Causes serious eye damage.

Symptoms/effects after ingestion : Oral toxicity is associated with methanol, the solvent and a hydrolysis product which causes

nausea, vomiting, headache, visual effects including blindness.

Print date: 10/04/2019 EN (English) SDS ID: **SII6453.7** 2/12

Safety Data Sheet

Chronic symptoms

On contact with water this compound liberates methanol which is known to have a chronic effect on the central nervous system. Methanol may effect the central nervous system resulting in persistent or recurring headaches or impaired vision.

4.3. Indication of any immediate medical attention and special treatment needed

NOTE TO PHYSICIAN: This product reacts with water in the acid contents of the stomach to form methanol. The combination of visual disturbances, metabolic acidosis and formic acid in urine is evidence of methanol poisoning. The therapeutic intravenous administration of ethanol (10 mls/hour) allows methanol to be preferentially oxidized and reduces production of methanol metabolites. Acidosis must be treated with intravenous administration of sodium bicarbonate and methanol elimination may be increased by hemodialysis, as indicated. Treatment should be based on blood methanol levels and acid-base balance.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Foam. Carbon dioxide. Dry chemical.

5.2. Special hazards arising from the substance or mixture

Fire hazard

: Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.

5.3. Advice for firefighters

Firefighting instructions

: Use water spray to cool exposed surfaces. Exercise caution when fighting any chemical fire.

Protection during firefighting

Do not enter fire area without proper protective equipment, including respiratory protection.

Avoid all eye and skin contact and do not breathe vapour and mist.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Eliminate every possible source of ignition. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

: Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or shovel spills into appropriate container for disposal.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

: Handle empty containers with care because residual vapours are flammable.

Precautions for safe handling

: Provide local exhaust or general room ventilation. Avoid all eye and skin contact and do not breathe vapour and mist. Ground/bond container and receiving equipment. Take precautionary measures against static discharge. Use only non-sparking tools.

Hygiene measures

: Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container tightly closed.

Incompatible materials : Water. Moisture.

Storage area : Store in a well-ventilated place. Store away from heat.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Methanol (67-56-1)		
EU	IOELV TWA (mg/m³)	260 mg/m³
EU	IOELV TWA (ppm)	200 ppm
Austria	MAK (mg/m³)	260 mg/m³
Austria	MAK (ppm)	200 ppm
Austria	MAK Short time value (mg/m³)	1040 mg/m³

Print date: 10/04/2019 EN (English) SDS ID: **SII6453.7** 3/12

Safety Data Sheet

Methanol (67-56-1)		
Austria	MAK Short time value (ppm)	800 ppm
Belgium	Limit value (mg/m³)	266 mg/m³
Belgium	Limit value (mg/m²) Limit value (ppm)	200 ppm
Belgium	Short time value (mg/m³)	333 mg/m ³
Belgium	Short time value (mg/m/) Short time value (ppm)	250 ppm
Bulgaria	OEL TWA (mg/m³)	260 mg/m³
Bulgaria	OEL TWA (ppm)	200 ppm
Cyprus	OEL TWA (mg/m³)	260 mg/m³
Cyprus	OEL TWA (ppm)	200 ppm
France	VLE (mg/m³)	1300 mg/m ³
France	VLE (ppm)	1000 ppm
France	VME (mg/m³)	260 mg/m³ (restrictive limit)
France	VME (ppm)	200 ppm (restrictive limit)
Germany	TRGS 900 Occupational exposure limit value (mg/m³)	270 mg/m³ (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Germany	TRGS 900 Occupational exposure limit value (ppm)	200 ppm (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Germany	TRGS 903 Biological limit value	30 mg/l (Medium: urine - Time: end of shift - Parameter: Methanol) 30 mg/l (Medium: urine - Time: end of several shifts - Parameter: Methanol (for long-term exposures)
Gibraltar	Eight hours mg/m3	260 mg/m ³
Gibraltar	Eight hours ppm	200 ppm
Greece	OEL TWA (mg/m³)	260 mg/m ³
Greece	OEL TWA (ppm)	200 ppm
Greece	OEL STEL (mg/m³)	325 mg/m³
Greece	OEL STEL (ppm)	250 ppm
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	200 ppm
Italy - Portugal - USA ACGIH	ACGIH STEL (ppm)	250 ppm
Italy Italy	OEL TWA (mg/m³) OEL TWA (ppm)	260 mg/m³ 200 ppm
Latvia	OEL TWA (mg/m³)	260 mg/m³
Latvia	OEL TWA (IIIghti) OEL TWA (ppm)	200 ppm
USA IDLH	US IDLH (ppm)	6000 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m³)	260 mg/m³
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m³)	325 mg/m³
USA NIOSH	NIOSH REL (STEL) (ppm)	250 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	260 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
Spain	VLA-ED (mg/m³)	266 mg/m³ (indicative limit value)
Spain	VLA-ED (ppm)	200 ppm (indicative limit value)
Switzerland	KZGW (mg/m³)	1040 mg/m³
Switzerland	KZGW (ppm)	800 ppm
Switzerland	MAK (mg/m³)	260 mg/m³
Switzerland	MAK (ppm)	200 ppm
Netherlands	Grenswaarde TGG 8H (mg/m³)	133 mg/m³
Netherlands	Grenswaarde TGG 8H (ppm)	100 ppm
United Kingdom	WEL TWA (mg/m³)	266 mg/m³
United Kingdom	WEL TWA (ppm)	200 ppm
United Kingdom	WEL STEL (mg/m³)	333 mg/m³
United Kingdom	WEL STEL (ppm)	250 ppm
Czech Republic Denmark	Expoziční limity (PEL) (mg/m³) Grænseværdie (langvarig) (mg/m³)	250 mg/m³ 260 mg/m³
Denmark	Grænseværdie (langvarig) (ppm)	
Delillar	Grænseværdie (langvang) (ppm)	200 ppm

Print date: 10/04/2019 EN (English) SDS ID: **\$116453.7** 4/12

Safety Data Sheet

Methanol (67-56-1)		
Finland	HTP-arvo (8h) (mg/m³)	270 mg/m³
Finland	HTP-arvo (8h) (ppm)	200 ppm
Finland	HTP-arvo (15 min)	330 mg/m³
Finland	HTP-arvo (15 min) (ppm)	250 ppm
Hungary	AK-érték	260 mg/m³
Ireland	OEL (8 hours ref) (mg/m³)	260 mg/m³
Ireland	OEL (8 hours ref) (ppm)	200 ppm
Ireland	OEL (15 min ref) (mg/m3)	780 mg/m³ (calculated)
Ireland	OEL (15 min ref) (ppm)	600 ppm (calculated)
Lithuania	IPRV (mg/m³)	260 mg/m³
Lithuania	IPRV (ppm)	200 ppm
Malta	OEL TWA (mg/m³)	260 mg/m³
Malta	OEL TWA (Ing/III)	200 ppm
Norway	Grenseverdier (AN) (mg/m³)	130 mg/m ³
Norway	Grenseverdier (AN) (ppm)	100 ppm
Norway	Grenseverdier (Korttidsverdi) (mg/m3)	130 mg/m³
Norway	Grenseverdier (Korttidsverdi) (ppm)	100 ppm
Poland	NDS (mg/m³)	100 mg/m³
Poland	NDSCh (mg/m³)	300 mg/m³
Romania	OEL TWA (mg/m³)	260 mg/m³
Romania	OEL TWA (mg/m-) OEL TWA (ppm)	200 ppm
Romania	OEL STEL (ppm)	5 ppm
Slovakia	NPHV (priemerná) (mg/m³)	260 mg/m³
Slovakia	NPHV (priemerná) (ppm)	200 ppm
Sweden	nivågränsvärde (NVG) (mg/m³)	250 mg/m³
Sweden	nivågränsvärde (NVG) (ppm)	200 ppm
Sweden	kortidsvärde (KTV) (mg/m³)	350 mg/m ³
Sweden	kortidsvärde (KTV) (ppm)	250 ppm
Canada (Quebec)	VECD (mg/m³)	328 mg/m³
Canada (Quebec)	VECD (ppm)	250 ppm
Canada (Quebec)	VEMP (mg/m³)	262 mg/m³
Canada (Quebec)	VEMP (ppm)	200 ppm
Australia	TWA (mg/m³)	262 mg/m ³
Australia		
Australia	TWA (ppm) STEL (mg/m³)	200 ppm 328 mg/m³
	STEL (mg/m²) STEL (ppm)	
Australia		250 ppm
Portugal	OEL TWA (mg/m³)	260 mg/m³ (indicative limit value)
Portugal	OEL TWA (ppm)	200 ppm (indicative limit value)
Portugal Portugal	OEL STEL (ppm) OEL chemical category (PT)	250 ppm skin - potential for cutaneous exposure indicative limit value

8.2. Exposure controls

Appropriate engineering controls:

Provide local exhaust or general room ventilation.

Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Hand protection:

Neoprene or nitrile rubber gloves

Eye protection:

Print date: 10/04/2019 EN (English) SDS ID: **SII6453.7** 5/12

Safety Data Sheet

Chemical goggles. Contact lenses should not be worn

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified organic vapor (black cartridge) respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Clear liquid.
Molecular mass : 178.3 g/mol
Colour : Straw.
Odour : Mild.

Odour threshold : No data available

Refractive index : No additional information available

pH : No data available Relative evaporation rate (butylacetate=1) : No data available Melting point : No data available

Freezing point : < 0 °C Boiling point : 154 °C Flash point : 42 °C

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Flammability (solid, gas) : Highly flammable liquid and vapour.

Vapour pressure : No data available

Relative vapour density at 20 °C : > 1
Relative density : 0.933

Insoluble. Reacts. Solubility Log Pow : No data available : No data available Log Kow No data available Viscosity, kinematic : No data available Viscosity, dynamic : No data available Explosive properties : No data available Oxidising properties **Explosive limits** : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable in sealed containers.

10.3. Possibility of hazardous reactions

Reacts with water and moisture in air, liberating methanol.

10.4. Conditions to avoid

Heat. ignition sources. Open flame. Sparks.

10.5. Incompatible materials

Water. Moisture.

10.6. Hazardous decomposition products

Organic acid vapors. Methanol.

Print date: 10/04/2019 EN (English) SDS ID: \$116453.7 6/12

Safety Data Sheet

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Harmful if swallowed.

ISOBUTYLTRIMETHOXYSILANE (18395-30-7)	
ATE CLP (oral)	526.316 mg/kg bodyweight
Methanol (67-56-1)	
LC50 inhalation rat (ppm)	22500 ppm (Exposure time: 8 h)
ATE CLP (oral)	100 mg/kg bodyweight
ATE CLP (dermal)	300 mg/kg bodyweight
ATE CLP (vapours)	3 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified Carcinogenicity : Not classified Reproductive toxicity : Not classified

STOT-single exposure : May cause respiratory irritation.

STOT-repeated exposure : Not classified
Aspiration hazard : Not classified

Symptoms/effects after inhalation : May cause irritation to the respiratory tract. Overexposure may cause: Cough. Headache.

Nausea.

Symptoms/effects after skin contact : May cause skin irritation.

Symptoms/effects after eye contact : Causes serious eye damage.

Symptoms/effects after ingestion : Oral toxicity is associated with methanol, the solvent and a hydrolysis product which causes

nausea, vomiting, headache, visual effects including blindness.

Chronic symptoms : On contact with water this compound liberates methanol which is known to have a chronic

effect on the central nervous system. Methanol may effect the central nervous system resulting

in persistent or recurring headaches or impaired vision.

Reason for classification : Expert judgment

SECTION 12: Ecological information

12.1. Toxicity

Acute aquatic toxicity : Not classified Chronic aquatic toxicity : Not classified

Methanol (67-56-1)	
LC50 fish 1	28200 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Methanol (67-56-1)	
BCF fish 1	< 10
Log Pow	-0.77

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Other adverse effects : This substance may be hazardous to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : May be incinerated. Dispose of contents/container to licensed waste disposal facility.

Additional information : Handle empty containers with care because residual vapours are flammable.

Ecology - waste materials : Avoid release to the environment.

Print date: 10/04/2019 EN (English) SDS ID: \$16453.7 7/12

Safety Data Sheet

SECTION 14: Transport information

14.1. UN number

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR) : 1993 UN-No. (IMDG) : 1993 UN-No. (IATA) : 1993 UN-No. (ADN) : 1993 UN-No. (RID) : 1993

14.2. UN proper shipping name

Proper Shipping Name (ADR) : FLAMMABLE LIQUID, N.O.S.
Proper Shipping Name (IMDG) : FLAMMABLE LIQUID, N.O.S.
Proper Shipping Name (IATA) : Flammable liquid, n.o.s.
Proper Shipping Name (ADN) : FLAMMABLE LIQUID, N.O.S.
Proper Shipping Name (RID) : FLAMMABLE LIQUID, N.O.S.

Transport document description (ADR)

: UN 1993 FLAMMABLE LIQUID, N.O.S. (ISOBUTYLTRIMETHOXYSILANE), 3, III, (D/E)

Transport document description (IMDG)

: UN 1993 FLAMMABLE LIQUID, N.O.S. (ISOBUTYLTRIMETHOXYSILANE), 3, III

Transport document description (ADN)

: UN 1993 FLAMMABLE LIQUID, N.O.S. (ISOBUTYLTRIMETHOXYSILANE), 3, III

Transport document description (ADN)

: UN 1993 FLAMMABLE LIQUID, N.O.S. (ISOBUTYLTRIMETHOXYSILANE), 3, III

Transport document description (RID)

: UN 1993 FLAMMABLE LIQUID, N.O.S. (ISOBUTYLTRIMETHOXYSILANE), 3, III

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 3
Danger labels (ADR) : 3



IMDG

Transport hazard class(es) (IMDG) : 3
Danger labels (IMDG) : 3



IATA

Transport hazard class(es) (IATA) : 3
Hazard labels (IATA) : 3



ADN

Transport hazard class(es) (ADN) : 3
Danger labels (ADN) : 3

Print date: 10/04/2019 EN (English) SDS ID: \$116453.7 8/12

Safety Data Sheet



RID

: 3 Transport hazard class(es) (RID) Danger labels (RID) : 3



Packing group

Packing group (ADR) : 111 : III Packing group (IMDG) Packing group (IATA) : 111 : 111 Packing group (ADN) : 111 Packing group (RID)

Environmental hazards

Dangerous for the environment : No Marine pollutant : No

Other information : No supplementary information available

14.6. Special precautions for user

- Overland transport

Classification code (ADR) : F1

Special provisions (ADR) : 274, 601, 640E

Limited quantities (ADR) : 51 Excepted quantities (ADR) : E1

P001, IBC03, LP01, R001 Packing instructions (ADR)

Mixed packing provisions (ADR) : MP19 Portable tank and bulk container instructions : T4

(ADR)

Portable tank and bulk container special

provisions (ADR)

: TP1, TP29

: LGBF Tank code (ADR) : FL Vehicle for tank carriage Transport category (ADR) : 3 Special provisions for carriage - Packages : V12

(ADR)

Special provisions for carriage - Operation

(ADR)

: 30 Hazard identification number (Kemler No.)

Orange plates

30 1993

: S2

Tunnel restriction code (ADR) : D/E

- Transport by sea

Special provisions (IMDG) : 223, 274, 955

Limited quantities (IMDG) : 5 L Excepted quantities (IMDG) : E1 : P001, LP01 Packing instructions (IMDG) IBC packing instructions (IMDG) : IBC03 Tank instructions (IMDG) : T4

Print date: 10/04/2019 SDS ID: SII6453.7 9/12 EN (English)

Safety Data Sheet

Tank special provisions (IMDG) : TP1, TP29

EmS-No. (Fire) : F-E

EmS-No. (Spillage) : S-E

Stowage category (IMDG) : A

- Air transport

PCA Excepted quantities (IATA) : E1 PCA Limited quantities (IATA) : Y344 PCA limited quantity max net quantity (IATA) : 10L PCA packing instructions (IATA) : 355 PCA max net quantity (IATA) : 60L CAO packing instructions (IATA) : 366 CAO max net quantity (IATA) : 220L Special provisions (IATA) : A3 ERG code (IATA) : 3L

- Inland waterway transport

Classification code (ADN) : F1

Special provisions (ADN) : 274, 601, 640E

Limited quantities (ADN) : 5 L

Excepted quantities (ADN) : E1

Carriage permitted (ADN) : T

Equipment required (ADN) : PP, EX, A

Ventilation (ADN) : VE01

Number of blue cones/lights (ADN) : 0

- Rail transport

Classification code (RID) : F1

Special provisions (RID) : 274, 601, 640E

Limited quantities (RID) : 5L

Excepted quantities (RID) : E1

Packing instructions (RID) : P001, IBC03, LP01, R001

Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions : T4

(RID)

Portable tank and bulk container special : TP1, TP29

provisions (RID)

Tank codes for RID tanks (RID) : LGBF
Transport category (RID) : 3
Special provisions for carriage – Packages (RID) : W12

Colis express (express parcels) (RID) : CE4
Hazard identification number (RID) : 30

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

No REACH Annex XVII restrictions

ISOBUTYLTRIMETHOXYSILANE is not on the REACH Candidate List

ISOBUTYLTRIMETHOXYSILANE is not on the REACH Annex XIV List

ISOBUTYLTRIMETHOXYSILANE is not subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.

ISOBUTYLTRIMETHOXYSILANE is not subject to Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Directive 79/117/EEC

15.1.2. National regulations

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Print date: 10/04/2019 EN (English) SDS ID: \$116453.7 10/12

Safety Data Sheet

Germany

Reference to AwSV : Water hazard class (WGK) 1, Slightly hazardous to water (Classification according to VwVwS,

Annex 1 or 2; ID No. 1849)

: The substance is not listed

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV

: Is not subject of the 12. BlmSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen : The substance is not listed SZW-lijst van mutagene stoffen The substance is not listed : The substance is not listed NIET-limitatieve lijst van voor de voortplanting

giftige stoffen - Borstvoeding

NIET-limitatieve lijst van voor de voortplanting giftige stoffen - Vruchtbaarheid

NIET-limitatieve lijst van voor de voortplanting giftige stoffen - Ontwikkeling

: The substance is not listed

Denmark

Class for fire hazard : Class II-1 Store unit : 5 liter

Classification remarks R10 <H226;H302;H315;H319;H335>; Emergency management guidelines for the storage of

flammable liquids must be followed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

15.2. **Chemical safety assessment**

No additional information available

SECTION 16: Other information

Abbreviations and acronyms:

Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemcial Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor

Other information

Prepared by safety and environmental affairs.

Full text of H- and EUH-statements:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 1	Specific target organ toxicity — single exposure, Category 1
STOT SE 2	Specific target organ toxicity — Single exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H370	Causes damage to organs.
H371	May cause damage to organs.


Print date: 10/04/2019 EN (English) SDS ID: SII6453.7 11/12

Safety Data Sheet

SDS EU (REACH Annex II) - Custom

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2019 Gelest Inc. Morrisville, PA 19067



Print date: 10/04/2019 EN (English) SDS ID: **SII6453.7** 12/12