

Safety Data Sheet SII6453.7
Date of issue: 06/15/2015 Version: 1.

## **SECTION 1: Identification**

#### 1.1. Identification

Product name : ISOBUTYLTRIMETHOXYSILANE

Product code : SII6453.7
Product form : Substance
Physical state : Liquid
Formula : C7H18O3Si

Synonyms : TRIMETHOXYSILYL-2-METHYLPROPANE

Chemical family : ORGANOSILANE

### 1.2. Recommended use and restrictions on use

Recommended use : Chemical intermediate

#### 1.3. Supplier

#### GELEST, INC.

11 East Steel Road Morrisville, PA 19067

**USA** 

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

## **SECTION 2: Hazard(s) identification**

#### 2.1. Classification of the substance or mixture

## **GHS-US** classification

Flammable liquids Category 3 H226 Flammable liquid and vapor Serious eye damage/eye irritation Category 1 H318 Causes serious eye damage

Full text of H statements : see section 16

## 2.2. GHS Label elements, including precautionary statements

## **GHS US labeling**

Hazard pictograms (GHS US)





Signal word (GHS US) : Danger

Hazard statements (GHS US) : H226 - Flammable liquid and vapor

H318 - Causes serious eye damage

Precautionary statements (GHS US) : P280 - Wear eye protection, face protection, face shield, protective clothing, protective gloves.

P302+P352 - If on skin: Wash with plenty of soap and water P210 - Keep away from heat, open flames, sparks. - No smoking.

P233 - Keep container tightly closed.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

## 2.3. Hazards not otherwise classified (HNOC)

Other hazards not contributing to the classification

: On contact with water this compound liberates methanol which is known to have a chronic effect on the central nervous system.

## 2.4. Unknown acute toxicity (GHS US)

Not applicable

## **SECTION 3: Composition/Information on ingredients**

## 3.1. Substances

Substance type : Mono-constituent

Name : ISOBUTYLTRIMETHOXYSILANE

CAS-No. : 18395-30-7

Print date: 04/10/2019 EN (English US) SDS ID: **SII6453.7** Page 1

## Safety Data Sheet

Name	Product identifier	%	GHS-US classification
Isobutyltrimethoxysilane	(CAS-No.) 18395-30-7	> 96	Flam. Liq. 3, H226 Eye Dam. 1, H318
Methanol	(CAS-No.) 67-56-1		Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 1, H370 STOT SE 3, H336

Full text of hazard classes and H-statements: see section 16

#### 3.2. Mixtures

Not applicable

### **SECTION 4: First-aid measures**

First-aid measures after skin contact

#### 4.1. Description of first aid measures

First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek

medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel

unwell, seek medical advice.

First-aid measures after eye contact : Consult an eye specialist. Immediately flush eyes thoroughly with water for at least 15 minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Get medical advice/attention.

: Wash with plenty of soap and water.

#### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : May cause irritation to the respiratory tract. Overexposure may cause: Coughing. Headache.

Nausea.

Symptoms/effects after skin contact : May cause skin irritation.

Symptoms/effects after eye contact : Causes serious eye damage.

Symptoms/effects after ingestion : Oral toxicity is associated with methanol, the solvent and a hydrolysis product which causes

nausea, vomiting, headache, visual effects including blindness.

Chronic symptoms : On contact with water this compound liberates methanol which is known to have a chronic effect on the central nervous system. Methanol may effect the central nervous system resulting

in persistent or recurring headaches or impaired vision.

#### 4.3. Immediate medical attention and special treatment, if necessary

NOTE TO PHYSICIAN: This product reacts with water in the acid contents of the stomach to form methanol. The combination of visual disturbances, metabolic acidosis and formic acid in urine is evidence of methanol poisoning. The therapeutic intravenous administration of ethanol (10 mls/hour) allows methanol to be preferentially oxidized and reduces production of methanol metabolites. Acidosis must be treated with intravenous administration of sodium bicarbonate and methanol elimination may be increased by hemodialysis, as indicated. Treatment should be based on blood methanol levels and acid-base balance.

## **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Foam. Carbon dioxide. Dry chemical.

## 5.2. Specific hazards arising from the chemical

Fire hazard : Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.

#### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use water spray to cool exposed surfaces. Exercise caution when fighting any chemical fire.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Avoid all eye and skin contact and do not breathe vapor and mist.

#### **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Eliminate every possible source of ignition. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

## 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

Print date: 04/10/2019 EN (English US) SDS ID: \$16453.7 2/7

## Safety Data Sheet

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or

shovel spills into appropriate container for disposal.

#### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Additional hazards when processed

: Handle empty containers with care because residual vapors are flammable.

Precautions for safe handling : Provide local exhaust or general room ventilation. Avoid all eye and skin contact and do not

breathe vapor and mist. Ground/bond container and receiving equipment. Take precautionary

measures against static discharge. Use only non-sparking tools.

Hygiene measures : Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild

soap and water before eating, drinking or smoking and when leaving work.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container tightly closed.

Incompatible materials : Water. Moisture.

Storage area : Store in a well-ventilated place. Store away from heat.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

Methanol (67-56-1)			
ACGIH	ACGIH TWA (ppm)		200 ppm
ACGIH	ACGIH STEL (ppm)		250 ppm
OSHA	OSHA PEL (TWA) (mg/m³)		260 mg/m³
OSHA	OSHA PEL (TWA) (ppm)		200 ppm
IDLH	US IDLH (ppm)		6000 ppm
NIOSH	NIOSH REL (TWA) (mg/m³)	TO Y	260 mg/m³
NIOSH	NIOSH REL (TWA) (ppm)		200 ppm
NIOSH	NIOSH REL (STEL) (mg/m³)		325 mg/m³
NIOSH	NIOSH REL (STEL) (ppm)		250 ppm

#### 8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation.

## 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

## Hand protection:

Neoprene or nitrile rubber gloves

## Eye protection:

Chemical goggles. Contact lenses should not be worn

## Skin and body protection:

Wear suitable protective clothing

## Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified organic vapor (black cartridge) respirator.

## **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Clear liquid.
Molecular mass : 178.3 g/mol

Print date: 04/10/2019 EN (English US) SDS ID: \$116453.7 3/7

# Safety Data Sheet

Color : Straw.
Odor : Mild.

Odor threshold : No data available
Refractive index : No data available
pH : No data available
Relative evaporation rate (butyl acetate=1) : No data available
Melting point : No data available

Freezing point :  $< 0 \, ^{\circ}\text{C}$  Boiling point :  $154 \, ^{\circ}\text{C}$  Flash point :  $42 \, ^{\circ}\text{C}$ 

Auto-ignition temperature : No data available Decomposition temperature : No data available

Flammability (solid, gas) : Highly flammable liquid and vapor

Vapor pressure : No data available

Relative vapor density at 20 °C : > 1
Relative density : 0.933

Solubility : Insoluble. Reacts. Log Pow : No data available Log Kow : No data available Viscosity, kinematic No data available Viscosity, dynamic No data available : No data available Explosive properties Oxidizing properties : No data available Explosion limits No data available

## 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

## 10.1. Reactivity

No additional information available

## 10.2. Chemical stability

Stable in sealed containers.

#### 10.3. Possibility of hazardous reactions

Reacts with water and moisture in air, liberating methanol.

## 10.4. Conditions to avoid

Heat. ignition sources. Open flame. Sparks.

#### 10.5. Incompatible materials

Water. Moisture.

Reproductive toxicity

## 10.6. Hazardous decomposition products

Organic acid vapors. Methanol.

# **SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects

Acute toxicity : Not classified

Methanol (67-56-1)		
LC50 inhalation rat (ppm)	22500 ppm (Exposure time: 8 h)	
ATE US (oral)	100 mg/kg body weight	
ATE US (dermal)	300 mg/kg body weight	
ATE US (vapors)	3 mg/l/4h	

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Print date: 04/10/2019 EN (English US) SDS ID: **SII6453.7** 4/7

: Not classified

## Safety Data Sheet

Specific target organ toxicity - single exposure : Not classified

Specific target organ toxicity - repeated

exposure

: Not classified

Aspiration hazard : Not classified

Symptoms/effects after inhalation : May cause irritation to the respiratory tract. Overexposure may cause: Coughing. Headache.

Nausea.

Symptoms/effects after skin contact : May cause skin irritation.

Symptoms/effects after eye contact : Causes serious eye damage.

Symptoms/effects after ingestion : Oral toxicity is associated with methanol, the solvent and a hydrolysis product which causes

nausea, vomiting, headache, visual effects including blindness.

Chronic symptoms : On contact with water this compound liberates methanol which is known to have a chronic

effect on the central nervous system. Methanol may effect the central nervous system resulting

in persistent or recurring headaches or impaired vision.

Reason for classification : Expert judgment

### **SECTION 12: Ecological information**

#### 12.1. Toxicity

Methanol (67-56-1)	
LC50 fish 1	28200 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

#### 12.2. Persistence and degradability

No additional information available

#### 12.3. Bioaccumulative potential

Methanol (67-56-1)		
BCF fish 1	< 10	
Log Pow	-0.77	

### 12.4. Mobility in soil

No additional information available

## 12.5. Other adverse effects

Other adverse effects : This substance may be hazardous to the environment.

Effect on the ozone layer : No additional information available

## **SECTION 13: Disposal considerations**

### 13.1. Disposal methods

Product/Packaging disposal recommendations : May be incinerated. Dispose of contents/container to licensed waste disposal facility.

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials : Avoid release to the environment.

## **SECTION 14: Transport information**

## 14.1. UN number

UN-No.(DOT) : 1993 DOT NA no. UN1993

## 14.2. UN proper shipping name

Transport document description : UN1993 Flammable liquids, n.o.s. ( (ISOBUTYLTRIMETHOXYSILANE)), 3, III

Proper Shipping Name (DOT) : Flammable liquids, n.o.s.

(ISOBUTYLTRIMETHOXYSILANE)

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Packing group (DOT) : III - Minor Danger Hazard labels (DOT) : 3 - Flammable liquid



DOT Packaging Non Bulk (49 CFR 173.xxx) : 203 DOT Packaging Bulk (49 CFR 173.xxx) : 242

Print date: 04/10/2019 EN (English US) SDS ID: \$\mathbb{S}\mathbb{ID}\$: \$\mathbb{S}\mathbb{S}\$: \$\mathbb{S}\mathbb{S}\$: \$\mathbb{S}\mathbb{S}\$: \$\mathbb{S}\mathbb{S}\$: \$\mathbb{S}\mathbb{S}\$: \$\mathbb{S}\mathbb{S}\$: \$\mathbb{S}\mathbb{S}\$: \$\mathbb{S}\$: \$

# Safety Data Sheet

DOT Packaging Exceptions (49 CFR 173.xxx) : 150

DOT Symbols : G - Identifies PSN requiring a technical name

14.3. Additional information

Emergency Response Guide (ERG) Number : 128

Other information : No supplementary information available.

Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 60 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L

CFR 175.75)

## **SECTION 15: Regulatory information**

#### 15.1. US Federal regulations

## ISOBUTYLTRIMETHOXYSILANE (18395-30-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

# Methanol (67-56-1) Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313 SARA Section 313 - Emission Reporting 1 %

### 15.2. International regulations

#### **CANADA**

Methanol (67-56-1)	
Listed on the Canadian DSL (Domestic S	ubstances List)
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects

## Isobutyltrimethoxysilane (18395-30-7)

Listed on the Canadian DSL (Domestic Substances List)

## **EU-Regulations**

#### Methanol (67-56-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

#### Isobutyltrimethoxysilane (18395-30-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

## **National regulations**

# Methanol (67-56-1)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Japanese Poisonous and Deleterious Substances Control Law

Listed on the Canadian IDL (Ingredient Disclosure List)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Listed on CICR (Turkish Inventory and Control of Chemicals)

#### Isobutyltrimethoxysilane (18395-30-7)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Japanese ISHL (Industrial Safety and Health Law)

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Print date: 04/10/2019 EN (English US) SDS ID: \$16453.7 6/7

## Safety Data Sheet

### 15.3. US State regulations

MARNING:

This product can expose you to Methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Methanol (67-56-1)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
No	Yes	No	No		

## Methanol (67-56-1)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

## **SECTION 16: Other information**

Full text of H-phrases::

H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H301	Toxic if swallowed
H311	Toxic in contact with skin
H315	Causes skin irritation
H318	Causes serious eye damage
H331	Toxic if inhaled
H336	May cause drowsiness or dizziness
H370	Causes damage to organs

Abbreviations and acronyms

: Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemcial Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor.

## **Hazard Rating**

Health

: 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is

Flammability

 2 Moderate Hazard - Materials which must be moderately heated or exposed to high ambient temperatures before ignition will occur. Includes liquids having a flash point at or above 100 F but below 200 F. (Classes II & IIIA)

Physical

: 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.

Prepared by safety and environmental affairs.

Date of issue: 06/15/2015 Version: 1.0

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2019 Gelest Inc. Morrisville, PA 19067

Print date: 04/10/2019 EN (English US) SDS ID: \$16453.7 7/7