

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product form	: Substance
Physical state	: Liquid
Substance name	: (METHACRYLOXYMETHYL)METHYLDIMETHOXSILANE
Product code	: SIM6481.46
Formula	: C8H16O4Si
Synonyms	: (DIMETHOXYMETHYLSILYL)METHYLMETHACRYLATE METHACRYLOXYMETHYLENEMETHYLDIMETHOXSILANE (DIMETHOXY)(METHACRYLOXYLOXYMETHYL)(METHYL)SILANE
Chemical family	: ORGANOSILANE

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.2.1. Relevant identified uses**

Use of the substance/mixture : Chemical intermediate

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet**GELEST, INC.**

11 East Steel Road
Morrisville, PA 19067

USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com

GELEST INC.

Fritz-Klatte-Strasse 8
65933 Frankfurt

Germany

T +49 (0) 69 3535106-500 - F +49 (0) 69 3535106-501 - (M-F): 8:00 AM - 4:00 PM

info@gelestde.com - www.gelestde.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Serious eye damage/eye irritation, Category 2

H319

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP) :



GHS07

Signal word (CLP) :

Warning

Hazard statements (CLP) :

H319 - Causes serious eye irritation.

Precautionary statements (CLP) :

P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P264 - Wash hands thoroughly after handling.

(METHACRYLOXYMETHYL)METHYLDIMETHOXYSIANE

Safety Data Sheet

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P337+P313 - If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

Other hazards not contributing to the classification : Additional methanol may be formed by reaction with moisture and water. The US OSHA PEL (TWA) for methanol is 200 ppm.

SECTION 3: Composition/information on ingredients

3.1. Substances

Substance type : Mono-constituent
Name : (METHACRYLOXYMETHYL)METHYLDIMETHOXYSIANE
CAS-No. : 121177-93-3

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
(Methacryloxymethyl)methyldimethoxysilane	(CAS-No.) 121177-93-3 (EC-No.) 479-600-3	95 - 100	Eye Irrit. 2, H319
Hydroquinone monomethyl ether	(CAS-No.) 150-76-5 (EC-No.) 205-769-8 (EC Index-No.) 604-044-00-7	< 0.05	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 Skin Sens. 1, H317

Full text of H-statements: see section 16

3.2. Mixtures

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If you feel unwell, seek medical advice.
First-aid measures after skin contact : Wash with plenty of water/.... Get medical advice/attention.
First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : May cause irritation to the respiratory tract.
Symptoms/effects after skin contact : May cause skin irritation.
Symptoms/effects after eye contact : Causes serious eye irritation.
Symptoms/effects after ingestion : May be harmful if swallowed.
Chronic symptoms : On contact with water this compound liberates methanol which is known to have a chronic effect on the central nervous system. Methanol may affect the central nervous system resulting in persistent or recurring headaches or impaired vision.

4.3. Indication of any immediate medical attention and special treatment needed

NOTE TO PHYSICIAN: This product reacts with water in the acid contents of the stomach to form methanol. The combination of visual disturbances, metabolic acidosis and formic acid in urine is evidence of methanol poisoning. The therapeutic intravenous administration of ethanol (10 mls/hour) allows methanol to be preferentially oxidized and reduces production of methanol metabolites. Acidosis must be treated with intravenous administration of sodium bicarbonate and methanol elimination may be increased by hemodialysis, as indicated. Treatment should be based on blood methanol levels and acid-base balance.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Foam. Carbon dioxide. Dry chemical.
Unsuitable extinguishing media : Do not use straight streams.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Combustible liquid. Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.

5.3. Advice for firefighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Use spray to cool exposed surfaces.

(METHACRYLOXYMETHYL)METHYLDIMETHOXYSILANE

Safety Data Sheet

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Avoid all eye and skin contact and do not breathe vapour and mist.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

Protective equipment : Wear protective equipment as described in Section 8.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Use only non-sparking tools.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapour and mist. Ground/bond container and receiving equipment. Provide good ventilation in process area to prevent formation of vapour. Use only non-sparking tools.

Hygiene measures : Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Keep container tightly closed. Keep in a cool place. Store < 5°C.

Incompatible materials : Moisture. Water.

Storage area : Store in a well-ventilated place. Store away from heat.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Hydroquinone monomethyl ether (150-76-5)		
Austria	MAK (mg/m ³)	5 mg/m ³
Austria	MAK Short time value (mg/m ³)	10 mg/m ³
Belgium	Limit value (mg/m ³)	5 mg/m ³
France	VME (mg/m ³)	5 mg/m ³
Greece	OEL TWA (mg/m ³)	5 mg/m ³
Italy - Portugal - USA ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	5 mg/m ³
Spain	VLA-ED (mg/m ³)	5 mg/m ³
Denmark	Grænseværdie (langvarig) (mg/m ³)	5 mg/m ³
Ireland	OEL (8 hours ref) (mg/m ³)	5 mg/m ³
Ireland	OEL (15 min ref) (mg/m ³)	15 mg/m ³ (calculated)
Norway	Grænseverdier (AN) (mg/m ³)	5 mg/m ³
Norway	Grænseverdier (Korttidsverdi) (mg/m ³)	5 mg/m ³
Poland	NDS (mg/m ³)	5 mg/m ³
Canada (Quebec)	VEMP (mg/m ³)	5 mg/m ³

(METHACRYLOXYMETHYL)METHYLDIMETHOXYSILANE

Safety Data Sheet

Hydroquinone monomethyl ether (150-76-5)		
Australia	TWA (mg/m ³)	5 mg/m ³
Portugal	OEL TWA (mg/m ³)	5 mg/m ³

8.2. Exposure controls

Appropriate engineering controls:

Provide local exhaust or general room ventilation.

Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Hand protection:

Neoprene or nitrile rubber gloves

Eye protection:

Chemical goggles. Contact lenses should not be worn

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified organic vapor (black cartridge) respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear liquid.
Molecular mass	: 204.3 g/mol
Colour	: Straw.
Odour	: Mild.
Odour threshold	: No data available
Refractive index	: 1.4274
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: < 0 °C
Boiling point	: 205 °C
Flash point	: 82 °C
Auto-ignition temperature	: 300 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: Combustible liquid
Vapour pressure	: ~ 1 mm Hg @ 25°C
Relative vapour density at 20 °C	: > 1
Relative density	: 1.02
% Volatiles	: < 5 %
Solubility	: Insoluble in water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

(METHACRYLOXYMETHYL)METHYLDIMETHOXYSILANE

Safety Data Sheet

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable in sealed containers stored in the dark at 0-5°C. Polymerization can occur when stored at elevated temperature.

10.3. Possibility of hazardous reactions

Reacts with water and moisture in air, liberating methanol.

10.4. Conditions to avoid

Heat. Open flame. Sparks.

10.5. Incompatible materials

Moisture. Water.

10.6. Hazardous decomposition products

Methanol. Organic acid vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Hydroquinone monomethyl ether (150-76-5)

LD50 oral rat	1600 mg/kg
---------------	------------

(Methacryloxymethyl)methyldimethoxysilane (121177-93-3)

LD50 oral rat	> 2000 mg/kg
---------------	--------------

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

None of the components in this product at concentrations >0.1% are listed by IARC, NTP, OSHA or ACGIH as a carcinogen.

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

Potential adverse human health effects and symptoms : This material liberates small amounts of methanol on contact with moisture. Material generates methanol on contact with water or moisture in skin, eyes and mucous membranes and has an irritating, dehydrating effect on overexposed tissue.

Symptoms/effects after inhalation : May cause irritation to the respiratory tract.

Symptoms/effects after skin contact : May cause skin irritation.

Symptoms/effects after eye contact : Causes serious eye irritation.

Symptoms/effects after ingestion : May be harmful if swallowed.

Chronic symptoms : On contact with water this compound liberates methanol which is known to have a chronic effect on the central nervous system. Methanol may effect the central nervous system resulting in persistent or recurring headaches or impaired vision.

Reason for classification : Expert judgment

SECTION 12: Ecological information

12.1. Toxicity

Acute aquatic toxicity : Not classified

Chronic aquatic toxicity : Not classified

Hydroquinone monomethyl ether (150-76-5)

LC50 fish 1	84.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
-------------	---

LC50 fish 2	28.5 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
-------------	---

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

(METHACRYLOXYMETHYL)METHYLDIMETHOXYSIANE

Safety Data Sheet

Hydroquinone monomethyl ether (150-76-5)

Log Pow 1.34

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Other adverse effects : This substance may be hazardous to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Sewage disposal recommendations : Do not dispose of waste into sewer.
Product/Packaging disposal recommendations : May be incinerated. Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to licensed waste disposal facility.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

14.1. UN number

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR) : Not applicable
UN-No. (IMDG) : Not applicable
UN-No. (IATA) : Not applicable
UN-No. (ADN) : Not applicable
UN-No. (RID) : Not applicable

14.2. UN proper shipping name

Proper Shipping Name (ADR) : Not applicable
Proper Shipping Name (IMDG) : Not applicable
Proper Shipping Name (IATA) : Not applicable
Proper Shipping Name (ADN) : Not applicable
Proper Shipping Name (RID) : Not applicable

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : Not applicable

IATA

Transport hazard class(es) (IATA) : Not applicable

ADN

Transport hazard class(es) (ADN) : Not applicable

RID

Transport hazard class(es) (RID) : Not applicable

14.4. Packing group

Packing group (ADR) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable
Packing group (ADN) : Not applicable
Packing group (RID) : Not applicable

14.5. Environmental hazards

Dangerous for the environment : No
Marine pollutant : No

(METHACRYLOXYMETHYL)METHYLDIMETHOXYSILANE

Safety Data Sheet

Other information : This product is Combustible as defined by the US Department of Transportation (DOT). It is regulated for transport in the US in container > 119 gallons (450 liters). The product is not regulated for transport by the IATA, ADR/RID, ADNR or the IMDG regulations.

14.6. Special precautions for user

- Overland transport

Not applicable

- Transport by sea

Not applicable

- Air transport

Not applicable

- Inland waterway transport

Not applicable

- Rail transport

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

No REACH Annex XVII restrictions

(METHACRYLOXYMETHYL)METHYLDIMETHOXYSILANE is not on the REACH Candidate List

(METHACRYLOXYMETHYL)METHYLDIMETHOXYSILANE is not on the REACH Annex XIV List

(METHACRYLOXYMETHYL)METHYLDIMETHOXYSILANE is not subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.

(METHACRYLOXYMETHYL)METHYLDIMETHOXYSILANE is not subject to Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Directive 79/117/EEC

% Volatiles : < 5 %

15.1.2. National regulations

Germany

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen : The substance is not listed

SZW-lijst van mutagene stoffen : The substance is not listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : The substance is not listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : The substance is not listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : The substance is not listed

Denmark

Class for fire hazard : Class III-1

Store unit : 50 liter

Classification remarks : Flammable according to the Danish Ministry of Justice; Emergency management guidelines for the storage of flammable liquids must be followed

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Abbreviations and acronyms:

(METHACRYLOXYMETHYL)METHYLDIMETHOXYSILANE

Safety Data Sheet

Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor

Other information

: Prepared by safety and environmental affairs.

Full text of H- and EUH-statements:

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
H302	Harmful if swallowed.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.

SDS EU (REACH Annex II) - Custom

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2019 Gelest Inc. Morrisville, PA 19067

The logo for Gelest, featuring the word "Gelest" in a large, white, serif font. The letters are set against a light blue background that is shaped like a right-angled triangle pointing to the right. The "G" is partially cut off on the left side of the image.