



2-[METHOXPOLY(ETHYLENOXY)6-9PROPYL]DIMETHYLMETHOXYSILANE, tech-90

Safety Data Sheet SIM6492.58

Date of issue: 07/21/2015 Version: 1.0

SECTION 1: Identification

1.1. Identification

| | |
|-----------------|---|
| Product name | : 2-[METHOXPOLY(ETHYLENOXY)6-9PROPYL]DIMETHYLMETHOXYSILANE, tech-90 |
| Product code | : SIM6492.58 |
| Product form | : Substance |
| Physical state | : Liquid |
| Formula | : CH ₃ O(C ₂ H ₄ O) ₆₋₉ (CH ₂) ₃ (CH ₃) ₂ Si(OCH ₃) |
| Synonyms | : DIMETHYLMETHOXYSILYLPROPYLPOLYETHYLENEOXIDE METHYL ETHER |
| Chemical family | : ORGANOMETHOXYSILANE |

1.2. Recommended use and restrictions on use

| | |
|-----------------|-------------------------|
| Recommended use | : Chemical intermediate |
|-----------------|-------------------------|

1.3. Supplier

GELEST, INC.

11 East Steel Road
Morrisville, PA 19067
USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com

1.4. Emergency telephone number

| | |
|------------------|---|
| Emergency number | : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International) |
|------------------|---|

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

| | |
|---|------------------------------------|
| Flammable liquids Category 4 | H227 Combustible liquid |
| Serious eye damage/eye irritation Category 2A | H319 Causes serious eye irritation |
| Full text of H statements : see section 16 | |

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



| | |
|-----------------------------------|--|
| Signal word (GHS US) | : Warning |
| Hazard statements (GHS US) | : H227 - Combustible liquid H319 - Causes serious eye irritation |
| Precautionary statements (GHS US) | : P280 - Wear protective gloves/protective clothing/eye protection/face protection. P210 - Keep away from heat, open flames, sparks. - No smoking. P264 - Wash hands thoroughly after handling. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P337+P313 - If eye irritation persists: Get medical advice/attention. P370+P378 - In case of fire: Use water spray, foam, carbon dioxide, dry chemical to extinguish. P403+P235 - Keep in a cool place P501 - Dispose of contents/container to licensed waste disposal facility. |

2.3. Hazards not otherwise classified (HNOC)

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

| | |
|----------------|---|
| Substance type | : Mono-constituent |
| Name | : 2-[METHOXPOLY(ETHYLENOXY)6-9PROPYL]DIMETHYLMETHOXYSILANE, tech-90 |
| CAS-No. | : Not found |

2-[METHOXPOLY(ETHYLENOXY)6-9PROPYL]DIMETHYLMETHOXYSILANE, tech-90

Safety Data Sheet

| Name | Product identifier | % | GHS-US classification |
|---|--------------------|------|--|
| 2-[METHOXPOLY(ETHYLENOXY)6-9PROPYL]DIMETHYLMETHOXYSILANE, tech-90 | | > 95 | Eye Irrit. 2A, H319 |
| Methanol | (CAS-No.) 67-56-1 | | Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 1, H370 STOT SE 3, H336 |

Full text of hazard classes and H-statements : see section 16

3.2. Mixtures

Not applicable

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.
- First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
- First-aid measures after skin contact : Wash with plenty of soap and water.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
- First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Get medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects after inhalation : May cause irritation to the respiratory tract. Overexposure may cause: Cough. Headache. Nausea.
- Symptoms/effects after skin contact : May cause skin irritation.
- Symptoms/effects after eye contact : Causes serious eye irritation.
- Symptoms/effects after ingestion : Oral toxicity is associated with methanol, the solvent and a hydrolysis product which causes nausea, vomiting, headache, visual effects including blindness.
- Chronic symptoms : On contact with water this compound liberates methanol which is known to have a chronic effect on the central nervous system. Methanol may effect the central nervous system resulting in persistent or recurring headaches or impaired vision.

4.3. Immediate medical attention and special treatment, if necessary

NOTE TO PHYSICIAN: This product reacts with water in the acid contents of the stomach to form methanol. The combination of visual disturbances, metabolic acidosis and formic acid in urine is evidence of methanol poisoning. The therapeutic intravenous administration of ethanol (10 mls/hour) allows methanol to be preferentially oxidized and reduces production of methanol metabolites. Acidosis must be treated with intravenous administration of sodium bicarbonate and methanol elimination may be increased by hemodialysis, as indicated. Treatment should be based on blood methanol levels and acid-base balance.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Water spray. Foam. Carbon dioxide. Dry chemical.
- Unsuitable extinguishing media : None known.

5.2. Specific hazards arising from the chemical

- Fire hazard : Combustible liquid. Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.

5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Use water spray to cool exposed surfaces. Exercise caution when fighting any chemical fire.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Avoid all eye and skin contact and do not breathe vapor and mist.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

- Protective equipment : Wear protective equipment as described in Section 8.
- Emergency procedures : Evacuate unnecessary personnel.

2-[METHOXYPOLY(ETHYLENOXY)6-9PROPYL]DIMETHYLMETHOXYSILANE, tech-90

Safety Data Sheet

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or shovel spills into appropriate container for disposal. Use only non-sparking tools.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Keep away from heat, open flames, sparks. - No smoking.
Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapor and mist. Provide good ventilation in process area to prevent accumulation of vapors. Take precautionary measures against static discharge. Use only in well ventilated areas.
Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.
Storage conditions : Keep container tightly closed.
Incompatible materials : Moisture. Water.
Storage area : Store in a well-ventilated place. Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| Methanol (67-56-1) | | |
|--------------------|---------------------------------------|-----------------------|
| ACGIH | ACGIH TWA (ppm) | 200 ppm |
| ACGIH | ACGIH STEL (ppm) | 250 ppm |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 260 mg/m ³ |
| OSHA | OSHA PEL (TWA) (ppm) | 200 ppm |
| IDLH | US IDLH (ppm) | 6000 ppm |
| NIOSH | NIOSH REL (TWA) (mg/m ³) | 260 mg/m ³ |
| NIOSH | NIOSH REL (TWA) (ppm) | 200 ppm |
| NIOSH | NIOSH REL (STEL) (mg/m ³) | 325 mg/m ³ |
| NIOSH | NIOSH REL (STEL) (ppm) | 250 ppm |

8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Hand protection:

Neoprene or nitrile rubber gloves

Eye protection:

Chemical goggles. Contact lenses should not be worn

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

2-[METHOXYPOLY(ETHYLENOXY)6-9PROPYL]DIMETHYLMETHOXYSILANE, tech-90

Safety Data Sheet

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified organic vapor (black cartridge) respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|--|
| Physical state | : Liquid |
| Appearance | : Clear liquid. |
| Molecular mass | : 427 - 559 g/mol |
| Color | : Straw. |
| Odor | : Mild. |
| Odor threshold | : No data available |
| Refractive index | : 1.444 |
| pH | : No data available |
| Relative evaporation rate (butyl acetate=1) | : No data available |
| Melting point | : No data available |
| Freezing point | : < 0 °C |
| Boiling point | : > 250 °C |
| Flash point | : > 65 °C |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Flammability (solid, gas) | : Combustible liquid |
| Vapor pressure | : No data available |
| Relative vapor density at 20 °C | : > 1 |
| Relative density | : 1.01 |
| Solubility | : Soluble in water. Reacts with water. |
| Log Pow | : No data available |
| Log Kow | : No data available |
| Viscosity, kinematic | : 20 - 35 cSt |
| Viscosity, dynamic | : No data available |
| Explosive properties | : No data available |
| Oxidizing properties | : No data available |
| Explosion limits | : No data available |

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable in sealed containers.

10.3. Possibility of hazardous reactions

Reacts with water and moisture in air, liberating methanol.

10.4. Conditions to avoid

Heat. Sparks. Open flame.

10.5. Incompatible materials

Moisture. Water.

10.6. Hazardous decomposition products

Methanol. Organic acid vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

| Methanol (67-56-1) | |
|---------------------------|--------------------------------|
| LC50 inhalation rat (ppm) | 22500 ppm (Exposure time: 8 h) |
| ATE US (oral) | 100 mg/kg body weight |

2-[METHOXYPOLY(ETHYLENOXY)6-9PROPYL]DIMETHYLMETHOXYSILANE, tech-90

Safety Data Sheet

| Methanol (67-56-1) | |
|--|---|
| ATE US (dermal) | 300 mg/kg body weight |
| ATE US (vapors) | 3 mg/l/4h |
| Skin corrosion/irritation | : Not classified |
| Serious eye damage/irritation | : Causes serious eye irritation. |
| Respiratory or skin sensitization | : Not classified |
| Germ cell mutagenicity | : Not classified |
| Carcinogenicity | : Not classified |
| Reproductive toxicity | : Not classified |
| Specific target organ toxicity – single exposure | : Not classified |
| Specific target organ toxicity – repeated exposure | : Not classified |
| Aspiration hazard | : Not classified |
| Symptoms/effects after inhalation | : May cause irritation to the respiratory tract. Overexposure may cause: Cough. Headache. Nausea. |
| Symptoms/effects after skin contact | : May cause skin irritation. |
| Symptoms/effects after eye contact | : Causes serious eye irritation. |
| Symptoms/effects after ingestion | : Oral toxicity is associated with methanol, the solvent and a hydrolysis product which causes nausea, vomiting, headache, visual effects including blindness. |
| Chronic symptoms | : On contact with water this compound liberates methanol which is known to have a chronic effect on the central nervous system. Methanol may effect the central nervous system resulting in persistent or recurring headaches or impaired vision. |
| Reason for classification | : Expert judgment |

SECTION 12: Ecological information

12.1. Toxicity

| Methanol (67-56-1) | |
|--------------------|--|
| LC50 fish 1 | 28200 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) |
| LC50 fish 2 | > 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static]) |

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

| Methanol (67-56-1) | |
|--------------------|-------|
| BCF fish 1 | < 10 |
| Log Pow | -0.77 |

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

| | |
|---------------------------|---|
| Other adverse effects | : This substance may be hazardous to the environment. |
| Effect on the ozone layer | : No additional information available |

SECTION 13: Disposal considerations

13.1. Disposal methods

| | |
|--|--|
| Product/Packaging disposal recommendations | : May be incinerated. Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to licensed waste disposal facility. |
| Ecology - waste materials | : Avoid release to the environment. |

SECTION 14: Transport information

14.1. UN number

| | |
|------------|--------|
| DOT NA no. | NA1993 |
|------------|--------|

14.2. UN proper shipping name

| | |
|--------------------------------|--|
| Transport document description | : NA1993 COMBUSTIBLE LIQUID, N.O.S. (2-[METHOXY(POLYETHYLENEOXY)9-12PROPYL]TRIMETHOXYSILANE), 3, III |
|--------------------------------|--|

2-[METHOXPOLY(ETHYLENOXY)6-9PROPYL]DIMETHYLMETHOXYSILANE, tech-90

Safety Data Sheet

| | |
|---|--|
| Proper Shipping Name (DOT) | : COMBUSTIBLE LIQUID, N.O.S. (2-[METHOXY(POLYETHYLENOXY)9-12PROPYL]TRIMETHOXYSILANE) |
| Class (DOT) | : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120 |
| Packing group (DOT) | : III - Minor Danger |
| DOT Packaging Non Bulk (49 CFR 173.xxx) | : 203 |
| DOT Packaging Bulk (49 CFR 173.xxx) | : 241 |
| DOT Packaging Exceptions (49 CFR 173.xxx) | : 150 |
| DOT Symbols | : D - Proper shipping name for domestic use only, or to and from Canada, G - Identifies PSN requiring a technical name |

14.3. Additional information

| | |
|-------------------|--|
| Other information | : This product is Combustible as defined by the US Department of Transportation (DOT). It is regulated for transport in the US in container > 119 gallons (450 liters). The product is not regulated for transport by the IATA, ADR/RID, ADNR or the IMDG regulations. |
|-------------------|--|

Transport by sea

| | |
|-----------------------------|---|
| DOT Vessel Stowage Location | : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel. |
|-----------------------------|---|

Air transport

| | |
|--|---------|
| DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) | : 60 L |
| DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) | : 220 L |

SECTION 15: Regulatory information

15.1. US Federal regulations

2-[METHOXPOLY(ETHYLENOXY)6-9PROPYL]DIMETHYLMETHOXYSILANE, tech-90 (Not found)

| | |
|--------------------------|---|
| TSCA Exemption/Exclusion | CAUTION: This material is supplied for research and development purposes subject to the R&D exemption under TSCA, 40 CFR 720.36, and must meet the requirements of the exemption, including supervision by a "technically qualified individual" as defined by 40 CFR 720.3(ee). The use of this material for "commercial purposes" as defined by 40 CFR 720.3(r) is not permitted in the United States. |
|--------------------------|---|

Methanol (67-56-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313

| | |
|---------------------------------------|-----|
| SARA Section 313 - Emission Reporting | 1 % |
|---------------------------------------|-----|

2-[METHOXPOLY(ETHYLENOXY)6-9PROPYL]DIMETHYLMETHOXYSILANE, tech-90

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

Methanol (67-56-1)

Listed on the Canadian DSL (Domestic Substances List)

| | |
|----------------------|---|
| WHMIS Classification | Class B Division 2 - Flammable Liquid Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects |
|----------------------|---|

EU-Regulations

Methanol (67-56-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

2-[METHOXYPOLY(ETHYLENOXY)6-9PROPYL]DIMETHYLMETHOXYSIANE, tech-90

Safety Data Sheet

Methanol (67-56-1)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Japanese Poisonous and Deleterious Substances Control Law
Listed on the Canadian IDL (Ingredient Disclosure List)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)

15.3. US State regulations

WARNING: This product can expose you to Methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Methanol (67-56-1)

| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significant risk level (NSRL) | Maximum allowable dose level (MADL) |
|---|---|---|---|----------------------------------|-------------------------------------|
| No | Yes | No | No | | |

Methanol (67-56-1)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Full text of H-phrases::

| | |
|------|-----------------------------------|
| H225 | Highly flammable liquid and vapor |
| H227 | Combustible liquid |
| H301 | Toxic if swallowed |
| H311 | Toxic in contact with skin |
| H315 | Causes skin irritation |
| H318 | Causes serious eye damage |
| H319 | Causes serious eye irritation |
| H331 | Toxic if inhaled |
| H336 | May cause drowsiness or dizziness |
| H370 | Causes damage to organs |

Abbreviations and acronyms

: Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor.

Hazard Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur
Flammability : 2 Moderate Hazard - Materials which must be moderately heated or exposed to high ambient temperatures before ignition will occur. Includes liquids having a flash point at or above 100 F but below 200 F. (Classes II & IIIA)
Physical : 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.

Prepared by safety and environmental affairs.

Date of issue: 07/21/2015

Version: 1.0

2-[METHOXPOLY(ETHYLENOXY)6- 9PROPYL]DIMETHYLMETHOXYSILANE, tech-90

Safety Data Sheet

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2019 Gelest Inc. Morrisville, PA 19067

