

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form	: Substance
Physical state	: Liquid
Substance name	: PHENYLMETHYLDIMETHOXYISILANE
Product code	: SIP6740.0
Formula	: C <sub>9</sub> H <sub>14</sub> O <sub>2</sub> Si
Synonyms	: METHYLPHENYLDIMETHOXYISILANE; DIMETHOXYMETHYLPHENYLSILANE
Chemical family	: ORGANOMETHOXYISILANE

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Use of the substance/mixture : Chemical intermediate

#### 1.2.2. Uses advised against

No additional information available

### 1.3. Details of the supplier of the safety data sheet

#### GELEST, INC.

11 East Steel Road  
Morrisville, PA 19067

#### USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

[info@gelest.com](mailto:info@gelest.com) - [www.gelest.com](http://www.gelest.com)

#### GELEST INC.

Fritz-Klatte-Strasse 8  
65933 Frankfurt

#### Germany

T +49 (0) 69 3535106-500 - F +49 (0) 69 3535106-501 - (M-F): 8:00 AM - 4:00 PM

[info@gelestde.com](mailto:info@gelestde.com) - [www.gelestde.com](http://www.gelestde.com)

### 1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (oral), Category 4	H302
Serious eye damage/eye irritation, Category 2	H319
Full text of H statements : see section 16	

#### Adverse physicochemical, human health and environmental effects

No additional information available

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07

Signal word (CLP) :

Warning

Hazard statements (CLP) :

H302 - Harmful if swallowed.  
H319 - Causes serious eye irritation.

Precautionary statements (CLP) :

P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

# PHENYLMETHYLDIMETHOXY SILANE

## Safety Data Sheet

contact lenses, if present and easy to do. Continue rinsing.  
P270 - Do not eat, drink or smoke when using this product.  
P301+P312 - IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell.  
P330 - Rinse mouth.  
P264 - Wash hands thoroughly after handling.

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Substance type : Mono-constituent  
Name : PHENYLMETHYLDIMETHOXY SILANE  
CAS-No. : 3027-21-2  
EC-No. : 221-192-4

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Phenylmethyldimethoxysilane	(CAS-No.) 3027-21-2 (EC-No.) 221-192-4	> 95	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319
Methanol	(CAS-No.) 67-56-1 (EC-No.) 200-659-6 (EC Index-No.) 603-001-00-X		Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 STOT SE 1, H370

#### Specific concentration limits:

Name	Product identifier	Specific concentration limits
Methanol	(CAS-No.) 67-56-1 (EC-No.) 200-659-6 (EC Index-No.) 603-001-00-X	( 3 =<C < 10) STOT SE 2, H371 ( 10 =<C < 100) STOT SE 1, H370

Full text of H-statements: see section 16

### 3.2. Mixtures

Not applicable

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If you feel unwell, seek medical advice.

First-aid measures after skin contact : Wash with plenty of water/....

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.

First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Call a POISON CENTER/doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : May cause irritation to the respiratory tract. Overexposure may cause: Cough. Headache. Nausea.

Symptoms/effects after skin contact : May cause skin irritation.

Symptoms/effects after eye contact : Causes serious eye irritation.

Symptoms/effects after ingestion : Oral toxicity is associated with methanol, the solvent and a hydrolysis product which causes nausea, vomiting, headache, visual effects including blindness.

Chronic symptoms : On contact with water this compound liberates methanol which is known to have a chronic effect on the central nervous system.

### 4.3. Indication of any immediate medical attention and special treatment needed

NOTE TO PHYSICIAN: This product reacts with water in the acid contents of the stomach to form methanol. The combination of visual disturbances, metabolic acidosis and formic acid in urine is evidence of methanol poisoning. The therapeutic intravenous administration of ethanol (10 mls/hour) allows methanol to be preferentially oxidized and reduces production of methanol metabolites. Acidosis must be treated with intravenous administration of sodium bicarbonate and methanol elimination may be increased by hemodialysis, as indicated. Treatment should be based on blood methanol levels and acid-base balance.

# PHENYLMETHYLDIMETHOXY SILANE

## Safety Data Sheet

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Foam. Carbon dioxide. Dry chemical.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Combustible liquid. Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.

#### 5.3. Advice for firefighters

Firefighting instructions : Use water spray to cool exposed surfaces. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Avoid all eye and skin contact and do not breathe vapour and mist.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges.

##### 6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or shovel spills into appropriate container for disposal.

#### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Additional hazards when processed : Keep away from heat, open flames, sparks. No smoking.

Precautions for safe handling : Use only in well ventilated areas. Avoid all eye and skin contact and do not breathe vapour and mist. Take precautionary measures against static discharge. Ground/bond container and receiving equipment. Use only non-sparking tools.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before reuse.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Keep container tightly closed.

Incompatible materials : Water : Moisture.

Storage area : Store in a well-ventilated place. Store away from heat.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Methanol (67-56-1)		
EU	IOELV TWA (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
EU	IOELV TWA (ppm)	200 ppm
Austria	MAK (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
Austria	MAK (ppm)	200 ppm
Austria	MAK Short time value (mg/m <sup>3</sup> )	1040 mg/m <sup>3</sup>
Austria	MAK Short time value (ppm)	800 ppm
Belgium	Limit value (mg/m <sup>3</sup> )	266 mg/m <sup>3</sup>
Belgium	Limit value (ppm)	200 ppm
Belgium	Short time value (mg/m <sup>3</sup> )	333 mg/m <sup>3</sup>
Belgium	Short time value (ppm)	250 ppm
Bulgaria	OEL TWA (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
Bulgaria	OEL TWA (ppm)	200 ppm

# PHENYLMETHYLDIMETHOXSILANE

## Safety Data Sheet

Methanol (67-56-1)		
Cyprus	OEL TWA (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
Cyprus	OEL TWA (ppm)	200 ppm
France	VLE (mg/m <sup>3</sup> )	1300 mg/m <sup>3</sup>
France	VLE (ppm)	1000 ppm
France	VME (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup> (restrictive limit)
France	VME (ppm)	200 ppm (restrictive limit)
Germany	TRGS 900 Occupational exposure limit value (mg/m <sup>3</sup> )	270 mg/m <sup>3</sup> (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Germany	TRGS 900 Occupational exposure limit value (ppm)	200 ppm (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Germany	TRGS 903 Biological limit value	30 mg/l (Medium: urine - Time: end of shift - Parameter: Methanol) 30 mg/l (Medium: urine - Time: end of several shifts - Parameter: Methanol (for long-term exposures))
Gibraltar	Eight hours mg/m <sup>3</sup>	260 mg/m <sup>3</sup>
Gibraltar	Eight hours ppm	200 ppm
Greece	OEL TWA (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
Greece	OEL TWA (ppm)	200 ppm
Greece	OEL STEL (mg/m <sup>3</sup> )	325 mg/m <sup>3</sup>
Greece	OEL STEL (ppm)	250 ppm
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	200 ppm
Italy - Portugal - USA ACGIH	ACGIH STEL (ppm)	250 ppm
Italy	OEL TWA (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
Italy	OEL TWA (ppm)	200 ppm
Latvia	OEL TWA (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
Latvia	OEL TWA (ppm)	200 ppm
USA IDLH	US IDLH (ppm)	6000 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m <sup>3</sup> )	325 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (STEL) (ppm)	250 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
Spain	VLA-ED (mg/m <sup>3</sup> )	266 mg/m <sup>3</sup> (indicative limit value)
Spain	VLA-ED (ppm)	200 ppm (indicative limit value)
Switzerland	KZGW (mg/m <sup>3</sup> )	1040 mg/m <sup>3</sup>
Switzerland	KZGW (ppm)	800 ppm
Switzerland	MAK (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
Switzerland	MAK (ppm)	200 ppm
Netherlands	Grenswaarde TGG 8H (mg/m <sup>3</sup> )	133 mg/m <sup>3</sup>
Netherlands	Grenswaarde TGG 8H (ppm)	100 ppm
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	266 mg/m <sup>3</sup>
United Kingdom	WEL TWA (ppm)	200 ppm
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	333 mg/m <sup>3</sup>
United Kingdom	WEL STEL (ppm)	250 ppm
Czech Republic	Expoziční limity (PEL) (mg/m <sup>3</sup> )	250 mg/m <sup>3</sup>
Denmark	Grænseværdie (langvarig) (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
Denmark	Grænseværdie (langvarig) (ppm)	200 ppm
Finland	HTP-arvo (8h) (mg/m <sup>3</sup> )	270 mg/m <sup>3</sup>
Finland	HTP-arvo (8h) (ppm)	200 ppm
Finland	HTP-arvo (15 min)	330 mg/m <sup>3</sup>
Finland	HTP-arvo (15 min) (ppm)	250 ppm
Hungary	AK-érték	260 mg/m <sup>3</sup>

# PHENYLMETHYLDIMETHOXY SILANE

## Safety Data Sheet

Methanol (67-56-1)		
Ireland	OEL (8 hours ref) (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
Ireland	OEL (8 hours ref) (ppm)	200 ppm
Ireland	OEL (15 min ref) (mg/m <sup>3</sup> )	780 mg/m <sup>3</sup> (calculated)
Ireland	OEL (15 min ref) (ppm)	600 ppm (calculated)
Lithuania	IPRV (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
Lithuania	IPRV (ppm)	200 ppm
Malta	OEL TWA (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
Malta	OEL TWA (ppm)	200 ppm
Norway	Grenseverdier (AN) (mg/m <sup>3</sup> )	130 mg/m <sup>3</sup>
Norway	Grenseverdier (AN) (ppm)	100 ppm
Norway	Grenseverdier (Korttidsverdi) (mg/m <sup>3</sup> )	130 mg/m <sup>3</sup>
Norway	Grenseverdier (Korttidsverdi) (ppm)	100 ppm
Poland	NDS (mg/m <sup>3</sup> )	100 mg/m <sup>3</sup>
Poland	NDSch (mg/m <sup>3</sup> )	300 mg/m <sup>3</sup>
Romania	OEL TWA (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
Romania	OEL TWA (ppm)	200 ppm
Romania	OEL STEL (ppm)	5 ppm
Slovakia	NPHV (priemerná) (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
Slovakia	NPHV (priemerná) (ppm)	200 ppm
Sweden	nivågränsvärde (NVG) (mg/m <sup>3</sup> )	250 mg/m <sup>3</sup>
Sweden	nivågränsvärde (NVG) (ppm)	200 ppm
Sweden	kortidsvärde (KTV) (mg/m <sup>3</sup> )	350 mg/m <sup>3</sup>
Sweden	kortidsvärde (KTV) (ppm)	250 ppm
Canada (Quebec)	VECD (mg/m <sup>3</sup> )	328 mg/m <sup>3</sup>
Canada (Quebec)	VECD (ppm)	250 ppm
Canada (Quebec)	VEMP (mg/m <sup>3</sup> )	262 mg/m <sup>3</sup>
Canada (Quebec)	VEMP (ppm)	200 ppm
Australia	TWA (mg/m <sup>3</sup> )	262 mg/m <sup>3</sup>
Australia	TWA (ppm)	200 ppm
Australia	STEL (mg/m <sup>3</sup> )	328 mg/m <sup>3</sup>
Australia	STEL (ppm)	250 ppm
Portugal	OEL TWA (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup> (indicative limit value)
Portugal	OEL TWA (ppm)	200 ppm (indicative limit value)
Portugal	OEL STEL (ppm)	250 ppm
Portugal	OEL chemical category (PT)	skin - potential for cutaneous exposure indicative limit value

### 8.2. Exposure controls

#### Appropriate engineering controls:

Provide local exhaust or general room ventilation.

#### Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

#### Hand protection:

Neoprene or nitrile rubber gloves

#### Eye protection:

Chemical goggles. Contact lenses should not be worn

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

# PHENYLMETHYLDIMETHOXYSILANE

## Safety Data Sheet

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified organic vapor (black cartridge) respirator.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear liquid.
Molecular mass	: 182.29 g/mol
Colour	: Straw.
Odour	: Mild.
Odour threshold	: No data available
Refractive index	: 1.4694
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: < 0 °C
Boiling point	: 199 - 200 °C
Flash point	: 76 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Combustible liquid
Vapour pressure	: 15 mm Hg @ 91°C
Relative vapour density at 20 °C	: > 1
Relative density	: 0.9934
Solubility	: Insoluble in water. Reacts with water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

#### 9.2. Other information

No additional information available

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No additional information available

#### 10.2. Chemical stability

Stable in sealed containers.

#### 10.3. Possibility of hazardous reactions

Reacts with water and moisture in air, liberating methanol.

#### 10.4. Conditions to avoid

Heat. Sparks. Open flame.

#### 10.5. Incompatible materials

Water : Moisture.

#### 10.6. Hazardous decomposition products

Methanol. Organic acid vapors.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Harmful if swallowed.

#### PHENYLMETHYLDIMETHOXYSILANE (3027-21-2)

LD50 oral rat	892 mg/kg
---------------	-----------

#### Methanol (67-56-1)

LC50 inhalation rat (ppm)	22500 ppm (Exposure time: 8 h)
---------------------------	--------------------------------

# PHENYLMETHYLDIMETHOXYSILANE

## Safety Data Sheet

<b>Methanol (67-56-1)</b>	
ATE CLP (oral)	100 mg/kg bodyweight
ATE CLP (dermal)	300 mg/kg bodyweight
ATE CLP (vapours)	3 mg/l/4h

<b>Phenylmethyldimethoxysilane (3027-21-2)</b>	
LD50 oral rat	892 mg/kg

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Potential adverse human health effects and symptoms	: Harmful if swallowed.
Symptoms/effects after inhalation	: May cause irritation to the respiratory tract. Overexposure may cause: Cough. Headache. Nausea.
Symptoms/effects after skin contact	: May cause skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: Oral toxicity is associated with methanol, the solvent and a hydrolysis product which causes nausea, vomiting, headache, visual effects including blindness.
Chronic symptoms	: On contact with water this compound liberates methanol which is known to have a chronic effect on the central nervous system.

## SECTION 12: Ecological information

### 12.1. Toxicity

Acute aquatic toxicity	: Not classified
Chronic aquatic toxicity	: Not classified

<b>Methanol (67-56-1)</b>	
LC50 fish 1	28200 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

<b>Methanol (67-56-1)</b>	
BCF fish 1	< 10
Log Pow	-0.77

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

Other adverse effects : This substance may be hazardous to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	: Avoid release to the environment.

## SECTION 14: Transport information

### 14.1. UN number

In accordance with ADR / RID / IMDG / IATA / ADN

# PHENYLMETHYLDIMETHOXYSILANE

## Safety Data Sheet

### 14.1. UN number

UN-No. (ADR)	: Not applicable
UN-No. (IMDG)	: Not applicable
UN-No. (IATA)	: Not applicable
UN-No. (ADN)	: Not applicable
UN-No. (RID)	: Not applicable

### 14.2. UN proper shipping name

Proper Shipping Name (ADR)	: Not applicable
Proper Shipping Name (IMDG)	: Not applicable
Proper Shipping Name (IATA)	: Not applicable
Proper Shipping Name (ADN)	: Not applicable
Proper Shipping Name (RID)	: Not applicable

### 14.3. Transport hazard class(es)

#### ADR

Transport hazard class(es) (ADR)	: Not applicable
----------------------------------	------------------

#### IMDG

Transport hazard class(es) (IMDG)	: Not applicable
-----------------------------------	------------------

#### IATA

Transport hazard class(es) (IATA)	: Not applicable
-----------------------------------	------------------

#### ADN

Transport hazard class(es) (ADN)	: Not applicable
----------------------------------	------------------

#### RID

Transport hazard class(es) (RID)	: Not applicable
----------------------------------	------------------

### 14.4. Packing group

Packing group (ADR)	: Not applicable
Packing group (IMDG)	: Not applicable
Packing group (IATA)	: Not applicable
Packing group (ADN)	: Not applicable
Packing group (RID)	: Not applicable

### 14.5. Environmental hazards

Dangerous for the environment	: No
Marine pollutant	: No
Other information	: This product is Combustible as defined by the US Department of Transportation (DOT). It is regulated for transport in the US in container > 119 gallons (450 liters). The product is not regulated for transport by the IATA, ADR/RID, ADN or the IMDG regulations.

### 14.6. Special precautions for user

#### - Overland transport

No data available

#### - Transport by sea

No data available

#### - Air transport

No data available

#### - Inland waterway transport

No data available

#### - Rail transport

No data available

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable



# PHENYLMETHYLDIMETHOXYSILANE

## Safety Data Sheet

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### 15.1.1. EU-Regulations

No REACH Annex XVII restrictions

PHENYLMETHYLDIMETHOXYSILANE is not on the REACH Candidate List

PHENYLMETHYLDIMETHOXYSILANE is not on the REACH Annex XIV List

PHENYLMETHYLDIMETHOXYSILANE is not subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.

PHENYLMETHYLDIMETHOXYSILANE is not subject to Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Directive 79/117/EEC

##### 15.1.2. National regulations

###### Germany

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

###### Netherlands

SZW-lijst van kankerverwekkende stoffen : The substance is not listed

SZW-lijst van mutagene stoffen : The substance is not listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : The substance is not listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : The substance is not listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : The substance is not listed

###### Denmark

Class for fire hazard : Class III-1

Store unit : 50 liter

Classification remarks : Flammable according to the Danish Ministry of Justice; Emergency management guidelines for the storage of flammable liquids must be followed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

### SECTION 16: Other information

Abbreviations and acronyms:

Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor

Other information : Prepared by safety and environmental affairs.

Full text of H- and EUH-statements:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
STOT SE 1	Specific target organ toxicity — single exposure, Category 1
STOT SE 2	Specific target organ toxicity — Single exposure, Category 2
H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H319	Causes serious eye irritation.

# PHENYLMETHYLDIMETHOXSILANE

## Safety Data Sheet

H331	Toxic if inhaled.
H370	Causes damage to organs.
H371	May cause damage to organs.

SDS EU (REACH Annex II) - Custom

*The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.*

© 2019 Gelest Inc. Morrisville, PA 19067

