

PLATINUM-DIVINYLTETRAMETHYLDISILOXANE COMPLEX; 5% Pt in xylene

Safety Data Sheet SIP6831.5

Issue date: 01/09/2015

Revision date: 05/12/2020

Version: 2.2

SECTION 1: Identification

1.1. Identification

Product name	: PLATINUM-DIVINYLTETRAMETHYLDISILOXANE COMPLEX; 5% Pt in xylene
Product code	: SIP6831.5
Product form	: Mixture
Physical state	: Liquid
Formula	: C ₂₄ H ₅₄ O ₃ Pt ₂ Si ₆
Synonyms	: KARSTEDT CATALYST DIETHENYLTETRAMETHYLDISILOXANE-PLATINUM COMPLEX COMPLEXES, DISILOXANE, 1,3-DIETHENYL-1,1,3,3-TETRAMETHYL PLATINUM, 1,3-DIETHENYL-1,1,3,3-TETRAMETHYLDISILOXANE COMPLEXES
Chemical family	: ORGANOSILOXANE

1.2. Recommended use and restrictions on use

Recommended use	: Chemical intermediate
-----------------	-------------------------

1.3. Supplier

GELEST, INC.

11 East Steel Road
Morrisville, PA 19067

USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com

1.4. Emergency telephone number

Emergency number	: CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)
------------------	---

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 3	H226 Flammable liquid and vapor
Acute toxicity (dermal) Category 4	H312 Harmful in contact with skin
Skin corrosion/irritation Category 2	H315 Causes skin irritation
Serious eye damage/eye irritation Category 2A	H319 Causes serious eye irritation
Specific target organ toxicity (single exposure) Category 3	H335 May cause respiratory irritation
Specific target organ toxicity (repeated exposure) Category 2	H373 May cause damage to organs through prolonged or repeated exposure
Hazardous to the aquatic environment - Acute Hazard Category 1	H400 Very toxic to aquatic life

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)



Signal word (GHS US)

: Warning

Hazard statements (GHS US)

: H226 - Flammable liquid and vapor
H312 - Harmful in contact with skin
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H335 - May cause respiratory irritation
H373 - May cause damage to organs through prolonged or repeated exposure
H400 - Very toxic to aquatic life

Precautionary statements (GHS US)

: P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P210 - Keep away from heat, open flames, sparks. - No smoking.
P240 - Ground/Bond container and receiving equipment.
P241 - Use explosion-proof electrical equipment.
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P260 - Do not breathe vapors.
P264 - Wash hands thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.

PLATINUM-DIVINYLTETRAMETHYLDISILOXANE COMPLEX; 5% Pt in xylene

Safety Data Sheet

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P303+P361+P353 - If on skin (or hair): take off immediately all contaminated clothing. rinse skin with water/shower
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P337+P313 - If eye irritation persists: Get medical advice/attention.
P314 - Get medical advice/attention if you feel unwell.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use water spray or fog, foam, carbon dioxide, dry chemical to extinguish.
P391 - Collect spillage.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P403+P235 - Keep in a cool place
P405 - Store locked up.
P501 - Dispose of contents/container to licensed waste disposal facility..

2.3. Hazards not otherwise classified (HNOC)

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Xylene	(CAS-No.) 1330-20-7	> 90	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 STOT RE 2, H373 Aquatic Acute 1, H400
Platinum-divinyltetramethyldisiloxane complex	(CAS-No.) 68478-92-2	< 10	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2A, H319

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.
First-aid measures after skin contact	: Wash with plenty of soap and water. Get medical advice/attention.
First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
First-aid measures after ingestion	: Never give anything by mouth to an unconscious person. Get medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects	: Causes damage to organs.
Symptoms/effects after inhalation	: May cause respiratory irritation. May be harmful if inhaled.
Symptoms/effects after skin contact	: Causes skin irritation. Harmful in contact with skin. Repeated exposure to this material can result in absorption through skin causing significant health hazard.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: May be harmful if swallowed.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water fog. Water spray. Foam. Carbon dioxide. Dry chemical.
Unsuitable extinguishing media	: None known.

PLATINUM-DIVINYLTETRAMETHYLDISILOXANE COMPLEX; 5% Pt in xylene

Safety Data Sheet

5.2. Specific hazards arising from the chemical

- Fire hazard : Flammable liquid and vapor. Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.
- Explosion hazard : May form flammable/explosive vapor-air mixture.

5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Avoid all eye and skin contact and do not breathe vapor and mist.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Evacuate area. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

- Protective equipment : Wear protective equipment as described in Section 8.
- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
- Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Use only non-sparking tools.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- Precautions for safe handling : Avoid breathing vapors. Ground/bond container and receiving equipment. Take precautionary measures against static discharge. Use only outdoors or in a well-ventilated area. Use only non-sparking tools.
- Hygiene measures : Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof electrical equipment.
- Storage conditions : Keep container tightly closed. Keep in a cool place. Store locked up.
- Incompatible materials : Oxidizing agent.
- Storage area : Store in a well-ventilated place. Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Xylene (1330-20-7)		
ACGIH	ACGIH TWA (ppm)	100 ppm
ACGIH	ACGIH STEL (ppm)	150 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	435 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm

8.2. Appropriate engineering controls

- Appropriate engineering controls : Provide local exhaust or general room ventilation.

PLATINUM-DIVINYLTETRAMETHYLDISILOXANE COMPLEX; 5% Pt in xylene

Safety Data Sheet

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Hand protection:

Neoprene or nitrile rubber gloves

Eye protection:

Chemical goggles. Contact lenses should not be worn

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified organic vapor (black cartridge) respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Hazy liquid.
Molecular mass	: 474.68 g/mol
Color	: Orange.
Odor	: Characteristic. Mild.
Odor threshold	: No data available
Refractive index	: 1.4954
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: < 0 °C
Freezing point	: No data available
Boiling point	: 138 °C - initial (xylene)
Flash point	: 38 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Flammable liquid and vapor
Vapor pressure	: 7 mm Hg @ 21°C (xylene)
Relative vapor density at 20 °C	: > 1
Relative density	: 0.8852
% Volatiles	: < 90 %
Solubility	: Insoluble in water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable.

PLATINUM-DIVINYLTETRAMETHYLDISILOXANE COMPLEX; 5% Pt in xylene

Safety Data Sheet

10.3. Possibility of hazardous reactions

Will generate hydrogen gas in presence of hydridosilanes and protic materials such as water and alcohol.

10.4. Conditions to avoid

Heat. Open flame. Sparks.

10.5. Incompatible materials

Oxidizing agent.

10.6. Hazardous decomposition products

Organic acid vapors. Platinum (Pt). Silicon dioxide. Xylene.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Harmful in contact with skin.
Acute toxicity (inhalation) : Not classified

PLATINUM-DIVINYLTETRAMETHYLDISILOXANE COMPLEX; 5% Pt in xylene (68478-92-2)	
ATE US (dermal)	1888.889 mg/kg body weight
Xylene (1330-20-7)	
LD50 oral rat	3500 mg/kg ; 4300 mg/kg
LD50 dermal rabbit	1700 mg/kg
LC50 inhalation rat (mg/l)	29.08 mg/l/4h
ATE US (oral)	3500 mg/kg body weight
ATE US (dermal)	1700 mg/kg body weight
ATE US (vapors)	29.08 mg/l/4h
ATE US (dust, mist)	29.08 mg/l/4h
Additional information	LCLo Inhalation man: 10,000ppm/6H

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.
Eye Irritation - rabbit: 5 mg/24H: severe (xylene)
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
None of the components in this product at concentrations >0.1% are listed by IARC, NTP, OSHA or ACGIH as a carcinogen.

Xylene (1330-20-7)	
IARC group	3 - Not classifiable

Reproductive toxicity : Not classified
Xylene has been found to have experimental reproductive effects.
STOT-single exposure : May cause respiratory irritation.
STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.
May cause damage to organs through prolonged or repeated exposure
Aspiration hazard : Not classified
Symptoms/effects after inhalation : May cause respiratory irritation. May be harmful if inhaled.
Symptoms/effects after skin contact : Causes skin irritation. Harmful in contact with skin. Repeated exposure to this material can result in absorption through skin causing significant health hazard.
Symptoms/effects after eye contact : Causes serious eye irritation.
Symptoms/effects after ingestion : May be harmful if swallowed.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Very toxic to aquatic life.

Xylene (1330-20-7)	
LC50 fish 1	13.4 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	3.82 mg/l (Exposure time: 48 h - Species: water flea)
LC50 fish 2	2.661 - 4.093 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])

PLATINUM-DIVINYLTETRAMETHYLDISILOXANE COMPLEX; 5% Pt in xylene

Safety Data Sheet

Xylene (1330-20-7)

EC50 Daphnia 2 : 0.6 mg/l (Exposure time: 48 h - Species: Gammarus lacustris)

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Xylene (1330-20-7)

BCF fish 1 : 0.6 - 15

Log Pow : 2.77 - 3.15

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other adverse effects : This substance may be hazardous to the environment.

Effect on the ozone layer : No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Sewage disposal recommendations : Do not dispose of waste into sewer.

Product/Packaging disposal recommendations : Return to manufacturer for precious metal recovery.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

14.1. UN number

UN-No.(DOT) : 1307

DOT NA No : UN1307

14.2. UN proper shipping name

Transport document description : UN1307 Xylenes (PLATINUM-DIVINYLTETRAMETHYLDISILOXANE COMPLEX; 5% Pt in xylene), 3, III

Proper Shipping Name (DOT) : Xylenes
(PLATINUM-DIVINYLTETRAMETHYLDISILOXANE COMPLEX; 5% Pt in xylene)

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Packing group (DOT) : III - Minor Danger

Hazard labels (DOT) : 3 - Flammable liquid



Dangerous for the environment : Yes

Marine pollutant : Yes



DOT Packaging Non Bulk (49 CFR 173.xxx) : 203

DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Packaging Exceptions (49 CFR 173.xxx) : 150

14.3. Additional information

Emergency Response Guide (ERG) Number : 130

Other information : No supplementary information available.

Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

PLATINUM-DIVINYLTETRAMETHYLDISILOXANE COMPLEX; 5% Pt in xylene

Safety Data Sheet

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 60 L
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L
CFR 175.75)

SECTION 15: Regulatory information

15.1. US Federal regulations

Xylene (1330-20-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313

SARA Section 313 - Emission Reporting 1 %

Platinum-divinyltetramethyldisiloxane complex (68478-92-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

Xylene (1330-20-7)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification Class B Division 2 - Flammable Liquid
Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
Class D Division 2 Subdivision B - Toxic material causing other toxic effects

Platinum-divinyltetramethyldisiloxane complex (68478-92-2)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

Xylene (1330-20-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Platinum-divinyltetramethyldisiloxane complex (68478-92-2)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

Xylene (1330-20-7)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Japanese Poisonous and Deleterious Substances Control Law
Japanese Pollutant Release and Transfer Register Law (PRTR Law)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)

Platinum-divinyltetramethyldisiloxane complex (68478-92-2)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Xylene (1330-20-7)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

PLATINUM-DIVINYLTETRAMETHYLDISILOXANE COMPLEX; 5% Pt in xylene

Safety Data Sheet

Full text of H-phrases::

H226	Flammable liquid and vapor
H312	Harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life

Abbreviations and acronyms

: Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor.

Hazard Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur
Flammability : 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 F and boiling points above 100 F. as well as liquids with flash points between 73 F and 100 F. (Classes IB & IC)
Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Prepared by safety and environmental affairs.

Issue date: 01/09/2015

Revision date: 05/12/2020

Version: 2.2

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2020 Gelest Inc. Morrisville, PA 19067