

Safety Data Sheet SIP6911.0
Date of issue: 11/17/2014 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product name : n-PROPYLDIMETHYLMETHOXYSILANE

Product code : SIP6911.0
Product form : Substance
Physical state : Liquid
Formula : C6H16OSi

Synonyms : METHOXYPROPYLDIMETHYLSILANE

Chemical family : ORGANOMETHOXYSILANE

1.2. Recommended use and restrictions on use

Recommended use : Chemical intermediate

1.3. Supplier

GELEST, INC.

11 East Steel Road Morrisville, PA 19067

USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable liquids Category 3 H226 Flammable liquid and vapor Serious eye damage/eye irritation Category 2A H319 Causes serious eye irritation

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)





Signal word (GHS US) : Warning

Hazard statements (GHS US) : H226 - Flammable liquid and vapor

H319 - Causes serious eye irritation

Precautionary statements (GHS US) : P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P210 - Keep away from heat, open flames, sparks. - No smoking.

P233 - Keep container tightly closed.

P240 - Ground/Bond container and receiving equipment

P241 - Use explosion-proof electrical equipment

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P264 - Wash hands thoroughly after handling.

P303+P361+P353 - If on skin (or hair): take off immediately all contaminated clothing. rinse

skin with water/shower

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing

P337+P313 - If eye irritation persists: Get medical advice/attention.

P370+P378 - In case of fire: Use water spray or fog, foam, carbon dioxide, dry chemical to

extinguish.

P403+P235 - Keep in a cool place

P501 - Dispose of contents/container to licensed waste disposal facility.

2.3. Hazards not otherwise classified (HNOC)

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

Print date: 04/11/2019 EN (English US) SDS ID: **SIP6911.0** Page 1

Safety Data Sheet

SECTION 3: Composition/Information on ingredients

Substances

Substance type : Multi-constituent

: n-PROPYLDIMETHYLMETHOXYSILANE Name

CAS-No. : 18182-14-4

| Name | Product identifier | % | GHS-US classification |
|-------------------------------|----------------------|-------|--|
| n-Propyldimethylmethoxysilane | (CAS-No.) 18182-14-4 | > 95 | Flam. Liq. 3, H226 Eye Irrit. 2A, H319 |
| Methanol | (CAS-No.) 67-56-1 | < 0.5 | Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 1, H370 STOT SE 3, H336 |

Full text of hazard classes and H-statements: see section 16

3.2. **Mixtures**

Not applicable

SECTION 4: First-aid measures

Description of first aid measures

: Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek First-aid measures general

medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.

First-aid measures after inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel

unwell, seek medical advice.

First-aid measures after skin contact Wash with plenty of soap and water.

First-aid measures after eye contact Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical advice/attention.

Never give anything by mouth to an unconscious person. Get medical advice/attention. First-aid measures after ingestion

Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : May cause irritation to the respiratory tract.

Symptoms/effects after skin contact May cause skin irritation. Symptoms/effects after eye contact Causes serious eye irritation. Symptoms/effects after ingestion : May be harmful if swallowed.

Chronic symptoms : On contact with water this compound liberates methanol which is known to have a chronic

effect on the central nervous system.

Immediate medical attention and special treatment, if necessary

NOTE TO PHYSICIAN: This product reacts with water in the acid contents of the stomach to form methanol. The combination of visual disturbances, metabolic acidosis and formic acid in urine is evidence of methanol poisoning. The therapeutic intravenous administration of ethanol (10 mls/hour) allows methanol to be preferentially oxidized and reduces production of methanol metabolites. Acidosis must be treated with intravenous administration of sodium bicarbonate and methanol elimination may be increased by hemodialysis, as indicated. Treatment should be based on blood methanol levels and acid-base balance.

SECTION 5: Fire-fighting measures

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Water fog. Foam. Carbon dioxide. Dry chemical.

Unsuitable extinguishing media : None known.

Specific hazards arising from the chemical

Fire hazard : Flammable liquid and vapor. Irritating fumes and organic acid vapors may develop when

material is exposed to elevated temperatures or open flame.

Special protective equipment and precautions for fire-fighters

: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any Firefighting instructions

chemical fire.

Protection during firefighting Do not enter fire area without proper protective equipment, including respiratory protection.

Avoid all eye and skin contact and do not breathe vapor and mist. Vapors extremely dangerous to eyes.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges.

Print date: 04/11/2019 EN (English US) SDS ID: SIP6911.0 2/8

Safety Data Sheet

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Environmental precautions 6.2.

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

: Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or Methods for cleaning up

shovel spills into appropriate container for disposal. Use only non-sparking tools.

Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

: Handle empty containers with care because residual vapors are flammable.

Precautions for safe handling

Avoid all eye and skin contact and do not breathe vapor and mist. Containers must be properly grounded before beginning transfer. Provide good ventilation in process area to prevent accumulation of vapors. Take precautionary measures against static discharge. Use only non-

sparking tools.

Hygiene measures

Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions Keep container tightly closed.

Incompatible materials Oxidizing agent.

Storage area Store in a well-ventilated place. Store away from heat.

SECTION 8: Exposure controls/personal protection

Control parameters 8.1.

| Methanol (67-56-1) | | |
|--------------------|--------------------------|-----------|
| ACGIH | ACGIH TWA (ppm) | 200 ppm |
| ACGIH | ACGIH STEL (ppm) | 250 ppm |
| OSHA | OSHA PEL (TWA) (mg/m³) | 260 mg/m³ |
| OSHA | OSHA PEL (TWA) (ppm) | 200 ppm |
| IDLH | US IDLH (ppm) | 6000 ppm |
| NIOSH | NIOSH REL (TWA) (mg/m³) | 260 mg/m³ |
| NIOSH | NIOSH REL (TWA) (ppm) | 200 ppm |
| NIOSH | NIOSH REL (STEL) (mg/m³) | 325 mg/m³ |
| NIOSH | NIOSH REL (STEL) (ppm) | 250 ppm |

Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Hand protection:

Neoprene or nitrile rubber gloves

Eye protection:

Chemical goggles. Contact lenses should not be worn

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Print date: 04/11/2019 EN (English US) SDS ID: SIP6911.0 3/8

Safety Data Sheet

NIOSH-certified organic vapor (black cartridge) respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Clear liquid.
Molecular mass : 132.28 g/mol
Color : No data available
Odor : Characteristic.
Odor threshold : No data available

Refractive index : 1.3927

pH : No data available

Relative evaporation rate (butyl acetate=1) : < 1 Melting point : < 0 °C

Freezing point : No data available
Boiling point : 94 - 96 °C
Flash point : 27 °C

Auto-ignition temperature : No data available Decomposition temperature : No data available

Flammability (solid, gas) : Flammable liquid and vapor

Vapor pressure : No data available

Relative vapor density at 20 °C : > 1
Relative density : 0.787
% Volatiles : 100 %

Solubility : Insoluble in water. Reacts with water.

Log Pow : No data available
Log Kow : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidizing properties : No data available
Explosion limits : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Material decomposes slowly in contact with moist air or with water liberating methanol.

10.4. Conditions to avoid

Heat. Sparks. Open flame.

10.5. Incompatible materials

Oxidizing agent.

10.6. Hazardous decomposition products

Methanol. Organic acid vapors. Silicon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

| Methanol (67-56-1) | | | |
|---------------------------|--------------------------------|--|--|
| LC50 inhalation rat (ppm) | 22500 ppm (Exposure time: 8 h) | | |
| ATE US (oral) | 100 mg/kg body weight | | |
| ATE US (dermal) | 300 mg/kg body weight | | |

Print date: 04/11/2019 EN (English US) SDS ID: **SIP6911.0** 4/8

Safety Data Sheet

| Methanol (67-56-1) | | |
|---|---|--|
| ATE US (vapors) | 3 mg/l/4h | |
| Skin corrosion/irritation | : Not classified | |
| Serious eye damage/irritation | : Causes serious eye irritation. | |
| Respiratory or skin sensitization | : Not classified | |
| Germ cell mutagenicity | : Not classified | |
| Carcinogenicity | : Not classified | |
| Reproductive toxicity | : Not classified | |
| Specific target organ toxicity – single exposure | : Not classified | |
| Specific target organ toxicity – repeated exposure | : Not classified | |
| Aspiration hazard | : Not classified | |
| Potential Adverse human health effects and symptoms | : The hydrolysis product of this compound is methanol. | |
| Symptoms/effects after inhalation | : May cause irritation to the respiratory tract. | |
| Symptoms/effects after skin contact | : May cause skin irritation. | |
| Symptoms/effects after eye contact | : Causes serious eye irritation. | |
| Symptoms/effects after ingestion | : May be harmful if swallowed. | |
| Chronic symptoms | : On contact with water this compound liberates methanol which is known to have a chronic effect on the central nervous system. | |

SECTION 12: Ecological information

12.1. Toxicity

Reason for classification

| Methanol (67-56-1) | |
|--------------------|--|
| LC50 fish 1 | 28200 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) |
| LC50 fish 2 | > 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static]) |

: Expert judgment

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

| Methanol (67-56-1) | | |
|--------------------|-------|--|
| BCF fish 1 | < 10 | |
| Log Pow | -0.77 | |

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the ozone layer : No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of

contents/container to licensed waste disposal facility.

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

14.1. UN number

UN-No.(DOT) : 1993 DOT NA no. UN1993

14.2. UN proper shipping name

Transport document description : UN1993 Flammable liquids, n.o.s. (n-PROPYLDIMETHYLMETHOXYSILANE), 3, III

Proper Shipping Name (DOT) : Flammable liquids, n.o.s.

(n-PROPYLDIMETHYLMETHOXYSILANE)

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Print date: 04/11/2019 EN (English US) SDS ID: SIP6911.0 5/8

Safety Data Sheet

Packing group (DOT) : III - Minor Danger Hazard labels (DOT) : 3 - Flammable liquid



DOT Packaging Non Bulk (49 CFR 173.xxx) : 203

DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Packaging Exceptions (49 CFR 173.xxx) : 150

DOT Symbols : G - Identifies PSN requiring a technical name

14.3. Additional information

Emergency Response Guide (ERG) Number : 128

Other information : No supplementary information available.

Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 60 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L

CFR 175.75)

SECTION 15: Regulatory information

15.1. US Federal regulations

| n-PROPYLDIME | IHYLMETHOXY | SILANE (18 | 182-14-4) |
|--------------|-------------|------------|-----------|
| | | | |

TSCA Exemption/Exclusion

CAUTION: This material is supplied for research and development purposes subject to the R&D exemption under TSCA, 40 CFR 720.36, and must meet the requirements of the exemption, including supervision by a "technically qualified individual" as defined by 40 CFR 720.3(ee). The use of this material for "commercial purposes" as defined by 40 CFR 720.3(r) is not permitted in the United States.

Methanol (67-56-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313

SARA Section 313 - Emission Reporting 1

n-Propyldimethylmethoxysilane (18182-14-4)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

| Methanol (67-56-1) |
|---|
| Listed on the Canadian DSL (Domestic Substances List) |

WHMIS Classification Class B Division 2 - Flammable Liquid

Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects

Class D Division 2 Subdivision A - Very toxic material causing other toxic effects

Class D Division 2 Subdivision B - Toxic material causing other toxic effects

EU-Regulations

Methanol (67-56-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

Print date: 04/11/2019 EN (English US) SDS ID: SIP6911.0 6/8

Safety Data Sheet

Methanol (67-56-1)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Japanese Poisonous and Deleterious Substances Control Law

Listed on the Canadian IDL (Ingredient Disclosure List)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Listed on CICR (Turkish Inventory and Control of Chemicals)

15.3. US State regulations

MARNING:

This product can expose you to Methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

| Methanol (67-56-1) | | | | | |
|--|---|---|---|----------------------------------|--|
| U.S California - Proposition 65 - Carcinogens List | U.S California - Proposition 65 - Developmental Toxicity | U.S California - Proposition 65 - Reproductive Toxicity - Female | U.S California - Proposition 65 - Reproductive Toxicity - Male | No significant risk level (NSRL) | Maximum allowable dose level (MADL) |
| No | Yes | No | No | | |

Methanol (67-56-1)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

SECTION 16: Other information

Full text of H-phrases::

| lex | t of H-philases | | |
|-----|-----------------|---|-----------------------------------|
| | H225 | | Highly flammable liquid and vapor |
| | H226 | 1 | Flammable liquid and vapor |
| - 1 | H301 | | Toxic if swallowed |
| | H311 | | Toxic in contact with skin |
| | H315 | V | Causes skin irritation |
| | H318 | 1 | Causes serious eye damage |
| ` | H319 | | Causes serious eye irritation |
| | H331 | | Toxic if inhaled |
| | H336 | | May cause drowsiness or dizziness |
| | H370 | | Causes damage to organs |

Abbreviations and acronyms

: Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemcial Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor.

Hazard Rating

Health

: 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

Flammability

: 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 F and boiling points above 100 F. as well as liquids with flash points between 73 F and 100 F. (Classes IB & IC)

Physical

: 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.

Prepared by safety and environmental affairs.

Date of issue: 11/17/2014 Version: 1.0

Print date: 04/11/2019 EN (English US) SDS ID: SIP6911.0 7/8


Safety Data Sheet

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2019 Gelest Inc. Morrisville, PA 19067



Print date: 04/11/2019 EN (English US) SDS ID: **SIP6911.0** 8/8