

Safety Data Sheet SIP6930.0 Date of issue: 09/01/2015 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product form : Substance Physical state : Liquid

: 2-(2-PYRIDYLETHYL)TRIMETHOXYSILANE Substance name

Product code · SIP6930.0 Formula C10H17NO3Si

: 2-(TRIMETHOXYSILYLETHYL)PYRIDINE Synonyms

Chemical family : ORGANOMETHOXYSILANE

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant identified uses

Use of the substance/mixture : Chemical intermediate

Uses advised against 1.2.2.

No additional information available

1.3. Details of the supplier of the safety data sheet

GELEST, INC.

11 East Steel Road Morrisville, PA 19067

USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com

GELEST INC.

Fritz-Klatte-Strasse 8 65933 Frankfurt

Germany

T +49 (0) 69 3535106-500 - F +49 (0) 69 3535106-501 - (M-F): 8:00 AM - 4:00 PM

info@gelestde.com - www.gelestde.com

Emergency telephone number

: CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International) **Emergency number**

SECTION 2: Hazards identification

Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

H315 Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 2 H319 Specific target organ toxicity — Single exposure, Category 3, H335

Respiratory tract irritation

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS07

Signal word (CLP) : Warning

Hazard statements (CLP) H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

EN (English) Print date: 11/04/2019 SDS ID: SIP6930.0 1/11

Safety Data Sheet

H335 - May cause respiratory irritation.

P280 - Wear protective gloves/protective clothing/eye protection/face protection. Precautionary statements (CLP)

P264 - Wash hands thoroughly after handling.

P302+P352 - IF ON SKIN: Wash with plenty of water.

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P312 - Call a doctor if you feel unwell.

Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

Substances

Substance type : Mono-constituent

Name : 2-(2-PYRIDYLETHYL)TRIMETHOXYSILANE

CAS-No. : 27326-65-4

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
2-(2-Pyridylethyl)trimethoxysilane	(CAS-No.) 27326-65-4	> 95	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335
Methanol	(CAS-No.) 67-56-1 (EC-No.) 200-659-6 (EC Index-No.) 603-001-00-X		Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 STOT SE 1, H370

Specific concentration limits:

Name	Product identifier	Specific concentration limits
Methanol	(CAS-No.) 67-56-1 (EC-No.) 200-659-6	(3 = <c 10)="" 2,="" <="" h371<br="" se="" stot="">(10 =<c 1,="" 100)="" <="" h370<="" se="" stot="" th=""></c></c>
	(EC Index-No.) 603-001-00-X	

Full text of H-statements: see section 16

Mixtures

Not applicable

SECTION 4: First aid measures

Description of first aid measures

First-aid measures general Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where

possible). If possible show this sheet; if not available show packaging or label.

First-aid measures after inhalation Remove person to fresh air and keep comfortable for breathing. If you feel unwell, seek medical

advice.

First-aid measures after skin contact Wash with plenty of water/.... Get medical advice/attention.

Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if First-aid measures after eye contact

present and easy to do. Continue rinsing. Get medical advice/attention.

First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Get medical advice/attention.

Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : May cause irritation to the respiratory tract. Overexposure may cause: Cough. Headache.

Nausea.

Symptoms/effects after skin contact : Causes skin irritation.

Symptoms/effects after eye contact Causes serious eye irritation.

Symptoms/effects after ingestion Oral toxicity is associated with methanol, the solvent and a hydrolysis product which causes nausea, vomiting, headache, visual effects including blindness. Onset of symptoms may be

delayed up to 48 hours.

Chronic symptoms : On contact with water this compound liberates methanol which is known to have a chronic effect on the central nervous system. Methanol may effect the central nervous system resulting

in persistent or recurring headaches or impaired vision.

Print date: 11/04/2019 EN (English) SDS ID: SIP6930.0 2/11

Safety Data Sheet

4.3. Indication of any immediate medical attention and special treatment needed

NOTE TO PHYSICIAN: This product reacts with water in the acid contents of the stomach to form methanol. The combination of visual disturbances, metabolic acidosis and formic acid in urine is evidence of methanol poisoning. The therapeutic intravenous administration of ethanol (10 mls/hour) allows methanol to be preferentially oxidized and reduces production of methanol metabolites. Acidosis must be treated with intravenous administration of sodium bicarbonate and methanol elimination may be increased by hemodialysis, as indicated. Treatment should be based on blood methanol levels and acid-base balance.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Foam. Carbon dioxide. Dry chemical.

Unsuitable extinguishing media : None known.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Irritating fumes and organic acid vapors may develop when material is exposed to elevated

temperatures or open flame.

5.3. Advice for firefighters

Firefighting instructions : Use water spray to cool exposed surfaces. Exercise caution when fighting any chemical fire.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Avoid all eye and skin contact and do not breathe vapour and mist.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or

shovel spills into appropriate container for disposal.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Use only in well ventilated areas. Avoid all eye and skin contact and do not breathe vapour and

mist.

Hygiene measures : Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild

soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container tightly closed.

Incompatible materials : Acids. alcohols. Oxidizing agent. Peroxides. Moisture. Water :

Storage area : Store in a well-ventilated place. Store away from heat.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Methanol (67-56-1)			
EU	IOELV TWA (mg/m³)	260 mg/m³	
EU	IOELV TWA (ppm)	200 ppm	
Austria	MAK (mg/m³)	260 mg/m³	
Austria	MAK (ppm)	200 ppm	
Austria	MAK Short time value (mg/m³)	1040 mg/m³	
Austria	MAK Short time value (ppm)	800 ppm	
Belgium	Limit value (mg/m³)	266 mg/m³	
Belgium	Limit value (ppm)	200 ppm	
Belgium	Short time value (mg/m³)	333 mg/m³	
Belgium	Short time value (ppm)	250 ppm	

Print date: 11/04/2019 EN (English) SDS ID: SIP6930.0 3/11

Safety Data Sheet

Mothered (67 EG 4)					
Methanol (67-56-1) Bulgaria	OEL TWA (mg/m³)	260 mg/m³			
Bulgaria	OEL TWA (mg/m²) OEL TWA (ppm)	200 ppm			
	OEL TWA (ppm) OEL TWA (mg/m³)	260 mg/m³			
Cyprus	OEL TWA (mg/m²) OEL TWA (ppm)	200 ppm			
Cyprus France		1300 mg/m³			
France	VLE (mg/m³) VLE (ppm)	1000 ppm			
France	VME (mg/m³)	260 mg/m³ (restrictive limit)			
France	VME (ppm)	200 ppm (restrictive limit)			
Germany	TRGS 900 Occupational exposure limit value (mg/m³)	270 mg/m³ (The risk of damage to the embryo or fetus			
Germany	Troo 900 Occupational exposure limit value (mg/m/)	can be excluded when AGW and BGW values are observed)			
Germany	TRGS 900 Occupational exposure limit value (ppm)	200 ppm (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)			
Germany	TRGS 903 Biological limit value	30 mg/l (Medium: urine - Time: end of shift - Parameter: Methanol) 30 mg/l (Medium: urine - Time: end of several shifts - Parameter: Methanol (for long-term exposures)			
Gibraltar	Eight hours mg/m3	260 mg/m³			
Gibraltar	Eight hours ppm	200 ppm			
Greece	OEL TWA (mg/m³)	260 mg/m³			
Greece	OEL TWA (ppm)	200 ppm			
Greece	OEL STEL (mg/m³)	325 mg/m³			
Greece	OEL STEL (ppm)	250 ppm			
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	200 ppm			
Italy - Portugal - USA ACGIH	ACGIH STEL (ppm)	250 ppm			
Italy	OEL TWA (mg/m³)	260 mg/m³			
Italy	OEL TWA (ppm)	200 ppm			
Latvia	OEL TWA (mg/m³)	260 mg/m³			
Latvia	OEL TWA (ppm)	200 ppm			
USA IDLH	US IDLH (ppm)	6000 ppm			
USA NIOSH	NIOSH REL (TWA) (mg/m³)	260 mg/m³			
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm			
USA NIOSH	NIOSH REL (STEL) (mg/m³)	325 mg/m³			
USA NIOSH	NIOSH REL (STEL) (ppm)	250 ppm			
USA OSHA	OSHA PEL (TWA) (mg/m³)	260 mg/m³			
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm			
Spain	VLA-ED (mg/m³)	266 mg/m³ (indicative limit value)			
Spain	VLA-ED (ppm)	200 ppm (indicative limit value)			
Switzerland	KZGW (mg/m³)	1040 mg/m³			
Switzerland	KZGW (ppm)	800 ppm			
Switzerland	MAK (mg/m³)	260 mg/m³			
Switzerland	MAK (ppm)	200 ppm			
Netherlands	Grenswaarde TGG 8H (mg/m³)	133 mg/m³			
Netherlands	Grenswaarde TGG 8H (ppm)	100 ppm			
United Kingdom	WEL TWA (mg/m³)	266 mg/m³			
United Kingdom	WEL TWA (ppm)	200 ppm			
United Kingdom	WEL STEL (mg/m³)	333 mg/m³			
United Kingdom	WEL STEL (ppm)	250 ppm			
Czech Republic	Expoziční limity (PEL) (mg/m³)	250 mg/m³			
Denmark	Grænseværdie (langvarig) (mg/m³)	260 mg/m³			
Denmark Finland	Grænseværdie (langvarig) (ppm) HTP-arvo (8h) (mg/m³)	200 ppm 270 mg/m³			
Finland	HTP-arvo (8h) (ppm)	270 mg/m² 200 ppm			
Finland	HTP-arvo (15 min)	330 mg/m ³			
Finland	HTP-arvo (15 min) (ppm)	250 ppm			
		(*F****			

Print date: 11/04/2019 EN (English) SDS ID: **SIP6930.0** 4/11

Safety Data Sheet

Methanol (67-56-1)				
Hungary	AK-érték	260 mg/m³		
Ireland	OEL (8 hours ref) (mg/m³)	260 mg/m³		
Ireland	OEL (8 hours ref) (ppm)	200 ppm		
Ireland	OEL (15 min ref) (mg/m3)	780 mg/m³ (calculated)		
Ireland	OEL (15 min ref) (ppm)	600 ppm (calculated)		
Lithuania	IPRV (mg/m³)	260 mg/m³		
Lithuania	IPRV (ppm)	200 ppm		
Malta	OEL TWA (mg/m³)	260 mg/m³		
Malta	OEL TWA (ppm)	200 ppm		
Norway	Grenseverdier (AN) (mg/m³)	130 mg/m³		
Norway	Grenseverdier (AN) (ppm)	100 ppm		
Norway	Grenseverdier (Korttidsverdi) (mg/m3)	130 mg/m³		
Norway	Grenseverdier (Korttidsverdi) (ppm)	100 ppm		
Poland	NDS (mg/m³)	100 mg/m³		
Poland	NDSCh (mg/m³)	300 mg/m³		
Romania	OEL TWA (mg/m³)	260 mg/m³		
Romania	OEL TWA (ppm)	200 ppm		
Romania	OEL STEL (ppm)	5 ppm		
Slovakia	NPHV (priemerná) (mg/m³)	260 mg/m ³		
Slovakia	NPHV (priemerná) (ppm)	200 ppm		
Sweden	nivågränsvärde (NVG) (mg/m³)	250 mg/m³		
Sweden	nivågränsvärde (NVG) (ppm)	200 ppm		
Sweden	kortidsvärde (KTV) (mg/m³)	350 mg/m³		
Sweden	kortidsvärde (KTV) (ppm)	250 ppm		
Canada (Quebec)	VECD (mg/m³)	328 mg/m³		
Canada (Quebec)	VECD (ppm)	250 ppm		
Canada (Quebec)	VEMP (mg/m³)	262 mg/m³		
Canada (Quebec)	VEMP (ppm)	200 ppm		
Australia	TWA (mg/m³)	262 mg/m³		
Australia	TWA (ppm)	200 ppm		
Australia	STEL (mg/m³)	328 mg/m³		
Australia	STEL (ppm)	250 ppm		
Portugal	OEL TWA (mg/m³)	260 mg/m³ (indicative limit value)		
Portugal	OEL TWA (ppm)	200 ppm (indicative limit value)		
Portugal	OEL STEL (ppm)	250 ppm		
Portugal	OEL chemical category (PT)	skin - potential for cutaneous exposure indicative limit value		

8.2. Exposure controls

Appropriate engineering controls:

Provide local exhaust or general room ventilation.

Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Hand protection:

Wear protective gloves. Neoprene or nitrile rubber gloves

Eye protection:

Chemical goggles. Contact lenses should not be worn

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Print date: 11/04/2019 EN (English) SDS ID: SIP6930.0 5/11

Safety Data Sheet

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified combination organic vapor - amine gas (brown cartridge) respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Clear liquid.

Molecular mass : 227.33 g/mol

Colour : Straw. Amber.

Odour : Amine. Ammonia-like.
Odour threshold : No data available

Refractive index : 1.4755

pH : No data available
Relative evaporation rate (butylacetate=1) : No data available
Melting point : No data available

Freezing point : < 0 °C

Boiling point : 105 °C @ 0.3 mm Hg

Flash point : $> 110 \, ^{\circ}\text{C}$

Auto-ignition temperature : No data available
Decomposition temperature : No data available
Flammability (solid, gas) : No data available
Vapour pressure : < 0.1 mm Hg

Relative vapour density at 20 °C : > 1
Relative density : 1.06
% Volatiles : < 30 %

Solubility : Reacts with water. Log Pow : No data available No data available Log Kow Viscosity, kinematic No data available No data available Viscosity, dynamic Explosive properties No data available : No data available Oxidising properties **Explosive limits** : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable when stored in sealed containers.

10.3. Possibility of hazardous reactions

Reacts with water and moisture in air, liberating methanol.

10.4. Conditions to avoid

Heat. Sparks. Open flame.

10.5. Incompatible materials

Acids. alcohols. Oxidizing agent. Peroxides. Moisture. Water:

10.6. Hazardous decomposition products

Methanol. Organic acid vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Methanol (67-56-1)	
LC50 inhalation rat (ppm)	22500 ppm (Exposure time: 8 h)
ATE CLP (oral)	100 mg/kg bodyweight

Print date: 11/04/2019 EN (English) SDS ID: **SIP6930.0** 6/11

Safety Data Sheet

Methanol (67-56-1)	
ATE CLP (dermal)	300 mg/kg bodyweight
ATE CLP (vapours)	3 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified

STOT-single exposure : May cause respiratory irritation.

STOT-repeated exposure : Not classified
Aspiration hazard : Not classified

Symptoms/effects after inhalation : May cause irritation to the respiratory tract. Overexposure may cause: Cough. Headache.

Nausea.

Symptoms/effects after skin contact : Causes skin irritation.

Symptoms/effects after eye contact : Causes serious eye irritation.

Symptoms/effects after ingestion : Oral toxicity is associated with methanol, the solvent and a hydrolysis product which causes

nausea, vomiting, headache, visual effects including blindness. Onset of symptoms may be

delayed up to 48 hours.

Chronic symptoms : On contact with water this compound liberates methanol which is known to have a chronic

effect on the central nervous system. Methanol may effect the central nervous system resulting

in persistent or recurring headaches or impaired vision.

Reason for classification : Expert judgment

SECTION 12: Ecological information

12.1. Toxicity

Acute aquatic toxicity : Not classified Chronic aquatic toxicity : Not classified

Methanol (67-56-1)			
LC50 fish 1	28200 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])		
LC50 fish 2 > 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])			

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Methanol (67-56-1)		
BCF fish 1	< 10	
Log Pow	-0.77	

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Other adverse effects : This substance may be hazardous to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : May be incinerated. Dispose in a safe manner in accordance with local/national regulations.

Dispose of contents/container to licensed waste disposal facility.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

14.1. UN number

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR) : 1760 UN-No. (IMDG) : 1760

Print date: 11/04/2019 EN (English) SDS ID: SIP6930.0 7/11

Safety Data Sheet

UN-No. (IATA) : 1760 UN-No. (ADN) : 1760 UN-No. (RID) : 1760

14.2. UN proper shipping name

Proper Shipping Name (ADR) : CORROSIVE LIQUID, N.O.S.
Proper Shipping Name (IMDG) : CORROSIVE LIQUID, N.O.S.
Proper Shipping Name (IATA) : Corrosive liquid, n.o.s.
Proper Shipping Name (ADN) : CORROSIVE LIQUID, N.O.S.
Proper Shipping Name (RID) : CORROSIVE LIQUID, N.O.S.

Transport document description (ADR) : UN 1760 CORROSIVE LIQUID, N.O.S. (2-(2-PYRIDYLETHYL)TRIMETHOXYSILANE), 8, III,

(F)

Transport document description (IMDG)

: UN 1760 CORROSIVE LIQUID, N.O.S. (2-(2-PYRIDYLETHYL)TRIMETHOXYSILANE), 8, III

Transport document description (ADN)

: UN 1760 Corrosive liquid, n.o.s. (2-(2-PYRIDYLETHYL)TRIMETHOXYSILANE), 8, III

Transport document description (ADN)

: UN 1760 CORROSIVE LIQUID, N.O.S. (2-(2-PYRIDYLETHYL)TRIMETHOXYSILANE), 8, III

Transport document description (RID)

: UN 1760 CORROSIVE LIQUID, N.O.S. (2-(2-PYRIDYLETHYL)TRIMETHOXYSILANE), 8, III

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 8
Danger labels (ADR) : 8



IMDG

Transport hazard class(es) (IMDG) : 8
Danger labels (IMDG) : 8



IATA

Transport hazard class(es) (IATA) : 8
Hazard labels (IATA) : 8



ADN

Transport hazard class(es) (ADN) : 8
Danger labels (ADN) : 8



RID

Transport hazard class(es) (RID) : 8
Danger labels (RID) : 8

Print date: 11/04/2019 EN (English) SDS ID: SIP6930.0 8/11

Safety Data Sheet



14.4. Packing group

Packing group (ADR) : III
Packing group (IMDG) : III
Packing group (IATA) : III
Packing group (ADN) : III
Packing group (RID) : III

14.5. Environmental hazards

Dangerous for the environment : No Marine pollutant : No

Other information : No supplementary information available

14.6. Special precautions for user

- Overland transport

Classification code (ADR) : C9
Special provisions (ADR) : 274
Limited quantities (ADR) : 51
Excepted quantities (ADR) : E1

Packing instructions (ADR) : P001, IBC03, LP01, R001

Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions : T7

(ADR)

Portable tank and bulk container special : TP1, TP28

provisions (ADR)

Tank code (ADR) : L4BN

Vehicle for tank carriage : AT

Transport category (ADR) : 3

Special provisions for carriage - Packages : V12

(ADR)

Hazard identification number (Kemler No.) : 80

Orange plates :

80 1760

Tunnel restriction code (ADR) : E
EAC code : 2X
APP code : B

- Transport by sea

Special provisions (IMDG) : 223, 274 Limited quantities (IMDG) : 5 L Excepted quantities (IMDG) : E1 : P001, LP01 Packing instructions (IMDG) IBC packing instructions (IMDG) : IBC03 Tank instructions (IMDG) : T7 Tank special provisions (IMDG) : TP1, TP28 EmS-No. (Fire) : F-A EmS-No. (Spillage) : S-B Stowage category (IMDG) : A Stowage and handling (IMDG) : SW2

Properties and observations (IMDG) : Causes burns to skin, eyes and mucous membranes.

- Air transport

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y841

Print date: 11/04/2019 EN (English) SDS ID: **SIP6930.0** 9/11

Safety Data Sheet

PCA limited quantity max net quantity (IATA)	:	1L
PCA packing instructions (IATA)	:	852
PCA max net quantity (IATA)	:	5L
CAO packing instructions (IATA)	:	856
CAO max net quantity (IATA)	:	60L
Special provisions (IATA)	:	А3
ERG code (IATA)	:	8L

- Inland waterway transport

Classification code (ADN) : C9
Special provisions (ADN) : 274
Limited quantities (ADN) : 5 L
Excepted quantities (ADN) : E1
Carriage permitted (ADN) : T
Equipment required (ADN) : PP, EP
Number of blue cones/lights (ADN) : 0

- Rail transport

Classification code (RID) : C9
Special provisions (RID) : 274
Limited quantities (RID) : 5L
Excepted quantities (RID) : E1

Packing instructions (RID) : P001, IBC03, LP01, R001

Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions : T7

(RID)

Portable tank and bulk container special : TP1, TP28

provisions (RID)

Tank codes for RID tanks (RID) : L4BN

Transport category (RID) : 3

Special provisions for carriage – Packages : W12
(RID)

Colis express (express parcels) (RID) : CE8
Hazard identification number (RID) : 80

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

No REACH Annex XVII restrictions

 $\hbox{2-(2-PYRIDYLETHYL)} TRIMETHOXYSILANE is not on the REACH Candidate List \\$

2-(2-PYRIDYLETHYL)TRIMETHOXYSILANE is not on the REACH Annex XIV List

2-(2-PYRIDYLETHYL)TRIMETHOXYSILANE is not subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.

2-(2-PYRIDYLETHYL)TRIMETHOXYSILANE is not subject to Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Directive 79/117/EEC

% Volatiles : < 30 %

15.1.2. National regulations

Germany

12th Ordinance Implementing the Federal : Is not subject of the 12. BlmSchV (Hazardous Incident Ordinance) Immission Control Act - 12.BlmSchV

Netherlands

SZW-lijst van kankerverwekkende stoffen : The substance is not listed SZW-lijst van mutagene stoffen : The substance is not listed

Print date: 11/04/2019 EN (English) SDS ID: SIP6930.0 10/11

Safety Data Sheet

NIET-limitatieve lijst van voor de voortplanting

giftige stoffen - Borstvoeding

: The substance is not listed

NIET-limitatieve lijst van voor de voortplanting

giftige stoffen - Vruchtbaarheid

: The substance is not listed

NIET-limitatieve lijst van voor de voortplanting

giftige stoffen - Ontwikkeling

: The substance is not listed

Denmark

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:

Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemcial Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor

Other information

: Prepared by safety and environmental affairs.

Full text of H- and EUH-statements:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3		
Acute Tox. 3 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 3		
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3		
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2		
Flam. Liq. 2	Flammable liquids, Category 2		
Skin Irrit. 2	Skin corrosion/irritation, Category 2		
STOT SE 1	Specific target organ toxicity — single exposure, Category 1		
STOT SE 2	Specific target organ toxicity — Single exposure, Category 2		
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation		
H225	Highly flammable liquid and vapour.		
H301	Toxic if swallowed.		
H311	Toxic in contact with skin.		
H315	Causes skin irritation.		
H319	Causes serious eye irritation.		
H331	Toxic if inhaled.		
H335	May cause respiratory irritation.		
H370	Causes damage to organs.		
H371	May cause damage to organs.		

SDS EU (REACH Annex II) - Custom

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2019 Gelest Inc. Morrisville, PA 19067

Print date: 11/04/2019 EN (English) SDS ID: SIP6930.0 11/11