



TETRAMETHYLAMMONIUM SILOXANOLATE

Safety Data Sheet SIT7520.0

Date of issue: 08/31/2015 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product name : TETRAMETHYLAMMONIUM SILOXANOLATE
 Product code : SIT7520.0
 Product form : Substance
 Physical state : Liquid
 Synonyms : N-CAT
 Chemical family : ORGANOSILOXANE

1.2. Recommended use and restrictions on use

Recommended use : Chemical intermediate

1.3. Supplier

GELEST, INC.

11 East Steel Road
 Morrisville, PA 19067

USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable liquids Category 4	H227 Combustible liquid
Acute toxicity (oral) Category 4	H302 Harmful if swallowed
Acute toxicity (dermal) Category 2	H310 Fatal in contact with skin
Skin corrosion/irritation Category 1B	H314 Causes severe skin burns and eye damage
Serious eye damage/eye irritation Category 1	H318 Causes serious eye damage
Specific target organ toxicity (single exposure) Category 1	H370 Causes damage to organs
Specific target organ toxicity (repeated exposure) Category 1	H372 Causes damage to organs through prolonged or repeated exposure
Hazardous to the aquatic environment - Chronic Hazard Category 3	H412 Harmful to aquatic life with long lasting effects

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H227 - Combustible liquid
 H302 - Harmful if swallowed
 H310 - Fatal in contact with skin
 H314 - Causes severe skin burns and eye damage
 H370 - Causes damage to organs
 H372 - Causes damage to organs through prolonged or repeated exposure
 H412 - Harmful to aquatic life with long lasting effects

Precautionary statements (GHS US) :

P280 - Wear protective gloves/protective clothing/eye protection/face protection.
 P210 - Keep away from heat, open flames, sparks. - No smoking.
 P260 - Do not breathe vapors.
 P262 - Do not get in eyes, on skin, or on clothing.
 P264 - Wash hands thoroughly after handling.
 P270 - Do not eat, drink or smoke when using this product.
 P273 - Avoid release to the environment.
 P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting
 P301+P312 - If swallowed: Call a doctor if you feel unwell
 P303+P361+P353 - If on skin (or hair): take off immediately all contaminated clothing. rinse skin with water/shower
 P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

TETRAMETHYLAMMONIUM SILOXANOLATE

Safety Data Sheet

P310 - Immediately call a doctor
P321 - Specific treatment (see first aid instructions on this label)
P361 - Take off immediately all contaminated clothing.
P363 - Wash contaminated clothing before reuse.
P370+P378 - In case of fire: Use foam, carbon dioxide, dry chemical to extinguish.
P403+P235 - Keep in a cool place
P405 - Store locked up.
P501 - Dispose of contents/container to licensed waste disposal facility.

2.3. Hazards not otherwise classified (HNOC)

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Substance type : Multi-constituent
Name : TETRAMETHYLAMMONIUM SILOXANOLATE
CAS-No. : 68440-88-0

Name	Product identifier	%	GHS-US classification
Tetramethylammonium siloxanolate	(CAS-No.) 68440-88-0	95 - 100	Flam. Liq. 4, H227 Skin Corr. 1C, H314 Eye Dam. 1, H318
Tetramethylammonium hydroxide	(CAS-No.) 75-59-2	1 - 5	Acute Tox. 2 (Oral), H300 Acute Tox. 1 (Dermal), H310 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 1, H370 STOT RE 1, H372 Aquatic Chronic 2, H411

Full text of hazard classes and H-statements : see section 16

3.2. Mixtures

Not applicable

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label. IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.

First-aid measures after skin contact : Wash with plenty of soap and water. Get immediate medical advice/attention.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Get medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : Causes severe skin burns and eye damage. Causes damage to organs through prolonged or repeated exposure.

Symptoms/effects after inhalation : May cause irritation to the respiratory tract. Inhalation will cause sneezing, irritation and burns.

Symptoms/effects after skin contact : Fatal in contact with skin. Repeated exposure to this material can result in absorption through skin causing significant health hazard. Causes (severe) skin burns. If skin and air are dry, powder on skin may not cause irritation or burns. Worker will notice a slippery feeling on washing. However, if moisture is present, the powder can cause severe burns.

Symptoms/effects after eye contact : Causes serious eye damage.

Symptoms/effects after ingestion : Harmful if swallowed. Swallowing a small quantity of this material will result in serious health hazard.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Carbon dioxide. Dry chemical. Foam.
Unsuitable extinguishing media : Do not use straight streams.

5.2. Specific hazards arising from the chemical

Fire hazard : Combustible liquid. Irritating fumes and caustic vapors may develop when material is exposed to elevated temperatures or open flame.

TETRAMETHYLAMMONIUM SILOXANOLATE

Safety Data Sheet

5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Exercise caution when fighting any chemical fire.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Avoid all eye and skin contact and do not breathe vapor and mist.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

- Protective equipment : Wear protective equipment as described in Section 8.
Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

- Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or shovel spills into appropriate container for disposal. Use only non-sparking tools.

6.4. Reference to other sections

- No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapor and mist. Ground/bond container and receiving equipment. Use only in well ventilated areas. Use only non-sparking tools.
Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep container tightly closed. Store under dry nitrogen or argon in sealed containers. Keep in a cool place. Store locked up.
Incompatible materials : Acids. Alcohols. Carbon dioxide. Esters. Halogens. Ketones. Moist air. Water.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Tetramethylammonium hydroxide (75-59-2)		
ACGIH	Remark (ACGIH)	OELs not established
OSHA	Remark (OSHA)	OELs not established

8.2. Appropriate engineering controls

- Appropriate engineering controls : Provide local exhaust or general room ventilation.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Hand protection:

Neoprene or nitrile rubber gloves

Eye protection:

Chemical goggles or face shield. Contact lenses should not be worn

Skin and body protection:

Wear suitable protective clothing

TETRAMETHYLAMMONIUM SILOXANOLATE

Safety Data Sheet

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified combination organic vapor - amine gas (brown cartridge) respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid. Viscous. May solidify with time.
Color	: No data available
Odor	: Mild.
Odor threshold	: No data available
Refractive index	: 1.438
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: 10 - 40 °C
Freezing point	: No data available
Boiling point	: > 130 °C decomposes
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Combustible liquid
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: 0.98
Solubility	: Insoluble in water. Reacts slowly with water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under nitrogen or argon in sealed containers.

10.3. Possibility of hazardous reactions

Material decomposes slowly in contact with moist air and rapidly in contact with water.

10.4. Conditions to avoid

Heat. Open flame. Sparks.

10.5. Incompatible materials

Acids. Alcohols. Carbon dioxide. Esters. Halogens. Ketones. Moist air. Water.

10.6. Hazardous decomposition products

Caustic organic vapors. Methanol. Octamethylcyclotetrasiloxane. Tetramethylammonium hydroxide. Trimethylamine.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

TETRAMETHYLAMMONIUM SILOXANOLATE (68440-88-0)	
ATE US (oral)	680 mg/kg body weight
ATE US (dermal)	100 mg/kg body weight
Acute toxicity additional information	Tetramethylammonium hydroxide: subcutaneous, mouse, LDLo: 20mg/kg

TETRAMETHYLAMMONIUM SILOXANOLATE

Safety Data Sheet

Tetramethylammonium hydroxide (75-59-2)	
LD50 oral rat	34 - 50 mg/kg
LD50 dermal rat	112 mg/kg
ATE US (oral)	34 mg/kg body weight
ATE US (dermal)	5 mg/kg body weight

Skin corrosion/irritation	: Causes severe skin burns and eye damage.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: Causes damage to organs.
Specific target organ toxicity – repeated exposure	: Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
Symptoms/effects after inhalation	: May cause irritation to the respiratory tract. Inhalation will cause sneezing, irritation and burns.
Symptoms/effects after skin contact	: Fatal in contact with skin. Repeated exposure to this material can result in absorption through skin causing significant health hazard. Causes (severe) skin burns. If skin and air are dry, powder on skin may not cause irritation or burns. Worker will notice a slippery feeling on washing. However, if moisture is present, the powder can cause severe burns.
Symptoms/effects after eye contact	: Causes serious eye damage.
Symptoms/effects after ingestion	: Harmful if swallowed. Swallowing a small quantity of this material will result in serious health hazard.
Reason for classification	: Expert judgment

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other adverse effects : This substance may be hazardous to the environment.

Effect on the ozone layer : No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Sewage disposal recommendations : Do not dispose of waste into sewer.

Product/Packaging disposal recommendations : Incinerate. Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to licensed waste disposal facility.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

14.1. UN number

UN-No.(DOT) : 3267

DOT NA no. UN3267

14.2. UN proper shipping name

Transport document description : UN3267 Corrosive liquid, basic, organic, n.o.s. (TETRAMETHYLAMMONIUM SILOXANOLATE), 8, III

Proper Shipping Name (DOT) : Corrosive liquid, basic, organic, n.o.s.
(TETRAMETHYLAMMONIUM SILOXANOLATE)

Class (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136

TETRAMETHYLAMMONIUM SILOXANOLATE

Safety Data Sheet

Packing group (DOT) : III - Minor Danger
Hazard labels (DOT) : 8 - Corrosive



DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
DOT Packaging Bulk (49 CFR 173.xxx) : 241
DOT Packaging Exceptions (49 CFR 173.xxx) : 154
DOT Symbols : G - Identifies PSN requiring a technical name

14.3. Additional information

Emergency Response Guide (ERG) Number : 153

Other information : No supplementary information available.

Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other : 40 - Stow "clear of living quarters", 52 - Stow "separated from" acids

Air transport

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L

SECTION 15: Regulatory information

15.1. US Federal regulations

Tetramethylammonium siloxanolate (68440-88-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Tetramethylammonium hydroxide (75-59-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

No additional information available

Tetramethylammonium hydroxide (75-59-2)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Tetramethylammonium hydroxide (75-59-2)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on KECI (Korean Existing Chemicals Inventory)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Tetramethylammonium hydroxide (75-59-2)

U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Full text of H-phrases::

H227	Combustible liquid
H300	Fatal if swallowed

TETRAMETHYLAMMONIUM SILOXANOLATE

Safety Data Sheet

H302	Harmful if swallowed
H310	Fatal in contact with skin
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H370	Causes damage to organs
H372	Causes damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

Abbreviations and acronyms

: Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor.

Hazard Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

Flammability : 2 Moderate Hazard - Materials which must be moderately heated or exposed to high ambient temperatures before ignition will occur. Includes liquids having a flash point at or above 100 F but below 200 F. (Classes II & IIIA)

Physical : 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.

Prepared by safety and environmental affairs.

Date of issue: 08/31/2015 Version: 1.0

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2019 Gelest Inc. Morrisville, PA 19067