



N-(TRIETHOXYSILYLPROPYL)-O-POLYETHYLENE OXIDE URETHANE, 95%

Safety Data Sheet SIT8192.0

Date of issue: 01/08/2015

Revision date: 11/14/2018

Version: 1.1

SECTION 1: Identification

1.1. Identification

Product name : N-(TRIETHOXYSILYLPROPYL)-O-POLYETHYLENE OXIDE URETHANE, 95%
 Product code : SIT8192.0
 Product form : Substance
 Physical state : Liquid
 Formula : C₁₀H₂₂NO₄SiO(CH₂CH₂O)₄-6H
 Synonyms : O-POLYETHYLENE OXIDE-N-(TRIETHOXYSILYLPROPYL)-URETHANE
 Chemical family : POLYALKYLENE OXIDE

1.2. Recommended use and restrictions on use

Recommended use : Chemical intermediate

1.3. Supplier

GELEST, INC.

11 East Steel Road
 Morrisville, PA 19067
 USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Serious eye damage/eye irritation Category 2A H319 Causes serious eye irritation

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Warning

Hazard statements (GHS US) :

H319 - Causes serious eye irritation

Precautionary statements (GHS US) :

P280 - Wear protective gloves/protective clothing/eye protection/face protection.
 P264 - Wash hands thoroughly after handling.
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 P337+P313 - If eye irritation persists: Get medical advice/attention.

2.3. Hazards not otherwise classified (HNOC)

Other hazards not contributing to the classification

: The hydrolysis product of this compound is ethanol. Overexposure to ethanol by skin absorption, inhalation or ingestion may have a narcotic effect (headache, nausea, drowsiness). Ethanol is metabolized to acetaldehyde and acetic acid which in large quantities result in metabolic acidosis, CNS depression and death due to respiratory arrest. This product contains ethanol which is classified as a carcinogen by IARC in alcoholic beverages.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Substance type : Mono-constituent
 Name : N-(TRIETHOXYSILYLPROPYL)-O-POLYETHYLENE OXIDE URETHANE, 95%
 CAS-No. : 74695-91-3

| Name | Product identifier | % | GHS-US classification |
|--|----------------------|------|-----------------------|
| N-(Triethoxysilylpropyl)-o-polyethylene oxide urethane | (CAS-No.) 74695-91-3 | > 95 | Eye Irrit. 2A, H319 |

N-(TRIETHOXYSILYL)PROPYL)-O-POLYETHYLENE OXIDE URETHANE, 95%

Safety Data Sheet

Full text of hazard classes and H-statements : see section 16

3.2. Mixtures

Not applicable

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.
- First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.
- First-aid measures after skin contact : Wash with plenty of soap and water.
- First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
- First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Get medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects after inhalation : May cause irritation to the respiratory tract. Overexposure may cause: Coughing. Headache. Nausea.
- Symptoms/effects after skin contact : May cause skin irritation.
- Symptoms/effects after eye contact : Causes serious eye irritation.
- Symptoms/effects after ingestion : May be harmful if swallowed.
- Chronic symptoms : On contact with water this compound liberates ethanol which is known to have a chronic effect on the central nervous system.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Water spray. Foam. Carbon dioxide. Dry chemical.

5.2. Specific hazards arising from the chemical

- Fire hazard : Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.

5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Use water spray to cool exposed surfaces. Exercise caution when fighting any chemical fire.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Avoid all eye and skin contact and do not breathe vapor and mist.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or shovel spills into appropriate container for disposal.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapor and mist. Provide good ventilation in process area to prevent accumulation of vapors.
- Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before reuse.

N-(TRIETHOXYSILYL)PROPYL)-O-POLYETHYLENE OXIDE URETHANE, 95%

Safety Data Sheet

7.2. Conditions for safe storage, including any incompatibilities

| | |
|------------------------|---|
| Storage conditions | : Keep container tightly closed. |
| Incompatible materials | : Moisture. Water. |
| Storage area | : Store in a well-ventilated place. Store away from heat. |

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Hand protection:

Neoprene or nitrile rubber gloves

Eye protection:

Chemical goggles. Contact lenses should not be worn

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Air-purifying respirator with a combination of HEPA filter.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|-----------------------|
| Physical state | : Liquid |
| Appearance | : Clear liquid. |
| Molecular mass | : 400 - 500 g/mol |
| Color | : Straw. |
| Odor | : Mild. |
| Odor threshold | : No data available |
| Refractive index | : 1.454 |
| pH | : No data available |
| Relative evaporation rate (butyl acetate=1) | : No data available |
| Melting point | : No data available |
| Freezing point | : < 0 °C |
| Boiling point | : > 180 °C decomposes |
| Flash point | : > 110 °C |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Flammability (solid, gas) | : No data available |
| Vapor pressure | : < 1 mm Hg @ 20°C |
| Relative vapor density at 20 °C | : No data available |
| Relative density | : 1.09 |
| % Volatiles | : < 1 % |
| Solubility | : Reacts with water. |
| Log Pow | : No data available |
| Log Kow | : No data available |
| Viscosity, kinematic | : 75 - 125 cSt |
| Viscosity, dynamic | : No data available |
| Explosive properties | : No data available |

N-(TRIETHOXYSILYLPROPYL)-O-POLYETHYLENE OXIDE URETHANE, 95%

Safety Data Sheet

Oxidizing properties : No data available
Explosion limits : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable in sealed containers.

10.3. Possibility of hazardous reactions

Reacts with water and moisture in air, liberating ethanol.

10.4. Conditions to avoid

Heat. Open flame. Sparks.

10.5. Incompatible materials

Moisture. Water.

10.6. Hazardous decomposition products

Ethanol. Organic acid vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified
Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
None of the components in this product at concentrations >0.1% are listed by IARC, NTP, OSHA or ACGIH as a carcinogen.
Reproductive toxicity : Not classified
Specific target organ toxicity – single exposure : Not classified
Specific target organ toxicity – repeated exposure : Not classified
Aspiration hazard : Not classified
Symptoms/effects after inhalation : May cause irritation to the respiratory tract. Overexposure may cause: Coughing. Headache. Nausea.
Symptoms/effects after skin contact : May cause skin irritation.
Symptoms/effects after eye contact : Causes serious eye irritation.
Symptoms/effects after ingestion : May be harmful if swallowed.
Chronic symptoms : On contact with water this compound liberates ethanol which is known to have a chronic effect on the central nervous system.
Reason for classification : Expert judgment

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

N-(TRIETHOXYSILYLPROPYL)-O-POLYETHYLENE OXIDE URETHANE, 95%

Safety Data Sheet

12.5. Other adverse effects

Effect on the ozone layer : No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : May be incinerated. Dispose in a safe manner in accordance with local/national regulations.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

14.1. UN number

Not regulated for transport.

14.2. UN proper shipping name

Not applicable

14.3. Additional information

Other information : No supplementary information available.

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

N-(TRIETHOXYSILYLPROPYL)-O-POLYETHYLENE OXIDE URETHANE, 95% (74695-91-3)

TSCA Exemption/Exclusion

Low Volume Exemption in accordance with 40 CFR 723.50(c)(1). Use of this substance is restricted to use in hydrophilic modification of surfaces such as silica, glass and titania. Anyone who intends to use this chemical substance for commercial purposes must comply with specific use restrictions and controls specified herein. This LVE limits site of manufacture of this substance to Gelest, Inc. unless otherwise approved by U.S. EPA

N-(Triethoxysilylpropyl)-o-polyethylene oxide urethane (74695-91-3)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

Full text of H-phrases::

H319

Causes serious eye irritation

N-(TRIETHOXYSILYL)PROPYL)-O-POLYETHYLENE OXIDE URETHANE, 95%

Safety Data Sheet

Abbreviations and acronyms : Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor.

Hazard Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)

Physical : 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.

Prepared by safety and environmental affairs.

Date of issue: 01/08/2015 Revision date: 11/14/2018 Version: 1.1

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2019 Gelest Inc. Morrisville, PA 19067



11 E. Steel Road
Morrisville, PA 19067

215-547-1015 phone
215-547-2484 fax
www.gelest.com

**NOTICE OF TSCA USE RESTRICTIONS AND REQUIRED CONTROLS FOR
SIT8192.0
N-(TRIETHOXYSILYL)PROPYL- O-POLYETHYLENE OXIDE URETHANE 95%**

Dear Customer:

The chemical product purchased, SIT8192.0 has been granted a Low Volume Exemption by the U.S. Environmental Protection Agency (EPA) under the Toxic Substances Control Act (TSCA) regulations (40 CFR 723.50). Any manufacturer or processor who intends to use this chemical substance for commercial purposes must comply with the specific use restrictions and controls specified as follows:

USE OF THIS CHEMICAL SUBSTANCE IS RESTRICTED TO: Hydrophilic modification of surfaces such as silica, glass, titania

CONTROLS: Workers must use personal protection equipment to limit dermal and inhalation exposures as described in Section 8: Exposure Controls/Personal Protection of the Safety Data Sheet (SDS). These exposure controls include:

Hand protection: Impervious gloves (neoprene or nitrile rubber gloves)

Eye Protection: Chemical goggles. Contact lenses should not be worn.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: Air-purifying respirator with a combination of HEPA filter.

WASTE DISPOSAL: Customer must rinse containers with solvent prior to disposal. Residues and wash solvents must be containerized for off-site disposal by incineration at licensed waste disposal facility. Do not release to publicly owned treatment works (POTW) via sewer or to surface waters.

If you have questions or need more information related to allowable use of this substance, contact Gelest Regulatory Affairs at 215-547-1015.

Best Regards,

Gelest, Inc.
Regulatory Affairs Department