



A MITSUBISHI CHEMICAL GROUP company

TRIETHYLSILANE, 98%**Safety Data Sheet SIT8330.0**

Issue date: 01/09/2015

Revision date: 11/29/2023

Version: 3.3

SECTION 1: Identification**1.1. Identification**

Product name	: TRIETHYLSILANE, 98%
Product code	: SIT8330.0
Product form	: Substance
Physical state	: Liquid
Formula	: C ₆ H ₁₆ Si
Synonyms	: TRIETHYLSILYL HYDRIDE; TRIETHYLSILICON HYDRIDE
Chemical family	: ORGANOHYDRIDOSILANE

1.2. Recommended use and restrictions on use

Recommended use	: Chemical intermediate
-----------------	-------------------------

1.3. Supplier**GELEST, INC.**

11 East Steel Road
Morrisville, PA 19067

USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com**1.4. Emergency telephone number**

Emergency number	: CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)
------------------	---

SECTION 2: Hazard(s) identification**2.1. Classification of the substance or mixture****GHS US classification**

Flammable liquids Category 2	H225	Highly flammable liquid and vapor
Full text of H statements : see section 16		

2.2. GHS Label elements, including precautionary statements**GHS US labeling**

Hazard pictograms (GHS US)



Signal word (GHS US)

: Danger

Hazard statements (GHS US)

: H225 - Highly flammable liquid and vapor

Precautionary statements (GHS US)

: P210 - Keep away from heat, open flames, sparks. - No smoking.
 P233 - Keep container tightly closed.
 P240 - Ground/Bond container and receiving equipment.
 P241 - Use explosion-proof electrical equipment.
 P242 - Use only non-sparking tools.
 P243 - Take precautionary measures against static discharge.
 P280 - Wear protective gloves/protective clothing/eye protection/face protection.
 P303+P361+P353 - If on skin (or hair): take off immediately all contaminated clothing. rinse skin with water/shower
 P370+P378 - In case of fire: Use water spray or fog, foam, carbon dioxide, dry chemical to

TRIETHYLSILANE, 98%

Safety Data Sheet

extinguish.

P403+P235 - Keep in a cool place

P501 - Dispose of contents/container to licensed waste disposal facility..

2.3. Hazards not otherwise classified (HNOC)

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Substance type : Mono-constituent
Name : TRIETHYLSILANE, 98%
CAS-No. : 617-86-7

Name	Product identifier	%	GHS US classification
Triethylsilane	CAS-No.: 617-86-7	95 – 100	Flam. Liq. 2, H225 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of hazard classes and H-statements : see section 16

3.2. Mixtures

Not applicable

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.

First-aid measures after skin contact : Wash with plenty of soap and water.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.

First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Get medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : No information available.

Symptoms/effects after skin contact : May cause skin irritation.

Symptoms/effects after eye contact : May cause eye irritation.

Symptoms/effects after ingestion : No information available.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Foam. Carbon dioxide. Dry chemical. Water fog.

Unsuitable extinguishing media : Do not use a heavy water stream.

TRIETHYLSILANE, 98%

Safety Data Sheet

5.2. Specific hazards arising from the chemical

- Fire hazard : Highly flammable liquid and vapor. Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.
- Explosion hazard : May form flammable/explosive vapor-air mixture.

5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Avoid all eye and skin contact and do not breathe vapor and mist.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or shovel spills into appropriate container for disposal.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.
- Precautions for safe handling : Containers must be properly grounded before beginning transfer. Provide good ventilation in process area to prevent accumulation of vapors. Use only non-sparking tools.
- Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical equipment.
- Storage conditions : Keep container tightly closed.
- Incompatible materials : Store away from alkalis, oxidizers, metal salts, precious metals, chlorine, bromine.
- Storage area : Store in a well-ventilated place. Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

TRIETHYLSILANE, 98%

Safety Data Sheet

8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Hand protection:

Neoprene or nitrile rubber gloves

Eye protection:

Chemical goggles. Contact lenses should not be worn

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified organic vapor (black cartridge) respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear liquid.
Molecular mass	: 116.28 g/mol
Color	: Colorless.
Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: > 1
Melting point	: -157 °C
Freezing point	: No data available
Boiling point	: 107 – 108 °C
Flash point	: -3 °C
Auto-ignition temperature	: 250 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: Highly flammable liquid and vapor.
Vapor pressure	: 40 mm Hg @ 20°C
Relative vapor density at 20°C	: > 1
Relative density	: 0.7309
Solubility	: Insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Partition coefficient n-octanol/water (Log Kow)	: No data available
Viscosity, kinematic	: 4.9 cSt
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

TRIETHYLSILANE, 98%

Safety Data Sheet

10.2. Chemical stability

Stable in sealed containers stored under a dry inert atmosphere.

10.3. Possibility of hazardous reactions

The product can generate small amounts of hydrogen when exposed to alkalis and protic materials such as water and alcohol in combination with metal salts such as aluminum chloride or precious metals such as platinum.

10.4. Conditions to avoid

Heat. Open flame. Sparks.

10.5. Incompatible materials

Store away from alkalis, oxidizers, metal salts, precious metals, chlorine, bromine.

10.6. Hazardous decomposition products

Hydrogen. Formaldehyde. Carbon monoxide. Organic acid vapors. Silicon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Triethylsilane (617-86-7)

LD50 oral rat	> 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: other:
LC50 Inhalation - Rat	> 21.3 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: other:
LC50 Inhalation - Rat [ppm]	> 1774 ppm Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Remarks on results: other:

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified

Triethylsilane (617-86-7)

NOAEC (inhalation, rat, vapor, 90 days)	≥ 24 mg/l air Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
---	--

Aspiration hazard	: Not classified
Symptoms/effects after inhalation	: No information available.
Symptoms/effects after skin contact	: May cause skin irritation.
Symptoms/effects after eye contact	: May cause eye irritation.
Symptoms/effects after ingestion	: No information available.

TRIETHYLSILANE, 98%

Safety Data Sheet

SECTION 12: Ecological information

12.1. Toxicity

Triethylsilane (617-86-7)

LC50 - Fish [1]	2.372 mg/l Source: Ecological Structure Activity Relationships
EC50 - Crustacea [1]	0.577 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	52 mg/l Daphnia
EC50 72h - Algae [1]	1.14 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	1.961 mg/l Source: Ecological Structure Activity Relationships
ErC50 algae	1.14 mg/l
NOEC chronic algae	0.127 mg/l

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Triethylsilane (617-86-7)

Partition coefficient n-octanol/water (Log Pow)	3.64 Source: National Library of Medicine
---	---

12.4. Mobility in soil

Triethylsilane (617-86-7)

Mobility in soil	252.8 Source: Quantitative Structure Activity Relation
------------------	--

12.5. Other adverse effects

Effect on the ozone layer : No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to licensed waste disposal facility..

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecological information : Avoid release to the environment.




SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
1993	Not applicable	1993	1993
14.2. Proper Shipping Name			
Flammable liquids, n.o.s. ((TRIETHYLSILANE))	Not applicable	FLAMMABLE LIQUID, N.O.S. (TRIETHYLSILANE)	Flammable liquid, n.o.s. (TRIETHYLSILANE)

TRIETHYLSILANE, 98%

Safety Data Sheet

DOT	TDG	IMDG	IATA
Transport document description			
UN1993 Flammable liquids, n.o.s. (TRIETHYLSILANE), 3, II	Not applicable	UN 1993 FLAMMABLE LIQUID, N.O.S. (TRIETHYLSILANE), 3, II	UN 1993 Flammable liquid, n.o.s. (TRIETHYLSILANE), 3, II
14.3. Transport hazard class(es)			
3	Not applicable	3	3
	Not applicable		
14.4. Packing group			
II	Not applicable	II	II
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available			

14.6. Special precautions for user

DOT

UN-No.(DOT) : UN1993

DOT Special Provisions (49 CFR 172.102) : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.
T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F).
TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150

DOT Packaging Non Bulk (49 CFR 173.xxx) : 202

DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

TDG

Emergency Response Guide (ERG) Number : 128

IMDG

Special provision (IMDG) : 274

TRIETHYLSILANE, 98%

Safety Data Sheet

Limited quantities (IMDG)	: 1 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T7
Tank special provisions (IMDG)	: TP1, TP8, TP28
EmS-No. (Fire)	: F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage)	: S-E - SPILLAGE SCHEDULE Echo - FLAMMABLE LIQUIDS, FLOATING ON WATER
Stowage category (IMDG)	: B

IATA

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y341
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 353
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L
Special provision (IATA)	: A3
ERG code (IATA)	: 3H

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

Name	CAS-No.	Listing	Commercial status	Flags
Triethylsilane	617-86-7	Present	Active	

15.2. International regulations

CANADA

Triethylsilane (617-86-7)

Listed on the Canadian NDSL (Non-Domestic Substances List)

EU-Regulations

Triethylsilane (617-86-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

Triethylsilane (617-86-7)

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on KECL/KECI (Korean Existing Chemicals Inventory)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the NCI (Vietnam - National Chemical Inventory)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

TRIETHYLSILANE, 98%

Safety Data Sheet

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

Full text of H-phrases::

H225	Highly flammable liquid and vapor
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

Abbreviations and acronyms

: Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor.

Hazard Rating

Health

Flammability

Physical

: 1 Slight Hazard - Irritation or minor reversible injury possible
: 4 Severe Hazard - Flammable gases, or very volatile flammable liquids with flash points below 73 F, and boiling points below 100 F. Materials may ignite spontaneously with air. (Class IA)
: 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.

Prepared by safety and environmental affairs.

Issue date: 01/09/2015

Revision date: 11/29/2023

Version: 3.3

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2023 Gelest Inc. Morrisville, PA 19067