



Enabling Your Technology

DI-n-BUTYLBIS(2-ETHYLHEXANOATE)TIN, 50% in xylene

Safety Data Sheet SND2901

Date of issue: 10/06/2016

Version: 1.0

SECTION 1: Identification**1.1. Identification**

Product name	: DI-n-BUTYLBIS(2-ETHYLHEXANOATE)TIN, 50% in xylene
Product code	: SND2901
Product form	: Mixture
Physical state	: Liquid
Formula	: C ₂₄ H ₄₈ O ₄ Sn
Synonyms	: DIBUTYLTINDIOCTOATE DIBUTYLTIN DI-2-ETHYLHEXANOATE STANNANE, DIBUTYLBIS[(2-ETHYL-1-OXOHEXYL)OXY]- HEXANOIC ACID, 2-ETHYL-, 1,1'-(DIBUTYLSTANNYLENE) ESTER
Chemical family	: ORGANOTIN

1.2. Recommended use and restrictions on use

Recommended use	: Chemical intermediate
-----------------	-------------------------

1.3. Supplier**GELEST, INC.**11 East Steel Road
Morrisville, PA 19067**USA**

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com**1.4. Emergency telephone number**

Emergency number	: CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)
------------------	---

SECTION 2: Hazard(s) identification**2.1. Classification of the substance or mixture****GHS-US classification**

Flammable liquids Category 3	H226 Flammable liquid and vapor
Acute toxicity (oral) Category 3	H301 Toxic if swallowed
Skin corrosion/irritation Category 2	H315 Causes skin irritation
Serious eye damage/eye irritation Category 2A	H319 Causes serious eye irritation
Specific target organ toxicity (single exposure) Category 3	H335 May cause respiratory irritation
Specific target organ toxicity (repeated exposure) Category 2	H373 May cause damage to organs through prolonged or repeated exposure
Hazardous to the aquatic environment - Acute Hazard Category 1	H400 Very toxic to aquatic life
Full text of H statements : see section 16	

2.2. GHS Label elements, including precautionary statements**GHS US labeling**

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger

Hazard statements (GHS US) :

H226 - Flammable liquid and vapor
H301 - Toxic if swallowed
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H335 - May cause respiratory irritation
H373 - May cause damage to organs through prolonged or repeated exposure
H400 - Very toxic to aquatic life

Precautionary statements (GHS US) :

P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P210 - Keep away from heat, open flames, sparks. - No smoking.
P240 - Ground/Bond container and receiving equipment
P241 - Use explosion-proof electrical equipment
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P260 - Do not breathe vapors.
P264 - Wash hands thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.

DI-n-BUTYLBIS(2-ETHYLHEXANOATE)TIN, 50% in xylene

Safety Data Sheet

P273 - Avoid release to the environment.
P330 - Rinse mouth.
P301+P310 - If swallowed: Immediately call a POISON CENTER
P303+P361+P353 - If on skin (or hair): take off immediately all contaminated clothing. rinse skin with water/shower
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P337+P313 - If eye irritation persists: Get medical advice/attention.
P314 - Get medical advice/attention if you feel unwell.
P321 - Specific treatment (see first aid instructions on this label)
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use water spray, foam, carbon dioxide, dry chemical to extinguish.
P391 - Collect spillage.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P403+P235 - Keep in a cool place
P405 - Store locked up.
P501 - Dispose of contents/container to licensed waste disposal facility.

2.3. Hazards not otherwise classified (HNOC)

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Di-n-butylbis(2-ethylhexanoate)tin	(CAS-No.) 2781-10-4	45 - 50	Acute Tox. 3 (Oral), H301 Skin Irrit. 2, H315 Eye Irrit. 2A, H319
Xylene	(CAS-No.) 1330-20-7	45 - 50	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 STOT RE 2, H373 Aquatic Acute 1, H400

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.

First-aid measures after skin contact : Wash with plenty of soap and water. Get medical advice/attention.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.

First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : May cause damage to organs through prolonged or repeated exposure.

Symptoms/effects after inhalation : May cause respiratory irritation. May be harmful if inhaled.

Symptoms/effects after skin contact : Causes skin irritation. May be harmful in contact with skin.

Symptoms/effects after eye contact : Causes serious eye irritation.

Symptoms/effects after ingestion : Toxic if swallowed. Swallowing a small quantity of this material will result in serious health hazard.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Foam. Carbon dioxide. Dry chemical.

Unsuitable extinguishing media : Do not use straight streams.

DI-n-BUTYLBIS(2-ETHYLHEXANOATE)TIN, 50% in xylene

Safety Data Sheet

5.2. Specific hazards arising from the chemical

- Fire hazard : Flammable liquid and vapor. Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.
- Explosion hazard : May form flammable/explosive vapor-air mixture.

5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Exercise caution when fighting any chemical fire. Use water spray to cool exposed surfaces.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Avoid all eye and skin contact and do not breathe vapor and mist.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Eliminate every possible source of ignition. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

- Protective equipment : Wear protective equipment as described in Section 8.
- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

- Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
- Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Collect spillage. Use only non-sparking tools.

6.4. Reference to other sections

- See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapors are flammable. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapor and mist. Ground/bond container and receiving equipment. Take precautionary measures against static discharge. Use only outdoors or in a well-ventilated area. Use only non-sparking tools.
- Hygiene measures : Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof electrical equipment.
- Storage conditions : Keep container tightly closed. Keep in a cool place. Store locked up.
- Incompatible materials : Bases. Reducing agents.
- Storage area : Store in a well-ventilated place. Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Di-n-butylbis(2-ethylhexanoate)tin (2781-10-4)		
ACGIH	ACGIH TWA (mg/m ³)	0.1 mg/m ³ as tin
OSHA	OSHA PEL (TWA) (mg/m ³)	0.1 mg/m ³ as tin
Xylene (1330-20-7)		
ACGIH	ACGIH TWA (ppm)	100 ppm
ACGIH	ACGIH STEL (ppm)	150 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	435 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm

DI-n-BUTYLBIS(2-ETHYLHEXANOATE)TIN, 50% in xylene

Safety Data Sheet

8.2. Appropriate engineering controls

Appropriate engineering controls : Handle in an enclosing hood with exhaust ventilation.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Hand protection:

Neoprene or nitrile rubber gloves

Eye protection:

Chemical goggles. Contact lenses should not be worn

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified organic vapor (black cartridge) respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Molecular mass	: 519.34 g/mol
Color	: Straw.
Odor	: Characteristic.
Odor threshold	: No data available
Refractive index	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: < 54 - 60 °C
Boiling point	: 138 °C initial (xylene)
Flash point	: 30 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Flammable liquid and vapor
Vapor pressure	: 7 mm Hg @ 21°C (xylene)
Relative vapor density at 20 °C	: No data available
Relative density	: 0.97
% Volatiles	: > 50 %
Solubility	: Insoluble in water. Reacts slowly with water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable.

DI-n-BUTYLBIS(2-ETHYLHEXANOATE)TIN, 50% in xylene

Safety Data Sheet

10.3. Possibility of hazardous reactions

Reacts with moisture in air and water, slowly releasing butanol and dibutyltin oxide. Direct sunlight causes degradation to an inorganic tin salt.

10.4. Conditions to avoid

Heat. Open flame. Sparks.

10.5. Incompatible materials

Bases. Reducing agents.

10.6. Hazardous decomposition products

Organic acid vapors. Tin oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

DI-n-BUTYLBIS(2-ETHYLHEXANOATE)TIN, 50% in xylene (2781-10-4)	
ATE US (oral)	241.379 mg/kg body weight

Di-n-butylbis(2-ethylhexanoate)tin (2781-10-4)	
LD50 oral rat	125 mg/kg 136 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
ATE US (oral)	125 mg/kg body weight

Xylene (1330-20-7)	
LD50 oral rat	3500 mg/kg ; 4300 mg/kg
LD50 dermal rabbit	1700 mg/kg
LC50 inhalation rat (mg/l)	29.08 mg/l/4h
ATE US (oral)	3500 mg/kg body weight
ATE US (dermal)	1700 mg/kg body weight
ATE US (vapors)	29.08 mg/l/4h
ATE US (dust, mist)	29.08 mg/l/4h
Additional information	LCLo Inhalation man: 10,000ppm/6H

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.
Eye Irritation - rabbit: 5 mg/24H: severe (xylene)
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
None of the components in this product at concentrations >0.1% are listed by IARC, NTP, OSHA or ACGIH as a carcinogen.

Xylene (1330-20-7)	
IARC group	3 - Not classifiable

Reproductive toxicity : Not classified
Xylene has been found to have experimental reproductive effects.
Specific target organ toxicity – single exposure : May cause respiratory irritation.
Specific target organ toxicity – repeated exposure : May cause damage to organs through prolonged or repeated exposure.
May cause damage to organs through prolonged or repeated exposure
Aspiration hazard : Not classified
Symptoms/effects after inhalation : May cause respiratory irritation. May be harmful if inhaled.
Symptoms/effects after skin contact : Causes skin irritation. May be harmful in contact with skin.
Symptoms/effects after eye contact : Causes serious eye irritation.
Symptoms/effects after ingestion : Toxic if swallowed. Swallowing a small quantity of this material will result in serious health hazard.
Reason for classification : Expert judgment

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Very toxic to aquatic life.

Xylene (1330-20-7)	
LC50 fish 1	13.4 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])

DI-n-BUTYLBIS(2-ETHYLHEXANOATE)TIN, 50% in xylene

Safety Data Sheet

Xylene (1330-20-7)	
EC50 Daphnia 1	3.82 mg/l (Exposure time: 48 h - Species: water flea)
LC50 fish 2	2.661 - 4.093 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 2	0.6 mg/l (Exposure time: 48 h - Species: Gammarus lacustris)

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Xylene (1330-20-7)	
BCF fish 1	0.6 - 15
Log Pow	2.77 - 3.15

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the ozone layer : No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Sewage disposal recommendations : Do not dispose of waste into sewer.
Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to licensed waste disposal facility.
Additional information : Handle empty containers with care because residual vapors are flammable.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

14.1. UN number

UN-No.(DOT) : 1992
DOT NA no. : UN1992

14.2. UN proper shipping name

Transport document description : UN1992 Flammable liquids, toxic, n.o.s. (DI-n-BUTYLBIS(2-ETHYLHEXANOATE)TIN, 50% in xylene), 3 (6.1), III
Proper Shipping Name (DOT) : Flammable liquids, toxic, n.o.s.
(DI-n-BUTYLBIS(2-ETHYLHEXANOATE)TIN, 50% in xylene)
Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Packing group (DOT) : III - Minor Danger
Hazard labels (DOT) : 3 - Flammable liquid
6.1 - Poison



Dangerous for the environment : Yes

Marine pollutant : Yes



DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Symbols : G - Identifies PSN requiring a technical name

14.3. Additional information

Emergency Response Guide (ERG) Number : 131

Other information : No supplementary information available.

DI-n-BUTYLBIS(2-ETHYLHEXANOATE)TIN, 50% in xylene

Safety Data Sheet

Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 60 L
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L
CFR 175.75)

SECTION 15: Regulatory information

15.1. US Federal regulations

Di-n-butylbis(2-ethylhexanoate)tin (2781-10-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Xylene (1330-20-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	
SARA Section 313 - Emission Reporting	1 %

15.2. International regulations

CANADA

Di-n-butylbis(2-ethylhexanoate)tin (2781-10-4)	
Listed on the Canadian DSL (Domestic Substances List)	
Xylene (1330-20-7)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects

EU-Regulations

Di-n-butylbis(2-ethylhexanoate)tin (2781-10-4)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	
Xylene (1330-20-7)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	

National regulations

Di-n-butylbis(2-ethylhexanoate)tin (2781-10-4)	
Listed on the AICS (Australian Inventory of Chemical Substances) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory Listed on the Korean ECL (Existing Chemicals List) Listed on NZIoC (New Zealand Inventory of Chemicals) Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Japanese Pollutant Release and Transfer Register Law (PRTR Law) Listed on the Canadian IDL (Ingredient Disclosure List)	
Xylene (1330-20-7)	
Listed on the AICS (Australian Inventory of Chemical Substances) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory Listed on the Korean ECL (Existing Chemicals List) Listed on NZIoC (New Zealand Inventory of Chemicals) Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Japanese Poisonous and Deleterious Substances Control Law Japanese Pollutant Release and Transfer Register Law (PRTR Law) Listed on INSQ (Mexican National Inventory of Chemical Substances) Listed on CICR (Turkish Inventory and Control of Chemicals)	

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Di-n-butylbis(2-ethylhexanoate)tin (2781-10-4)
U.S. - Massachusetts - Right To Know List

DI-n-BUTYLBIS(2-ETHYLHEXANOATE)TIN, 50% in xylene

Safety Data Sheet

Xylene (1330-20-7)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Full text of H-phrases::

H226	Flammable liquid and vapor
H301	Toxic if swallowed
H312	Harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life

Abbreviations and acronyms

: Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor.

Hazard Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

Flammability : 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 F and boiling points above 100 F. as well as liquids with flash points between 73 F and 100 F. (Classes IB & IC)

Physical : 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.

Prepared by safety and environmental affairs.

Date of issue: 10/06/2016 Version: 1.0

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2019 Gelest Inc. Morrisville, PA 19067