

## TRIETHOXYSILYL MODIFIED POLY-1,2-BUTADIENE, 50% in toluene

Safety Data Sheet SSP-055

Date of issue: 13/01/2015

Revision date: 08/03/2019

Version: 2.1

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form	: Mixture
Physical state	: Liquid
Product name	: TRIETHOXYSILYL MODIFIED POLY-1,2-BUTADIENE, 50% in toluene
Product code	: SSP-055
Synonyms	: VINYLTRIETHOXYSILANE-1,2-BUTADIENE COPOLYMER; 1,3-BUTADIENE, HOMOPOLYMER, TRIETHOXYSILYL-MODIFIED
Chemical family	: ORGANOSILANE

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Use of the substance/mixture : Chemical intermediate

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

##### GELEST, INC.

11 East Steel Road  
Morrisville, PA 19067

##### USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

[info@gelest.com](mailto:info@gelest.com) - [www.gelest.com](http://www.gelest.com)

##### GELEST INC.

Fritz-Klatte-Strasse 8  
65933 Frankfurt

##### Germany

T +49 (0) 69 3535106-500 - F +49 (0) 69 3535106-501 - (M-F): 8:00 AM - 4:00 PM

[info@gelestde.com](mailto:info@gelestde.com) - [www.gelestde.com](http://www.gelestde.com)

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2	H225
Skin corrosion/irritation, Category 2	H315
Reproductive toxicity, Category 2	H361
Specific target organ toxicity — Single exposure, Category 3, Narcosis	H336
Specific target organ toxicity — Repeated exposure, Category 2	H373
Full text of H statements : see section 16	

##### Adverse physicochemical, human health and environmental effects

No additional information available

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

GHS08

Signal word (CLP) :

: Danger

# TRIETHOXSILYL MODIFIED POLY-1,2-BUTADIENE, 50% in toluene

## Safety Data Sheet

Hazardous ingredients	: Toluene
Hazard statements (CLP)	: H225 - Highly flammable liquid and vapour. H315 - Causes skin irritation. H336 - May cause drowsiness or dizziness. H361 - Suspected of damaging fertility or the unborn child. H373 - May cause damage to organs through prolonged or repeated exposure.
Precautionary statements (CLP)	: P280 - Wear protective gloves/protective clothing/eye protection/face protection. P202 - Do not handle until all safety precautions have been read and understood. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P240 - Ground/bond container and receiving equipment. P264 - Wash hands thoroughly after handling. P308+P313 - IF exposed or concerned: Get medical advice/attention.

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Triethoxysilyl modified poly-1,2-butadiene	(CAS-No.) 72905-90-9	45 - 50	Not classified
Toluene	(CAS-No.) 108-88-3 (EC-No.) 203-625-9 (EC Index-No.) 601-021-00-3 (REACH-no) 01-2119471310-51-0127	45 - 50	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.
First-aid measures after skin contact	: Wash with plenty of water/.... Get medical advice/attention.
First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
First-aid measures after ingestion	: Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Suspected of damaging fertility or the unborn child.
Symptoms/effects after inhalation	: May cause drowsiness or dizziness. May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: May be harmful if swallowed. Oral toxicity is associated with toluene which causes psychophysiological and bone marrow changes nausea, vomiting, headache, visual effects including blindness.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Foam. Carbon dioxide. Dry chemical.

# TRIETHOXSILYL MODIFIED POLY-1,2-BUTADIENE, 50% in toluene

## Safety Data Sheet

Unsuitable extinguishing media : Do not use straight streams.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapour. Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.

Explosion hazard : May form flammable/explosive vapour-air mixture.

### 5.3. Advice for firefighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Use water spray to cool exposed surfaces.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Avoid all eye and skin contact and do not breathe vapour and mist.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Eliminate every possible source of ignition. Use special care to avoid static electric charges.

#### 6.1.1. For non-emergency personnel

Protective equipment : Wear protective equipment as described in Section 8.

Emergency procedures : Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or shovel spills into appropriate container for disposal. Use only non-sparking tools.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapours are flammable. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid all eye and skin contact and do not breathe vapour and mist. Ground/bond container and receiving equipment. Take precautionary measures against static discharge. Use only outdoors or in a well-ventilated area. Use only non-sparking tools.

Hygiene measures : Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof electrical equipment.

Storage conditions : Keep container tightly closed. Store cold.

Incompatible materials : Acids. Oxidizing agent. Peroxides. Moisture. Water :

Storage area : Store in a well-ventilated place. Store away from heat.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Toluene (108-88-3)		
EU	IOELV TWA (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup>
EU	IOELV TWA (ppm)	50 ppm
EU	IOELV STEL (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
EU	IOELV STEL (ppm)	100 ppm
Austria	MAK (mg/m <sup>3</sup> )	190 mg/m <sup>3</sup>
Austria	MAK (ppm)	50 ppm
Austria	MAK Short time value (mg/m <sup>3</sup> )	380 mg/m <sup>3</sup>

# TRIETHOXYSYLYL MODIFIED POLY-1,2-BUTADIENE, 50% in toluene

## Safety Data Sheet

Toluene (108-88-3)		
Austria	MAK Short time value (ppm)	100 ppm
Belgium	Limit value (mg/m <sup>3</sup> )	77 mg/m <sup>3</sup>
Belgium	Limit value (ppm)	20 ppm
Belgium	Short time value (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
Belgium	Short time value (ppm)	100 ppm
Bulgaria	OEL TWA (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup>
Bulgaria	OEL TWA (ppm)	50 ppm
Bulgaria	OEL STEL (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
Bulgaria	OEL STEL (ppm)	100 ppm
Cyprus	OEL TWA (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup>
Cyprus	OEL TWA (ppm)	50 ppm
Cyprus	OEL STEL (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
Cyprus	OEL STEL (ppm)	100 ppm
France	VLE (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup> (restrictive limit)
France	VLE (ppm)	100 ppm (restrictive limit)
France	VME (mg/m <sup>3</sup> )	76.8 mg/m <sup>3</sup> (restrictive limit)
France	VME (ppm)	20 ppm (restrictive limit)
Germany	TRGS 900 Occupational exposure limit value (mg/m <sup>3</sup> )	190 mg/m <sup>3</sup> (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Germany	TRGS 900 Occupational exposure limit value (ppm)	50 ppm (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Germany	TRGS 903 Biological limit value	600 µg/l (Medium: whole blood - Time: end of shift - Parameter: Toluene) 1.5 mg/l (Medium: urine - Time: end of several shifts - Parameter: o-Cresol (after hydrolysis))
Gibraltar	Eight hours mg/m <sup>3</sup>	192 mg/m <sup>3</sup>
Gibraltar	Eight hours ppm	50 ppm
Gibraltar	Short-term mg/m <sup>3</sup>	384 mg/m <sup>3</sup>
Gibraltar	Short-term ppm	100 ppm
Greece	OEL TWA (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup>
Greece	OEL TWA (ppm)	50 ppm
Greece	OEL STEL (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
Greece	OEL STEL (ppm)	100 ppm
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	20 ppm
Italy	OEL TWA (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup>
Italy	OEL TWA (ppm)	50 ppm
Latvia	OEL TWA (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
Latvia	OEL TWA (ppm)	14 ppm
USA IDLH	US IDLH (ppm)	500 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	375 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m <sup>3</sup> )	560 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (STEL) (ppm)	150 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
USA OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm
Spain	VLA-ED (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup> (indicative limit value; manufacturing, commercialization, and use restrictions under REACH)
Spain	VLA-ED (ppm)	50 ppm (indicative limit value; manufacturing, commercialization, and use restrictions under REACH)
Spain	VLA-EC (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
Spain	VLA-EC (ppm)	100 ppm
Switzerland	KZGW (mg/m <sup>3</sup> )	760 mg/m <sup>3</sup>
Switzerland	KZGW (ppm)	200 ppm
Switzerland	MAK (mg/m <sup>3</sup> )	190 mg/m <sup>3</sup>
Switzerland	MAK (ppm)	50 ppm
Netherlands	Grenswaarde TGG 8H (mg/m <sup>3</sup> )	150 mg/m <sup>3</sup>

# TRIETHOXYSYLYL MODIFIED POLY-1,2-BUTADIENE, 50% in toluene

## Safety Data Sheet

Toluene (108-88-3)		
Netherlands	Grenswaarde TGG 15MIN (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	191 mg/m <sup>3</sup>
United Kingdom	WEL TWA (ppm)	50 ppm
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
United Kingdom	WEL STEL (ppm)	100 ppm
Czech Republic	Expoziční limity (PEL) (mg/m <sup>3</sup> )	200 mg/m <sup>3</sup>
Denmark	Grænseværdie (langvarig) (mg/m <sup>3</sup> )	94 mg/m <sup>3</sup>
Denmark	Grænseværdie (langvarig) (ppm)	25 ppm
Finland	HTP-arvo (8h) (mg/m <sup>3</sup> )	81 mg/m <sup>3</sup>
Finland	HTP-arvo (8h) (ppm)	25 ppm
Finland	HTP-arvo (15 min)	380 mg/m <sup>3</sup>
Finland	HTP-arvo (15 min) (ppm)	100 ppm
Hungary	AK-érték	190 mg/m <sup>3</sup>
Hungary	CK-érték	380 mg/m <sup>3</sup>
Ireland	OEL (8 hours ref) (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup>
Ireland	OEL (8 hours ref) (ppm)	50 ppm
Ireland	OEL (15 min ref) (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
Ireland	OEL (15 min ref) (ppm)	100 ppm
Lithuania	IPRV (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup>
Lithuania	IPRV (ppm)	50 ppm
Lithuania	TPRV (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
Lithuania	TPRV (ppm)	100 ppm
Malta	OEL TWA (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup>
Malta	OEL TWA (ppm)	50 ppm
Malta	OEL STEL (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
Malta	OEL STEL (ppm)	100 ppm
Norway	Grenseverdier (AN) (mg/m <sup>3</sup> )	94 mg/m <sup>3</sup>
Norway	Grenseverdier (AN) (ppm)	25 ppm
Norway	Grenseverdier (Korttidsverdi) (mg/m <sup>3</sup> )	94 mg/m <sup>3</sup>
Norway	Grenseverdier (Korttidsverdi) (ppm)	25 ppm
Poland	NDS (mg/m <sup>3</sup> )	100 mg/m <sup>3</sup>
Poland	NDSCh (mg/m <sup>3</sup> )	200 mg/m <sup>3</sup>
Romania	OEL TWA (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup>
Romania	OEL TWA (ppm)	50 ppm
Romania	OEL STEL (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
Romania	OEL STEL (ppm)	100 ppm
Slovakia	NPHV (priemerná) (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup>
Slovakia	NPHV (priemerná) (ppm)	50 ppm
Slovakia	NPHV (Hraničná) (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
Sweden	nivågränsvärde (NVG) (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup>
Sweden	nivågränsvärde (NVG) (ppm)	50 ppm
Sweden	kortidsvärde (KTV) (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
Sweden	kortidsvärde (KTV) (ppm)	100 ppm
Canada (Quebec)	VEMP (mg/m <sup>3</sup> )	188 mg/m <sup>3</sup>
Canada (Quebec)	VEMP (ppm)	50 ppm
Australia	TWA (mg/m <sup>3</sup> )	191 mg/m <sup>3</sup>
Australia	TWA (ppm)	50 ppm
Australia	STEL (mg/m <sup>3</sup> )	574 mg/m <sup>3</sup>
Australia	STEL (ppm)	150 ppm
Portugal	OEL TWA (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup> (indicative limit value)
Portugal	OEL TWA (ppm)	50 ppm (indicative limit value)

# TRIETHOXSILYL MODIFIED POLY-1,2-BUTADIENE, 50% in toluene

## Safety Data Sheet

Toluene (108-88-3)		
Portugal	OEL STEL (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup> (indicative limit value)
Portugal	OEL STEL (ppm)	100 ppm (indicative limit value)
Portugal	OEL chemical category (PT)	A4 - Not Classifiable as a Human Carcinogen, skin - potential for cutaneous exposure indicative limit value

### 8.2. Exposure controls

#### Appropriate engineering controls:

Provide local exhaust or general room ventilation.

#### Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

#### Hand protection:

Neoprene or nitrile rubber gloves

#### Eye protection:

Chemical goggles. Contact lenses should not be worn

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified organic vapor (black cartridge) respirator.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Solution.
Molecular mass	: 3500 - 4500 g/mol
Colour	: Pale yellow. Amber.
Odour	: No data available
Odour threshold	: No data available
Refractive index	: No additional information available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: < 0 °C
Freezing point	: No data available
Boiling point	: 110 °C (initial, toluene)
Flash point	: 4 °C
Auto-ignition temperature	: 536 (toluene)
Decomposition temperature	: No data available
Flammability (solid, gas)	: Highly flammable liquid and vapour.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: > 3
Relative density	: 0.9
% Volatiles	: > 45 °C
Solubility	: Reacts with water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: 75 - 400 cSt
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: 1.27 - 7 vol % (lower; upper: toluene)

### 9.2. Other information

No additional information available



# TRIETHOXSILYL MODIFIED POLY-1,2-BUTADIENE, 50% in toluene

## Safety Data Sheet

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No additional information available

#### 10.2. Chemical stability

Stable in sealed containers stored under a dry inert atmosphere.

#### 10.3. Possibility of hazardous reactions

Reacts with water and moisture in air liberating ethanol and crosslinking.

#### 10.4. Conditions to avoid

Heat. Open flame. Sparks.

#### 10.5. Incompatible materials

Acids. Oxidizing agent. Peroxides. Moisture. Water :

#### 10.6. Hazardous decomposition products

Organic acid vapors.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Not classified

Toluene (108-88-3)	
LD50 oral rat	2600 mg/kg
LD50 dermal rabbit	12000 mg/kg
LC50 inhalation rat (mg/l)	12.5 mg/l/4h
ATE CLP (oral)	2600 mg/kg bodyweight
ATE CLP (dermal)	12000 mg/kg bodyweight
ATE CLP (vapours)	12.5 mg/l/4h
ATE CLP (dust,mist)	12.5 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Not classified

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Toluene (108-88-3)	
IARC group	3 - Not classifiable

Reproductive toxicity : Suspected of damaging fertility or the unborn child.

STOT-single exposure : May cause drowsiness or dizziness.

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

Potential adverse human health effects and symptoms : Vapor inhalation of toluene may lead to impairment of coordination mental alertness, and reaction times, leading to accident proneness. Exposure to levels around 500ppm leads to narcotic effects including nausea, headache and mental confusion.

Symptoms/effects after inhalation : May cause drowsiness or dizziness. May cause irritation to the respiratory tract.

Symptoms/effects after skin contact : Causes skin irritation.

Symptoms/effects after eye contact : Causes serious eye irritation.

Symptoms/effects after ingestion : May be harmful if swallowed. Oral toxicity is associated with toluene which causes psychophysiological and bone marrow changes nausea, vomiting, headache, visual effects including blindness.

Reason for classification : Expert judgment

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : Harmful to aquatic life.

Acute aquatic toxicity : Not classified

Chronic aquatic toxicity : Not classified

Toluene (108-88-3)	
LC50 fish 1	15.22 - 19.05 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	5.46 - 9.83 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 fish 2	12.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

# TRIETHOXSILYL MODIFIED POLY-1,2-BUTADIENE, 50% in toluene

## Safety Data Sheet

### Toluene (108-88-3)

EC50 Daphnia 2	11.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)
----------------	--

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

### Toluene (108-88-3)

Log Pow	2.65
---------	------

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Sewage disposal recommendations : Do not dispose of waste into sewer.  
Product/Packaging disposal recommendations : May be incinerated. Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to licensed waste disposal facility.  
Additional information : Handle empty containers with care because residual vapours are flammable.  
Ecology - waste materials : Avoid release to the environment.

## SECTION 14: Transport information

### 14.1. UN number

In accordance with ADR / RID / IMDG / IATA / ADN

### 14.1. UN number

UN-No. (ADR)	: 1294
UN-No. (IMDG)	: 1294
UN-No. (IATA)	: 1294
UN-No. (ADN)	: 1294
UN-No. (RID)	: 1294

### 14.2. UN proper shipping name

Proper Shipping Name (ADR)	: TOLUENE
Proper Shipping Name (IMDG)	: TOLUENE
Proper Shipping Name (IATA)	: Toluene
Proper Shipping Name (ADN)	: TOLUENE
Proper Shipping Name (RID)	: TOLUENE
Transport document description (ADR)	: UN 1294 TOLUENE (TRIETHOXSILYL MODIFIED POLY-1,2-BUTADIENE, 50% in toluene), 3, II, (D/E)
Transport document description (IMDG)	: UN 1294 TOLUENE (TRIETHOXSILYL MODIFIED POLY-1,2-BUTADIENE, 50% in toluene), 3, II (7°C c.c.)
Transport document description (IATA)	: UN 1294 Toluene (TRIETHOXSILYL MODIFIED POLY-1,2-BUTADIENE, 50% in toluene), 3, II
Transport document description (ADN)	: UN 1294 TOLUENE (TRIETHOXSILYL MODIFIED POLY-1,2-BUTADIENE, 50% in toluene), 3, II
Transport document description (RID)	: UN 1294 TOLUENE (TRIETHOXSILYL MODIFIED POLY-1,2-BUTADIENE, 50% in toluene), 3, II

### 14.3. Transport hazard class(es)

#### ADR

Transport hazard class(es) (ADR)	: 3
Danger labels (ADR)	: 3





# TRIETHOXSILYL MODIFIED POLY-1,2-BUTADIENE, 50% in toluene

## Safety Data Sheet

### IMDG

Transport hazard class(es) (IMDG) : 3  
Danger labels (IMDG) : 3



### IATA

Transport hazard class(es) (IATA) : 3  
Hazard labels (IATA) : 3



### ADN

Transport hazard class(es) (ADN) : 3  
Danger labels (ADN) : 3



### RID

Transport hazard class(es) (RID) : 3  
Danger labels (RID) : 3



### 14.4. Packing group

Packing group (ADR) : II  
Packing group (IMDG) : II  
Packing group (IATA) : II  
Packing group (ADN) : II  
Packing group (RID) : II

### 14.5. Environmental hazards

Dangerous for the environment : No  
Marine pollutant : No  
Other information : No supplementary information available

### 14.6. Special precautions for user


#### - Overland transport

Classification code (ADR) : F1  
Limited quantities (ADR) : 11  
Excepted quantities (ADR) : E2  
Packing instructions (ADR) : P001, IBC02, R001  
Special packing provisions (ADR) : RR7  
Mixed packing provisions (ADR) : MP19

# TRIETHOXSILYL MODIFIED POLY-1,2-BUTADIENE, 50% in toluene

## Safety Data Sheet

Portable tank and bulk container instructions (ADR) : T4  
Portable tank and bulk container special provisions (ADR) : TP1  
Tank code (ADR) : LGBF  
Vehicle for tank carriage : FL  
Transport category (ADR) : 2  
Special provisions for carriage - Operation (ADR) : S2, S20  
Hazard identification number (Kemler No.) : 33  
Orange plates :



Tunnel restriction code (ADR) : D/E  
EAC code : 3YE

### - Transport by sea

Limited quantities (IMDG) : 1 L  
Excepted quantities (IMDG) : E2  
Packing instructions (IMDG) : P001  
IBC packing instructions (IMDG) : IBC02  
Tank instructions (IMDG) : T4  
Tank special provisions (IMDG) : TP1  
EmS-No. (Fire) : F-E  
EmS-No. (Spillage) : S-D  
Stowage category (IMDG) : B  
Flash point (IMDG) : 7°C c.c.  
Properties and observations (IMDG) : Colourless liquid with a benzene-like odour. Flashpoint: 7°C c.c. Explosive limits: 1.27% to 7% Immiscible with water.

### - Air transport

PCA Excepted quantities (IATA) : E2  
PCA Limited quantities (IATA) : Y341  
PCA limited quantity max net quantity (IATA) : 1L  
PCA packing instructions (IATA) : 353  
PCA max net quantity (IATA) : 5L  
CAO packing instructions (IATA) : 364  
CAO max net quantity (IATA) : 60L  
ERG code (IATA) : 3L

### - Inland waterway transport

Classification code (ADN) : F1  
Limited quantities (ADN) : 1 L  
Excepted quantities (ADN) : E2  
Carriage permitted (ADN) : T  
Equipment required (ADN) : PP, EX, A  
Ventilation (ADN) : VE01  
Number of blue cones/lights (ADN) : 1

### - Rail transport

Classification code (RID) : F1  
Limited quantities (RID) : 1L  
Excepted quantities (RID) : E2  
Packing instructions (RID) : P001, IBC02, R001  
Mixed packing provisions (RID) : MP19  
Portable tank and bulk container instructions (RID) : T4  
Portable tank and bulk container special provisions (RID) : TP1  
Tank codes for RID tanks (RID) : LGBF

# TRIETHOXSILYL MODIFIED POLY-1,2-BUTADIENE, 50% in toluene

## Safety Data Sheet

Transport category (RID) : 2  
Colis express (express parcels) (RID) : CE7  
Hazard identification number (RID) : 33

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions  
Contains no substance on the REACH candidate list  
Contains no REACH Annex XIV substances  
Contains no substance subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.  
Substance(s) are not subject to Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Directive 79/117/EEC.  
Contains no REACH Annex XIV substances

% Volatiles : > 45 °C

#### 15.1.2. National regulations

##### Germany

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

##### Netherlands

SZW-lijst van kankerverwekkende stoffen : Toluene is listed  
SZW-lijst van mutagene stoffen : None of the components are listed  
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed  
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed  
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Toluene is listed

##### Denmark

Class for fire hazard : Class I-1  
Store unit : 1 liter  
Classification remarks : F <Flam. Liq. 2>; Emergency management guidelines for the storage of flammable liquids must be followed  
Danish National Regulations : Young people below the age of 18 years are not allowed to use the product  
Pregnant/breastfeeding women working with the product must not be in direct contact with the product  
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

### 15.2. Chemical safety assessment

No additional information available

## SECTION 16: Other information

Abbreviations and acronyms:

Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor

Other information : Prepared by safety and environmental affairs.

Full text of H- and EUH-statements:

Acute Tox. 4 (Inhalation:vapour) Acute toxicity (inhalation:vapour) Category 4

# TRIETHOXYSILYL MODIFIED POLY-1,2-BUTADIENE, 50% in toluene

## Safety Data Sheet

Asp. Tox. 1	Aspiration hazard, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Repr. 2	Reproductive toxicity, Category 2
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.

SDS EU (REACH Annex II) - Custom

*The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.*

© 2019 Gelest Inc. Morrisville, PA 19067

The logo for Gelest, featuring the word "Gelest" in a large, white, serif font. The letters are set against a light blue background that is shaped like a right-angled triangle pointing to the right. The "G" is partially cut off by the left edge of the frame.