
FLOAT TRAILERS
TANDEM/TRIDEM, TRIDEM +1, QUAD

gincor.com

The GINCOR Werx JC-Series trailer design holds a proven track record of over 40 years of excellence. Our trailers offer structural loading capacities that match or exceed those of our competitors, demonstrating our commitment to strength and reliability. Our long-term success comes from meeting customer needs and delivering a premium product.

GINCOR Werx JC-Series Trailers are engineered to meet your operational needs.

Contact your local sales manager for further details.





OPTIONS

- Aluminum/Steel Gooseneck Fenders
- Gooseneck Mounted Pup Motor
- Two Position Removable King Pin
- Gooseneck Extension
- Recessed Air Activated Deck Ramps
- Knuckle Well
- Deck Stiffeners
- Extendable Deck
- Shimmable/Detachable Deck
- Axle Spread 49”, 60”, & 72”
- Lift Axle
- Load Bearing Bridge Fenders (Optional Wood Covering)
- Wide Load Sign (Permanent, Removable, Fold Over)
- Pins and Connections For Future Pin On Axle
- Bridge Beavertail And Ramps
- Aluminum Wheels

FLOAT TRAILERS
TANDEM/TRIDEM, TRIDEM +1, QUAD

gincor.com
info@gincor.com
(519) 676 7900

Configuration	
Tandem (35-40 ton)	Optional
Tridem (55-60-75 ton)	Optional
Tridem + 1 (55-60-75 ton)	Optional
Quad (55-60-75 ton)	Optional
Dimensions	
Width 8’ 6” - 10’	Optional
24” Deck height (loaded)	Standard
Overall length 46’ +	Optional
Deck length 24’ - 30’	Optional
Construction	
Main beams 16” heavy duty I beam	Standard
T1 (100 KDI yield) steel chassis beams	Standard
Cross members 10” flange beams	Standard
Removeable Non-Ground Bearing Hydraulic Gooseneck	
12’ length	Standard
16” setback with 94” swing	Standard
Connections for future g/n extension	Standard
50” approximate 5th wheel height	Standard

Storage	
Storage box with lockable lid in gooseneck	Standard
Front deck storage box between main beams	Standard
Decking	
2-1/4” oak decking & 1/4” checker plate	Standard
Primary Suspension	
Air ride 9” ride height	Standard
Axles	
25,000 lbs	Standard
10 bolt piloted hubs tapered spindles and bearings	Standard
Brakes	
Air with 30/30 chambers	Standard
16.50 x 7 auto slacks outboard drum	Standard
Tires	
275/70 R 22.5	Standard
Wheels	
Ten bolt 8.25 x 22.5 steel white	Standard

ABS	
2S1M (50 Ton or lighter)	Standard
Securement	
Standard 1” “D” rings	Standard
Standard forged outriggers	Standard
Electrical	
Grote ultra blue sealed wire harness	Standard
Lighting	
LED lighting	Standard
Surface Preparation	
Commercial sand blast	Standard
Paint	
Two part epoxy primer, polyurethane finish	Standard

This literature is for illustrative purposes only. Some standard features and options may not be exactly as shown or reflective of your geographic region of operation. Consult your GINCOR Werx representative for details. Specifications are subject to change without notice.

JC-FT 03/2025 NA

GINCOR Werx JC-Series Trailers are SPIF compliant.

