STEP DECK TRAILERS
TANDEM/TRIDEM, 3 +1 LIFT/STEER

gincor.com

The GINCOR Werx JC-Series trailer design holds a proven track record of over 40 years of excellence. Our trailers offer structural loading capacities that match or exceed those of our competitors, demonstrating our commitment to strength and reliability. Our long-term success comes from meeting customer needs and delivering a premium product.

GINCOR Werx JC-Series Trailers are engineered to meet your operational needs.

Contact your local sales manager for further details.





STANDARD FEATURES

- T1 (100 KDI Yield) steel chassis beams
- Hardwood upper deck
- Air ride 6.5” ride height
- 25,000 lbs axles
- Commercial sand blast surface preparation
- Two part epoxy primer, polyurethane finish
- LED lighting

OPTIONS

- Beavertail And Ramps
- 1-5/16” Shiplap Hardwood
- Recessed Air Activated Deck Ramps
- Aluminum Storage Box
- Winch Hydraulic/Electric
- Aluminum Wheels
- Axle Spread 49”, 60” & 72”
- Lift Axle
- Wide Load Sign

STEP DECK TRAILERS
TANDEM/TRIDEM, 3 +1 LIFT/STEER

gincor.com
info@gincor.com
(519) 676 7900

Dimensions	
Overall length 53	Standard
Width 8’ 6” - 10’	Optional
Construction	
6” Channel crossmembers	Standard
T1 (100 KDI Yield) steel chassis beams	Standard
8”-10” perimeter channel	Optional
Upper Deck	
11’ length	Standard
Hardwood	Standard
Coupler height 50” approximate	Standard
Lower Deck	
50” approximate 5th wheel height	Standard
42’ long	Standard
Storage	Optional

Primary Suspension	
Air ride 6.5” ride height	Standard
Axles	
25,000 lbs	Standard
8 bolt piloted hubs tapered spindles and bearings	Standard
Brakes	
Air with 30/30 chambers	Standard
16.50 x 7 auto slacks outboard drum	Standard
Tires	
245/70 R 17.5	Standard
Wheels	
6.75 x 17.5 steel white	Standard
ABS	
2S1M	Standard

Securement	
Upper deck rub rail and pocket	Standard
Lower deck optional rub rail and pocket or “D” rings	Standard
Electrical	
Grote ultra blue sealed wire harness	Standard
Lighting	
LED lighting	Standard
Surface Preparation	
Commercial sand blast	Standard
Paint	
Two part epoxy primer, polyurethane finish	Standard

This literature is for illustrative purposes only. Some standard features and options may not be exactly as shown or reflective of your geographic region of operation. Consult your GINCOR Werx representative for details. Specifications are subject to change without notice.

JC-SD 03/2025 NA

GINCOR Werx JC-Series Trailers are SPIF compliant.

