GINCOR WERX LIVE BOTTOM SPECIFICATION CHART

304LBC-S



393LBC-S



413LBC-S



484LBC-S



485LBC-S



458LBC-S



MODEL	304LBC-S		393LBC-S		413LBC-S		484LBC-S		485LBC-S		458LBC-S	
	capacity (m^3) Top rail	capacity (cu.yrds) Top rail	capacity (m^3) Top rail	capacity (cu.yrds) Top rail	capacity (m^3) Top rail	capacity (cu.yrds) Top rail	capacity (m^3) Top rail	capacity (cu.yrds) Top rail	capacity (m^3) Top rail	capacity (cu.yrds) Top rail	capacity (m^3) Top rail	capacity (cu.yrds) Top rail
CAPACITY	21 m^3	27.5 yd^3	27.4 m^3	35.8 yd^3	28.8 m^3	37.7 yd^3	34.1 m^3	44.6 yd^3	34.1 m^3	44.6 yd^3	31.7 m^3	41.5 yd^3
TARE	7,650 kg, EST.	16,865 lb, EST.	9,750 kg, EST.	21,495 lb, EST.	8,800 kg, EST.	19,400 lb, EST.	11,500 kg, EST.	25,353 lb, EST.	12,990 kg, EST.	28,700 lb, EST.	14,780 kg, EST.	32,665 lb, EST.
GVWR	57,379 kg	126,499 lb	46,947 kg	103,750 lb	46,947 kg	103,750 lb	57,379 kg	126,499 lb	64,087 kg	141,630 lb	99,110 kg	218,500 lb
OVERALL LENGTH	378-5/8"		478-5/8"		492-10 5/8"		584-7/8"		588-11/16"		551-1/2"	
OVERALL WIDTH	101-9/16"		101-5/8"		101-9/16"		101-1/4"		101-9/16"		101-5/8"	
OVERALL HEIGHT	124-1/2"		125-3/8"		125-1/2"		125-3/8"		125-3/8"		124-3/16"	
# OF AXLES	4		3		3		4		5		8	





GINCOR WERX

1 Solvay Drive, Blenheim, Ontario - N0P 1A0 - Canada
Phone: (519) 676-7900 | Email: info@gincor.com | www.gincor.com

JEFF REED
Regional Sales Manager – NE USA
Phone: 1 (226) 542-3608 | Email: jeffreed@gincor.com

TARA NEAD
Inside Sales
Phone: 1 (519) 809-6127 | Email: taranead@gincor.com

gincor.com

START YOUR BUILD AT OUR NEW WEBSITE

Visit our new website at **www.gincor.com** to start building your Live Bottom Trailer today!



The depictions of the Live Bottom Trailers in this brochure are for general information purposes only, as to those manufactured by GINCOR Werx during the current model year. Since we continually strive to improve our products, actual products may differ and specifications are subject to change with or without notice. Product information, specifications, and photography in this brochure may contain some features that are optional on your Live Bottom Trailer. All capacities are approximate and dimensions are nominal. Availability may be limited.

GTW-LIVE BOTTOM TRAILER 02/2026 NA

gincor.com

GINCOR WERX

LIVE BOTTOM TRAILERS



WORK SAFER, FASTER, AND SMARTER.





ONE PLATFORM. MULTIPLE SOLUTIONS.

GINCOR Werx Live Bottom Trailers are built for the long haul and engineered to be stronger and more reliable than our competitors. Our heavy-duty main beams and cross-member designs are just a few of the many quality features that set our trailers above others. All components and design elements are specifically chosen with longevity and ease-of-use in mind.

Our primary focus is on quality and attention to detail. We strive to build every product we manufacture with pride and passion for excellence with our customers satisfaction in mind.



Live Bottom Trailer with Microsurfacing tank option.



393LBC-S Model shown.

FEATURES & BENEFITS

STANDARD FEATURES

- 1/8" 450 AR steel body
- 4" full-roller chain
- Standard reversible-direction belt
- Air ride suspension w/ 25,000 lb axle
- Automatic chain oilers
- Sherwin-Williams® Epoxy Primer Polyurethane Topcoat
- Full LED lighting
- 2-speed landing gear with Gearbox on D/S 17" Travel
- Black poly half-moon fenders
- Aluminum light bars
- Fully insulated walls
- Electric slide tarp (front-back)
- Rear strobe lights
- Air operated tailgate
- Aluminum wheels
- Stainless steel No. 8 mirror finished exterior side wall sheeting

POPULAR OPTIONS

- Frame colour
- Aluminum release agent tank & spray
- Camera systems to monitor unloading
- Stainless steel half round fenders
- Aluminum endgate
- Aluminum mill finished exterior side wall sheeting
- Back-up alarm, back-up lights
- 25,000 lb steerable lift axle
- Auto-sensing lift axles
- Various tarp options
- Secondary gate locks

FEATURES & BENEFITS



KNIFE GATE
Heavy-duty design for precise control and clean material shutoff.

OPTIONAL.



RELEASE AGENT TANK
Optional tank with hose reel and sprayer for applying asphalt release agents.

OPTIONAL.



REVERSIBLE-DIRECTION BELT
Industrial-grade belt system engineered for controlled unloading and recovery.

STANDARD.



SPREADER CHUTE
Rugged rear discharge solution for consistent, accurate material placement.

OPTIONAL.



AIR OPERATED TAILGATE
Robust air-actuated system designed for secure transport and smooth unloading.

STANDARD.



BELT OPTIONS
High-performance belt configurations matched to demanding materials and workloads.

OPTIONAL.



ELECTRIC SLIDE TARP
Heavy-duty electric tarp system for fast, safe load coverage.

STANDARD.



TARP OPTIONS
Our sliding tarp system offers fast, secure coverage, while our side-rolling tarp system reduces bulk and maximizes access.

OPTIONAL.



FULLY INSULATED WALLS WITH HEATED PANELS
Engineered to maintain material temperature even in harsh, cold-weather conditions.

OPTIONAL.