gincor.com

GINCOR WERX®

JC-SERIES TRAILERS



STRENGTH YOU CAN COUNT ON.



JC-Series Tridem Tag Trailer
with optional air ramps

TAG TRAILERS

The GINCOR Werx JC-Series Tag Trailer is built for dependable performance and lasting durability. Designed to handle demanding loads and tough job sites, it provides the strength and stability needed for efficient equipment transport.

Engineered with productivity in mind, the JC-Series Tag Trailer delivers reliable performance you can trust every day.

STANDARD FEATURES

- 34" deck height (loaded)
- Steer axle models come with T1 100 KSI yield steel chassis beams
- Main beams 12" heavy duty I beam (wide flange)
- SAF Holland DB-100 pintle eyes
- Adjustable pintle eye (24"/28"/32")
- Dual 60,000lbs landing gear with 2 speed gear box
- Full LED lighting
- 5' beavertail ramps
- 2-1/4" oak decking & 1/4" checker plate over wheels
- Standard tongue storage
- 235/75 R 17.5 tires
- Two part epoxy primer, polyurethane finish

POPULAR OPTIONS

- Paver or construction style
- Over width 9' and 9' 6"
- Deck lengths available in 1' increments
- Manual or air tilt deck
- Flat deck
- Drive on beavertail
- Air suspension
- Lift axle kit (non-conforming)
- Axle spread 49" 60" 72"
- Aluminum rims
- Outriggers
- Winch track and winches
- Galvanized finish
- Air ramp

GINCOR WERX®

TRIDEM TAG



CHECKER PLATE (Wheel Wells & Beavertail)

OPTIONAL



D-RINGS

STANDARD



ALUMINUM WHEELS

OPTIONAL



GALVANIZED FINISH

OPTIONAL



OAK DECK

STANDARD



TONGUE STORAGE

STANDARD



12" 35 lb MAIN BEAM

STANDARD



LANDING GEAR

STANDARD

DESCRIPTION	25 TON TRIDEM TAG (SPIF 26)	25 TON TRIDEM AIR TILT TAG (East Coast)
Overall Length (ft)	36'-6"	36'-6"
Overall Width (in)	8'-6"	8'-6"
Main Deck Length (ft)	25'	24'
Tongue Length(ft)	6'	6'
Beavertail(ft)	5'	6'
Ramp Length (ft)	6'	6'
Ramp Width(in)	40"	40"
Laden Deck Height(in)	34"	34"
Axle Count	3	3
Track Spacing (in)	79.5	79.5
Axle Spread (in)	72	49
Suspension Type	Spring	Spring
Suspension Ride Height (in)	6.5	6.5
Wheel Material	Steel (inside & outside)	Steel (inside & outside)
Wheel Size (in)	6.75 x 17.5	6.75 x 17.5
Tire Size	235/75R-17.5 (Qty 12)	235/75R-17.5 (Qty 12)
Brake Spec (in)	12.25 x 7.5 (air drum); Auto slacks; 30/30 maxis	12.25 x 7.5 (air drum); Auto slacks; 30/30 maxis
Landing Gear	HOLLAND double leg, Mark-V, 2-speed	HOLLAND double leg, Mark-V, 2-speed
Air Tilt Mechanism	Not Available	Tilts on Four Airbags

GINCOR WERX®



JC-Series 3 Axle 55-Tonne Float

FLOAT TRAILERS

The GINCOR Werx JC-Series Float Trailer is engineered for high structural capacity and long-term durability. Built to perform in tough working conditions, it handles the demanding requirements of heavy equipment transport with confidence.

Designed with your operation in mind, the JC-Series delivers dependable performance—job after job.

GINCOR WERX®

STANDARD FEATURES

- 16" - 24" deck height (loaded)
- 16" setback with 94" swing
- T1 (100 KSI yield) steel chassis beams
- Cross members 10" flange beams
- 275/70 R 22.5 tires
- Full LED lighting
- Air ride 9" ride height
- 2-1/4" oak decking & 1/4" checker plate
- Standard deck storage
- 2S1M ABS brakes(50 Tonne or lighter)
- Two part epoxy primer, polyurethane finish

POPULAR OPTIONS

- Aluminum/steel gooseneck fenders
- Gooseneck mounted pup motor
- Two position removable king pin
- Gooseneck extension
- Recessed air activated deck ramps
- Extendable deck
- Pins and connections for future pin on axle
- Bridge beavertail and ramps
- Wide load sign (permanent, removable or fold over)
- Axle spread 55", 60", and 72"
- Shimmable/detachable deck

55/60/75-TONNE FLOAT

(120,000 lb - 165,000 lb)



AIR RAMPS

OPTIONAL



LED LIGHTS

STANDARD



FLIP RAMPS

OPTIONAL



OUTRIGGERS

STANDARD



LOADER POCKET

OPTIONAL



STEEL LOAD-BEARING FENDERS

OPTIONAL



BRIDGE STORAGE

OPTIONAL



OAK OVER LOAD-BEARING FENDERS

OPTIONAL

DESCRIPTION	55-TONNE 3 AXLE LOWBOY	60-TONNE 4 AXLE LOWBOY	75-TONNE 4 AXLE LOWBOY
Deck Capacity (12')	120,000 lb	132,000 lb	165,000 lb
King Pin Setback	16"	16"	16"
Swing Clearance	94" and 112"	94" and 112"	94" and 112"
Main Deck Length	20' to 35'	20' to 35'	20' to 30'
Main Deck Width	8.5' to 10'	8.5' to 10'	8.5' to 10'
Tires	275/70R 22.5	275/70R 22.5	275/70R 22.5
Rims (Outer)	Aluminum outer rim	Aluminum outer rim	Aluminum outer rim
Rims (Inner)	Steel, white (inner) rim	Steel, white (inner) rim	Steel, white (inner) rim
Decking	Oak, 2-1/4 in	Oak, 2-1/4 in	Oak, 2-1/4 in
Nose	Construction-Paver Hybrid	Construction-Paver Hybrid	Construction-Paver Hybrid
Air Ramps	Optional	Optional	Optional
Deck Height (Loaded, optional)	16" - 24"	16" - 24"	16" - 24"
Fenders (optional)	Steel fenders over lift axle; wood-covered load-bearing fender	Steel fenders over lift axle; wood-covered load-bearing fender	Steel fenders over lift axle; wood-covered load-bearing fender
Strobe Lights	LED strobe lights with self-charging battery pack	LED strobe lights with self-charging battery pack	LED strobe lights with self-charging battery pack
D-Rings + Outriggers	Standard	Standard	Standard

GINCOR WERX®



JC-Series - 53' Tridem Step-Deck trailer

STEP DECK TRAILERS

The GINCOR Werx JC-Series Step Deck Trailer is built for strength, versatility, and dependable performance. Its durable construction and lower deck height provide improved clearance and efficient transport for a wide range of equipment and materials.

The JC-Series Step Deck Trailer delivers the stability and performance you need to keep your operations running smoothly.

GINCOR WERX®

STANDARD FEATURES

- T1 (100 KSI Yield) steel chassis beams
- Hardwood upper & lower deck
- Air ride 6.5" ride height
- 25,000 lb axles
- Two-speed Holland 60,000 lb landing gear
- LED lighting
- Axle spread 49", 60" & 72"
- Beavertail ramps

POPULAR OPTIONS

- 1-5/16" shiplap hardwood
- Recessed air activated deck ramps
- Aluminum storage box
- Winch hydraulic/electric
- Aluminum wheels
- Lift axle
- Wide load sign
- Hot dip galvanized finish

STEPDECKS



ROLLER STOP

OPTIONAL



WIDE LOAD SIGN

OPTIONAL



RUBRAIL AND POCKET

OPTIONAL



WINCH

OPTIONAL



BEAVERTAIL RAMPS

STANDARD



RAMP STOOL

OPTIONAL



RECESSED MID RAMPS

OPTIONAL



AIR RAMPS

OPTIONAL

DESCRIPTION	53' TRIDEM EQUIPMENT STEPDECK
Overall Length (ft)	53'
Overall Width (in)	8.5' to 9.5'
Main Deck Length (ft)	33'-6"
Upper Deck Length (ft)	11'
Deck Height Unladen (in)	37"
Deck Height Laden (in)	34"
Kingpin Setting (in)	18"
Swing Clearance (in)	96"
Beavertail Length & Drop	8' Long with 12" Drop
Ramp Size (in)	72"
Axle Track Spacing (in)	79.5"
Axle Spread (in)	49" / 60" / 72"
Suspension Type	Weld-On Under-Slung (ht250) Ride Height 6.5"
Brake Type	Air Drum, Outboard 12.5 X 7.5, Auto Slacks, 30/30 Maxis, Dust Covers
Tire Size	245/70R - 17.5
Rim Size	6.75 X 17.5
Optional Winch & Remote	Electric/Hydraulic Winch (optional)
Landing Gear	Holland Double Leg, Mark-V, 2-Speed

GINCOR WERX®



25975 Woodbine Ave, Keswick, Ontario - L4P 3E9 - Canada

Phone: (905) 476 -6572 I Email: sales@gincor.com I www.gincor.com

JAMES THOMS

Inside Sales

Phone: 1 (365) 253 -0220 I Email: jamesthoms@gincor.com

JC Engineered Solutions. We will build a trailer for you.

gincor.com

START YOUR BUILD AT OUR NEW WEBSITE

Visit our new website at **www.gincor.com** to start building your GINCOR Werx JC-Series Trailer today!



The depictions of the GINCOR Werx JC-Series Trailers in this brochure are for general information purposes only, as to those manufactured by GINCOR Werx during the current model year. Since we continually strive to improve our products, actual products may differ and specifications are subject to change with or without notice. Product information, specifications, and photography in this brochure may contain some features that are optional on your GINCOR Werx JC-Series Trailers. All capacities are approximate and dimensions are nominal. Availability may be limited.

JC-SERIES 03/2026 NA