

PLUG FUSES & ADAPTERS

Bussmann®

125VAC DUAL-ELEMENT, TIME-DELAY PLUG FUSES

Used for all commercial applications, the Type T and Type S plug fuses are industrial strength products. They provides superior protection, yet will not open under repeated motor startups. Available in a wide amp range to permit exact sizing for motor protection.

- Used for air conditioners, furnace blower motors, swimming pool pumps, deep freezers or any circuit where motors frequently turn on and off
- This spring loaded design provides superior short circuit and overload protection
- IR:
 - 10 kA RMS Sym.
- Certifications
 - UL® Listed (up to 6-1/4 A), Std. 248-11, Guide JFHR, File E56412, (7 to 30 A) Guide JEFV, File E12112
 - CSA® Certified, Class 1423-01, File 53787
 - CE



Part Number	Amps 1/4 – 30	Mars Equivalent	Other Equivalents	Case Qty
TYPE S (REJECTION BASE)				
S-1-1/4	1 1/4	82307	SOO (Littelfuse)	4
S-1-6/10	1 6/10	82308		4
S-2	2	82311		4
S-2-8/10	2 8/10	–		4
S-3	3	82315		4
S-3-2/10	3 2/10	82316		4
S-4	4	82318		4
S-5	5	82320		4
S-6	6	–		4
S-6-1/4	6 1/4	82323		4
S-7	7	–		4
S-8	8	82325		4
S-10	10	82327		4
S-12	12	82328		4
S-14	14	–		4
S-15	15	82330		4
S-20	20	82331		4
S-25	25	82332		4
S-30	30	82333		4

Part Number	Amps 1/4 – 30	Mars Equivalent	Other Equivalents	Case Qty
TYPE T (EDISON BASE)				
T-1-1/4	1 1/4	82334	TOO (Littelfuse)	4
T-1-6/10	1 6/10	–		4
T-2-1/4	2 1/4	–		4
T-3-2/10	3 2/10	82338		4
T-4	4	82339		4
T-5	5	82340		4
T-6	6	–		4
T-6-1/4	6 1/4	82341		4
T-8	8	82342		4
T-10	10	82343		4
T-12	12	–		4
T-15	15	82346		4
T-20	20	82347		4
T-25	25	82348		4

Additional amp sizes available. Please call for details



⚠ WARNING: Cancer and Reproductive Harm | www.P65Warnings.ca.gov

WWW.GLOBALTHESOURCE.COM | 800.531.5967