

## The 2008 FEMA Flood Damage Resistant Materials Guide accepts the use of “Non Paper-Faced Gypsum Board” for use on walls and ceilings.

An August 2008 FEMA Technical Bulletin (*Flood Damage-Resistant Materials Requirements for buildings located in special flood hazard areas in accordance with the National Flood Insurance Program*) providing guidance under National Flood Insurance Program (NFIP) regulations indicates that the use of non-paper-faced gypsum board for walls and ceilings is acceptable for certain special flood hazard areas and that the use of paper-faced gypsum board is unacceptable for walls and ceilings in these flood hazard areas.

More than just an acceptable non-paper-faced gypsum board for these flood hazard areas, both **DensArmor Plus®** and **DensShield® Tile Backer** are fiberglass mat gypsum boards.

The NFIP regulations for flood damage-resistant materials state that certain flood risk communities in Special Flood Hazard Areas (SFHAs) subscribe to the following practice:

“...If a proposed building site is in a flood prone area, all new construction and substantial improvements shall... (ii) be constructed with materials resistant to flood damage...” (44 CFR Section 60.3(a)(3))

The FEMA bulletin provides guidance on what constitutes “materials resistant to flood damage” and indicates that non-paper-faced gypsum board for walls and ceilings is acceptable in these flood risk communities, but that paper-faced gypsum board for walls and ceilings is unacceptable for such communities.

SFHAs are determined by FEMA through a map called a FIRM (Flood Insurance Rate Map) which delineates these 100 year flood zones and other risk premium zones applicable to a community, for example, an area below a dam. It is estimated that there are more than 12,000 SFHAs in the US.

The Bulletin is available on the FEMA website at [www.fema.gov/library/viewRecord.do?id=1580](http://www.fema.gov/library/viewRecord.do?id=1580). Look for the “Non-Paper-Faced Gypsum Board” on page seven and the diagram of the “drainable dryable wall” (as diagramed by Building Science Corp) listing non-paper-faced drywall on page 16 for flood resistant wall assemblies outside Special Flood Hazard Areas





U.S.A. – Georgia-Pacific Gypsum LLC  
Canada – Georgia-Pacific Canada LP

**Sales Information & Order Placement**

U.S.A. Midwest: **1-800-876-4746**  
West: **1-800-824-7503**  
South: **1-800-327-2344**  
Northeast: **1-800-947-4497**

CANADA Canada Toll Free: **1-800-387-6823**  
Quebec Toll Free: **1-800-361-0486**

**Technical Information**

Georgia-Pacific Gypsum Technical Hotline  
U.S.A. and Canada: **1-800-225-6119**  
[www.gpgypsum.com](http://www.gpgypsum.com)

**TRADEMARKS** DENSARMOR PLUS, DENSSHIELD and the GEORGIA-PACIFIC logo are trademarks owned by or licensed to Georgia-Pacific Gypsum LLC.

**WARRANTIES, REMEDIES AND TERMS OF SALE**

For current warranty information for this product, please go to [www.gpgypsum.com](http://www.gpgypsum.com) and select the product for warranty information. All sales of this product by Georgia-Pacific are subject to our Terms of Sale available at [www.gpgypsum.com](http://www.gpgypsum.com).

**UPDATES AND CURRENT INFORMATION** The information in this document may change without notice. Visit our website at [www.gpgypsum.com](http://www.gpgypsum.com) for updates and current information.

**CAUTION For product fire, safety and use information, go to [www.gp.com/safetyinfo](http://www.gp.com/safetyinfo) or call 1-800-225-6119.**

**HANDLING AND USE—CAUTION** This product contains fiberglass facings which may cause skin irritation. Dust and fibers produced during the handling and installation of the product may cause skin, eye and respiratory tract irritation. Avoid breathing dust and minimize contact with skin and eyes. Wear long sleeve shirts, long pants and eye

protection. Always maintain adequate ventilation. Use a dust mask or NIOSH/MSHA approved respirator as appropriate in dusty or poorly ventilated areas.

**FIRE SAFETY CAUTION** Passing a fire test in a controlled laboratory setting and/or certifying or labeling a product as having a one-hour, two-hour, or any other fire resistance or protection rating and, therefore, as acceptable for use in certain fire rated assemblies/systems, does not mean that either a particular assembly/system incorporating the product, or any given piece of the product itself, will necessarily provide one-hour fire resistance, two-hour fire resistance, or any other specified fire resistance or protection in an actual fire. In the event of an actual fire, you should immediately take any and all actions necessary for your safety and the safety of others without regard for any fire rating of any product or assembly/system.