

Model: RDHC-110

Designed for rugged commercial use and efficient moisture removal. Ideal for commercial and industrial environments and for water damage restoration.





Washable Filter

FEATURES

Designed for Commercial Use

- Rugged metal housing for heavy duty use
- Efficient moisture removal (140 Pints per day @95°F, 90% RH)

Digital Controls

- Digital trouble shooting display and electronic controls allow you to set the desired humidity level and 24 hour timer
- Auto restart after a power outage at previous settings

Portable Design

- Easy to move around with pneumatic wheels and easy grip handle
- Stackable for convenient storage of multiple units when not in use; built-in side handles to help lift unit

Washable Filter

• Collects large dust particles and prevents bacteria build up. Easy to remove for cleaning

140 Pint Commercial Dehumidifier



Model: RDHC-110

PRODUCT OVERVIEW







Digital Control Panel Digital trouble shooting display and electronic controls allow you to set the desired humidity level and 24 hour timer

Water Tank or Continuous Drainage Includes 5.5 L water collection tank or 5 m (16.4 ft) hose for continuous drainage



- **Rugged, Heavy Duty Wheels** Provides easy mobility
- (5) Cord Management Bracket included on back of unit to wrap power cord

SPECIFICATIONS

Attributes

Dehumidifying Capacity (Pints/ Day): 140 Pints/ Day @ 95°F, 90% RH 127 Pints/ Day @ 90°F, 90% RH 110 Pints/ Day @ 86°F, 80% RH 70 Pints/ Day @ 80°F, 60% RH Air Circulation/ Flow: 450 m3/ hr (264.8 CFM) Humidistat Range: Adjustable Operating Temperature Range: 5°C - 38°C Effective Application Area: 111.5 sq. m (1,200 sq. ft.) Bucket Full Indicator/ Alarm: Yes Bucket Capacity: 5.5 L (1.45 Gallons) Continuous Direct Drain Option: Yes Drainage Hose Length: 5 m (16.4 ft) Sound: 60 dB Electronic Controls/ Digital Display: Yes Washable Filter: Yes On/ Off Timer (Hrs.): 24 Hrs Auto Restart: Yes Auto Defrost: Yes Refrigerant: R410A

Dimensions & Weights

Unit (W x D x H): 17" x 20.3" x 32.5" (430 mm x 515 mm x 825 mm) Unit Weight: 79.3 lbs (36 kg)

Box (W x D x H): 20.5" x 22.2" x 28.7" (520 mm x 565 mm x 730 mm) Box Weight: 87 lbs (39.5 kg)

Electrical Rating

Power Supply: 115V/ 60Hz Power Consumption: 728W / 6.75 A @ 86°F, 80% RH Cord Length: 3 m (10 ft) Certification: cETLus

UPC CODE Individual Box: 849023080596

Warranty 1 Year Limited Parts & Labour

