Safety Data Sheet

Section 1 - Chemical Product and Company Information

Product Name: Sealer Beyond Paint Product Code: CCR-0800

Trade Name: Sealer Manufactured for: Beyond Paint Clearwater, FL 33762

Chemtrec

2900 Fairview Park Drive Falls Church, VA 22042-4513

(800) 262-8200

Emergency Hot Line: (800) 424-9300

Section 2 - Hazards Identification

GHS Ratings:

Inhalation Toxicity

Acute Tox. 4

Gases>2500+<=5000ppm, Vapors>10+<=20mg/l, Dusts&mists>1+<=5mg/l

Skin corrosive

2

Reversible adverse effects in dermal tissue. Draize score: >= 2.3 < 4.0 or persistent inflammation

Eye corrosive

1

Serious eye damage: Irreversible damage 21 days after exposure, Draize score: Corneal opacity >= 3, Iritis > 1.5

Skin sensitizer

1

Skin sensitizer

Reproductive toxin

2

Human or animal evidence possibly with other information

GHS Hazards

H315

Causes skin irritation

H317

May cause an allergic skin reaction

H318

Causes serious eye damage

H332

Harmful if inhaled

H361

Suspected of damaging fertility or the unborn child

GHS Precautions

P201

Obtain special instructions before use

P202

Do not handle until all safety precautions have been read and understood

P261

Avoid breathing dust/fume/gas/mist/vapours/spray

P264

Wash ... thoroughly after handling

P271

Use only outdoors or in a well-ventilated area

P272

Contaminated work clothing should not be allowed out of the workplace

P280

Wear protective gloves/protective clothing/eye protection/face protection

D201

Use personal protective equipment as required

P310

Immediately call a POISON CENTER or doctor/physician

P312

Call a POISON CENTER or doctor/physician if you feel unwell

P321

Specific treatment (see ... on this label)

P362

Take off contaminated clothing and wash before reuse

P363

Wash contaminated clothing before reuse

P302+P352

IF ON SKIN: Wash with soap and water

P304+P340

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

CCR-0800

Reviewer Revision

Page 1 of 5

P305+P351+P338

IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing P308+P313

IF exposed or concerned: Get medical advice/attention

P332+P313

If skin irritation occurs: Get medical advice/attention

P333+P313

If skin irritation or a rash occurs: Get medical advice/attention

P405

Store locked up

P501

Dispose of contents/container to ...

Signal Word: Danger

Section 3 - Composition/Information on Ingredients

Chemical Name CAS number Weight Concentration % Inert 50.00% - 60.00%

Water softened

7732-18-5 30.00% - 40.00%

Section 4 - First Aid Measures

INHALATION - If product solids are inhaled either as dust or in the form of a spray mist, remove the person from exposure immediately. If breathing is difficult, irregular, or has stopped, start resuscitation; call a physician. Administer oxygen if a qualified operator is available.

EYE CONTACT - In case of eye contact, flush the eyes with water for fifteen (15) minutes. If contact lenses are worn, quickly remove them, then flush the eyes with water. Have a physician examine the eyes.

SKIN CONTACT - In case of skin contact, remove contaminated clothing. Flush the skin with large amounts of water, then wash the skin with soap and water. Call a POISON CENTER or doctor/physican if you feel unwell.

INGESTION - If material is ingested, seek immediate medical attention. Rinse mouth thoroughly. Do not induce vomiting. **Notes to Physician**: Symptoms may be delayed.

Section 5 - Fire Fighting Measures

Flash Point: > 100 C (>212 F)

LEL: 2.00 UEL: 17.00

Flammable Limits:

EXTINGUISHING MEDIA: Use carbon dioxide (CO2), "alcohol" foam, dry chemical, or water spray/water fog extinguishing systems.

UNUSUAL FIRE OR EXPLOSION HAZARDS: The product vapor is heavier than air and may travel a considerable distance to a source of ignition and flashback.

HAZARDOUS COMBUSTION PRODUCTS: See section 10 for a list of hazardous decomposition products for this mixture.

FIRE FIGHTING: If evacuation of personnel is necessary, evacuate to an upwind area. Decontaminate personnel and equipment with a water wash-down after fire and smoke exposure.

FIRE FIGHTING EQUIPMENT: Firemen and emergency responders: wear full turnout gear or Level A equipment, CCR-0800

Page 2 of 5

Reviewer Revision

including positive-pressure, self-contained breathing apparatus (SCBA).

Section 6 - Accidental Release Measures

SPILL AND LEAK PROCEDURES: Spill supervisor - Ensure cleanup personnel wear all appropriate Personal Protective Equipment (PPE), including respiratory protection. Remove all ignition sources. Keep nonessential personnel away from the contaminated area.

SMALL SPILLS: Ventilate the contaminated area. Using nonsparking tools, mix the appropriate sorbent into the spilled material. Use an absorbent like sawdust for aqueous, waterborne, and solvent-borne coatings.

Collect the saturated sorbent and transfer it into a covered container. Steel containers are acceptable for all wastes except wastes which contain acid. Use suitable plastic containers for acid-bearing wastes.

Dispose of the waste in compliance with all Federal, state, regional, and local regulations.

LARGE SPILLS: Prevent this material from entering sewers and watercourses by diking or impounding the spilled material. Advise authorities if the product has entered or may enter, sewers, watercourses, or extensive land areas.

Ventilate the contaminated area. Using nonsparking tools, mix the appropriate sorbent into the spilled material. Use an absorbent like sawdust for aqueous, waterborne, and solvent-borne coatings.

Collect the saturated sorbent and transfer it into a covered container. Steel containers are acceptable for all wastes except wastes which contain acid. Use suitable plastic containers for acid-bearing wastes.

Label the waste container. Dispose of the waste in compliance with all Federal, state, regional, and local regulations.

Section 7 - Handling and Storage

HANDLING PRECAUTIONS: Wear all appropriate Personal Protective Equipment (PPE). Wear respiratory protection or ensure adequate ventilation at all times as vapors can accumulate in confined or poorly ventilated areas. Use the product in a manner which minimizes splashes and/or the creation of dust. Keep containers closed when not in use. Do not handle or store material near heat, sparks, open flames, or other sources of ignition. Store at room temperatures, i.e., 40 to 95 F (4 to 35 C).

STORAGE: Prevent from freezing. Do not store above 120 F (49 C).

Store only in original containers.

Section 8 - Exposure Controls / Personal Protection

Other Exposure Limits

ACGIH Exposure Limits
OSHA Exposure Limits
Chemical Name / CAS No.

Inert

Not Established Not Established Not Established

Water softened 7732-18-5

No component of this product at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

No component of this product at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Not Established

CCR-0800

Page 3 of 5

Reviewer Revision

Section 9 - Physical and Chemical Properties

This mixture typically exhibits the following properties under normal circumstance:

Liquid

Slight Amine Appearance:

Odor: Not Determined

Vapor Pressure:

Not Determined

Odor threshold:

Not Determined Vapor Density:

1.04 Specific Gravity:

Not Determined

Melting point:

Not Determined Freezing point:

Not Determined Solubility:

Not Determined

Boiling range:

100°C

Not Determined Flash point:

Not Determined Evaporation rate:

Not Determined Flammability:

Not Determined Explosive Limits:

Partition coefficient (n-octanol/water):

Not Determined

Autoignition temperature:

Not Determined

Decomposition temperature:

Section 10 - Stability and Reactivity

Stability:

STABLÉ

Incompatibilities/Condictions to avoid: Elevated temperatures. Contact with oxidizing agent/oxidizers.

No Data Available

Hazardous Decomposition: Can produce Carbon Monoxide and/or Carbon Dioxide.

No Data Available

Hazardous polymerization will not occur.

Section 11 - Toxicological Information

Mixture Toxicity

Inhalation Toxicity LC50: 11mg/L

Component Toxicity

Primary routes of entry: Inhalation, Skin contact.

Carcinogenicity: The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing).

Carcinogen Rating

CAS Number

Description

% Weight

No Data Available

None

Component Ecotoxicity Water softened

Toxicity of the Products of Biodegradation: The product itself and its products of degradation are not toxic.

Section 13 - Disposal Considerations

CCR-0800

Page 4 of 5 Reviewer Revision

Dispose in accordance with all applicable regulations.

Section 14 - Transport Information

This material is classified for transport as follows:

As cited in the IATA Dangerous Goods Handbook:

Section 3.3.1.3: Liquids described in Section 3.3.1.2 with a flash point exceeding 35°C which do not sustain combustion need not be considered as flammable liquids for the purpose of these Regulations

(b) their fire point accoring to ISO 2592:1973 is greater than 100°C

Hazard Class
Packing Group
UN Number
Proper Shipping Name
Agency
DOT

Water Based Paint Unregulated Non Hazardous IATA

Water Based Paint Unregulated Non Hazardous ADR/RID Water Based Paint Unregulated Non Hazardous

IMDG Water Based Paint Unregulated Non Hazardous

Section 15 - Regulatory Information

All Components Listed Regulation Country

Section 16 - Other Information

Hazardous Material Information System (HMIS)
National Fire Protection Association (NFPA)
HMIS & NFPA Hazard Rating Legend
* = Chronic Health Hazard
0 = INSIGNIFICANT
1 = SLIGHT
2 = MODERATE
3 = HIGH
Special
Instability
Flammability

0

The material contained in this Safety Data Sheet is based on information supplied by the raw material suppliers of the individual components of this product. However, no warranty is expressed or implied regarding the accuracy of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and health and safety of your employees and users of this material. As more information becomes available from our vendors additional revisions will be forthcoming.

Date Prepared: 5/11/2016

CCR-0800

Health