SAFETY DATA SHEET



1. Identification

Product identifier BEHR® PRO i300 Interior Dead Flat - White Base

Other means of identification

Product number PR310

Recommended use Architectural Coating

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Supplier Behr Process Canada, Ltd.

2750 Centre Avenue N.E.

Calgary, AB T2A 2L3

Emergency telephone (US)+1 760 476 3962

(US)+1 866 519 4752

Access code 335213

2. Hazard identification

Physical hazards Not classified.

Health hazards Not classified.

Label elements

Hazard symbol None.
Signal word None.

Hazard statement The mixture does not meet the criteria for classification.

Precautionary statement

Prevention Observe good industrial hygiene practices.

Response Wash hands after handling.

Storage Store away from incompatible materials.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Other hazards None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Titanium dioxide		13463-67-7	10 - 30
Cristobalite		14464-46-1	1 - 5
Flux Calcined Diatomaceous Earth (DE)		68855-54-9	0.5 - 1.5
Quartz (crystalline silica)		14808-60-7	0.1 - 1

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in

percent by volume.

The exact concentrations of the above listed chemicals are being withheld as a trade secret.

SDS Canada

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

952366 Version #: 01 Revision date: - Issue date: 26-December-2019 1 / 7

Rinse mouth. Get medical attention if symptoms occur. Ingestion

Most important symptoms/effects, acute and

delayed

Treat symptomatically.

Indication of immediate medical attention and special

treatment needed

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Direct contact with eyes may cause temporary irritation.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store in tightly closed container. Store away from incompatible materials (see section 10 of the

SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Туре	Value	Form
Cristobalite (CAS 14464-46-1)	TWA	0.025 mg/m3	Respirable fraction.
Quartz (crystalline silica) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Туре	Value	Form
Cristobalite (CAS 14464-46-1)	TWA	0.025 mg/m3	Respirable.
·		0.025 mg/m3	Respirable particles.

Components	Туре	Value	Form
Quartz (crystalline silica) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable particles.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
Canada. British Columbia Safety Regulation 296/97, a	OELs. (Occupational Exposure Limits as amended)	for Chemical Substances, Oc	cupational Health and
Components	Туре	Value	Form
Cristobalite (CAS 14464-46-1)	TWA	0.025 mg/m3	Respirable fraction.
Quartz (crystalline silica) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Total dust.
Canada. Manitoba OELs (F Components	teg. 217/2006, The Workplace Safety A Type	and Health Act) Value	Form
Cristobalite (CAS 14464-46-1)	TWA	0.025 mg/m3	Respirable fraction.
Quartz (crystalline silica) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
Canada. Ontario OELs. (Co Components	ontrol of Exposure to Biological or Ch Type	emical Agents) Value	Form
Cristobalite (CAS 14464-46-1)	TWA	0.05 mg/m3	Respirable fraction.
Quartz (crystalline silica) (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
Canada. Quebec OELs. (M Components	inistry of Labor - Regulation respectir Type	g occupational health and sa Value	fety) Form
Cristobalite (CAS 14464-46-1)	TWA	0.05 mg/m3	Respirable dust.
Quartz (crystalline silica) (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable dust.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	Total dust.
Canada. Saskatchewan OE Components	Ls (Occupational Health and Safety F Type	egulations, 1996, Table 21) Value	Form
Cristobalite (CAS 14464-46-1)	15 minute	10 mg/m3	Inhalable fraction.
	8 hour	0.05 mg/m3	Respirable fraction.
Quartz (crystalline silica) (CAS 14808-60-7)	8 hour	0.05 mg/m3	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	15 minute	20 mg/m3	
	8 hour	10 mg/m3	
ogical limit values	No biological exposure limits noted for	or the ingredient(s).	
ropriate engineering trols	Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not beer established, maintain airborne levels to an acceptable level.		

SDS Canada

952366 Version #: 01 Revision date: - Issue date: 26-December-2019

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear suitable protective clothing.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators. Use a positive-pressure air-supplied respirator if there is any potential for an

uncontrolled release, exposure levels are not known, or any other circumstances where

air-purifying respirators may not provide adequate protection.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene Always observe good personal hygiene measures, such as washing after handling the material

considerations and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical stateLiquid.FormLiquid.ColourWhite.OdourSlight.

Odour threshold Not available.

pH 7 - 10

Melting point/freezing point Not available.

Initial boiling point and boiling > 37.2 °C (> 99 °F)

range

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

%)

Not available.

Vapour pressureNot available.Vapour densityNot available.

Relative density 1.52

Solubility(ies)

Solubility (water) Soluble.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity 50 - 140 KU (25 °C)

Other information

Density 12.69 lbs/gal

Explosive properties Not explosive.

Oxidising properties Not oxidising.

VOC 0 g/l (including water) (Material) 0 g/l (excluding water) (Coating)

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

BEHR® PRO i300 Interior Dead Flat - White Base
952366 Version #: 01 Revision date: - Issue date: 26-December-2019

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid

Contact with incompatible materials.

Incompatible materials

Strong oxidising agents.

Hazardous decomposition

and the state of t

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Prolonged skin contact may cause temporary irritation. **Eye contact** Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

Components Species Test Results

Quartz (crystalline silica) (CAS 14808-60-7)

Chronic Inhalation

LOEC Human 0.0563 mg/m3

Titanium dioxide (CAS 13463-67-7)

Acute Inhalation

LC50 Rat 3.43 mg/l, 4 Hours

Oral

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitisation

Canada - Alberta OELs: Irritant

Cristobalite (CAS 14464-46-1) Irritant Titanium dioxide (CAS 13463-67-7) Irritant

Respiratory sensitisation Not a respiratory sensitiser.

Skin sensitisation This product is not expected to cause skin sensitisation.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Due to the form of the product, exposure to the potentially carcinogenic components is not

expected.

ACGIH Carcinogens

Cristobalite (CAS 14464-46-1)

Quartz (crystalline silica) (CAS 14808-60-7)

A2 Suspected human carcinogen.

A2 Suspected human carcinogen.

Titanium dioxide (CAS 13463-67-7) A4 Not classifiable as a human carcinogen.

Canada - Alberta OELs: Carcinogen category

Cristobalite (CAS 14464-46-1)

Quartz (crystalline silica) (CAS 14808-60-7)

Suspected human carcinogen.

Suspected human carcinogen.

Canada - Manitoba OELs: carcinogenicity

Cristobalite (CAS 14464-46-1)

Quartz (crystalline silica) (CAS 14808-60-7)

Suspected human carcinogen.

Suspected human carcinogen.

Titanium dioxide (CAS 13463-67-7)

Not classifiable as a human carcinogen.

Canada - Quebec OELs: Carcinogen category

Cristobalite (CAS 14464-46-1) Detected carcinogenic effect in animals.

BEHR® PRO i300 Interior Dead Flat - White Base 952366 Version #: 01 Revision date: - Issue date: 26-December-2019 Quartz (crystalline silica) (CAS 14808-60-7) Suspected carcinogenic effect in humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Cristobalite (CAS 14464-46-1) 1 Carcinogenic to humans. Quartz (crystalline silica) (CAS 14808-60-7) 1 Carcinogenic to humans.

Titanium dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Cristobalite (CAS 14464-46-1) Known To Be Human Carcinogen.

Reasonably Anticipated to be a Human Carcinogen.

Quartz (crystalline silica) (CAS 14808-60-7) Known To Be Human Carcinogen.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

The product is not classified as environmentally hazardous. **Ecotoxicity**

No data is available on the degradability of any ingredients in the mixture. Persistence and degradability

Bioaccumulative potential No data available. Mobility in soil No data available. Other adverse effects No data available.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site.

Dispose in accordance with all applicable regulations. Local disposal regulations

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

TDG

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and Not applicable.

the IBC Code

15. Regulatory information

Canadian regulations This product has been classified in accordance with the hazard criteria of the HPR and the SDS

contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

BEHR® PRO i300 Interior Dead Flat - White Base 952366 Version #: 01 Revision date: -Issue date: 26-December-2019

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto Protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

16. Other information

Issue date 26-December-2019

Revision date - Version No. 01

List of abbreviations IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous

Chemicals in Bulk.

IMDG Code: International Maritime Dangerous Goods Code.

LC50: Lethal Concentration, 50%.

LD50: Lethal Dose, 50%.

LOEC: Lowest observable effect concentration.

MARPOL: International Convention for the Prevention of Pollution from Ships.

TDG: Transportation of Dangerous Goods. TWA: Time Weighted Average Value.

References HSDB® - Hazardous Substances Data Bank

IARC Monographs. Overall Evaluation of Carcinogenicity

Disclaimer Behr Process Corp cannot anticipate all conditions under which this information and its product, or

the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the

sheet was written based on the best knowledge and experience currently available.

SDS Canada

952366 Version #: 01 Revision date: - Issue date: 26-December-2019