

## CPVC Cement (Orange) - Medium Bodied



### DESCRIPTION

**Black Swan CPVC Cement - Orange - Medium** is an orange, medium bodied, medium to fast set, high strength cement used to join CPVC pipe and fittings. For CPVC pipe and fittings through 6" diameter. CPVC Cement - Orange is most effective when used in temperature ranges from 40°F to 100°F.

---

### SHELF LIFE

CPVC Cement - Orange has a shelf life of two years from date on bottom of can.

---

### STANDARDS AND APPROVALS

CPVC Cement - Orange meets ASTM D-2846 and ASTM F-493.

---

### PACKAGING

CPVC Cement - Orange is available in 1/4 pint, 1/2 pint, pint, and quart containers. Larger sizes available upon request. On sizes smaller than one gallon there is a dauber in each container to facilitate application of cement.

### UPC NUMBER AND CARTON INFORMATION

<b>STOCK NO.</b>	<b>SIZE</b>	<b>UPC NUMBER</b>	<b>CARTON CUBIC FEET</b>
07185	1/4 pt.	0 54647 07185 5	.222
07190	1/2 pt.	0 54647 07190 9	.385
07195	pt.	0 54647 07195 4	.376
07200	qt.	0 54647 07200 5	.711

